CMSH1-20 CMSH1-60
CMSH1-40 CMSH1-100

SURFACE MOUNT SILICON SCHOTTKY RECTIFIERS 1.0 AMP, 20 THRU 100 VOLT



SMB CASE

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMSH1-20 series 1.0 Amp surface mount silicon rectifier is a high quality, well constructed, highly reliable component designed for use in all types of commercial, industrial, entertainment, computer, and automotive applications.

MARKING CODE: SEE MARKING CODE TABLE ON FOLLOWING PAGE

FEATURES:

- High reliability
- Special selections available

MAXIMUM RATINGS: (T_A=25°C unless otherwise noted)

	SYMBOL	CMSH1 -20	CMSH1 -40	CMSH1 -60	CMSH1 -100	UNITS
Peak Repetitive Reverse Voltage	V_{RRM}	20	40	60	100	V
DC Blocking Voltage	V_R	20	40	60	100	V
RMS Reverse Voltage	$V_{R(RMS)}$	14	28	42	70	V
Average Forward Current (T_A=75°C)	I_O			1.0		A
Peak Forward Surge Current, tp=8.3ms	I_{FSM}			30		A
Operating and Storage Junction Temperature	T_J, T_{stg}			-65 to +150		°C
Thermal Resistance	Θ_{JL}			20		°C/W


ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	TYP	MAX	UNITS
I_R	V_R=Rated V_{RRM}		0.50	mA
I_R	V_R=Rated V_{RRM}, T_A=125°C		20	mA
V_F	I_F=1.0A (CMSH1-20)	0.46	0.55	V
V_F	I_F=1.0A (CMSH1-40)	0.48	0.55	V
V_F	I_F=1.0A (CMSH1-60)	0.48	0.70	V
V_F	I_F=1.0A (CMSH1-100)	0.75	0.85	V
C_J	V_R=4.0V, f=1.0MHz, (CMSH1-20)	68		pF
C_J	V_R=4.0V, f=1.0MHz, (CMSH1-40)	56		pF
C_J	V_R=4.0V, f=1.0MHz, (CMSH1-60)	42		pF
C_J	V_R=4.0V, f=1.0MHz, (CMSH1-100)	45		pF

CMSH1-20 CMSH1-60
CMSH1-40 CMSH1-100

SURFACE MOUNT SILICON SCHOTTKY RECTIFIERS 1.0 AMP, 20 THRU 100 VOLT

SMB CASE - MECHANICAL OUTLINE



DEVICE	MARKING CODE
CMSH1-20	CS20
CMSH1-40	CS40
CMSH1-60	CS60
CMSH1-100	CS100

DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.030	0.060	0.76	1.52
B	0.000	0.008	0.00	0.20
C	0.006	0.012	0.15	0.30
D	0.086	0.096	2.18	2.44
E	0.200	0.220	5.08	5.59
F	0.130	0.150	3.30	3.81
G	0.077	0.083	1.96	2.11
H	0.160	0.191	4.06	4.85


SMB (REV: R2)

CMSH1-20 CMSH1-60
CMSH1-40 CMSH1-100


SURFACE MOUNT SILICON SCHOTTKY RECTIFIERS 1.0 AMP, 20 THRU 100 VOLT

TYPICAL ELECTRICAL CHARACTERISTICS


Leakage Current for CMSH1-20




Leakage Current for CMSH1-40



Leakage Current for CMSH1-60



Leakage Current for CMSH1-100




CMSH1-20 CMSH1-60
CMSH1-40 CMSH1-100


SURFACE MOUNT SILICON SCHOTTKY RECTIFIERS 1.0 AMP, 20 THRU 100 VOLT

TYPICAL ELECTRICAL CHARACTERISTICS


Forward Voltage for CMSH1-20




Forward Voltage for CMSH1-40



Forward Voltage for CMSH1-60



Forward Voltage for CMSH1-100




CMSH1-20 CMSH1-60
CMSH1-40 CMSH1-100


SURFACE MOUNT SILICON SCHOTTKY RECTIFIERS 1.0 AMP, 20 THRU 100 VOLT

TYPICAL ELECTRICAL CHARACTERISTICS


Capacitance for CMSH1-20




Capacitance for CMSH1-40



Capacitance for CMSH1-60




Capacitance for CMSH1-100



CMSH1-20 CMSH1-60
CMSH1-40 CMSH1-100

SURFACE MOUNT SILICON SCHOTTKY RECTIFIERS 1.0 AMP, 20 THRU 100 VOLT

TYPICAL ELECTRICAL CHARACTERISTICS



OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms