Cool Power Technologies™ CPP 4:1 Chassis Series

RoHS COMPLIANT



DC/DC

Up to 72W Output Power

- Input Range: 9 - 36Vdc or 18 - 72Vdc
- Industrial Chassis Mount
- High Efficiency
- Remote Shutdown
- Undervoltage Lockout w/hyst

The up to 72 Watt CPP (Cool Power "Potted") 4:1 input series high performance compact 2" x 2" x 1.2" chassis mount series offers a rugged package in applications where a PCB may not be available to mount to. Additional features include trim or remote on/off control logic (negative or positive enable) and an operating temperature range of -40°C to +85°C (w/ derating.) Units are fully encapsulated, have the option for 4 threaded insert mounts and rugged screw terminals for I/O connections.

Specifications

INPUT	
Voltage Range	9 - 36 or 18 - 72 Vdc
Remote ON/OFF control	Neg. or Pos.
UVLO w/hysteresis	
OUTPUT	
Nominal Output	3.3, 5.0, 12 15 or 24Vdc
Setpoint accuracy	± 1.5%
Trim Range	±10%
Ripple and Noise (TYP)	50mV Pk-Pk
Short Circuit Protection	Auto-restart
GENERAL	
Efficiency	90% TYP
Isolation	2250Vdc
ENVIRONMENTAL	
Operating Temperature	-40 - +85C
Storage Temperature	-40 - +100C

Applications

These units are ideally suited for industrial, transportation, electric vehicles, solar and other unique applications where printed circuit board mount is not available.

www.dcdc.com
toll free 888.438.3232
toll free 888.GET.DCDC
SEMICONDUCTOR CIRCUITS, INC.

CPP 4:1 Series Ordering Information

Model Number	Vout (Volts)	Iout (A, max)	Power (W)	Vin Nom. (Volts)	Input Range (Volts)	Ripple (mV P-P)	Efficiency (Typ)
CPP15F36*	3.3	15	50	48	18 - 72	50	90%
CPP10A36*	5	10	50	48	18 - 72	50	91%
CPP4B36*	12	4.2	50	48	18 - 72	60	90%
CPP6B36*	12	6	72	48	18 - 72	80	92%
CPP3C36*	15	3	45	48	18 - 72	60	91%
CPP2D36*	24	2	48	48	18 - 72	100	91%
CPP15F18*	3.3	15	50	24	9 - 36	50	90%
CPP8A18*	5	8	40	24	9 - 36	50	90%
CPP4B18*	12	4.2	50	24	9 - 36	60	90%
CPP6B18*	12	6	72	24	9 - 36	80	92%
CPP3C18*	15	3	45	24	9 - 36	60	91%
CPP2D18*	24	2	48	24	9 - 36	100	91%

* add “T” for trim option, or either “N” or “P” for negative or positive enable option or leave blank for no connection; add “M” suffix for optional mounting inserts.

Note: Additional output voltages/power levels available upon request - consult factory

Mechanical Outline & Pin Assignments

Terminal Assignment

1. + Vin
2. - Vin
3. Trim or Enable
4. +Vout
5. -Vout

- All dimensions are in inches [mm]
- Terminal screws are #6-32 steel w/zinc clear chromate finish
- Converter Weight: 3.4 oz [96 g]

