
CTLDM7120-M621H

SURFACE MOUNT
N-CHANNEL
ENHANCEMENT-MODE
SILICON MOSFET



Top View Bottom View

TLM621H CASE

• Device is ***Halogen Free*** by design

APPLICATIONS:

• Load/Power switches
• Power supply converter circuits
• Battery powered portable equipment

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CTLDM7120-M621H is an Enhancement-mode N-Channel Field Effect Transistor, manufactured by the N-Channel DMOS Process, designed for high speed pulsed amplifier and driver applications. This MOSFET offers Low $r_{DS(ON)}$ and Low Threshold Voltage.

MARKING CODE: CNH

FEATURES:

• ESD protection up to 2kV
• Low $r_{DS(ON)}$ (0.25Ω MAX @ V_{GS}=1.5V)
• High current (I_D=1.0A)
• Logic level compatibility

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	8.0	V
Continuous Drain Current (Steady State)	I_D	1.0	A
Maximum Pulsed Drain Current, tp=10μs	I_{DM}	4.0	A
Power Dissipation (Note 1)	P_D	1.6	W
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	°C
Thermal Resistance (Note 1)	Θ_{JA}	75	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	**TEST CONDITIONS**	**MIN**	**TYP**	**MAX**	**UNITS**
I_{GSSF}, I_{GSSR}	V_{GS}=8.0V, V_{DS}=0			10	μA
I_{DSS}	V_{DS}=20V, V_{GS}=0			10	μA
BV_{DSS}	V_{GS}=0, I_D=250μA	20			V
$V_{GS(th)}$	V_{DS}=10V, I_D=1.0mA	0.5		1.2	V
V_{SD}	V_{GS}=0, I_S=1.0A			1.1	V
$r_{DS(ON)}$	V_{GS}=4.5V, I_D=0.5A		0.075	0.10	Ω
$r_{DS(ON)}$	V_{GS}=2.5V, I_D=0.5A		0.10	0.14	Ω
$r_{DS(ON)}$	V_{GS}=1.5V, I_D=0.1A		0.17	0.25	Ω
$Q_{g(tot)}$	V_{DS}=10V, V_{GS}=4.5V, I_D=1.0A		2.4		nC
Q_{gs}	V_{DS}=10V, V_{GS}=4.5V, I_D=1.0A		0.25		nC
Q_{gd}	V_{DS}=10V, V_{GS}=4.5V, I_D=1.0A		0.65		nC
g_{FS}	V_{DS}=10V, I_D=0.5A		4.2		S
C_{rss}	V_{DS}=10V, V_{GS}=0, f=1.0MHz		45		pF
C_{iss}	V_{DS}=10V, V_{GS}=0, f=1.0MHz		220		pF
C_{oss}	V_{DS}=10V, V_{GS}=0, f=1.0MHz		120		pF
t_{on}	V_{DD}=10V, V_{GS}=5.0V, I_D=0.5A		25		ns
t_{off}	V_{DD}=10V, V_{GS}=5.0V, I_D=0.5A		140		ns


Notes: (1) Mounted on a 4-layer JEDEC test board with one thermal vias connecting the exposed thermal pad to the first buried plane. PCB was constructed as per JEDEC standards JESD51-5 and JESD51-7.


R3 (2-August 2011)


CTLDM7120-M621H

SURFACE MOUNT
N-CHANNEL
ENHANCEMENT-MODE
SILICON MOSFET

TLM621H CASE - MECHANICAL OUTLINE








*Exposed pad P internally connected to pins 2, 3, 4, and 5.

DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.053	0.065	1.35	1.65
B	0.073	0.085	1.85	2.15
C	0.012	0.016	0.30	0.40
D	0.000	0.002	0.00	0.05
E	0.020		0.50	
F	0.008	0.012	0.20	0.30
G	0.027	0.035	0.69	0.89
H	0.053	0.057	1.35	1.45
J	0.039	0.047	0.99	1.19
K	0.011	0.015	0.28	0.38


TLM621H (REV:R0)

OPTIONAL MOUNTING PADS
(Dimensions in mm)



For standard mounting refer
to TLM621H Package Details

PIN CONFIGURATION



LEAD CODE:
1) Source
2) Drain
3) Drain
4) Drain
5) Drain
6) Gate

MARKING CODE: CNH

R3 (2-August 2011)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

Central Semiconductor Corp.

http://www.centralsemi.com

Product End of Life Notification

PDN ID:	PDN01096
Notification Date:	8/07/18
Last Buy Date:	2/07/19
Last Shipment Date	8/07/19

Summary:All devices in the TLM621 and TLM621H packages are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by other manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's ongoing Product Management Process. Any replacement products are noted below. The effective date for placing last purchase orders will be six (6) months from the date of this notice and twelve (12) months from the notice date for final shipments, and minimum order quantities may apply. The last purchase and shipment dates may be extended if inventory is available.

Central Part Number	Replacement
CTLDM7002A-M621 BK	N/A, Stock Only
CTLDM7002A-M621 TR	N/A, Stock Only
CTLDM7003-M621 BK	N/A, Stock Only
CTLDM7003-M621 TR	N/A, Stock Only
CTLDM7120-M621H BK	N/A, Stock Only
CTLDM7120-M621H TR	N/A, Stock Only
CTLDM8002A-M621 BK	N/A, Stock Only
CTLDM8002A-M621 TR	N/A, Stock Only
CTLDM8002A-M621H BK	N/A, Stock Only
CTLDM8002A-M621H TR	N/A, Stock Only
CTLDM8120-M621H BK	N/A, Stock Only
CTLDM8120-M621H TR	N/A, Stock Only
CTLSH05-40M621 BK	N/A, Stock Only
CTLSH05-40M621 TR	N/A, Stock Only
CTLSH1-40M621H BK	N/A, Stock Only
CTLSH1-40M621H TR	N/A, Stock Only
CTLT3410-M621 BK	N/A, Stock Only
CTLT3410-M621 TR	N/A, Stock Only
CTLT7410-M621 TR	N/A, Stock Only

Central would be happy to assist you by providing additional information or technical data to help locate an alternate source if we have no replacement available. Please email your requests to engineering@centralsemi.com.

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.