

# Capacitor Array

## Capacitor Array (IPC)

### BENEFITS OF USING CAPACITOR ARRAYS

KYOCERA AVX capacitor arrays offer designers the opportunity to lower placement costs, increase assembly line output through lower component count per board and to reduce real estate requirements.

#### Reduced Costs

Placement costs are greatly reduced by effectively placing one device instead of four or two. This results in increased throughput and translates into savings on machine time. Inventory levels are lowered and further savings are made on solder materials, etc.

#### Space Saving

Space savings can be quite dramatic when compared to the use of discrete chip capacitors. As an example, the 0508 4-element array offers a space reduction of >40% vs. 4 x 0402 discrete capacitors and of >70% vs. 4 x 0603 discrete capacitors. (This calculation is dependent on the spacing of the discrete components.)

#### Increased Throughput

Assuming that there are 220 passive components placed in a mobile phone:

A reduction in the passive count to 200 (by replacing discrete components with arrays) results in an increase in throughput of approximately 9%.

A reduction of 40 placements increases throughput by 18%.


For high volume users of cap arrays using the very latest placement equipment capable of placing 10 components per second, the increase in throughput can be very significant and can have the overall effect of reducing the number of placement machines required to mount components:

If 120 million 2-element arrays or 40 million 4-element arrays were placed in a year, the requirement for placement equipment would be reduced by one machine.

During a 20Hr operational day a machine places 720K components. Over a working year of 167 days the machine can place approximately 120 million. If 2-element arrays are mounted instead of discrete components, then the number of placements is reduced by a factor of two and in the scenario where 120 million 2-element arrays are placed there is a saving of one pick and place machine.


Smaller volume users can also benefit from replacing discrete components with arrays. The total number of placements is reduced thus creating spare capacity on placement machines. This in turn generates the opportunity to increase overall production output without further investment in new equipment.

#### W2A (0508) Capacitor Arrays



The 0508 4-element capacitor array gives a PCB space saving of over 40% vs four 0402 discretes and over 70% vs four 0603 discrete capacitors.

#### W3A (0612) Capacitor Arrays





The 0612 4-element capacitor array gives a PCB space saving of over 50% vs four 0603 discretes and over 70% vs four 0805 discrete capacitors.

Capacitor Array
Capacitor Array (IPC)



GENERAL DESCRIPTION

KYOCERA AVX is the market leader in the development and manufacture of capacitor arrays. The array family of products also includes the 0612 4-element device as well as 0508 2-element and 4-element series, all of which have received widespread acceptance in the marketplace.
KYOCERA AVX capacitor arrays are available in X5R, X7R and NP0 (C0G) ceramic dielectrics to cover a broad range of capacitance values. Voltage ratings from 6.3 Volts up to 100 Volts are offered. KYOCERA AVX also now offers a range of automotive capacitor arrays qualified to AEC-Q200 (see separate table).
Key markets for capacitor arrays are Mobile and Cordless Phones, Digital Set Top Boxes, Computer Motherboards and Peripherals as well as Automotive applications, RF Modems, Networking Products, etc.



HOW TO ORDER

Table with 11 columns: Style (W), Case Size (2), Array (A), Number of Caps (4), Voltage (3), Dielectric (C), Capacitance Code (103), Capacitance Tolerance (M), Failure Rate (A), Termination Code (T), Packaging & Quantity Code (2A). Each column contains specific options and codes.



NOTE: Contact factory for availability of Termination and Tolerance Options for Specific Part Numbers.

# Capacitor Array

## Capacitance Range – NP0/C0G

| SIZE           |       |      | W2 = 0508       |    |    | W3 = 0612       |    |    |
|----------------|-------|------|-----------------|----|----|-----------------|----|----|
| # Elements     |       |      | 4               |    |    | 4               |    |    |
| Soldering      |       |      | Reflow/Wave     |    |    | Reflow/Wave     |    |    |
| Packaging      |       |      | Paper/Embossed  |    |    | Paper/Embossed  |    |    |
| Length         | mm    |      | 1.30 ± 0.15     |    |    | 1.60 ± 0.150    |    |    |
|                | (in.) |      | (0.051 ± 0.006) |    |    | (0.063 ± 0.006) |    |    |
| Width          | mm    |      | 2.10 ± 0.15     |    |    | 3.20 ± 0.20     |    |    |
|                | (in.) |      | (0.083 ± 0.006) |    |    | (0.126 ± 0.008) |    |    |
| Max. Thickness | mm    |      | 0.94            |    |    | 1.35            |    |    |
|                | (in.) |      | (0.037)         |    |    | (0.053)         |    |    |
| WVDC           |       |      | 16              | 25 | 50 | 16              | 25 | 50 |
| 1R0            | Cap   | 1.0  |                 |    |    |                 |    |    |
| 1R2            | (pF)  | 1.2  |                 |    |    |                 |    |    |
| 1R5            |       | 1.5  |                 |    |    |                 |    |    |
| 1R8            |       | 1.8  |                 |    |    |                 |    |    |
| 2R2            |       | 2.2  |                 |    |    |                 |    |    |
| 2R7            |       | 2.7  |                 |    |    |                 |    |    |
| 3R3            |       | 3.3  |                 |    |    |                 |    |    |
| 3R9            |       | 3.9  |                 |    |    |                 |    |    |
| 4R7            |       | 4.7  |                 |    |    |                 |    |    |
| 5R6            |       | 5.6  |                 |    |    |                 |    |    |
| 6R8            |       | 6.8  |                 |    |    |                 |    |    |
| 8R2            |       | 8.2  |                 |    |    |                 |    |    |
| 100            |       | 10   |                 |    |    |                 |    |    |
| 120            |       | 12   |                 |    |    |                 |    |    |
| 150            |       | 15   |                 |    |    |                 |    |    |
| 180            |       | 18   |                 |    |    |                 |    |    |
| 220            |       | 22   |                 |    |    |                 |    |    |
| 270            |       | 27   |                 |    |    |                 |    |    |
| 330            |       | 33   |                 |    |    |                 |    |    |
| 390            |       | 39   |                 |    |    |                 |    |    |
| 470            |       | 47   |                 |    |    |                 |    |    |
| 560            |       | 56   |                 |    |    |                 |    |    |
| 680            |       | 68   |                 |    |    |                 |    |    |
| 820            |       | 82   |                 |    |    |                 |    |    |
| 101            |       | 100  |                 |    |    |                 |    |    |
| 121            |       | 120  |                 |    |    |                 |    |    |
| 151            |       | 150  |                 |    |    |                 |    |    |
| 181            |       | 180  |                 |    |    |                 |    |    |
| 221            |       | 220  |                 |    |    |                 |    |    |
| 271            |       | 270  |                 |    |    |                 |    |    |
| 331            |       | 330  |                 |    |    |                 |    |    |
| 391            |       | 390  |                 |    |    |                 |    |    |
| 471            |       | 470  |                 |    |    |                 |    |    |
| 561            |       | 560  |                 |    |    |                 |    |    |
| 681            |       | 680  |                 |    |    |                 |    |    |
| 821            |       | 820  |                 |    |    |                 |    |    |
| 102            |       | 1000 |                 |    |    |                 |    |    |
| 122            |       | 1200 |                 |    |    |                 |    |    |
| 152            |       | 1500 |                 |    |    |                 |    |    |
| 182            |       | 1800 |                 |    |    |                 |    |    |
| 222            |       | 2200 |                 |    |    |                 |    |    |
| 272            |       | 2700 |                 |    |    |                 |    |    |
| 332            |       | 3300 |                 |    |    |                 |    |    |
| 392            |       | 3900 |                 |    |    |                 |    |    |
| 472            |       | 4700 |                 |    |    |                 |    |    |
| 562            |       | 5600 |                 |    |    |                 |    |    |
| 682            |       | 6800 |                 |    |    |                 |    |    |
| 822            |       | 8200 |                 |    |    |                 |    |    |

 = Supported Values

# Capacitor Array


## Capacitance Range – X7R



| SIZE       |          | W2 = 0508       |    |    |    |    |     | W2 = 0508       |    |    |    |    |     | W3 = 0612       |    |    |    |    |     |
|------------|----------|-----------------|----|----|----|----|-----|-----------------|----|----|----|----|-----|-----------------|----|----|----|----|-----|
| # Elements |          | 2               |    |    |    |    |     | 4               |    |    |    |    |     | 4               |    |    |    |    |     |
| Soldering  |          | Reflow/Wave     |    |    |    |    |     | Reflow/Wave     |    |    |    |    |     | Reflow/Wave     |    |    |    |    |     |
| Packaging  |          | All Paper       |    |    |    |    |     | Paper/Embossed  |    |    |    |    |     | Paper/Embossed  |    |    |    |    |     |
| Length     | mm       | 1.30 ± 0.15     |    |    |    |    |     | 1.30 ± 0.15     |    |    |    |    |     | 1.60 ± 0.150    |    |    |    |    |     |
|            | (in.)    | (0.051 ± 0.006) |    |    |    |    |     | (0.051 ± 0.006) |    |    |    |    |     | (0.063 ± 0.006) |    |    |    |    |     |
| Width      | mm       | 2.10 ± 0.15     |    |    |    |    |     | 2.10 ± 0.15     |    |    |    |    |     | 3.20 ± 0.20     |    |    |    |    |     |
|            | (in.)    | (0.083 ± 0.006) |    |    |    |    |     | (0.083 ± 0.006) |    |    |    |    |     | (0.126 ± 0.008) |    |    |    |    |     |
| Max.       | mm       | 0.94            |    |    |    |    |     | 0.94            |    |    |    |    |     | 1.35            |    |    |    |    |     |
| Thickness  | (in.)    | (0.037)         |    |    |    |    |     | (0.037)         |    |    |    |    |     | (0.053)         |    |    |    |    |     |
| WVDC       |          | 6               | 10 | 16 | 25 | 50 | 100 | 6               | 10 | 16 | 25 | 50 | 100 | 6               | 10 | 16 | 25 | 50 | 100 |
| 101        | Cap (pF) | 100             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 121        |          | 120             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 151        |          | 150             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 181        |          | 180             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 221        |          | 220             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 271        |          | 270             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 331        |          | 330             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 391        |          | 390             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 471        |          | 470             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 561        |          | 560             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 681        |          | 680             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 751        |          | 750             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 821        |          | 820             |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 102        |          | 1000            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 122        |          | 1200            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 152        |          | 1500            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 182        |          | 1800            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 222        |          | 2000            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 272        |          | 2700            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 332        |          | 3300            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 392        |          | 3900            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 472        |          | 4700            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 562        |          | 5600            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 682        |          | 6800            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 822        |          | 8200            |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 103        | Cap (µF) | 0.010           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 153        |          | 0.015           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 183        |          | 0.018           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 223        |          | 0.022           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 273        |          | 0.027           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 333        |          | 0.033           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 393        |          | 0.039           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 473        |          | 0.047           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 563        |          | 0.056           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 683        |          | 0.068           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 823        |          | 0.082           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 104        |          | 0.100           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 154        |          | 0.150           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 224        |          | 0.220           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 274        |          | 0.270           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 334        |          | 0.330           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 394        |          | 0.390           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 474        |          | 0.470           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 564        |          | 0.560           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 684        |          | 0.680           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 824        |          | 0.820           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |
| 105        |          | 1.000           |    |    |    |    |     |                 |    |    |    |    |     |                 |    |    |    |    |     |

# Capacitor Array

## Automotive Capacitor Array (IPC)



As the market leader in the development and manufacture of capacitor arrays KYOCERA AVX is pleased to offer a range of AEC-Q200 qualified arrays to complement our product offering to the Automotive industry. Both the KYOCERA AVX 0612 and 0508 4-element capacitor array styles are qualified to the AEC-Q200 automotive specifications.

AEC-Q200 is the Automotive Industry qualification standard and a detailed qualification package is available on request. All KYOCERA AVX automotive capacitor array production facilities are certified to ISO/TS 16949:2002.

### HOW TO ORDER

| W                                    | 3                                        | A            | 4                     | Y                                                                      | C                                                  | 104                                                                                      | K                                                                  | 4                                     | T                                                                                                                     | 2A                                                                                           |
|--------------------------------------|------------------------------------------|--------------|-----------------------|------------------------------------------------------------------------|----------------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------------------------------|---------------------------------------|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|
| <b>Style</b><br>W = RoHS<br>L = SnPb | <b>Case Size</b><br>2 = 0508<br>3 = 0612 | <b>Array</b> | <b>Number of Caps</b> | <b>Voltage</b><br>Z = 10V<br>Y = 16V<br>3 = 25V<br>5 = 50V<br>1 = 100V | <b>Dielectric</b><br>A = NP0<br>C = X7R<br>F = X8R | <b>Capacitance Code (In pF)</b><br>Significant Digits + Number of Zeros<br>e.g. 10µF=106 | <b>Capacitance Tolerance</b><br>*J = ±5%<br>*K = ±10%<br>*M = ±20% | <b>Failure Rate</b><br>4 = Automotive | <b>Terminations</b><br>*T = Plated Ni and Sn<br>*Z = FLEXITERM®<br>B = 5% min lead<br>X = FLEXITERM® with 5% min lead | <b>Packaging &amp; Quantity Code</b><br>2A = 7" Reel<br>4A = 13" Reel<br>2F = 7" Reel (1000) |

\*RoHS Compliant

\*Contact factory for availability by part number for K = ±10% and J = ±5% tolerance.

### NP0/COG

| SIZE            |          | W3 = 0612   |    |    |  |
|-----------------|----------|-------------|----|----|--|
| No. of Elements |          | Reflow/Wave |    |    |  |
| WVDC            |          | 16          | 25 | 50 |  |
| 1R0             | Cap 1.0  |             |    |    |  |
| 1R2             | Cap 1.2  |             |    |    |  |
| 1R5             | Cap 1.5  |             |    |    |  |
| 1R8             | Cap 1.8  |             |    |    |  |
| 2R2             | Cap 2.2  |             |    |    |  |
| 2R7             | Cap 2.7  |             |    |    |  |
| 3R3             | Cap 3.3  |             |    |    |  |
| 3R9             | Cap 3.9  |             |    |    |  |
| 4R7             | Cap 4.7  |             |    |    |  |
| 5R6             | Cap 5.6  |             |    |    |  |
| 6R8             | Cap 6.8  |             |    |    |  |
| 8R2             | Cap 8.2  |             |    |    |  |
| 100             | Cap 10   |             |    |    |  |
| 120             | Cap 12   |             |    |    |  |
| 150             | Cap 15   |             |    |    |  |
| 180             | Cap 18   |             |    |    |  |
| 220             | Cap 22   |             |    |    |  |
| 270             | Cap 27   |             |    |    |  |
| 330             | Cap 33   |             |    |    |  |
| 390             | Cap 39   |             |    |    |  |
| 470             | Cap 47   |             |    |    |  |
| 560             | Cap 56   |             |    |    |  |
| 680             | Cap 68   |             |    |    |  |
| 820             | Cap 82   |             |    |    |  |
| 101             | Cap 100  |             |    |    |  |
| 121             | Cap 120  |             |    |    |  |
| 151             | Cap 150  |             |    |    |  |
| 181             | Cap 180  |             |    |    |  |
| 221             | Cap 220  |             |    |    |  |
| 271             | Cap 270  |             |    |    |  |
| 331             | Cap 330  |             |    |    |  |
| 391             | Cap 390  |             |    |    |  |
| 471             | Cap 470  |             |    |    |  |
| 561             | Cap 560  |             |    |    |  |
| 681             | Cap 680  |             |    |    |  |
| 821             | Cap 820  |             |    |    |  |
| 102             | Cap 1000 |             |    |    |  |
| 122             | Cap 1200 |             |    |    |  |
| 152             | Cap 1500 |             |    |    |  |
| 182             | Cap 1800 |             |    |    |  |
| 222             | Cap 2200 |             |    |    |  |
| 272             | Cap 2700 |             |    |    |  |
| 332             | Cap 3300 |             |    |    |  |
| 392             | Cap 3900 |             |    |    |  |
| 472             | Cap 4700 |             |    |    |  |
| 562             | Cap 5600 |             |    |    |  |
| 682             | Cap 6800 |             |    |    |  |
| 822             | Cap 8200 |             |    |    |  |

■ = NP0/COG

### X7R

| SIZE            |           | W2 = 0508 |    |    |     | W2 = 0508 |    |    |     | W3 = 0612 |    |    |    |     |
|-----------------|-----------|-----------|----|----|-----|-----------|----|----|-----|-----------|----|----|----|-----|
| No. of Elements |           | 2         |    |    |     | 4         |    |    |     | 4         |    |    |    |     |
| WVDC            |           | 16        | 25 | 50 | 100 | 16        | 25 | 50 | 100 | 10        | 16 | 25 | 50 | 100 |
| 101             | Cap 100   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 121             | Cap 120   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 151             | Cap 150   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 181             | Cap 180   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 221             | Cap 220   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 271             | Cap 270   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 331             | Cap 330   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 391             | Cap 390   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 471             | Cap 470   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 561             | Cap 560   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 681             | Cap 680   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 821             | Cap 820   |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 102             | Cap 1000  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 122             | Cap 1200  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 152             | Cap 1500  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 182             | Cap 1800  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 222             | Cap 2200  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 272             | Cap 2700  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 332             | Cap 3300  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 392             | Cap 3900  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 472             | Cap 4700  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 562             | Cap 5600  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 682             | Cap 6800  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 822             | Cap 8200  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 103             | Cap 0.010 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 123             | Cap 0.012 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 153             | Cap 0.015 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 183             | Cap 0.018 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 223             | Cap 0.022 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 273             | Cap 0.027 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 333             | Cap 0.033 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 393             | Cap 0.039 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 473             | Cap 0.047 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 563             | Cap 0.056 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 683             | Cap 0.068 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 823             | Cap 0.082 |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 104             | Cap 0.10  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 124             | Cap 0.12  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 154             | Cap 0.15  |           |    |    |     |           |    |    |     |           |    |    |    |     |
| 224             | Cap 0.22  |           |    |    |     |           |    |    |     |           |    |    |    |     |

■ = X7R

\*Not RoHS Compliant



LEAD-FREE  
LEAD-FREE COMPATIBLE  
COMPONENT



RoHS  
COMPLIANT


Capacitor Array

Part & Pad Layout Dimensions



PART & PAD LAYOUT DIMENSIONS

millimeters (inches)



PART DIMENSIONS

0508 - 2 Element

| L                              | W                              | T                       | BW                             | BL                             | P                       | S                              |
|--------------------------------|--------------------------------|-------------------------|--------------------------------|--------------------------------|-------------------------|--------------------------------|
| 1.30 ± 0.15<br>(0.051 ± 0.006) | 2.10 ± 0.15<br>(0.083 ± 0.006) | 0.94 MAX<br>(0.037 MAX) | 0.43 ± 0.10<br>(0.017 ± 0.004) | 0.33 ± 0.08<br>(0.013 ± 0.003) | 1.00 REF<br>(0.039 REF) | 0.50 ± 0.10<br>(0.020 ± 0.004) |

0508 - 4 Element

| L                              | W                              | T                       | BW                             | BL                             | P                       | X                              | S                              |
|--------------------------------|--------------------------------|-------------------------|--------------------------------|--------------------------------|-------------------------|--------------------------------|--------------------------------|
| 1.30 ± 0.15<br>(0.051 ± 0.006) | 2.10 ± 0.15<br>(0.083 ± 0.006) | 0.94 MAX<br>(0.037 MAX) | 0.25 ± 0.06<br>(0.010 ± 0.003) | 0.20 ± 0.08<br>(0.008 ± 0.003) | 0.50 REF<br>(0.020 REF) | 0.75 ± 0.10<br>(0.030 ± 0.004) | 0.25 ± 0.10<br>(0.010 ± 0.004) |

0612 - 4 Element

| L                              | W                              | T                       | BW                             | BL                                                                                     | P                       | X                              | S                              |
|--------------------------------|--------------------------------|-------------------------|--------------------------------|----------------------------------------------------------------------------------------|-------------------------|--------------------------------|--------------------------------|
| 1.60 ± 0.20<br>(0.063 ± 0.008) | 3.20 ± 0.20<br>(0.126 ± 0.008) | 1.35 MAX<br>(0.053 MAX) | 0.41 ± 0.10<br>(0.016 ± 0.004) | 0.18 <sup>+0.25</sup> <sub>-0.08</sub><br>(0.007 <sup>+0.010</sup> <sub>-0.003</sub> ) | 0.76 REF<br>(0.030 REF) | 1.14 ± 0.10<br>(0.045 ± 0.004) | 0.38 ± 0.10<br>(0.015 ± 0.004) |

PAD LAYOUT DIMENSIONS

0508 - 2 Element

| A               | B               | C               | D               | E               |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 0.68<br>(0.027) | 1.32<br>(0.052) | 2.00<br>(0.079) | 0.46<br>(0.018) | 1.00<br>(0.039) |

0508 - 4 Element

| A               | B               | C               | D               | E               |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 0.56<br>(0.022) | 1.32<br>(0.052) | 1.88<br>(0.074) | 0.30<br>(0.012) | 0.50<br>(0.020) |

0612 - 4 Element

| A               | B               | C               | D               | E               |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| 0.89<br>(0.035) | 1.65<br>(0.065) | 2.54<br>(0.100) | 0.46<br>(0.018) | 0.76<br>(0.030) |