



2M-Series

Miniature Toggles Switches

PRODUCT WEBPAGE

request sample, configure part



The 2M family of miniature toggle switches is composed of three switch series; the 2M1-Series miniature toggle switch, the 2MS-Series sealed miniature toggle switch, and the 2MIH-Series premium sealed miniature toggle switch. These series all feature PC mounting and offer a variety of ratings, circuits, contact materials, terminal platings, toggle styles and lengths, and optional color caps.

1-2
Poles

.4-5
Amps

125, 250
VAC

28
VDC


Typical Applications

- Instrumentation
- Telecommunications
- Networking
- Medical Equipment


Tech Specs



2MIH-Series
Premium Sealed
Miniature
Toggle Switch



2MS-Series
Sealed
Miniature
Toggle Switch



2MI-Series
Miniature
Toggle Switch

Electrical

Contact Rating	refer to ordering scheme
Electrical Life	50,000 make & break cycles @ full load
Contact Resistance	10 mΩ max. initial @ 2-4 VDC 100mA for both silver & gold plated contacts
Insulation Resistance	1000 MΩ min.
Dielectric Strength	1500 Volts RMS @ sea level

Physical

Operating Temperature	-30°C to +85°C
Index of Protection	2MIH-Series: IP67 2MS-Series: IP67
Solder Heat Resistance	MIL-STD-202, Method 210
Actuator Travel	25°

Material

Case	2MIH-Series & 2MI-Series: Dially phthalate (DAP) (UL 94V-0) 2MS-Series: Glass filled nylon 6/6, flame retardant, heat stabilized (UL 94V-0)
Toggle	2MIH-Series: Brass, black finish with o-ring seal 2MS-Series: Brass, chrome plated, internal o-ring sealed 2MI-Series: Brass, chrome plated
Bushing	2MIH-Series: Brass, black finish with o-ring seal 2MS-Series: Glass filled nylon 6/6, flame retardant, heat stabilized (UL 94V-0) 2MI-Series: Brass, nickel plated
Housing	Stainless Steel
Bracket	2MS-Series: Nylon (UL 94V-0) 2MI-Series: Stainless Steel
Actuator Retainer	2MS-Series: Stainless Steel
Switch Support	Brass, tin plated
Terminal Seal	Epoxy

Ordering Scheme

Sample Part Number: **2MIH** - **DP1** **TJ** - **BK** - **M2** **R** **E**

Selection: 1 2 3 4 5 6 7

1. SERIES

2MIH Premium Sealed Miniature Toggle Switch

2. POLES / CIRCUIT

() - momentary		
Position:	1	2
	2-3, 5-6	Connected Terminals
SP1	ON	NONE
SP2	ON	NONE
SP3	ON	OFF
SP4	(ON)	OFF
SP5	ON	OFF
DP1	ON	NONE
DP2	ON	NONE
DP3	ON	OFF
DP4	(ON)	OFF
DP5	ON	OFF
DP6 *	ON	ON
DP7 *	(ON)	ON
DP8 *	ON	ON

*Center position connects 2-3, 5-4

3. ACTUATOR STYLE

TJ .709" [18 mm] length **TK** .512" [13.00 mm] length

4. BUSHING

BK .386" [9.80 mm] threaded, flat

5. TERMINATION

M1 Solder Lug	M51 Wire Wrap, .750" [19.05mm] length
M2 PCB	M52 Wire Wrap, .964" [24.48mm] length
M3 Quick Connect	M53 Wire Wrap, .425" [10.80mm] length
	M54 Wire Wrap, 1.062" [25.97mm] length

6. CONTACTS / TERMINALS

Contact Material	Terminal Plating	Rating	Approvals
G silver ¹	gold over silver	5A 125VAC or 28VDC, 2A 250VAC	IP67
K gold ^{2,5}	tin ^{4,7}	0.4VA max 20V max (AC/DC)	IP67
P silver ^{1,6}	tin ^{4,7}	5A 125VAC or 28VDC, 2A 250VAC	IP67
Q silver ¹ silver ¹	5A	125VAC or 28VDC, 2A 250VAC	IP67
R gold ² gold ³	0.4VA max	20V max (AC/DC)	IP67

7. EPOXY SEAL

E Epoxy Seal

Notes: Switches supplied with (1) 2MI-HDW4 hex nut and (1) 3MNH-WCP-0872 O-Ring
 1 Movable contact and terminal platings: silver over copper alloy
 2 Movable contact and terminal platings: gold over nickel over copper alloy
 3 Terminal platings: gold over nickel over copper alloy
 4 Terminal platings: tin over copper alloy
 5 Terminal contact platings: gold over nickel alloy
 6 Terminal contact platings: silver over nickel alloy
 7 Tin option not available with M1 & M3 terminations.

[Configure Complete Part Number >](#)

[Browse Standard Parts >](#)

Ordering Scheme

Sample Part Number **2MS - WSP 1 - T1 - B4 - M1 G E**

Selection 1 2 3 4 5 6 7 8

1. SERIES

2MS Sealed Miniature Toggle Switch

2. POLES

WSP Single pole - uses terminals 1, 2 & 3
WDP Double pole - uses terminals 1, 2, 3, 4, 5 & 6
W3P Three pole - uses terminals 1, 2, 3, 4, 5, 6, 7, 8 & 9

3. CIRCUIT

() - momentary
Position:

1	2	3
2-3, 5-6	Connected Terminals	2-1, 5-4
1 ON	NONE	ON
2 ON	NONE	(ON)
3 ON	OFF	ON
4 (ON)	OFF	(ON)
5 ON	OFF	(ON)

4. ACTUATOR STYLE

T1 Round Bat **P1** Plastic Anti-Static .496" length
T2 Round Short Bat **P2** Plastic Anti-Static .299" length
T9 Long Black Plastic .492" length

5. BUSHING

B1 Threaded, Keyway **B4** Unthreaded, Short, Keyway, Flat

Notes:
B1 Bushing switches supplied with (2) 2M1-HDW2 nuts, (1) 2M1-HDW11 washer and (1) 2M1-HDW15 locking ring.
1 Movable contact & terminal platings: silver over copper alloy
2 Movable contact & terminal platings: gold over nickel over copper alloy
3 Terminal platings: tin over nickel over copper alloy
4 Tin option not available with M1 terminal

6. TERMINATION

M1 Solder Lug	VS21 Vertical, Snap-In, .460" [11.70mm]
M2 PCB	VS3 Vertical, .630" [16mm]
M3 Quick Connect	VS31 Vertical, Snap-In, .630" [16mm]
M51 Wire Wrap, .750" [19.05mm]	U2 Vertical, .551" [14mm] - only 3PDT
M52 Wire Wrap, .964" [24.48mm]	VS4 Vertical, .461" [11.70mm]
M53 Wire Wrap, .425" [10.80mm]	VS41 Vertical, Snap-In, .461" [11.70mm]
M54 Wire Wrap, 1.062" [25.97mm]	U4 Vertical, .551" [14mm] - only 3PDT
M6 Right Angle, PC Thru-Hole	VS5 Vertical, .630" [16mm]
M61 Right Angle, Snap-In	VS51 Vertical, Snap-In, .630" [16mm]
M7 Vertical, Right Angle, PC Thru-Hole	
M71 Vertical, Right Angle, Snap-In	
VS2 Vertical, .461" [11.70mm]	

7. CONTACTS / TERMINALS

Contact Material	Terminal Plating	Rating	Approvals
G silver ¹	gold over silver	5A 125VAC or 28VDC, 2A 250VAC	IP67
K gold ²	tin 3, 4	0.4VA max 20V max (AC/DC)	IP67
P silver ¹	tin 3, 4	5A 125VAC or 28VDC, 2A 250VAC	IP67
R gold ²	gold ²	0.4VA max 20V max (AC/DC)	IP67

8. EPOXY SEAL

E Epoxy Seal **0** without Epoxy Seal

[Configure Complete Part Number >](#)

[Browse Standard Parts >](#)

Sample Part Number **2M1 - SP 1 - T1 - B1 - M1 Q E**

Selection 1 2 3 4 5 6 7 8

1. SERIES

2M1 Miniature Toggle Switch

2. POLES

SP Single pole - uses terminals 1, 2 & 3
DP Double pole - uses terminals 1, 2, 3, 4, 5 & 6
3P Three pole - uses terminals 1, 2, 3, 4, 5, 6, 7, 8 & 9
4P Four pole - uses terminals 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11 & 12

3. CIRCUIT

() - momentary
Position:

1	2	3
2-3, 5-6, 8-9, 11-12	Connected Terminals	2-1, 5-4, 8-7, 11-10
1 ON	NONE	ON
2 ON	NONE	(ON)
3 ON	OFF	ON
4 (ON)	OFF	(ON)
5 ON	OFF	(ON)
6* ON	ON	ON
7* (ON)	ON	(ON)
8* ON	ON	(ON)

*Available with DP and 4P switches only. Center position connects 2-3, 5-4, 8-9, 11-10

4. ACTUATOR STYLE

T1 Round Bat	T7 Large Bat (B0 bushing)
T2 Round Short Bat	T8 X-Large Bat (B0 bushing)
T3 Paddle	T9 Black Plastic
T4 Medium Paddle	T0 Rectangular
TA Locking Lever	TA Locking Lever
T5 Long Paddle	TI Locking Lever
T6 Flat (B1,B2,B5,BA,BB,BE)	TL Locking Lever

Notes: B1 Bushing switches supplied with (2) 2M1-HDW2 nuts, (1) 2M1-HDW11 washer and (1) 2M1-HDW15 locking ring.

1 Movable contact & terminal platings: silver over copper alloy
2 Movable contact & terminal platings: gold over nickel over copper alloy
3 Terminal platings: tin over nickel over copper alloy
4 Tin option not available with M1 terminal Movable contact & terminal platings: silver over copper alloy
5 Movable contact & terminal platings: gold over nickel over copper alloy
6 Terminal platings: tin over nickel over copper alloy
7 Tin option not available with M1 terminal

5. BUSHING

B1 Threaded Standard, keyway	B9 Splashproof
B2 Non-Threaded Standard, keyway	B0 15/32" Threaded (Standard for T7 & T8 actuator styles)
B3 Threaded Short, keyway	BA Threaded for T6
B4 Non-Threaded Short, keyway	BA Threaded for T6
B5 High Torque, 7.5mm, flat	BB Non-Threaded for T6
B6 High Torque, 8.0mm, keyway	BE Threaded Hi Torque for T6
B7 Long threaded	BL Threaded, Locking
B8 Metric	

6. TERMINATION

M1 Solder Lug	VS21 Vertical, Snap-In, .460" [11.70mm]
M2 PCB	VS3 Vertical, .630" [16mm]
M3 Quick Connect	VS31 Vertical, Snap-In, .630" [16mm]
M51 Wire Wrap, .750" [19.05mm]	U2 Vertical, .551" [14mm] - only 3PDT
M52 Wire Wrap, .964" [24.48mm]	VS4 Vertical, .461" [11.70mm]
M53 Wire Wrap, .425" [10.80mm]	VS41 Vertical, Snap-In, .461" [11.70mm]
M54 Wire Wrap, 1.062" [25.97mm]	U4 Vertical, .551" [14mm] - only 3PDT
M6 Right Angle, PC Thru-Hole	VS5 Vertical, .630" [16mm]
M61 Right Angle, Snap-In	VS51 Vertical, Snap-In, .630" [16mm]
M7 Vertical, Right Angle, PC Thru-Hole	
M71 Vertical, Right Angle, Snap-In	
VS2 Vertical, .461" [11.70mm]	

7. CONTACTS / TERMINALS

Contact Material	Terminal Plating	Rating	Approvals
G silver ¹	gold over silver	5A 125VAC or 28VDC, 2A 250VAC	IP67
K gold ²	tin 3, 4	0.4VA max 20V max (AC/DC)	N/A
P silver ¹	tin 3, 4	5A 125VAC or 28VDC, 2A 250VAC	IP67
Q silver ¹	silver ¹	5A 125VAC or 28VDC, 2A 250VAC	IP67
R gold ²	gold ²	0.4VA max 20V max (AC/DC)	N/A

8. EPOXY SEAL

E Epoxy Seal **0** without Epoxy Seal

[Configure Complete Part Number >](#)

[Browse Standard Parts >](#)

Ordering Scheme Accessories

2M-Series Accessories

To order accessories assembled on a switch, specify the switch number followed by the accessory part number and the word "assembled".
Ex: 2M1-SPI-T1-B1-MIQE-T12 ASSEMBLED. To order accessories in bulk, specify the Series, followed by the accessory. Ex: 2M1-T12. See page 76 for dimensional specifications.

Optional Toggle Cap

Sample
Part Number 2M1 - T1 2

Selection 1 2 3

1. SERIES

2M1 Fits 2M1H, 2MS or 2M1

2. TOGGLE CAP SIZE

T1 10.6 mm **T2** 7.6 mm

3. CAP COLOR

1	White	5	Yellow
2	Black	6	Green
3	Red	7	Blue

Optional Dress and Knurled Nuts

Sample
Part Number 2M1 - HDW3

Selection 1 2

1. SERIES

2M1 Fits 2M1H, 2MS or 2M1

2. NUT

HDW3 Dress nut for 1/4" bushing
HDW5 Knurled nut for 15/32" bushing (2M1-Series only)

Optional Rubber Seals

Sample
Part Number 2M1 - E1A

Selection 1 2

1. SERIES

2M1 Fits 2M1H, 2MS or 2M1

2. RUBBER BOOT SEAL

E1A 1/4 - 40" UNS bushing (Not available for B0 bushing option)
K1 Metric M6 bushing (B8 bushing only)
YE1D 15/32 - 32" UNS bushing (TJ, TK and B0 bushings only)
YE1E 15/32 - 32" UNS bushing 1/2 boot (T7, T8, TJ, TK and B0 bushings only)

Sample
Part Number 3MNH - WCP-0872

Selection 1 2

1. SERIES

3MNH Fits 3MNH or 2M1H


2. RUBBER O-RING

WCP-0872 For 15/32 bushing option


Dimensional Specs

inches [millimeters]


Single Pole



Double Pole




Actuator Options



OPTION CODE	DIM. "A"
TJ	.709 [18.00]
TK	.512 [13.00]


Bushing Options & Mounting




OPTION CODE	DIM. "A"
BK	.386 [9.80]

Termination Options


M1 Standard Solder Lug




M2 PC Thru-Hole



M3 Quick Connect



M5 Wire Wrap




OPTION CODE	DIM. "A"
M5-1	.750 [19.05]
M5-2	.964 [24.48]
M5-3	.425 [10.80]
M5-4	1.062 [26.97]


Dimensional Specs

inches [millimeters]


Single Pole



Double Pole




Three Pole




Actuator Options


T1



T2




T9 with Plastic Cap





NO.	COLOR
1	White
2	Black(std.)
3	Red
4	Orange
5	Yellow
6	Green
7	Blue
8	Brown
9	Gray

P1 Plastic Toggle



P2 Plastic Toggle




* Shown with B4 bushing. Subtract 0.75" (1.90mm) from actuator height for B1 bushing.

Dimensional Specs


inches [millimeters]

Bushing Options

B1




B4




Termination Options


M1 Standard Solder Lug




M2 PC Thru-Hole



M3 Quick Connect






M5 Wire Wrap




OPTION CODE	DIM.'A'
M5-1	.750 [19.05]
M5-2	.964 [24.48]
M5-3	.425 [10.80]
M5-4	1.062 [26.97]




M6 Single Pole




P.C.MOUNTING






M6 Double Pole




P.C.MOUNTING






M6 Three Pole




P.C.MOUNTING



M7 Single Pole



P.C.MOUNTING






Dimensional Specs


inches [millimeters]

Termination Options




M7 Double Pole




P.C.MOUNTING





M7 Three Pole



P.C.MOUNTING




VS2-VS3 Single Pole





OPTION CODE	DIM.'A'
VS2	.461 [11.70]
VS3	.630 [16.00]

P.C.MOUNTING




VS2-VS3 Double Pole





OPTION CODE	DIM.'A'
VS2	.461 [11.70]
VS3	.630 [16.00]

P.C.MOUNTING




U2-VS3 Three Pole



OPTION CODE	DIM.'A'
U2	.551 [14.00]
VS3	.630 [16.00]

P.C.MOUNTING





Dimensional Specs

inches [millimeters]


Termination Options

VS4-VS5 Single Pole





OPTION CODE	DIM.'A'
VS4	.461 [11.70]
VS5	.630 [16.00]

P.C.MOUNTING




VS4-VS5 Double Pole





OPTION CODE	DIM.'A'
VS4	.461 [11.70]
VS5	.630 [16.00]

P.C.MOUNTING




U4-VS5 Three Pole




OPTION CODE	DIM.'A'
U4	.551 [14.00]
VS5	.630 [16.00]

P.C.MOUNTING




Snap-In Termination Options


M61




VS21, VS31



M71



VS41, VS51




* PC Mounting for M61, M71, VS21, VS31, VS41, VS51 refer to M6, M7, VS2, VS3, VS4, VS5 respectively.


Dimensional Specs

inches [millimeters]


Single Pole




Double Pole




Three Pole



Four Pole




Actuator Options for Panel Rear Mount



* T6 actuator is available with B1, B2, B5, B6, BA, BB & BE bushing. Actuator length shown for T1-T5, T9 and T10 is with B1 bushing. T7, P7, P8 does not require a bushing code.


Locking Lever

TA



FOR SP-1,DP-1
3P-1,4P-1 ONLY


TI




FOR SP-3,DP-3
3P-3,4P-3 ONLY

Locking Lever

TL




FOR SP-1,DP-1
3P-1,4P-1 ONLY




FOR SP-3,DP-3
3P-3,4P-3 ONLY

Locking Lever

TL




FOR SP-1,DP-1
3P-1,4P-1 ONLY




FOR SP-3,DP-3
3P-3,4P-3 ONLY

Bushing Options


B1 Threaded B2 Non-Threaded




B3 Threaded B4 Non-Threaded



B5 High Torque




B6 High Torque




Dimensional Specs

inches [millimeters]


B7 Long





B8 Metric




B9 Splash-Proof




BL Locking Lever




BA Threaded for T6



BB Non-Threaded for T6




BB High Torque for T6




Panel Mounting

1/4 INCH BUSHING




15/32 INCH BUSHING




Termination Options


M1 Standard Solder Lug




M2 PC Thru-Hole



M3 Quick Connect






M5 Wire Wrap




OPTION CODE	DIM.'A'
M5-1	.750 [19.05]
M5-2	.964 [24.48]
M5-3	.425 [10.80]
M5-4	1.062 [26.97]




M6 Single Pole




P.C.MOUNTING



M6 Double Pole



P.C.MOUNTING






Dimensional Specs


inches [millimeters]

Termination Options




M6 Three Pole




P.C.MOUNTING






M7 Single Pole




P.C.MOUNTING






M7 Double Pole




P.C.MOUNTING






M7 Three Pole




P.C.MOUNTING





M7 Four Pole



P.C.MOUNTING




VS2-VS3 Single Pole



OPTION CODE	DIM.'A'
VS2	.461 [11.70]
VS3	.630 [16.00]

P.C.MOUNTING





Dimensional Specs

inches [millimeters]


Termination Options

VS2-VS3 Double Pole





OPTION CODE	DIM.'A'
VS2	.461 [11.70]
VS3	.630 [16.00]

P.C.MOUNTING




VS4-VS5 Single Pole





OPTION CODE	DIM.'A'
VS4	.461 [11.70]
VS5	.630 [16.00]

P.C.MOUNTING




VS4-VS5 Double Pole




OPTION CODE	DIM.'A'
VS4	.461 [11.70]
VS5	.630 [16.00]

P.C.MOUNTING




Snap-In Termination Options


M61 (available with SP & DP)




VS21, VS31



M71 (available with SP & DP)



VS41, VS51



* PC Mounting for M61,M71,VS21,VS31,VS41,VS5 1 refer to M6,M7,VS2,VS3,VS4,VS5 respectively.