Wiha Power Blade Sets

Blade Holder For Power Blades



76000 CentroFix Cushion Grip Blade Holder
Wiha-SoftFinish® impact resistant, with roll off protection. Ergonomic cushion grip handle. Quick release bit holder with magnet.

Item No.	mm	mm	Inch	mm	Inch	lbs.
76000	6.0	149	5.9	34.6	1.36	.26



76079 Canvas Belt Wallet Storage Pouch
Holds 38 90mm power blades. Folding pouch.

Item No.	Size	lbs.	pkg.
76079	7-1/8" x 6" x 2"	.42	1



76087 61 Pc. Power Blade Service Kit, In Durable Zipper Case Set includes Bit Holding Handle, MicroBit Storage Handle, 4mm to 1/4" Magnetic Adapter, 9 power blades, 46 bits & 3 nut setters.

Item No. 76087 lbs. 1.34
90mm Power Blades: Slotted: 4.5, 5.5, 6.0mm
Phillips: #1, 2, 3 & **Square:** #1, 2, 3
75mm Security TORX® Bits: T10s, T15s, T20s, T25s, T27s, T30s
MicroBits: Phillips: #000, 00, 0, 1, 2, **Slotted:** .8, 1.2, 1.5, 1.8, 2.0, 2.5, 3.0, 3.5, 4.0mm
Hex Inch: .028, .035, .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
Hex Metric: 1.3, 1.5, 2.0, 2.5, 3.0, 4.0mm
TORX®: T1, T2, T3, T4, T5, T6, T7, T8, T9, T10
Magnetic Nut Setters: 1/4, 5/16, 3/8"



76099 37 Pc. Power Blade Set, In Durable Belt Pack Set includes cushion grip CentroFix Blade Holder & 36 interchangeable blades.

Item No. 76099 lbs. 2.06
Slotted: 2.5, 3.0, 4.5, 5.5, 6.0mm
Phillips: #0, 1, 2, 3
Security TORX®: T8s, T9s, T10s, T15s, T20s, T25s, T27s, T30s
Security Hex Inch: 1/16*, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4"
Pozidriv®: #1, 2, 3 & **Square:** #1, 2, 3
4" Nut Setters: 1/4, 5/16, 3/8"
Cushion Grip CentroFix Blade Holder
* 1/16" Standard Inch Hex Only



76098 36 Pc. Power Blade Set, In Durable Belt Pack Set includes cushion grip CentroFix Blade Holder & 35 interchangeable blades.

Item No. 76098 lbs. 1.86
Slotted: 2.5, 3.0, 4.5, 5.5, 6.0mm
Phillips: #0, 1, 2, 3
Security TORX®: T8s, T9s, T10s, T15s, T20s, T25s, T27s, T30s, T40s
Security Hex Metric: 2.5, 3.0, 4.0, 5.0mm
Pozidriv®: #1, 2, 3 & **Square:** #1, 2, 3
Spanner: #6, 8, 10 & **Tri-Wing:** #1, 2, 3, 4
Cushion Grip CentroFix Blade Holder

Inch



76085 9 Pc. Power Blade Nut Driver Set
30mm deep drilled Nut drivers. Use with #76000 CentroFix Blade Holder. 100mm OAL

Item No. 76085 lbs. .96
Inch: 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2"

Metric



76086 12 Pc. Power Blade Nut Driver Set
30mm deep drilled Nut drivers. Use with #76000 CentroFix Blade Holder. 100mm OAL

Item No. 76086 lbs. 1.22
Metric: 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0mm



76084 12 Pc. Power Blade Inch & Metric Nut Driver Set 30mm deep drilled Nut drivers. Use with #76000 CentroFix Blade Holder. 100mm OAL

Item No. 76084 lbs. 2.97
Inch: 3/16, 7/32, 1/4, 9/32, 5/16, 11/32, 3/8, 7/16, 1/2"
Metric: 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0, 9.0, 10.0, 11.0, 12.0, 13.0mm
Cushion Grip CentroFix Blade Holder

Wiha SYSTEM 4 Micro Bit Sets



75980 SYSTEM 4 Master Tech Micro Bit Set, 68 Pcs. Includes Wiha ESD Safe Precision Handle, 1/4" to 4mm Adapter, 100mm Bit Extension & 36 Micro Bits.

Item No.	SYSTEM 4 Micro Bit Set
75980	Includes The Following Bits:
	Slotted: 0.8, 1.2, 1.5, 1.8, 2.0, 2.5, 3.0, 3.5, 4.0mm
	Phillips: 000, 00, 0, 1, 2
	TORX®: T1, T2, T3, T4, T5, T6, T7, T8, T9, T10
	Hex Metric: 1.3, 1.5, 2.0, 2.5, 3.0, 4.0mm
	Pentalobe: PL1, PL2, PL3, PL4, PL5, PL6
lbs.	.38



75993 SYSTEM 4 Premium ESD Safe Micro Bit Set, 28 Pcs. Includes Wiha ESD Safe Precision Handle, 1/4" to 4mm Adapter, 100mm Bit Extension, ESD Safe Tweezers & 21 Micro Bits.

Item No.	SYSTEM 4 Micro Bit Set
75993	Micro Bits:
	Slotted: 0.8, 1.5, 2.0, 2.5, 3.0, 3.5mm
	Phillips: 000, 00, 0, 1, 2
	TORX®: T1, T2, T3, T4, T5, T6, T7, T8, T9, T10
	ESD Safe Tweezers: 5SA ESD, 7aSA ESD, 2ASA ESD, AASA ESD, OOSA ESD
lbs.	.95



75968 SYSTEM 4 Master Tech Micro Bit Set, 68 Pcs. Includes Wiha ESD Safe Precision Handle, Micro Bit Storage Handle, 1/4" to 4mm Adapter, 100mm Bit Extension & 64 Micro Bits.

Item No.	SYSTEM 4 Micro Bit Set
75968	Includes The Following Bits:
	Slotted: 0.8, 1.2, 1.5, 1.8, 2.0, 2.5, 3.0, 3.5, 4.0mm
	Phillips: 000, 00, 0, 1, 2
	TORX®: T1, T2, T3, T4, T5, T6, T7, T8, T9, T10, T15, T20
	Hex Metric: 1.3, 1.5, 2.0, 2.5, 3.0, 4.0mm
	Hex Inch: .028, .035, .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
	Pentalobe: PL1, PL2, PL3, PL4, PL5, PL6
	Nut Driver Metric: 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5mm
	Nut Driver Inch: 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32"
lbs.	.70



75971 SYSTEM 4 Master Tech Micro Bit Set, 68 Pcs. Includes Wiha ESD Safe Precision Handle, Micro Bit Storage Handle, 1/4" to 4mm Adapter, 100mm Bit Extension & 64 Micro Bits.

Item No.	SYSTEM 4 Micro Bit Set
75971	Includes The Following Bits:
	Slotted: 0.8, 1.2, 1.5, 1.8, 2.0, 2.5, 3.0, 3.5, 4.0mm
	Phillips: 000, 00, 0, 1, 2
	TORX®: T1, T2, T3, T4, T5, T6, T7, T8, T9, T10, T15, T20
	Hex Metric: 1.3, 1.5, 2.0, 2.5, 3.0, 4.0mm
	Hex Inch: .028, .035, .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
	Pentalobe: PL1, PL2, PL3, PL4, PL5, PL6
	Nut Driver Metric: 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5mm
	Nut Driver Inch: 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32"
lbs.	.96



75965 SYSTEM 4 Master Tech ESD & Ratchet With Micro Bits, 65 Pieces In Storage Box. Includes Wiha precision ESD Safe handle, micro bit extension, 72 tooth 1/4" ratchet & 62 interchangeable micro bits.

Item No.	Includes the following micro bits:
75965	**Slotted:** 0.8, 1.2, 1.5, 1.8, 2.0, 2.5, 3.0, 3.5, 4.0mm
	Phillips: 000, 00, 0, 1
lbs. 1.16	**TORX®:** T3, T4, T5, T6, T7, T8, T9, T10, T15, T20
	Hex Metric: .7, .9, 1.3, 1.5, 2.0, 2.5, 3.0, 4.0mm
	Hex Inch: .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
	Nut Drivers Metric: 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5mm
	Nut Drivers Inch: 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32"
	Pentalobe: PL1, PL2, PL3, PL4, PL5, PL6
	Magnetic 1/4" to 4mm Adapter



75977 SYSTEM 4 Master Tech Micro Bit Set, 68 Pcs. Includes Wiha ESD Safe Precision Handle, ESD Safe Tweezers, 1/4" to 4mm Adapter, 100mm Bit Extension & 64 Micro Bits.

Item No.	SYSTEM 4 Micro Bit Set
75977	Includes The Following Bits:
lbs. 1.00	**Slotted:** 0.8, 1.2, 1.5, 1.8, 2.0, 2.5, 3.0, 3.5, 4.0mm
	Phillips: 000, 00, 0, 1, 2
	TORX®: T1, T2, T3, T4, T5, T6, T7, T8, T9, T10, T15, T20
	Hex Metric: 1.3, 1.5, 2.0, 2.5, 3.0, 4.0mm
	Hex Inch: .028, .035, .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
	Pentalobe: PL1, PL2, PL3, PL4, PL5, PL6
	Nut Driver Metric: 2.0, 2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5mm
	Nut Driver Inch: 5/64, 3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32"
	ESD Fine Round Point Tweezers 3cSA

ESD Safe Adjustable TorqueControl Tools



Includes Certificate

285 ESD Safe TorqueVario-S, With Window Scale EN ISO 6798, BS EN 26789, ASME B107.14M, +/- 6% Accuracy. Ergonomic multi-component handle, light and compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained. With Certificate of accuracy. Pkg. 1

Item No.	Range Inch lbs.	Increments	mm	lbs.
28522*	15 - 80(in/oz)	2.5 In.oz.	122-127	.33
28524	5 - 10	.2 In.lbs.	122-127	.34

284 ESD Safe TorqueVario-S, W/Window

Item No.	Range Inch lbs.	Increments	mm	lbs.
28426	5 - 18	.5 In.lbs.	126-131	.46



Includes Certificate

28500 ESD Safe TorqueVario-S Newton Meter, With Window Scale

Item No.	Range Nm	mm	Inch	lbs.	pkg.
28500*	.04 - .46	124	4.875"	.35	1

* +/- 10% (This unit only)

Each TorqueVario handle has unique serial number and certificate of calibration

With Certificate of Calibration



Packed in a compact durable storage box

+/- 10%

28890 24 Piece TorqueVario-S ESD Safe Micro-Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool.

Item No.	
	Slotted: 1.5, 2.0, 3.0, 4.0mm
28890	**Phillips:** #00, #0, #1
	TORX®: T6, T7, T8, T9, T10, T15
lbs.	**Hex Inch:** .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
1.35	28522 - ESD Safe Handle Range 15-80 Inch/oz.

With Certificate of Calibration



28591 24 Piece ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.	
	Slotted: 1.5, 2.0, 3.0, 4.0mm
28591	**Phillips:** #00, #0, #1
	TORX®: T8, T7, T8, T9, T10, T15
lbs.	**Hex Inch:** .050, 1/16, 5/64, 3/32, 7/64, 1/8, 9/64, 5/32"
1.57	28524 - Handle ESD Safe Range 5 - 10 Inch lbs.

With Certificate of Calibration



28895 24 Piece ESD Safe Adjustable TorqueVario-S Bit Set

Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes ergonomic multi-component adjustable TorqueVario-S handle, 21 Micro Bits, Micro Bit holder and Torque adjustment tool, packed in a compact durable storage box.

Item No.	
	Slotted: 0.8, 1.2, 1.5, 2.0mm
28895	**Phillips:** #000, #00, #0
	TORX®: T1, T2, T3, T4, T5, T6
lbs.	**Hex Metric:** 0.7, 0.9, 1.3mm
1.30	**Pentalobe:** PL1, PL2, PL3, PL4 28500 - Handle ESD Safe .04 - .46Nm (+/-10%)



288 ESD Safe Slotted Interchangeable Blades For TorqueVario-S Slotted tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, satin hard chrome finish.

Item No.	mm	Inch	Max. Torque mm	Nm	lbs.	pkg.
28805	3.0	.118	175	0.6	.07	1
28809	4.0	.157	175	2.5	.07	1



288 ESD Safe TORX® Interchangeable Blades For TorqueVario-S

TORX® tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, hard chromed.

Item No.	Size	mm	Max. Torque mm	Nm	lbs.	pkg.
28825	T5	175	4.0	0.4	.07	1
28827	T7	175	4.0	0.9	.07	1
28828	T8	175	4.0	1.3	.07	1
28829	T9	175	4.0	2.5	.07	1
28830	T10	175	4.0	3.8	.07	1



28818 ESD Safe Pentalobe Interchangeable Blades For TorqueVario-S Newton Meter Handle tip blades on narrow 5/32 Hex shafts. High alloy CVM steel, hardened, hard chromed.

Item No.	Size	mm	mm	lbs.	pkg.
28818	PL1	175	4.0	.07	1



28882 ESD Safe Bit Holder Adapter For 1/4" Drive Bits Shaft CVM steel, hardened, corrosion protected. (Not for use in Insulated handles)

Item No.	Size	mm	mm	lbs.	pkg.
28882	1/4	162	4.0	.09	1

Wiha Insulated 1/2" Socket accessories



⚠1000Volt

12853 **Insulated 1/2" Drive Ratchet, IEC/EN 60900 & CSA**

Chrome-Vanadium steel. Reversible.

Item	OAL		OAL		
No.	Inch	mm	Inch	lbs.	pkg.
12853	1/2"	260	10.2	1.55	1



⚠1000Volt

128 **Insulated 1/2" Extension Bars, EN/IEC 60900 & CSA**

Chrome-vanadium steel.

Item	OAL		OAL		
No.	Inch	mm	Inch	lbs.	pkg.
12858	1/2"	125	4.9	.45	1
12859	1/2"	250	9.8	.91	1



⚠1000Volt

29012 **Insulated 1/2" Drive T-handle, With Insulated Handle. Insulation according to EN/IEC 60900 & CSA Specification, Up To 1000 Volt. Individually Tested** Blade VC steel, hardened.

Item		OAL	OAL		
No.	Inch	mm	Inch	lbs.	pkg.
29012	1/2	200	7.9"	.68	1



⚠1000Volt

12326 **Insulated 1/2" Drive Breaker Bar, IEC/EN 60900 & CSA**

Chrome-Vanadium steel.

Item	OAL		OAL		
No.	Inch	mm	Inch	lbs.	pkg.
12326	1/2"	267	10.5	1.04	1

Wiha Insulated Hacksaw



Uses standard 12" blade

⚠1000Volt

19767 **Hacksaw, With Insulated Handle Insulation According to EN/IEC 60900, DIN ISO, ASTM & CSA Specification, Up To 1000 Volt. Individually Tested.**

Item	OAL	OAL		
No.	mm	Inch	lbs.	pkg.
19767	457mm	18.0"	1.92	1

Insulated Waterpump Pliers



⚠1000Volt

29240 **Waterpump Pliers, With Insulated Handle. Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested** Box joint. Chrome-vanadium steel, drop forged, oil hardened.

Item	OAL	OAL	Capacity		
No.	mm	Inch	mm	lbs.	pkg.
29240	240	9.5	7/8"	1.1	1

Insulated Pliers Wrench



1-7/8" / 49mm Jaw Capacity

NEW



⚠1000Volt

11610 **Pliers Wrench, With Insulated Handle Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification, Up To 1000 Volt. Individually Tested.** Chrome-vanadium steel, drop forged, oil hardened.

Item	OAL	OAL		
No.	mm	Inch	lbs.	pkg.
11610	254	10.0"	1.67	1

Insulated Cable Cutters



⚠1000Volt

For cutting solid aluminum & copper conductors

11950 **Cable Cutter, With Insulated Handle. Insulation According to EN/IEC, ASTM & CSA Specification, Up To 1000 Volt. Individually Tested.** Blade alloyed tool steel. Induction hardened.

Item	OAL	OAL	Capacity			
No.	mm	Inch	mm	Inch	lbs.	pkg.
11950	500	19.6	12	1/2"	3.0	1

For cutting multi strand aluminum & copper cables

31.5"



⚠1000Volt

40800 **Large Capacity Cable Cutter, With Insulated Handle Insulation According to EN/IEC 60900, ASTM F-1505 & CSA Specification, Up to 1000 Volt. Individually Tested.** Easy cutting blades, dropped forged, oil hardened. Cuts cable diameters up to 50mm. Not to be used on steel rods.

Item	OAL	OAL	Capacity			
No.	mm	Inch	mm	Inch	lbs.	pkg.
40800	800	31.5	50	2"	8.0	1

For cutting solid aluminum, copper & medium hard wires




⚠1000Volt

29250 **End Cutters, With Insulated Handle. Insulation According to EN/IEC 60900, DIN ISO 8976, ASTM F-1505 & CSA Specification. Individually Tested.** Blade alloyed tool steel. Induction hardened.

Item	OAL	OAL	Capacity		
No.	mm	Inch	mm	lbs.	pkg.
29250	250	10	7/8"	1.1	1

Wiha Inomic 1000Volt Insulated Pliers





△1000volt

32850 **Inomic Combo Pliers. Insulation According to EN/IEC 60900, ASTM F-1505, NFPA70E & CSA, △up to 1000 volt. Individually Tested. DIN ISO 5749** Precision machined forged head. Induction hardened for longest tool life. Cross hatched flat jaw & deep cut radius jaws for secure gripping of the work piece. Cutting edges are matched for precise cutting action. Award winning ergonomic design with head mounted at 23° angle to grip for reduced user fatigue. Palm side of grip has molded soft panel for added comfort in prolonged use.

Item			Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32850	180	7.0	#6	1	.46

32852 **Inomic Long Nose Pliers**

Item			Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32852	160	6.3	#6	1	.43

32854 **Inomic Diagonal Cutters**

Item			Cutting Capacity		
No.	mm	Inch	Copper AWG	Pkg.	lbs.
32854	160	6.3	#6	1	.41



Holds any Inomic Pliers

91230 **Inomic Canvas Holster**

Item	Width		Height	lbs.	pkg.
No.	Size		Size		
91230	4.0	x	4.5	.05	1

Proturn Insulated Electrician's Shears



32951 **Proturn Insulated Electrician's Shears**
Insulation meets VDE, ASTM F1505, EN/IEC 60900, CSA, NFPA 70E, OSHA Specifications. Made from stainless 420 grade steel

Item				
No.	mm	Inch	Pkg.	lbs.
32951	160	6.3	1	.22

Meets VDE, EN/IEC, ASTM, CSA, NFPA standards



With Wire Puller Slot



61630 **Insulated Inch & Metric Folding Ruler**
10,000Volt Tested/1000Volt Rated. Inch & Metric deep embossed scales. 10 folding sections. 30% fiberglass reinforced polyimide.

Item						
No.	Meter	Inch	Sections	Increments	lbs.	pkg.
61630	2	78"	10	1/16 & 1mm	.31	1

Insulated Water Pump Pliers



△1000volt

32954 **Insulated Industrial Water Pump Pliers. Insulation According to VDE, EN/IEC, ASTM, NFPA70E & CSA, △up to 1000 Volt. Individually Tested.** 10 opening settings provides optimal adjustment to objects being gripped. Long life achieved through additional induction hardening of jaws to approx. 62HRC. Chrome-vanadium tool steel forgings, hardened and tempered. Black finish.

Item			Capacities			
No.	mm	Inch	Round	Hex	Pkg.	wt.
32954	250	10.0	1 3/4	2	1	.90

Rapid & simple push button setting & locking



△1000volt

32956 **Insulated Industrial Push Button Water Pump Pliers. Insulation According to VDE, EN/IEC, ASTM, NFPA70E & CSA, Individually Tested.** Extra narrow head for working in small spaces. Long life achieved through additional induction hardening of jaws to approx. 62HRC. Finger jam protection for safe operation at all settings. CVM tool steel forgings, hardened & tempered.

Item			Capacities			
No.	mm	Inch	Round	Hex	Pkg.	wt.
32956	250	10.0	1 3/4	2"	1	.90

Wiha Insulated Torque Ratchet Wrenches





301 **Insulated Torque Ratchet Wrenches, 1/4, 3/8, 1/2" Drives Insulated to EN/IEC 60900:2004, ASTM F1505, CSA Standards** Visible reading scale for easy reading and adjustment. Locking endcap Torque adjuster for easy adjustment. Accuracy +/- 10%. Dual scale reading Ft. lbs. / Nm.

Item No.	Inch	OAL mm	OAL Inch	Nm	lbs.	pkg.
30114	1/4"	210	8.25	5-25	1.02	1
30138	3/8"	370	14.5	5-50	2.72	1
30152	1/2"	530	21.0	40-220	3.64	1

Wiha Insulated TorqueControl & SlimLine Tool Sets

In Roll-up Pouch



1000Volt





28792 **16 Piece Insulated TorqueControl Set With SlimLine Blades** Certified to EN ISO 6798, BS EN 26789, ASME B107.14M. Set includes Insulated multi-component adjustable TorqueVario-S handle, 13 SlimLine blades, SlimLine blade holder & Torque adjustment tool.

Item No.	
28792	**SlimLine Slotted:** 4.0, 5.5, 6.5mm
	SlimLine Phillips: #1, 2
	SlimLine Terminal Xeno: #1, 2
	SlimLine TORX®: T8, T10, T15, T20
	SlimLine Square: #1, 2
	28727 - Handle Range 18-62 Inch/lbs.
	SlimLine Blade Holder
	lbs. 1.27

With Certificate of Calibration

In Roll-up Pouch

With Certificate of Calibration

1000Volt



Certified to EN ISO 6798, BS EN 26789, ASME B107.14M Specifications



28791 **8 Piece Insulated TorqueControl Set With Slotted & Phillips SlimLine Blades** Set includes Insulated multi-component adjustable TorqueVario-S handle, 5 SlimLine blades, SlimLine blade holder & Torque adjustment tool.

Item No.	
28791	**Slotted:** 3.0, 4.0, 5.5mm
	Phillips: #1, 2
	28726-Handle Range 10-50 Inch/lbs.
	lbs. .87

Wiha Insulated TorqueControl Tools



- Includes Certificate
- Includes SlimLine blade holder #28350
- Requires SlimLine Blades



1000Volt

287 **Insulated TorqueVario-S, With Window Scale Insulation** up to 1000Volt EN/IEC, EN ISO, BS EN, ASME & CSA, +/- 6% Accuracy. Ergonomic multi-component handle, light & compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained. In Plastic Tube Holder

Item No.	Range Inch lbs.	Increments	mm	lbs.	pkg.
28750	5 - 18	.5 In/lbs	126-131	.56	1
28751	10 - 50	2 In/lbs	133-136	.74	1
28752	18 - 62	2 In/lbs	137-142	.84	1

287 **Insulated TorqueVario-S Handle - In Newton Meter Scale**

Item No.	Range Nm	mm	lbs.	pkg.
28740	0.5 - 2.0	131	.84	1
28741	1.0 - 5.0	138	.56	1
28742	2.0 - 7.0	142	.84	1

Each TorqueVario handle has unique serial number & certificate of calibration

Wiha Insulated Torque Ratchet Wrench Sets



1000Volt

30190 **16 Pc. Insulated 3/8" Drive Ratcheting Torque Wrench & Socket Set - Inch** CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900.

Item No.	Inch 3/8" Drive Sockets:
30190	1/4, 9/32, 5/16, 11/32, 3/8, 7/16
	1/2, 9/16, 5/8, 11/16, 3/4, 13/16, 7/8"
lbs.	3/8" x 125mm Extension Bar
8.80	3/8" x 250mm Extension Bar
	3/8" Drive Ratcheting Torque Wrench - 5-50 Nm

*Sockets must be used with insulated ratchets & extensions



1000Volt

30192 **16 Pc. Insulated 3/8" Drive Ratcheting Torque Wrench & Socket Set - Metric** CV steel, forged, oil-hardened sockets. Insulated to EN/IEC 60900.

Item No.	Metric 3/8" Drive Sockets:
30192	8, 9, 10, 11, 12, 13, 14, 15, 16,
	17, 18, 19, 20mm
lbs.	3/8" x 125mm Extension Bar
8.80	3/8" x 250mm Extension Bar
	3/8" Drive Ratcheting Torque Wrench - 5-50 Nm

*Sockets must be used with insulated ratchets & extensions

Wiha Insulated TorqueControl Tools

Includes Certificate



1000Volt

*Requires SlimLine blade holder #28350

287 Insulated TorqueVario-S, With Window Scale Insulation up to 1000Volt. **EN/IEC 60900** EN ISO 6798, BS EN 26789, ASME B107.14M &CSA, +/- 6% Accuracy. Ergonomic multi-component handle, light & compact. Handle sizes proportioned to optimize torque range. Audible & perceptible click when torque setting has been attained.

Item No.	Range Inch	lbs.	Increments	mm	lbs.	pkg.
28724	5 - 18		.5 In/lbs	126-131	.43	1
28726	10 - 50		2 In/lbs	133-138	.40	1
28727	18 - 62		2 In/lbs	137-142	.69	1

287 Insulated TorqueVario-S Handle - In Newton Meter Scale

Item No.	Range Nm	mm	lbs.	pkg.
28734	0.5 - 2.0	131	.45	1
28736	1.0 - 5.0	138	.45	1
28738	2.0 - 7.0	142	.72	1

Each TorqueVario handle has unique serial number & certificate of calibration



1000Volt

28350 Insulated SlimLine Torque Blade Holder Chrome-vanadium-molybdenum steel. Through hardened black finish. ClicFix quick release holder securely locks bits.

Item No.	mm	OAL mm	OAL Inch	lbs.	pkg.
28350	6.0	170	6.75	.06	1

NEW

Meets VDE, EN/IEC, ASTM, CSA, NFPA specifications



1000Volt

283 Insulated Easy-TorqueControl Adapters Ideal for torque sensitive terminations. For use with SlimLine blades. Repeatable accuracy to +/- 10%

Item No.	Nm	In/lbs	OAL mm	OAL Inch	lbs.	pkg.
28366	0.8	7.0	60	2.38	.13	1
28367	2.0	17.7	60	2.38	.13	1
28368	2.5	23.1	60	2.38	.13	1
28369	2.8	24.7	60	2.38	.13	1
28371	4.0	35.4	60	2.38	.13	1

Wiha Cushion Grip Stubby SlimLine Blade Holder & Set



1000Volt

28302 SlimLine Stubby Blade Holder, With Wiha-SoftFinish® Handle. Insulation According to VDE, ASTM, EN/IEC, NFPA70E & CSA, up to 1000 Volt. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item No.	Size	mm	Inch	lbs.	pkg.
28302	1/4"	57	2.2	.11	1

1000Volt



slimTECHNOLOGY 33% Narrower

28396 20 Piece Insulated SlimLine Blade Set High quality CV steel, through hardened. Friction hold, stubby cushion grip handle. In zipper case.

Item No.	
28396	**Slotted:** 3.0, 3.5, 4.0, 5.5mm
	Phillips: #1, #2
lbs.	**Xeno SL/PH:** #1, #2
.85	**Xeno SL/PZ:** #1, #2
	TORX®: T8, T10, T15, T20
	Square: #1, #2
	Hex Metric: 3.0, 4.0, 5.0mm
	SlimLine Stubby Blade Holder

Wiha Insulated Pop-Up SlimLine Sets



1000Volt Rated 10,000 Volt Tested

Certified to VDE, EN ISO, BS EN, ASME specifications

"Apprentice"



28393 Insulated Pop-Up "Apprentice" Blade Holder Set With SlimLine Blades Insulated cushion grip multi-component handle. Friction hold bit holder holds SlimLine Blades securely. Convenient rotating cap.

28393	Set includes the following blades:
	Slotted: 3.0, 4.0, 5.5, 6.5mm
	Phillips: #1, #2
	lbs. .38

1000Volt "Residental"



28394 Insulated Pop-Up "Residental" Blade Holder Set With SlimLine Blades

28394	Set includes the following blades:
	Slotted: 3.0, 4.0mm
	Phillips: #1, #2
	Square: #1, #2
	lbs. .38

1000Volt "MRO"



28395 Insulated Pop-Up "MRO" Blade Holder Set With SlimLine Blades

28395	Set includes the following blades:
	Slotted: 3.0, 4.0mm
	Phillips: #1, #2
	Terminal Xeno: #1, #2
	lbs. .38



Each SlimLine bit can be taken in and out of the holder easily and conveniently

Wiha Insulated SlimLine Blade Sets



1000Volt

28391 **8 Piece Insulated SlimLine Blade Set** High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. Up to 33% narrower insulation diameter then standard insulated tools. In roll up pouch

Item No.	
28391	**Slotted:** 4.0, 6.5
	Phillips: #1, #2
	Xeno SL/PH: #2
lbs. .45	**TORX®:** T15, T20
	28301 - SlimLine Blade Holder



1000Volt

28392 **12 Piece Insulated SlimLine Blade Set** High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools. In roll up pouch

Item No.	
28392	**Slotted:** 3.0, 5.5mm
	Phillips: #2
	Xeno SL/PH: #1, #2
lbs.	**Square:** #1, #2
.52	**TORX®:** T8, T10, T15, T20
	28301 - SlimLine Blade Holder



1000Volt

28399 **30 Piece Insulated SlimLine Blade Set** High quality CV steel, through hardened. Friction hold blade holder, holds blades securely. In belt wallet storage pouch.

Item No.	
28399	**Slotted:** 2.5, 3.0, 3.5, 4.0, 5.5, 6.5mm
	Phillips: #1, #2
	Pozidriv®: #1, #2
lbs.	**Xeno SL/PH:** #1, #2
1.20	**Xeno SL/PZ:** #1, #2
	TORX®: T8, T9, T10, T15, T20, T25
	Square: #1, #2
	Hex Metric: 1.5, 2.0, 2.5, 3.0,
	4.0, 5.0, 6.0mm
	28301 - SlimLine Blade Holder



1000Volt

28390 **15 Piece Insulated SlimLine Blade Set** High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. Up to 33% narrower insulation diameter then standard insulated tools. In roll up pouch

Item No.	
28390	**Slotted:** 3.0, 4.0, 5.5, 6.5
	Phillips: #1, #2
	Xeno SL/PH: #1, #2
lbs.	**TORX®:** T8, T10, T15, T20
.56	**Square:** #1, #2
	28301 - SlimLine Blade Holder



1000Volt

28398 **19 Piece Insulated SlimLine Blade Set** High quality CV steel, through hardened. Cushion grip. Friction hold blade holder, holds blades securely. In zipper case

Item No.	
28398	**Slotted:** 3.0, 4.0, 5.5mm
	Phillips: #1, #2
lbs.	**Xeno SL/PH:** #1, #2
.64	**Xeno SL/PZ:** #1, 2
	TORX®: T8, T10, T15, T20
	Square: #1, 2
	Hex Metric: 3.0, 4.0, 5.0mm
	28301 - SlimLine Blade Holder

Wiha Cushion Grip SlimLine Blade Holder



1000Volt

28301 **SlimLine Blade Holder, With Wiha-SoftFinish® Handle Insulation According to VDE, ASTM F-1505 and EN/IEC 60900, NFPA70E & CSA, up to 1000 Volt.** Chrome-vanadium steel, through-hardened. Insulation molded directly onto blade. Blade holder, holds blades securely. Wiha-SoftFinish® handle, multi-component, cushion grip.

Item						
No.	Size	mm	Inch	mm	Inch	lbs.
28301	1/4"	50	2.0	160	6.3	.15

33% Narrower Insulation Diameter

Slim Diameter






1000Volt

28304 **SlimLine Blade Holder, With Wiha-SoftFinish® Handle. Insulation According to VDE, ASTM, EN/IEC, NFPA70E & CSA, up to 1000 Volt.** Wiha-SoftFinish® handle, multi-component, cushion grip.

Item					
No.	Size	mm	Inch	lbs.	pkg.
28304	1/4"	114	4.5	.21	1



1000Volt

28302 **SlimLine Stubby Blade Holder, With Wiha-SoftFinish® Handle. Insulation According to VDE, ASTM, EN/IEC, NFPA70E & CSA, up to 1000 Volt.** Wiha-SoftFinish® handle, multi-component, cushion grip.

Item					
No.	Size	mm	Inch	lbs.	pkg.
28302	1/4"	57	2.2	.11	1

Wiha Insulated SlimLine Blades



Wiha SlimTECHNOLOGY
Achieves blade diameters up to 33% narrower utilizing integrated insulation





283 Insulated Slotted SlimLine Blades

SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools.

Item No.	mm	Inch	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28307	2.5	3/32	4.0	0.4	3.5	.02	1
28308	3.0	1/8	4.0	0.6	5.3	.02	1
28310	3.5	9/64	4.0	2.5	22.1	.02	1
28309	4.0	5/32	4.0	2.5	22.1	.02	1
28312	5.5	7/32	6.0	3.8	33.6	.02	1
28315	6.5	1/4	6.0	5.5	48.6	.02	1



283 Insulated Phillips SlimLine Blades

SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Size	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28317	1	4.0	3.8	33.7	.02	1
28319	2	6.0	5.5	48.8	.02	1



283 Insulated Pozidriv® SlimLine Blades

SlimLine blades have up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Size	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28330	1	4.0	3.8	33.7	.02	1
28331	2	6.0	5.5	48.8	.02	1



283 Insulated Xeno Slotted/Pozidriv®

SlimLine Blades Up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Size	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28320	1	4.0	3.8	33.6	.02	1
28321	2	6.0	5.5	48.7	.02	1



283 Insulated Xeno Slotted/Phillips

SlimLine Blades Up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Size	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28327	1	4.0	3.8	33.6	.02	1
28329	2	6.0	5.5	48.7	.02	1



283 Insulated Square SlimLine Blades

Up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Size	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28346	1	4.0	3.8	33.6	.02	1
28347	2	6.0	5.5	48.7	.02	1



283 Insulated TORX® SlimLine Blades

Up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Size	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28339	T8	4.0	1.3	11.5	.02	1
28344	T9	4.0	1.3	11.5	.02	1
28340	T10	4.0	3.8	33.6	.02	1
28341	T15	6.0	5.5	48.7	.02	1
28342	T20	6.0	5.5	48.7	.02	1
28343	T25	6.0	5.5	48.7	.02	1



283 Insulated Hex Metric SlimLine

Blades Up to 33% narrower insulation diameter then standard insulated tools.

Item No.	Size	Slim Dia.	Max Nm	Inch/ lbs.	lbs.	Pkg.
28332	1.5	4.0	0.9	7.9	.02	1
28333	2.0	4.0	1.8	15.9	.02	1
28334	2.5	4.0	3.8	33.6	.02	1
28335	3.0	4.0	5.5	48.7	.02	1
28336	4.0	6.0	5.5	48.7	.02	1
28337	5.0	6.0	5.5	48.7	.02	1
28338	6.0	6.0	5.5	48.7	.02	1



28372 7 Piece SlimLine Blade Set

High quality CV steel, through hardened, black finish.

Item No.		lbs.
28372	**Slotted:** 2.5, 3.5, 5.5mm	.14
	Phillips: #1, #2	
	Square: #1, #2	



28373 7 Piece SlimLine Blade Set

High quality CV steel, through hardened, black finish.

Item No.		lbs.
28373	**Slotted:** 2.5, 3.5, 5.5mm	.14
	Phillips: #1, #2	
	Xeno Slt/Ph: #1, #2	



Double End Slotted Insert Bit - 2 Pack

Item No.	Description	Cat. No
77715	3.0+4.5mm	99951.wo
77716	4.0+6.0mm	
77717	5.5+6.5mm	



Double End Hex Inch & Metric Insert Bit-2 Pack

Item No.	Description	Cat. No
77719	2.0+2.5mm	99951.wo
77720	3.0+4.0mm	
77721	5.0+6.0mm	
77723	3/32+7/64"	
77724	1/8+9/64"	
77725	5/32+3/16"	
77726	7/32+1/4"	

Fits 26inOne Ultra Driver



Valve Stem Tool - 2 Pack

Item No.	Description	Cat. No
77740	Valve Stem Tool	99951.wo

Fits 26inOne Ultra Driver



1/4" Socket Adapter 30mm OAL - 2 Pack

Item No.	Description	Cat. No
77741	1/4" Socket Adapter	99951.wo



Double End TORX® Insert Bit - 10 Pack

Item No.	Description	Cat. No
77751	T6+T7	99951.wo
77752	T8+T9	
77753	T10+T15	
77754	T20+T25	
77755	T27+T30	



Double End Phillips Insert Bit - 10 Pack

Item No.	Description	Cat. No
77756	#1+#2	99951.wo
77757	#0+#3	



Double End Pozidriv® Insert Bit - 10 Pack

Item No.	Description	Cat. No
77758	#1+#2	99951.wo



Double End Square Insert Bit - 10 Pack

Item No.	Description	Cat. No
77758	#1+#2	99951.wo
77760	#0+#3	



Double End Slotted Insert Bit - 10 Pack

Item No.	Description	Cat. No
77761	3.0+4.5mm	99951.wo
77762	4.0+6.0mm	
77763	5.5+6.5mm	



Double End Hex Inch/Metric Insert Bit - 10 Pack

Item No.	Description	Cat. No
77764	2.0+2.5mm	99951.wo
77765	3.0+4.0mm	
77766	5.0+6.0mm	
77767	3/32+7/64"	
77768	1/8+9/64"	
77769	5/32+3/16"	
77770	7/32+1/4"	

Tradesman Bit Reload



13 Pc. Double End Bit Reload For Ultra Driver

Item No.	Description	Cat. No
77780	13 Pc. Bit Reload	99951.wo

Slotted: 3.0x4.5, 5.5x6.5mm & **Phillips:** #1x2, #0x3
Square: #1x2, #0x3 & **Pozidriv®:** #1x2
TORX: T10xT15, T20xT25 & **Hex Inch:** 1/8x9/64, 5/32x3/16" & **Hex Metric:** 3.0x4.0, 5.0x6.0mm

Technician's Bit Reload



13 Pc. Double End Bit Reload For Ultra Driver

Item No.	Description	Cat. No
77781	13 Pc. Bit Reload	99951.wo

Slotted: 3.0x4.5, 4.0x6.0, 5.5x6.5mm & **Pozidriv:** #1x2
Phillips: #1x2, #0x3 & **Square:** #1x2, #0x3
TORX: T6xT7, T8xT9, T10xT15, T20xT25, T27xT30

Industrial Bit Reload



13 Pc. Double End Bit Reload For Ultra Driver

Item No.	Description	Cat. No
77782	13 Pc. Bit Reload	99951.wo

Slotted: 4.0x6.0mm & **Phillips:** #1x2
TORX: T8xT9, T10xT15, T20xT25, T27xT30
Hex Inch: 3/32x7/64, 1/8x9/64, 5/32x3/16, 7/32x1/4"
Hex Metric: 2.0x2.5, 3.0x4.0, 5.0x6.0mm

Tradesman



15 Pc. Ultra Driver & BiCut SuperCut Pliers

Item No.	Description	Cat. No
77786	15 Pc. Combo Set	99951.wo

8.0"/200mm Vinyl Soft Grip BiCut SuperCut
Slotted: 3.0x4.5, 5.5x6.5mm & **Phillips:** #1x2, #0x3
Square: #1x2, #0x3 & **Pozidriv®:** #1x2
TORX: T10xT15, T20xT25
Hex Inch: 1/8x9/64, 5/32x3/16"
Hex Metric: 3.0x4.0, 5.0x6.0mm

Tradesman



27 Piece 26inOne Ultra Driver Set

Item No.	Description	Cat. No
77790	26inOne Set-1/4" Bits	99951.wo

Slotted: 3.0x4.5, 5.5x6.5mm & **Phillips:** #1x2, #0x3
Square: #1x2, #0x3 & **Pozidriv®:** #1x2
TORX: T10xT15, T20xT25
Hex Inch: 1/8x9/64, 5/32x3/16"
Hex Metric: 3.0x4.0, 5.0x6.0mm

Technician's



27 Piece 26inOne Ultra Driver Set

Item No.	Description	Cat. No
77791	26inOne Set-1/4" Bits	99951.wo

Slotted: 3.0x4.5, 4.0x6.0, 5.5x6.5mm & **Pozidriv:** #1x2
Phillips: #1x2, #0x3 & **Square:** #1x2, #0x3
TORX: T6xT7, T8xT9, T10xT15, T20xT25, T27xT30

Industrial



27 Piece 26inOne Ultra Driver Set

Item No.	Description	Cat. No
77792	26inOne Set-1/4" Bits	99951.wo

Slotted: 4.0x6.0mm & **Phillips:** #1x2
TORX: T8xT9, T10xT15, T20xT25, T27xT30
Hex Inch: 3/32x7/64, 1/8x9/64, 5/32x3/16, 7/32x1/4"
Hex Metric: 2.0x2.5, 3.0x4.0, 5.0x6.0mm

Tradesman



29 Pc. Ultra Driver & 1/4" Drive Sockets

Item No.	Description	Cat. No
77793	29 Pc. Combo Set	99951.wo

Slotted: 3.0x4.5, 5.5x6.5mm & **Phillips:** #1x2, #0x3
Square: #1x2, #0x3 & **Pozidriv®:** #1x2
TORX: T10xT15, T20xT25
Hex Inch: 1/8x9/64, 5/32x3/16"
Hex Metric: 3.0x4.0, 5.0x6.0mm
Inch Sockets: 5/32, 3/16, 7/32, 1/4, 9/32, 5/16, 3/8"
Metric Sockets: 4.0, 4.5, 5.0, 5.5, 6.0, 7.0, 8.0mm
1/4" x 1/4" Drive Socket Adapter



23 Piece Ultra Driver Bonus Pack

Item No.	Description	Cat. No
77795	Ultra Driver Set-1/4" Bits	99951.wo

Slotted: 3.0x4.5, 4.0x6.0, 5.5x6.5mm
Phillips: #1x2, #0x3
Square: #1x2, #0x3 & **Pozidriv®:** #1x2
TORX: T6xT7, T8xT9, T10xT15, T20xT25, T27xT30
Hex Metric: 2.0x2.5, 3.0x4.0, 5.0x6.0mm
Hex Inch: 3/32x7/64, 1/8x9/64, 5/32x3/16, 7/32x1/4"
1/4" Hex to 1/4" Square Socket Adapter
Double End Valve Stem Tool



1/4" Shank Stubby High Speed Drill Bits

Item No.	Description	Cat. No
78002	1/16 x 1.26"	99951.wo
78005	3/32 x 1.41"	
78008	1/8 x 1.57"	
78011	5/32 x 1.73"	
78015	3/16 x 1.97"	
78018	1/4 x 1.97"	



HSS 1/4" Drive Countersinks

Item No.	Description	Cat. No
78615	6.3 x 1.38"	99951.wo
78617	8.3 x 1.38"	
78619	10.4 x 1.38"	
78621	12.4 x 1.38"	
78622	16.5 x 1.38"	
78624	20.5 x 1.38"	



TORX® Bit-Selector Set

Item No.	Description	Cat. No
79242	TORX Bit-Selector Set	99951.wo

TORX: T5, T6, T7, T8, T9, T10, T15, T20, T25, T30
1/4" Bit Holder



Slotted, Phillips & TORX® Bit-Selector Set

Item No.	Description	Cat. No
79243	Bit-Selector Set	99951.wo

Slotted: 4.5, 5.5, 6.0mm & **Phillips:** #0, 1, 2, 3
TORX: T10, T15, T20 & 1/4" Bit Holder



TORX® Bit-Selector Set

Item No.	Description	Cat. No
79245	TORX Bit-Selector Set	99951.wo

TORX: T7, T8, T9, T10, T15, T20, T25, T27, T30, T40
1/4" Bit Holder

Wiha Power Blade Nut Drivers - 100mm



760 Power Blade Inch Nut Drivers

High alloy CVM steel, hardened, hard chromed.

Item No.	mm	mm	Inch	lbs.
76059	3/16	100	3.9	.12
76060	7/32	100	3.9	.14
76061	1/4	100	3.9	.14
76062	9/32	100	3.9	.14
76063	5/16	100	3.9	.14
76064	11/32	100	3.9	.15
76065	3/8	100	3.9	.15
76066	7/16	100	3.9	.15
76067	1/2	100	3.9	.18



760 Power Blade Metric Nut Drivers

High alloy CVM steel, hardened, hard chromed.

Item No.	mm	mm	Inch	lbs.
76068	4.0	100	3.9	.12
76069	4.5	100	3.9	.12
76070	5.0	100	3.9	.12
76071	5.5	100	3.9	.14
76072	6.0	100	3.9	.14
76073	7.0	100	3.9	.14
76074	8.0	100	3.9	.14
76075	9.0	100	3.9	.14
76076	10.0	100	3.9	.14
76077	11.0	100	3.9	.15
76078	12.0	100	3.9	.18
76080	13.0	100	3.9	.19

Wiha Nut Driver Precision Series



265 Metric Metric Nut Driver With Precision Handle Metric sizes.

Blade Chrome-Vanadium-Molybdenum steel. Hard chrome finished.

Item No.	mm	mm	Inch	mm	Inch	mm	mm	lbs.	pkg.
26510	1.5	60	2.4	140	5.5	2.5	3.0	.03	10
26515	1.8	60	2.4	140	5.5	2.9	3.5	.03	10
26520	2.0	60	2.4	140	5.5	3.2	4.0	.04	10
26525	2.5	60	2.4	155	6.1	4.0	4.0	.04	10
26530	3.0	60	2.4	155	6.1	5.0	5.0	.05	10
26532	3.2	60	2.4	155	6.1	5.0	5.0	.05	10
26535	3.5	60	2.4	155	6.1	5.3	6.0	.05	10
26540	4.0	60	2.4	155	6.1	5.5	6.0	.05	10
26545	4.5	60	2.4	155	6.1	6.2	7.0	.05	10
26550	5.0	60	2.4	155	6.1	6.8	7.0	.05	10
26555	5.5	60	2.4	170	6.7	7.6	8.0	.06	10
26560	6.0	60	2.4	170	6.7	8.2	9.0	.06	10
26570	7.0	60	2.4	170	6.7	9.6	10.0	.06	10

*Metric dimensions actual - Inch dimensions approximate

265 Inch Inch Nut Driver With Precision Handle Inch sizes.

Blade Chrome-Vanadium-Molybdenum steel. Hard chrome finished.

Item No.	Inch	mm	Inch	mm	Inch	Inch	Inch	lbs.	pkg.
26523	3/32	60	2.4	155	6.1	.16	.16	.04	10
26527	7/64	60	2.4	155	6.1	.20	.20	.05	10
26531	1/8	60	2.4	155	6.1	.20	.20	.05	10
26536	9/64	60	2.4	155	6.1	.21	.24	.05	10
26539	5/32	60	2.4	155	6.1	.22	.24	.05	10
26547	3/16	60	2.4	155	6.1	.25	.28	.05	10
26556	7/32	60	2.4	170	6.7	.30	.32	.06	10
26563	1/4	60	2.4	170	6.7	.34	.36	.06	10

*Metric dimensions actual - Inch dimensions approximate

Wiha Nut Driver Sets Precision Series



26590 8 Pc. Precision Nut Driver Set - Metric Blade CVM steel. Hard chrome finish.

Item No.	Metric Nut Drivers:	
26590	2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0mm x 60mm	lbs. .48

26592 Set 7 Pcs. Nut Driver Metric

Item No.	
26592	1.5, 1.8, 2.0, 2.5, 3.0, 3.5, 4.0mm



In canvas storage pouch

26598 8 Pc. Precision Nut Driver Set - Metric

Blade CVM steel. Hard chrome finished.

Item No.	Metric Nut Drivers:	
26598	2.5, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5, 6.0mm x 60mm	lbs. .70



26591 8 Pc. Precision Nut Driver Set - Inch

Blade CVM steel. Hard chrome finished.

Item No.	Inch Nut Drivers:	
26591	3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4" x 2.4"	lbs. 47



In canvas storage pouch

26599 8 Pc. Precision Nut Driver Set - Inch

Blade CVM steel. Hard chrome finished.

Item No.	Inch Nut Drivers:	
26599	3/32, 7/64, 1/8, 9/64, 5/32, 3/16, 7/32, 1/4" x 2.4"	lbs. .72

Ergo Wire Stripper



44219 **Compact Ergo Wire Stripper**
Molded ergo pistol grip design. Top mounted thumb lock. Strip length 7/32 to 1/2" (5 - 12mm). Wire capacity AWG #10-24 (0.2 - 6.2mm).

Item No.	mm	Inch	Strip Range
44219	184	7.25	5-12mm

Cable Stripper



44216 **Cable Stripper - Adjustable**
Safe stripping of all common round cables from Ø 4mm - 28mm. Ergonomic impact resistant handle makes for perfect handling. Hooked blade and cutter are made of hardened steel. Additional spare blades in the handle. Includes safety cap.
lbs. .25

Item No.	mm	Inch	Strip Range
44216	165	6.5	4.0-28mm²

CATV/Satellite Stripper





Strips: RG59 & RG6 CATV coaxial cables

44206 **CATV/Satellite Stripper**
Quickly & simply strips RG59 & RG6 coaxial cables for CATV "F" type connectors giving industry standard strip lengths of 6.35mm/.25" for both the braid and the conductor. Patented spring-like action and built-in stop eliminates the need for manual adjustment for different cables. lbs. .05

Item No.	mm	Inch	Strip Length
44206	83	3.3"	6.35mm/.25" Braid/Conductor

Precision Adjustable Stripping Tool





Replaceable Blade

Cables: Multi core cable, Modplug cable. Fiber optic cable etc.



44220 **Precision Adjustable Stripping Tool** Professional stripping tool removes the outer cable jacket from signal, telephone, audiovisual, instrumentation and data transmission copper and fiber optic cables up to 11mm/0.43" diameter. The tool features a 9 position indexed blade height adjustment wheel ensuring accurate & repeatable stripping results. Simply squeeze together to open the stripping cavity - insert cable, rotate once and pull off the scrap insulation. Smooth, Lightweight and pocket size. No open blade, replacement blades encased within cassette.
lbs. .06

Item No.	mm	Inch	Strip Range	Strip Range
44220	90.5	3.6	2.5-11mm	.10"/0.43"

Replacement Blade



Replacement Blade



44221 **Replacement Blade For 44220 Stripper** Stripping capacity of up to 2.5-11mm/0.43" diameter.

Item No.	Strip Range	Strip Dim.	lbs.	Pkg.
44221	2.5-11mm	11mm/0.43"	.01	1

Notes:

Finding The Right Bit Is This Easy






- Phillips
- Pozidriv®
- Hex
- TORX®
- Square

T-Bit + Y-Bit = Terminator



- Y-Bits & T-Bits 25X Performance Over Standard Bits
- UV Light Makes Easy To Find Bits If Dropped
- Suitable For Both Impact Drivers or Fastening By Hand
- Patented Wiha Bit Technology For Optimised Torsion Zones

Easy Concept, Easy Instructions:



If you have screws with a 90° angle at the screw head which largely fit flat onto the material surface, then you need the new blue T-Bits. Suitable for fastening in materials such as metal (tough fastenings)

You should choose the yellow Y-Bits for screws with an angle greater than 90°. Suitable for fastening in materials such as wood (soft applications)

If you wish to fasten both types, then the red Terminator Bits are right for you





Wiha Impact Y-Bit - 1/4" Insert & Power Bits

NEW



726 Phillips 1/4" Insert Y-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72604	1	25	2
72605	2	25	2
72606	3	25	2

727 Phillips 1/4" Insert Y-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72704	1	25	5
72705	2	25	5
72706	3	25	5

728 Phillips 1/4" Insert Y-Bits - 10 Bit Pack

Item No.	Size	mm	pkg.
72804	1	25	10
72805	2	25	10
72806	3	25	10

729 Phillips 1/4" Insert Y-Bits-25 Bit Pack

Item No.	Size	mm	pkg.
72904	1	25	25
72905	2	25	25
72906	3	25	25



726 Pozidriv® 1/4" Insert Y-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72610	1	25	2
72611	2	25	2
72612	3	25	2

727 Pozidriv® 1/4" Insert Y-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72710	1	25	5
72711	2	25	5
72712	3	25	5

728 Pozidriv® 1/4" Insert Y-Bits - 10 Bit Pk

Item No.	Size	mm	pkg.
72810	1	25	10
72811	2	25	10
72812	3	25	10



726 TORX® 1/4" Insert Y-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72630	T10	25	2
72631	T15	25	2
72632	T20	25	2
72633	T25	25	2
72634	T27	25	2
72635	T30	25	2
72636	T40	25	2

727 TORX® 1/4" Insert Y-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72730	T10	25	5
72731	T15	25	5
72732	T20	25	5
72733	T25	25	5
72734	T27	25	5
72735	T30	25	5
72736	T40	25	5

728 TORX® 1/4" Insert Y-Bits - 10 Bit Pack

Item No.	Size	mm	pkg.
72830	T10	25	10
72831	T15	25	10
72832	T20	25	10
72833	T25	25	10
72834	T27	25	10
72835	T30	25	10
72836	T40	25	10

729 TORX® 1/4" Insert Y-Bits - 25 Bit Pack

Item No.	Size	mm	pkg.
72932	T20	25	25
72933	T25	25	25



726 Phillips 1/4" Power Y-Bits-2 Bit Pack

Item No.	Size	mm	pkg.
72643	1	50	2
72644	2	50	2
72645	3	50	2

727 Phillips 1/4" Power Y-Bits-5 Bit Pack

Item No.	Size	mm	pkg.
72743	1	50	5
72744	2	50	5
72745	3	50	5

728 Phillips 1/4" Power Y-Bits-10 Bit Pack

Item No.	Size	mm	pkg.
72843	1	50	10
72844	2	50	10
72845	3	50	10



726 Pozidriv® 1/4" Power Y-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72649	1	50	2
72650	2	50	2
72651	3	50	2

727 Pozidriv® 1/4" Power Y-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72749	1	50	5
72750	2	50	5
72751	3	50	5

728 Pozidriv® 1/4" Power Y-Bits - 10 Bit Pk

Item No.	Size	mm	pkg.
72849	1	50	10
72850	2	50	10
72851	3	50	10



728 TORX® 1/4" Power Y-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72669	T10	50	2
72670	T15	50	2
72671	T20	50	2
72672	T25	50	2
72673	T27	50	2
72674	T30	50	2
72675	T40	50	2

727 TORX® 1/4" Power Y-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72769	T10	50	5
72770	T15	50	5
72771	T20	50	5
72772	T25	50	5
72773	T27	50	5
72774	T30	50	5
72775	T40	50	5

728 TORX® 1/4" Power Y-Bits-10 Bit Pack

Item No.	Size	mm	pkg.
72869	T10	50	10
72870	T15	50	10
72871	T20	50	10
72872	T25	50	10
72873	T27	50	10
72874	T30	50	10
72875	T40	50	10

Wiha Impact T-Bit - 1/4" Insert Bits

NEW



726 Phillips 1/4" Insert T-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72601	1	25	2
72602	2	25	2
72603	3	25	2

727 Phillips 1/4" Insert T-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72701	1	25	5
72702	2	25	5
72703	3	25	5

728 Phillips 1/4" Insert T-Bits - 10 Bit Pack

Item No.	Size	mm	pkg.
72801	1	25	10
72802	2	25	10
72803	3	25	10

729 Phillips 1/4" Insert T-Bits-25 Bit Pack

Item No.	Size	mm	pkg.
72901	1	25	25
72902	2	25	25
72903	3	25	25



726 Hex Inch 1/4" Insert T-Bits - 2 Bit Pack

Item No.	Inch	mm	pkg.
72613	1/4	25	2
72614	1/8	25	2
72619	3/16	25	2
72620	5/32	25	2
72621	7/32	25	2
72622	9/64	25	2

727 Hex Inch 1/4" Insert T-Bits - 5 Bit Pack

Item No.	Inch	mm	pkg.
72713	1/4	25	5
72714	1/8	25	5
72719	3/16	25	5
72720	5/32	25	5
72721	7/32	25	5
72722	9/64	25	5

728 Hex Inch 1/4" Insert T-Bits-10 Bit Pack

Item No.	Inch	mm	pkg.
72813	1/4	25	10
72814	1/8	25	10
72819	3/16	25	10
72820	5/32	25	10
72821	7/32	25	10
72822	9/64	25	10



726 Hex Metric 1/4" Insert T-Bits - 2 Bit Pack

Item No.	mm	mm	pkg.
72615	3.0	25	2
72616	4.0	25	2
72617	5.0	25	2
72618	6.0	25	2

727 Hex Metric 1/4" Insert T-Bits-5 Bit Pack

Item No.	mm	mm	pkg.
72715	3.0	25	5
72716	4.0	25	5
72717	5.0	25	5
72718	6.0	25	5

728 Hex Metric 1/4" Insert T-Bits-10 Bit Pack

Item No.	mm	mm	pkg.
72815	3.0	25	10
72816	4.0	25	10
72817	5.0	25	10
72818	6.0	25	10



726 TORX® 1/4" Insert T-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72623	T10	25	2
72624	T15	25	2
72625	T20	25	2
72626	T25	25	2
72627	T27	25	2
72628	T30	25	2
72629	T40	25	2

727 TORX® 1/4" Insert T-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72723	T10	25	5
72724	T15	25	5
72725	T20	25	5
72726	T25	25	5
72727	T27	25	5
72728	T30	25	5
72729	T40	25	5

728 TORX® 1/4" Insert T-Bits - 10 Bit Pack

Item No.	Size	mm	pkg.
72823	T10	25	10
72824	T15	25	10
72825	T20	25	10
72826	T25	25	10
72827	T27	25	10
72828	T30	25	10
72829	T40	25	10

729 TORX® 1/4" Insert T-Bits - 25 Bit Pack

Item No.	Size	mm	pkg.
72923	T10	25	25
72924	T15	25	25
72925	T20	25	25
72926	T25	25	25



726 Pozidriv® 1/4" Insert T-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72607	1	25	2
72608	2	25	2
72609	3	25	2

727 Pozidriv® 1/4" Insert T-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72707	1	25	5
72708	2	25	5
72709	3	25	5

728 Pozidriv® 1/4" Insert T-Bits - 10 Bit Pk

Item No.	Size	mm	pkg.
72807	1	25	10
72808	2	25	10
72809	3	25	10



726 Square 1/4" Insert T-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72637	1	25	2
72638	2	25	2
72639	3	25	2

727 Square 1/4" Insert T-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72737	1	25	5
72738	2	25	5
72739	3	25	5

728 Square 1/4" Insert T-Bits - 10 Bit Pack

Item No.	Size	mm	pkg.
72837	1	25	10
72838	2	25	10
72839	3	25	10

729 Square 1/4" Insert T-Bits-25 Bit Pack

Item No.	Size	mm	pkg.
72937	1	25	25
72938	2	25	25

Wiha Impact T-Bit - 1/4" Power Bits

NEW



726 Phillips 1/4" Power T-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72640	1	50	2
72641	2	50	2
72642	3	50	2

727 Phillips 1/4" Power T-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72740	1	50	5
72741	2	50	5
72742	3	50	5

728 Phillips 1/4" Power T-Bits-10 Bit Pack

Item No.	Size	mm	pkg.
72840	1	50	10
72841	2	50	10
72842	3	50	10



726 Hex Inch 1/4" Power T-Bits - 2 Bit Pack

Item No.	Inch	mm	pkg.
72652	1/4	50	2
72653	1/8	50	2
72658	3/16	50	2
72659	5/32	50	2
72660	7/32	50	2
72661	9/64	50	2

727 Hex Inch 1/4" Power T-Bits - 5 Bit Pack

Item No.	Inch	mm	pkg.
72752	1/4	25	5
72753	1/8	25	5
72758	3/16	25	5
72759	5/32	25	5
72760	7/32	25	5
72761	9/64	25	5

728 Hex Inch 1/4" Power T-Bits-10 Bit Pack

Item No.	Inch	mm	pkg.
72852	1/4	25	10
72853	1/8	25	10
72858	3/16	25	10
72859	5/32	25	10
72860	7/32	25	10
72861	9/64	25	10



726 TORX® 1/4" Power T-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72662	T10	50	2
72663	T15	50	2
72664	T20	50	2
72665	T25	50	2
72666	T27	50	2
72667	T30	50	2
72668	T40	50	2

727 TORX® 1/4" Power T-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72762	T10	50	5
72763	T15	50	5
72764	T20	50	5
72765	T25	50	5
72766	T27	50	5
72767	T30	50	5
72768	T40	50	5

728 TORX® 1/4" Power T-Bits - 10 Bit Pack

Item No.	Size	mm	pkg.
72862	T10	50	10
72863	T15	50	10
72864	T20	50	10
72865	T25	50	10
72866	T27	50	10
72867	T30	50	10
72868	T40	50	10



726 Pozidriv® 1/4" Power T-Bits-2 Bit Pack

Item No.	Size	mm	pkg.
72646	1	50	2
72647	2	50	2
72648	3	50	2

727 Pozidriv® 1/4" Power T-Bits-5 Bit Pack

Item No.	Size	mm	pkg.
72746	1	50	5
72747	2	50	5
72748	3	50	5

728 Pozidriv® 1/4" Power T-Bits-10 Bit Pk

Item No.	Size	mm	pkg.
72846	1	50	10
72847	2	50	10
72848	3	50	10



726 Hex Metric 1/4" Power T-Bits-2 Bit Pack

Item No.	mm	mm	pkg.
72654	3.0	50	2
72655	4.0	50	2
72656	5.0	50	2
72657	6.0	50	2

727 Hex Metric 1/4" Power T-Bits-5 Bit Pack

Item No.	mm	mm	pkg.
72754	3.0	50	5
72755	4.0	50	5
72756	5.0	50	5
72757	6.0	50	5

728 Hex Metric 1/4" Power T-Bits-10 Bit Pk

Item No.	mm	mm	pkg.
72854	3.0	50	10
72855	4.0	50	10
72856	5.0	50	10
72857	6.0	50	10



726 Square 1/4" Power T-Bits - 2 Bit Pack

Item No.	Size	mm	pkg.
72676	1	50	2
72677	2	50	2
72678	3	50	2

727 Square 1/4" Power T-Bits - 5 Bit Pack

Item No.	Size	mm	pkg.
72776	1	50	5
72777	2	50	5
72778	3	50	5

728 Square 1/4" Power T-Bits - 10 Bit Pack

Item No.	Size	mm	pkg.
72876	1	50	10
72877	2	50	10
72878	3	50	10