


Heyco-Flex™ Mounting Brackets

- For mounting Heyco-Flex Conduit or Tubing securely into place, vertically or horizontally. See pages 2-1, 2-7, and 2-8.
- Only fingertip pressure is required to snap conduit or tubing into bracket.
- Low profile design for space savings and pleasing appearance.
- Recommended distance between brackets at intervals not greater than 3 feet (1m) as required by Article 351-27 of 1996 NEC.
- Use one standard #10 (4-5M) screw for attaching bracket to panel (screw not included).
- Resist salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents.

FITS CONDUIT/ TUBING SIZE	PART NO. Black	PART NO. Gray	DESCRIPTION	PART DIMENSIONS A Inside Dia. in.	A mm.	B Length in.	B mm.	C Height in.	C mm.	D Outside Dia. in.	D mm.	E Width in.	E mm.
3/8	**1025**	**1026**	HFB 3/8	.66	16,9	.91	23,2	.72	18,2	.90	22,9	.75	19,1
1/2	**1027**	**1028**	HFB 1/2	.79	20,0	1.07	27,3	.71	18,0	1.06	26,8		
3/4	**1029**	**1030**	HFB 3/4	1.05	26,7	1.27	32,2	.67	17,0	1.31	33,2		
1	**1031**	**1032**	HFB 1	1.24	31,5	1.52	38,6	.84	21,3	1.53	38,9		

Standard color black or gray.



Dimensions excluding draft




Heyco® Sealing Washers

- For use with Heyco-Flex fittings.
- Liquid tight, dust tight, and oil tight at enclosure.
- Suitable for wet locations requiring a separate gasket between the box and fitting.
- Also suitable for other panel sealing applications.
- Easy to install since washers seal off on the perimeter, not on the connector threads.
- Special double sealing ridges compensate for minor unevenness at enclosure.

Will Fit These Electrical Fitting NPT Trade Sizes	PART NO. Black	DESCRIPTION	PART DIMENSIONS A Inside Diameter in.	A mm.	B Outside Diameter in.	B mm.	C Thickness in.	C mm.
1/4	**3258**	SW 1/4	.54	13,7	.80	20,2	.13	3,2
3/8	**3259**	SW 3/8	.67	17,0	1.01	25,5		
1/2	**3260**	SW 1/2	.85	21,6	1.24	31,5		
3/4	**3261**	SW 3/4	1.03	26,2	1.50	38,1	.14	3,4
1	**3262**	SW 1	1.28	32,5	1.77	45,0	.18	4,6
1-1/4	**3264**	SW 1-1/4	1.66	42,2	2.16	54,8	.16	4,1
1-1/2	**3265**	SW 1-1/2	1.86	47,2	2.44	62,0		
2	**3257**	SW 2	2.32	58,9	2.93	74,4	.18	4,6

Standard color black.



Quick Specs

Material	HFB - Nylon 6/6	SW - Thermoplastic Elastomer
Flammability Rating	HFB - 94V-2	SW - 94V-0
Temperature Range	-22°F (-30°C) to 221°F (105°C)	

1-800-526-4182 • 732-286-1800 (NJ) • FAX: 732-244-8843 • www.heyco.com