
DiTom MICROWAVE INC.



Part Number: D3I0710N


Electrical Specifications

Frequency Range (GHz):	0.698 – 1.000	
Isolation (dB):	16	MIN
Insertion Loss (dB):	0.6	MAX
VSWR:	1.4:1	MIN
Forward Power (W):	300	AVG
	750	PK
Reflective Power (W):	10	AVG


Mechanical/Environmental Specifications

Connector Type:	Type-N
Connector Body:	Nickel plated brass
Connector Pin:	Gold plated copper
Load Body:	Brass
Magnetic Shunt:	Nickel plated CRS
Operational Temp:	-20˚C to +65˚C
Weight (oz)	5.5 MAX

D3I0710N Dimensions



D3I0710N-3 Dimensions



Dimensions are in inches
Tolerance
XX ±0.03
XXX ±0.010


Type of Device	PN Suffix	Connector Configuration Input / Output	PN Example
Single and Dual Junction Isolator, 2-Port Device Input / Output	N/A	Female / Female	D3I0710N
	-1	Male / Female	D3I0710N-1
	-2	Female / Male	D3I0710N-2
	-3	Male / Male	D3I0710N-3

DiTom Microwave · 7592 N Maroa Ave Fresno, CA USA · PH +001-559-790-1130 · FAX +001-559-255-1667

DiTom MICROWAVE INC.

MEASURED DATA

Part Number: D3I0710N, +25˚C



DiTom Microwave · 7592 N Maroa Ave Fresno, CA USA · PH +001-559-790-1130 · FAX +001-559-255-1667