DiTom MICROWAVE INC.



Part Number: D3I9521S


Electrical Specifications

Frequency Range (GHz):	0.95 – 2.15	
Isolation (dB):	12	MIN
Insertion Loss (dB):	1.0	MAX
VSWR:	1.65:1	MIN
Forward Power (W):	75	AVG
	100	PK
Reflective Power (W):	10	AVG


Mechanical/Environmental Specifications

Connector Type:	SMA
Connector Body:	Nickel plated brass
Connector Pin:	Gold plated copper
Load Body:	Brass
Magnetic Shunt:	Nickel plated CRS
Operational Temp:	10˚C to +55˚C
Weight (oz)	15 MAX

D3I9521S Dimensions



D3I9521S-3 Dimensions



Dimensions are in inches
Tolerance

XX	±0.03
XXX	±0.010


Type of Device	PN Suffix	Connector Configuration Input / Output	PN Example
Single and Dual Junction Isolator, 2-Port Device Input / Output	N/A	Female / Female	D3I9521S
	-1	Male / Female	D3I9521S-1
	-2	Female / Male	D3I9521S-2
	-3	Male / Male	D3I9521S-3

DiTom Microwave · 7592 N Maroa Ave Fresno, CA USA · PH +001-559-790-1130 · FAX +001-559-255-1667

DiTom MICROWAVE INC.

MEASURED DATA

Part Number: D3I9521S, +25˚C



DiTom Microwave • 7592 N Maroa Ave Fresno, CA USA • PH +001-559-790-1130 • FAX +001-559-255-1667