battery-related products

MASTER DISCONNECT SWITCHES

Back

Low Voltage Disconnect Switches
Master Disconnect Switches
Single Pole Master Disconnect Switches
Double Pole Master Disconnect Switches
Battery Selector/Master Disconnect Switches
Battery Isolators
Forward & Reverse Relay Module
Electronic Dual Relay
FlexMod Electronic Modules
Daytime Running Light Module
Trailer Tail Light Convertor
Battery-Related Accessories

2484-16 Master Disconnect Switch

SPST Two positions: Off-On. For 6-36V DC systems.

Will disconnect the battery circuit only.
Electrical Ratings ul listed 375Mt 250A at 6V, 125A at 12V intermittent; 40A at 6V, 20A at 12V continuous. Electrical ratings on UL labels are conservative.
Mounting stem: Brass, 3/4" -16 thread, 23/32" (18.3mm) long. Fits panels up to 3/16" (4.8mm) thick.
Terminals: Two 3/8" -24 studs.
Case: Plated steel.
Contacts: Silver



ADD TO QUOTE | PRINT

Specifications | Literature | Similar Products

Description	Master Disconnect Switch
Details	Single Pole battery disconnect, Two Positions: Off-On
UL listed	UL listed
Rating	250A at 6V, 125A at12V intermittent; 40A at 6V, 20A at 12V continuous
Terminals	two 3/8" copper studs
Actuators	diecast lever
Mounting stem	brass, 3/4" - 16 thread, 23/32" long, fits panel through 3/16" thick
Case	plated steel
Installation	Through hole - Clearance for 3/4" dia. mounting stem
Contacts	silver laminated

More

Related Products



24505
Lockout Lever Kit for Master Disconnect Switches

ADD TO QUOTE



2484-09
Master Disconnect Switch

ADD TO QUOTE



2484-A
Master Disconnect Switch

ADD TO QUOTE



75920
Master Disconnect Switch

ADD TO QUOTE



80101-B
Chrome-plated cast zinc Lever

ADD TO QUOTE

Customer Service

Contact Us
Find A Distributor
Request More Information
How to Order

© 2015 Littelfuse, Inc. All rights reserved. Cole Hersee is a Littelfuse brand.

Commercial Vehicle Products
20 Old Colony Avenue
Boston, MA 02127-2467, USA
+1 617.268.2100

Downloaded from Arrow.com.