Heyco® Double D Hole Plugs


For Mounting Holes with Flats
Multiple Locking Steps for Panel Thickness up to .125″ (3,2 mm)




PANEL DIMENSIONS D Mounting Hole Dia. in.	mm.	C To Prevent Rotation in.	mm.	PART NO. Black	White	DESCRIPTION	PART DIMENSIONS A Head Diameter in.	mm.	B Overall Height in.	mm.
.375	9,5	.345	8,8	**2617**	**2618**	DP 375*	.47	11,9	.41	10,3
.437	11,1	.390	9,9	**2488**	**2489**	DD 437-390	.53	13,5		
.500	12,7	.445	11,3	**2491**	**2492**	DD 500-445	.55	14,7		
.562	14,3	.530	13,5	**2494**	**2495**	DD 562-530	.66	16,7		
.625	15,9	.550	14,0	**2497**	**2498**	DD 625-550	.73	18,5		
.750	19,1	.625	15,9	**2503**	**2504**	DD 750-625	.92	23,4		
.875	22,2	.770	19,5	**2509**	**2510**	DD 875-770	1.02	25,8	.45	11,5
				2511	–	DD 875-770-9**	.94	23,8		
1.109	28,2	1.000	25,4	**2717**	**2718**	DD 1109-1000	1.22	30,9		
2.000	50,8	1.875	47,6	**2959**	**2963**	DD 2000-1875	2.17	55,1	.48	12,1

Standard colors black and white. Consult Heyco for other colors.
*On installation, DP 375 Locking Fingers must be aligned with Mounting Hole Flats.
**Smaller than standard Head Diameter, for clearance situations.


- **Close unwanted Strain Relief mounting holes** or other double faced or Double D holes punched or molded with two opposing flats.
- Convex, matte finish head tapers to a thin edge.
- Quick and easy installation.
- Lock firmly in panels up to .125″ (3,2 mm) thick.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Approximate Head Thickness: .062″ (1,6 mm). Thickness may vary.



DD Series



RP Series



3299, 3388, 3389

Heyco® Rectangular Blanking & Connector Port Plugs

Multiple Locking Steps for Various Panel Thicknesses



PANEL DIMENSIONS Maximum Thickness in.	mm.	Mounting Hole C Length in.	mm.	D Width in.	mm.	PART NO. Black	DESCRIPTION	PART DIMENSIONS A Head Dimensions in.	mm.	B Overall Height in.	mm.
Rectangular Blanking Plugs											
.03	0,64	.96	24,5	.96	24,5	**13910**	RP 245-245	1.06 x 1.06	26,9 x 26,9	.30	7,6
						13911	RB 245-245*	1.05 x 1.05	26,7 x 26,7		
.04	1,0	.27	6,9	.29	7,4	**2512**	RP 69-74	.37 x .37	9,4 x 9,4	.33	8,4
.10	2,5	.45	11,5	.51	13,9	**1890**	RP 115-130	.58 x .58	14,7 x 14,7	.40	10,2
.13	3,2	.94	23,8	1.65	42,0	**2513**	RP 239-419	2.17 x 1.38	55,1 x 35,0	.46	11,7
.16	4,0	.69	17,5	.69	17,5	**1892**	RP 175-175	.83 x .83	21,1 x 21,1	.47	11,9
Connector Port Plugs											
.14	3,5	.37	9,5	.51	13,0	**3299**	RP 95-130-1	.63	16,0	.41	10,5
						3388	RP 95-130	.87	22,0		
				1.02	26,0	**3389**	RP 95-260	1.38	35,0		

Standard color black.
*Bushing version of the above plug.

- Blank unused rectangular panel holes.
- **PN 1890** - UR Recognized under the Component Program of Underwriters' Laboratories File E15331.
- **PN 1892** - UR Recognized under the Component Program of Underwriters' Laboratories File E51579 and CSA Certified by the Canadian Standards Association File 8919.

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriter Laboratories File E51579 (DD only)
Flammability Rating	94V-2
Temperature Range	-40°F (-40°C) to 221°F (105°C)

Quick Specs