1	**Product code**	**YF-659-B-2**		11	**Testing Voltage**	**110**
2	**Size (mm)**	**1004*14**	**Tolerance: ±0.2**	12	**Testing frequency**	**400HZ**
3	**Emitting size (mm)**	**985*10**		13	**Candela (cd/ m^2)**	**35**
4	**Leads**	**FPC**		14	**Electric Current (mA/cm^2)**	**0.03**
5	**Distance of Leads (mm)**	**5.08**	**Tolerance: ±0.2**	15	**Power consumption (mw/cm^2)**	**3.6**
6	**Laminate**	**Double Sealing**		16	**High Voltage test (VPP)**	**≤200**
7	**Thickness (mm)**	**0.4**		**17**	**Optimal Life Time**	**8000 H**
8	**Surface color**	**Blue, Blue-Green, Red, White, Greene**		**18**	**Connection Wire**	**JST PHR-2 Female**
10	**Emitting Color**	**Blue, Blue-green, Red, Blue-White, Green**				

Reliability Test			
Item	**Test Condition**		**Life Time**
	Temperature	**Humidity**	
Normal Temperature	20℃	65%	3000-5000H
High Temperature, Humidity	40±2℃	90%	100H
High Temperature Storage	70±3℃	10%	1000H
Low Temperature Storage	-30±3℃,	/	1000H
High Temperature and Humidity Storage	60±2℃	90%	1000H

EL Tape (100* 1 cm) SPECIFICATIONS