EPC2105 – Enhancement-Mode GaN Power Transistor Half-Bridge

V_{DS}, 80 V

$R_{DS(on)}$, 14.5 mΩ (Q1), 3.6 mΩ (Q2)

I_D, 10 A (Q1), 40 A (Q2)

EFFICIENT POWER CONVERSION

RoHS | Halogen-Free

Revised June 19, 2020


Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low $R_{DS(on)}$, while its lateral device structure and majority carrier diode provide exceptionally low Q_G and zero Q_{RR}. The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

Questions: Ask a GaN Expert

Maximum Ratings				
DEVICE	**PARAMETER**		**VALUE**	**UNIT**
Q1	V_{DS}	Drain-to-Source Voltage (Continuous)	80	V
		Drain-to-Source Voltage (up to 10,000 5 ms pulses at 150°C)	96	
	I_D	Continuous (T_A = 25°C, $R_{\theta JA}$ = 45°C/W)	10	A
		Pulsed (25°C, T_{PULSE} = 300 µs)	70	
	V_{GS}	Gate-to-Source Voltage	6	V
		Gate-to-Source Voltage	-4	
	T_J	Operating Temperature	–40 to 150	°C
	T_{STG}	Storage Temperature	–40 to 150	
Q2	V_{DS}	Drain-to-Source Voltage (Continuous)	80	V
		Drain-to-Source Voltage (up to 10,000 5 ms pulses at 150°C)	96	
	I_D	Continuous (T_A = 25°C, $R_{\theta JA}$ = 11°C/W)	40	A
		Pulsed (25°C, T_{PULSE} = 300 µs)	300	
	V_{GS}	Gate-to-Source Voltage	6	V
		Gate-to-Source Voltage	-4	
	T_J	Operating Temperature	–40 to 150	°C
	T_{STG}	Storage Temperature	–40 to 150	

Thermal Characteristics				
	PARAMETER		**TYP**	**UNIT**
Q1	$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	0.4	°C/W
	$R_{\theta JB}$	Thermal Resistance, Junction-to-Board	2.5	
	$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	42	

Note 1: $R_{\theta JA}$ is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board. See https://epc-co.com/epc/documents/product-training/Appnote_Thermal_Performance_of_eGaN_FETs.pdf for details



Die size: 6.05 x 2.3 mm

EPC2105 eGaN® ICs are supplied only in passivated die form with solder bumps.

Applications

- High frequency DC-DC

Benefits

- High frequency operation
- Ultra high efficiency
- High density footprint

Scan QR code or click link below for more information including reliability reports, device models, demo boards!

https://l.ead.me/EPC2105

Static Characteristics (T_J = 25°C unless otherwise stated)							
DEVICE	PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
Q1	BV_{DSS}	Drain-to-Source Voltage	V_{GS} = 0 V, I_D = 0.3 mA	80			V
	I_{DSS}	Drain-Source Leakage	V_{GS} = 0 V, V_{DS} = 64 V		0.003	0.2	mA
	I_{GSS}	Gate-to-Source Forward Leakage	V_{GS} = 5 V		0.005	2.5	mA
		Gate-to-Source Reverse Leakage	V_{GS} = -4 V		0.003	0.2	mA
	$V_{GS(TH)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 2.5 mA	0.8	1.3	2.5	V
	$R_{DS(on)}$	Drain-Source On Resistance	V_{GS} = 5 V, I_D = 20 A		10	14.5	mΩ
	V_{SD}	Source-Drain Forward Voltage	V_{GS} = 0 V, I_S = 0.5 A		1.7		V
Q2	BV_{DSS}	Drain-to-Source Voltage	V_{GS} = 0 V, I_D = 0.75 mA	80			V
	I_{DSS}	Drain-Source Leakage	V_{GS} = 0 V, V_{DS} = 64 V		0.01	0.55	mA
	I_{GSS}	Gate-to-Source Forward Leakage	V_{GS} = 5 V		0.02	9	mA
		Gate-to-Source Reverse Leakage	V_{GS} = -4 V		0.01	0.55	mA
	$V_{GS(TH)}$	Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 10 mA	0.8	1.3	2.5	V
	$R_{DS(on)}$	Drain-Source On Resistance	V_{GS} = 5 V, I_D = 20 A		2.4	3.6	mΩ
	V_{SD}	Source-Drain Forward Voltage	V_{GS} = 0 V, I_S = 0.5 A		1.5		V

Dynamic Characteristics (T_J = 25°C unless otherwise stated)							
DEVICE	PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
Q1	C_{ISS}	Input Capacitance	V_{GS} = 0 V, V_{DS} = 40 V		300	360	pF
	C_{RSS}	Reverse Transfer Capacitance			3		
	C_{OSS}	Output Capacitance			170	255	
	$C_{OSS(ER)}$	Effective Output Capacitance, Energy Related (Note 2)	V_{GS} = 0 V, V_{DS} = 0 to 40 V		215		
	$C_{OSS(TR)}$	Effective Output Capacitance, Time Related (Note 3)			269		
	Q_G	Total Gate Charge	V_{GS} = 5 V, V_{DS} = 40 V, I_D = 20 A		2.7	3.5	nC
	Q_{GS}	Gate-to-Source Charge	V_{DS} = 40 V, I_D = 20 A		0.9		
	Q_{GD}	Gate-to-Drain Charge			0.5		
	$Q_{G(TH)}$	Gate Charge at Threshold			0.6		
	Q_{OSS}	Output Charge	V_{GS} = 0 V, V_{DS} = 40 V		11	17	
	Q_{RR}	Source-Drain Recovery Charge			0		
Q2	C_{ISS}	Input Capacitance	V_{GS} = 0 V, V_{DS} = 40 V		1170	1410	pF
	C_{RSS}	Reverse Transfer Capacitance			12		
	C_{OSS}	Output Capacitance			780	1170	
	$C_{OSS(ER)}$	Effective Output Capacitance, Energy Related (Note 2)	V_{GS} = 0 V, V_{DS} = 0 to 40 V		1000		
	$C_{OSS(TR)}$	Effective Output Capacitance, Time Related (Note 3)			1270		
	Q_G	Total Gate Charge	V_{GS} = 5 V, V_{DS} = 40 V, I_D = 20 A		11	15	nC
	Q_{GS}	Gate-to-Source Charge	V_{DS} = 40 V, I_D = 20 A		3		
	Q_{GD}	Gate-to-Drain Charge			2.1		
	$Q_{G(TH)}$	Gate Charge at Threshold			2		
	Q_{OSS}	Output Charge	V_{GS} = 0 V, V_{DS} = 40 V		51	77	
	Q_{RR}	Source-Drain Recovery Charge			0		

Note 2: $C_{OSS(ER)}$ is a fixed capacitance that gives the same stored energy as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.
Note 3: $C_{OSS(TR)}$ is a fixed capacitance that gives the same charging time as C_{OSS} while V_{DS} is rising from 0 to 50% BV_{DSS}.

Figure 1a (Q1): Typical Output Characteristics at 25°C




Figure 1b (Q2): Typical Output Characteristics at 25°C




Figure 2a (Q1): Typical Transfer Characteristics




Figure 2b (Q2): Typical Transfer Characteristics




Figure 3a (Q1): Typical $R_{DS(on)}$ vs. V_{GS} for Various Drain Currents




Figure 3b (Q2): Typical $R_{DS(on)}$ vs. V_{GS} for Various Drain Currents




Figure 4a (Q1): Typical $R_{DS(on)}$ vs. V_{GS} for Various Temperatures




Figure 4b (Q2): Typical $R_{DS(on)}$ vs. V_{GS} for Various Temperatures




Figure 5a (Q1): Typical Capacitance (Linear Scale)




Figure 5b (Q1): Typical Capacitance (Log Scale)




Figure 5c (Q2): Typical Capacitance (Linear Scale)




Figure 5d (Q2): Typical Capacitance (Log Scale)




Figure 6a (Q1): Typical Output Charge and C_{OSS} Stored Energy




Figure 6b (Q2): Typical Output Charge and C_{OSS} Stored Energy




Figure 7a (Q1): Typical Gate Charge




Figure 7b (Q2): Typical Gate Charge






Figure 8a (Q1): Typical Reverse Drain-Source Characteristics



Note: Negative gate drive voltage increases the reverse drain-source voltage. EPC recommends 0 V for OFF.

Figure 8b (Q2): Typical Reverse Drain-Source Characteristics



Note: Negative gate drive voltage increases the reverse drain-source voltage. EPC recommends 0 V for OFF.

Figure 9a (Q1):
Typical Normalized On-State Resistance vs. Temperature




Figure 9b (Q2):
Typical Normalized On-State Resistance vs. Temperature




Figure 10a (Q1):
Typical Normalized Threshold Voltage vs. Temperature




Figure 10b (Q2):
Typical Normalized Threshold Voltage vs. Temperature




Figure 11a (Q1): Safe Operating Area




Figure 11b (Q2): Safe Operating Area




Figure 12a
Typical Transient Thermal Response Curves




Figure 12b
Typical Transient Thermal Response Curves






Figure 13
Typical Application Circuit



TAPE AND REEL CONFIGURATION

8 mm pitch, 12 mm wide tape on 7" reel




EPC2105 (Note 1)	Dimension (mm) Target	MIN	MAX
a	12.00	11.90	12.30
b	1.75	1.65	1.85
c (Note 2)	5.50	5.45	5.55
d	4.00	3.90	4.10
e	8.00	7.90	8.10
f (Note 2)	2.00	1.95	2.05
g	1.50	1.50	1.60
h	1.50	1.50	1.75

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/JEDEC industry standard.

Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.


DIE MARKINGS



Part Number	Laser Markings Part # Marking Line 1	Lot_Date Code Marking Line 2	Lot_Date Code Marking Line 3
EPC2105	2105	YYYY	ZZZZ

DIE OUTLINE

Solder Bump View



DIM	MIN	Nominal	MAX
A	6020	6050	6080
B	2270	2300	2330
c	400	400	400
d	450	450	450
e	210	225	240
f	187	208	240

Pad 2 is Gate1 (high side);
Pad 4 is Gate2 (low side);
Pad 3 is HS Gate Return;


Pads 5, 12, 13, 14, 15, 22, 23, 24, 25, 32, 33, 34, 35, 42, 43, 44, 45, 52, 53, 54, 55, 62, 63, 64, 65, 72, 73, 74, 75 are Ground;

Pads 1, 11, 21, 31, 41, 51, 61, 71 are V_{IN};

Pads 6, 7, 8, 9, 10, 16, 17, 18, 19, 20, 26, 27, 28, 29, 30, 36, 37, 38, 39, 40, 46, 47, 48, 49, 50, 56, 57, 58, 59, 60, 66, 67, 68, 69, 70 are Switch Node

RECOMMENDED LAND PATTERN


(measurements in µm)



The land pattern is solder mask defined.
Suggest SMD Pads at 200 +20/–10 µm.
190 µm minimum.

RECOMMENDED STENCIL DRAWING

(measurements in µm)



Recommended stencil should be 4 mil (100 µm) thick, must be laser cut, openings per drawing.

Intended for use with SAC305 Type 4 solder, reference 88.5% metals content.

Additional assembly resources available at:
https://epc-co.com/epc/design-support

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

eGaN® is a registered trademark of Efficient Power Conversion Corporation.
EPC Patent Listing: https://epc-co.com/epc/about-epc/patents

Information subject to change without notice.