
2N5366
2N5367

PNP SILICON TRANSISTOR



TO-92 CASE

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR 2N5366 and 2N5367 are silicon PNP epitaxial planar transistors designed for general purpose switching and amplifier applications.

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Collector-Base Voltage	V_{CBO}	40	V
Collector-Emitter Voltage	V_{CEO}	40	V
Emitter-Base Voltage	V_{EBO}	4.0	V
Continuous Collector Current	I_C	300	mA
Continuous Collector Current (tp=10μs)	I_C	700	mA
Power Dissipation	P_D	625	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	200	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	**TEST CONDITIONS**	**MIN**	**TYP**	**MAX**	**UNITS**
I_{CBO}	V_{CB}=40V			100	nA
I_{CBO}	V_{CB}=40V, T_A=100°C			10	μA
I_{CES}	V_{CE}=40V			100	nA
I_{EBO}	V_{EB}=4.0V			10	μA
BV_{CEO}	I_C=10mA	40			V
$V_{CE(SAT)}$	I_C=50mA, I_B=2.5mA			0.25	V
$V_{CE(SAT)}$	I_C=300mA, I_B=30mA			1.0	V
$V_{BE(SAT)}$	I_C=50mA, I_B=2.5mA			1.1	V
$V_{BE(SAT)}$	I_C=300mA, I_B=30mA			2.0	V
$V_{BE(ON)}$	V_{CE}=10V, I_C=2.0mA	0.5		0.8	V
f_T	V_{CE}=10V, I_C=2.0mA		250		MHz


		2N5366		**2N5367**	
		MIN	**MAX**	**MIN**	**MAX**
h_{FE}	V_{CE}=10V, I_C=2.0mA	80	-	200	-
h_{FE}	V_{CE}=1.0V, I_C=50mA	100	300	250	500
h_{FE}	V_{CE}=5.0V, I_C=300mA	40	-	75	-
h_{fe}	V_{CE}=10V, I_C=2.0mA, f=1.0kHz	80	450	200	750

R2 (24-July 2019)

2N5366
2N5367

PNP SILICON TRANSISTOR

TO-92 CASE - MECHANICAL OUTLINE



R1

DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A (DIA)	0.175	0.205	4.45	5.21
B	0.170	0.210	4.32	5.33
C	0.500	-	12.70	-
D	0.016	0.022	0.41	0.56
E	0.100		2.54	
F	0.050		1.27	
G	0.125	0.165	3.18	4.19
H	0.080	0.105	2.03	2.67
I	0.015		0.38	

TO-92 (REV: R1)

LEAD CODE:
1) Emitter
2) Base
3) Collector

MARKING: FULL PART NUMBER

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms