FAIRCHILD SEMICONDUCTOR®

January 2000
Revised June 2005

74VCXH162244
Low Voltage 16-Bit Buffer/Line Driver with Bushold and 26Ω Series Resistor in Outputs

General Description

The VCXH162244 contains sixteen non-inverting buffers with 3-STATE outputs to be employed as a memory and address driver, clock driver, or bus oriented transmitter/receiver. The device is nibble (4-bit) controlled. Each nibble has separate 3-STATE control inputs which can be shorted together for full 16-bit operation.

The VCXH162244 data inputs include active bushold circuitry, eliminating the need for external pull-up resistors to hold unused or floating data inputs at a valid logic level

The 74VCXH162244 is also designed with 26Ω series resistors in the outputs. This design reduces line noise in applications such as memory address drivers, clock drivers, and bus transceivers/transmitters.

The 74VCXH162244 is designed for low voltage (1.4V to 3.6V) V_{CC} applications with output capability up to 3.6V.

The 74VCXH162244 is fabricated with an advanced CMOS technology to achieve high speed operation while maintaining low CMOS power dissipation.

Features


- 1.4V to 3.6V V_{CC} supply operation
- 3.6V tolerant control inputs and outputs
- Bushold on data inputs eliminates the need for external pull-up/pull-down resistors
- 26Ω series resistors in outputs
- t_{PD}
  - 3.3 ns max for 3.0V to 3.6V V_{CC}
- Static Drive (I_{OH}/I_{OL})
  - ±12 mA @ 3.0V V_{CC}
- Uses patented noise/EMI reduction circuitry
- Latch-up performance exceeds 300 mA
- ESD performance:
  - Human body model > 2000V
  - Machine model > 200V

Ordering Code:

Order Number	Package Number	Package Description
74VCXH162244MTD	MTD48	48-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide [TUBES]
74VCXH162244MTX (Note 1)	MTD48	48-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide [TAPE and REEL]

Note 1: Use this Order Number to receive devices in Tape and Reel.

Logic Symbol




Pin Descriptions

Pin Names	Description
$\overline{OE}_n$	Output Enable Input (Active LOW)
I_0–I_{15}	Bushold Inputs
O_0–O_{15}	Outputs

© 2005 Fairchild Semiconductor Corporation

Connection Diagram



Truth Tables

Inputs		Outputs
$\overline{OE}_1$	I_0–I_3	O_0–O_3
L	L	L
L	H	H
H	X	Z

Inputs		Outputs
$\overline{OE}_2$	I_4–I_7	O_4–O_7
L	L	L
L	H	H
H	X	Z

Inputs		Outputs
$\overline{OE}_3$	I_8–I_{11}	O_8–O_{11}
L	L	L
L	H	H
H	X	Z


Inputs		Outputs
$\overline{OE}_4$	I_{12}–I_{15}	O_{12}–O_{15}
L	L	L
L	H	H
H	X	Z

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immaterial (HIGH or LOW, inputs may not float)
Z = High Impedance

Functional Description

The 74VCXH162244 contains sixteen non-inverting buffers with 3-STATE outputs. The device is nibble (4 bits) controlled with each nibble functioning identically, but independent of each other. The control pins may be shorted together to obtain full 16-bit operation.The 3-STATE outputs are controlled by an Output Enable ($\overline{OE}_n$) input. When $\overline{OE}_n$ is LOW, the outputs are in the 2-state mode. When $\overline{OE}_n$ is HIGH, the standard outputs are in the high impedance mode but this does not interfere with entering new data into the inputs.

Logic Diagram



Absolute Maximum Ratings(Note 2)

Supply Voltage (V_{CC})	−0.5V to +4.6V
DC Input Voltage (V_I)	
$\overline{OE}_n$	−0.5V to 4.6V
$I_0 - I_{15}$	−0.5V to V_{CC} + 0.5V
Output Voltage (V_O)	
Outputs 3-STATE	−0.5V to +4.6V
Outputs Active (Note 3)	−0.5V to V_{CC} +0.5V
DC Input Diode Current (I_{IK})	
V_I < 0V	−50 mA
DC Output Diode Current (I_{OK})	
V_O < 0V	−50 mA
V_O > V_{CC}	+50 mA
DC Output Source/Sink Current	
(I_{OH}/I_{OL})	±50 mA
DC V_{CC} or GND Current per	
Supply Pin (I_{CC} or GND)	±100 mA
Storage Temperature Range (T_{STG})	−65°C to +150°C

Recommended Operating Conditions (Note 4)

Power Supply	
Operating	1.4V to 3.6V
Data Retention Only	1.2V to 3.6V
Input Voltage	−0.3V to V_{CC}
Output Voltage (V_O)	
Output in Active States	0V to V_{CC}
Output in 3-STATE	0.0V to 3.6V
Output Current in I_{OH}/I_{OL}	
V_{CC} = 3.0V to 3.6V	±12 mA
V_{CC} = 2.3V to 2.7V	±8 mA
V_{CC} = 1.65V to 2.3V	±3 mA
V_{CC} = 1.4V to 1.6V	±2 mA
Free Air Operating Temperature (T_A)	−40°C to +85°C
Minimum Input Edge Rate ($\Delta t/\Delta V$)	
V_{IN} = 0.8V to 2.0V, V_{CC} = 3.0V	10 ns/V

Note 2: The Absolute Maximum Ratings are those values beyond which the safety of the device cannot be guaranteed. The device should not be operated at these limits. The parametric values defined in the Electrical Characteristics tables are not guaranteed at the Absolute Maximum Ratings. The "Recommended Operating Conditions" table will define the conditions for actual device operation.

Note 3: I_O Absolute Maximum Rating must be observed.

Note 4: Floating or unused control inputs must be held HIGH or LOW.

DC Electrical Characteristics

Symbol	Parameter	Conditions	V_{CC} (V)	Min	Max	Units
V_{IH}	HIGH Level Input Voltage		2.7 - 3.6	2.0		V
			2.3 - 2.7	1.6		
			1.65 - 2.3	0.65 × V_{CC}		
			1.4 - 1.6	0.65 × V_{CC}		
V_{IL}	LOW Level Input Voltage		2.7 - 3.6		0.8	V
			2.3 - 2.7		0.7	
			1.65 - 2.3		0.35 × V_{CC}	
			1.4 - 1.6		0.35 × V_{CC}	
V_{OH}	HIGH Level Output Voltage	I_{OH} = −100 μA	2.7 - 3.6	V_{CC} - 0.2		V
		I_{OH} = −6 mA	2.7	2.2		
		I_{OH} = −8 mA	3.0	2.4		
		I_{OH} = −12 mA	3.0	2.2		
		I_{OH} = −100 μA	2.3 - 2.7	V_{CC} - 0.2		
		I_{OH} = −4 mA	2.3	2.0		
		I_{OH} = −6 mA	2.3	1.8		
		I_{OH} = −8 mA	2.3	1.7		
		I_{OH} = −100 μA	1.65 - 2.3	V_{CC} - 0.2		
		I_{OH} = −3 mA	1.65	1.25		
		I_{OH} = −100 μA	1.4 - 1.6	V_{CC} - 0.2		
		I_{OH} = −1 mA	1.4	1.05		

DC Electrical Characteristics (Continued)

Symbol	Parameter		Conditions	V_{CC} (V)	Min	Max	Units
V_{OL}	LOW Level Output Voltage		I_{OL} = 100 μA	2.7 - 3.6		0.2	V
			I_{OL} = 6 mA	2.7		0.4	
			I_{OL} = 8 mA	3.0		0.55	
			I_{OL} = 12 mA	3.0		0.8	
			I_{OL} = 100 μA	2.3 - 2.7		0.2	
			I_{OL} = 6 mA	2.3		0.4	
			I_{OL} = 8 mA	2.3		0.6	
			I_{OL} = 100 μA	1.65 - 2.3		0.2	
			I_{OL} = 3 mA	1.65		0.3	
			I_{OL} = 100 μA	1.4 - 1.6		0.2	
			I_{OL} = 1 mA	1.4		0.35	
I_I	Input Leakage Current	Control Pins	0 ≤ V_I ≤ 3.6V	1.4 - 3.6		±5.0	μA
		Data Pins	V_I = V_{CC} or GND	1.4 - 3.6		±5.0	
$I_{I(HOLD)}$	Bushold Input Minimum Drive Hold Current		V_{IN} = 0.8V	3.0	75		μA
			V_{IN} = 2.0V	3.0	−75		
			V_{IN} = 0.7V	2.3	45		
			V_{IN} = 1.6V	2.3	−45		
			V_{IN} = 0.57V	1.65	25		
			V_{IN} = 1.07V	1.65	−25		
$I_{I(OD)}$	Bushold Input Over-Drive Current to Change State		(Note 5)	3.6	450		μA
			(Note 6)	3.6	−450		
			(Note 5)	2.7	300		
			(Note 6)	2.7	−300		
			(Note 5)	1.95	200		
			(Note 6)	1.95	−200		
I_{OZ}	3-STATE Output Leakage		0 ≤ V_O ≤ 3.6V; V_I = V_{IH} or V_{IL}	2.7 - 3.6		±10.0	μA
I_{OFF}	Power-OFF Leakage Current		0 ≤ (V_O) ≤ 3.6V	0		10.0	μA
I_{CC}	Quiescent Supply Current		V_I = V_{CC} or GND	2.7 - 3.6		20.0	μA
			V_{CC} ≤ (V_O) ≤ 3.6V (Note 7)	2.7 - 3.6		±20.0	μA
ΔI_{CC}	Increase in I_{CC} per Input		V_{IH} = V_{CC} −0.6V	2.7 - 3.6		750	μA

Note 5: An external driver must source at least the specified current to switch from LOW-to-HIGH.

Note 6: An external driver must sink at least the specified current to switch from HIGH-to-LOW.

Note 7: Outputs disabled or 3-STATE only.

AC Electrical Characteristics (Note 8)

Symbol	Parameter	Conditions	V_{CC} (V)	$T_A = -40°C$ to $+85°C$		Units	Figure Number
				Min	Max		
t_{PHL} t_{PLH}	Propagation Delay	$C_L = 30$ pF, $R_L = 500\Omega$	3.3 ± 0.3	0.8	3.3	ns	Figures 1, 2
			2.5 ± 0.2	1.0	3.8		
			1.8 ± 0.15	1.5	7.6		
		$C_L = 30$ pF, $R_L = 500\Omega$	1.5 ± 0.1	1.0	15.2		Figures 5, 6
t_{PZL} t_{PZH}	Output Enable Time	$C_L = 30$ pF, $R_L = 500\Omega$	3.3 ± 0.3	0.8	3.8	ns	Figures 1, 3, 4
			2.5 ± 0.2	1.0	5.1		
			1.8 ± 0.15	1.5	9.8		
		$C_L = 30$ pF, $R_L = 500\Omega$	1.5 ± 0.1	1.0	19.6		Figures 5, 7, 8
t_{PLZ} t_{PHZ}	Output Disable Time	$C_L = 30$ pF, $R_L = 500\Omega$	3.3 ± 0.3	0.8	3.6	ns	Figures 1, 3, 4
			2.5 ± 0.2	1.0	4.0		
			1.8 ± 0.15	1.5	7.2		
			1.5 ± 0.1	1.0	14.4		Figures 5, 7, 8
t_{OSHL} t_{OSLH}	Output-to-Output Skew (Note 9)	$C_L = 30$ pF, $R_L = 500\Omega$	3.3 ± 0.3		0.5	ns	
			2.5 ± 0.2		0.5		
			1.8 ± 0.15		0.75		
		$C_L = 30$ pF, $R_L = 500\Omega$	1.5 ± 0.1		1.5		

Note 8: For $C_L = 50_P$F, add approximately 300 ps to the AC maximum specification.

Note 9: Skew is defined as the absolute value of the difference between the actual propagation delay for any two separate outputs of the same device. The specification applies to any outputs switching in the same direction, either HIGH-to-LOW (t_{OSHL}) or LOW-to-HIGH (t_{OSLH}).


Dynamic Switching Characteristics

Symbol	Parameter	Conditions	V_{CC} (V)	$T_A = +25°C$ Typical	Units
V_{OLP}	Quiet Output Dynamic Peak V_{OL}	$C_L = 30$ pF, $V_{IH} = V_{CC}$, $V_{IL} = 0V$	1.8	0.15	V
			2.5	0.25	
			3.3	0.35	
V_{OLV}	Quiet Output Dynamic Valley V_{OL}	$C_L = 30$ pF, $V_{IH} = V_{CC}$, $V_{IL} = 0V$	1.8	−0.15	V
			2.5	−0.25	
			3.3	−0.35	
V_{OHV}	Quiet Output Dynamic Valley V_{OH}	$C_L = 30$ pF, $V_{IH} = V_{CC}$, $V_{IL} = 0V$	1.8	1.55	V
			2.5	2.05	
			3.3	2.65	

Capacitance

Symbol	Parameter	Conditions	$T_A = +25°C$ Typical	Units
C_{IN}	Input Capacitance	$V_{CC} = 1.8$, 2.5V or 3.3V, $V_I = 0V$ or V_{CC}	6.0	pF
C_{OUT}	Output Capacitance	$V_I = 0V$ or V_{CC}, $V_{CC} = 1.8$V, 2.5V or 3.3V	7.0	pF
C_{PD}	Power Dissipation Capacitance	$V_I = 0V$ or V_{CC}, f = 10 MHz, $V_{CC} = 1.8$V, 2.5V or 3.3V	20.0	pF

AC Loading and Waveforms (V_{CC} 3.3V ± 0.3V to 1.8V ± 0.15V)



TEST	SWITCH
t_{PLH}, t_{PHL}	Open
t_{PZL}, t_{PLZ}	6V at V_{CC} = 3.3 ± 0.3V; V_{CC} x 2 at V_{CC} = 2.5 ± 0.2V; 1.8 ± 0.15V
t_{PZH}, t_{PHZ}	GND

FIGURE 1. AC Test Circuit




FIGURE 2. Waveform for Inverting and Non-Inverting Functions




FIGURE 3. 3-STATE Output High Enable and Disable Times for Low Voltage Logic





FIGURE 4. 3-STATE Output Low Enable and Disable Times for Low Voltage Logic

Symbol	V_{CC}		
	3.3V ± 0.3V	2.5V ± 0.2V	1.8V ± 0.15V
V_{mi}	1.5V	V_{CC}/2	V_{CC}/2
V_{mo}	1.5V	V_{CC}/2	V_{CC}/2
V_X	V_{OL} +0.3V	V_{OL} +0.15V	V_{OL} +0.15V
V_Y	V_{OH} −0.3V	V_{OH} −0.15V	V_{OH} −0.15V

AC Loading and Waveforms (V_{CC} 1.5V ± 0.1V)



TEST	SWITCH
t_{PLH}, t_{PHL}	Open
t_{PZL}, t_{PLZ}	V_{CC} x 2 at V_{CC} = 1.5V ± 0.1V
t_{PZH}, t_{PHZ}	GND

FIGURE 5. AC Test Circuit




FIGURE 6. Waveform for Inverting and Non-Inverting Functions




FIGURE 7. 3-STATE Output High Enable and Disable Times for Low Voltage Logic





FIGURE 8. 3-STATE Output Low Enable and Disable Times for Low Voltage Logic

Symbol	V_{CC}
	1.5V ± 0.1V
V_{mi}	V_{CC}/2
V_{mo}	V_{CC}/2
V_X	V_{OL} +0.1V
V_Y	V_{OH} −0.1V

Physical Dimensions inches (millimeters) unless otherwise noted



48-Lead Thin Shrink Small Outline Package (TSSOP), JEDEC MO-153, 6.1mm Wide
Package Number MTD48

Fairchild does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and Fairchild reserves the right at any time without notice to change said circuitry and specifications.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

www.fairchildsemi.com