Is Now Part of

ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

LM2904,LM358/LM358A,LM258/ LM258A

Dual Operational Amplifier

Features

- Internally Frequency Compensated for Unity Gain
- Large DC Voltage Gain: 100dB
- Wide Power Supply Range:
  LM258/LM258A, LM358/LM358A: 3V~32V (or ±1.5V ~ 16V)
  LM2904 : 3V~26V (or ±1.5V ~ 13V)
- Input Common Mode Voltage Range Includes Ground
- Large Output Voltage Swing: 0V DC to Vcc -1.5V DC
- Power Drain Suitable for Battery Operation.

Description

The LM2904,LM358/LM358A, LM258/LM258A consist of two independent, high gain, internally frequency compensated operational amplifiers which were designed specifically to operate from a single power supply over a wide range of voltage. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage. Application areas include transducer amplifier, DC gain blocks and all the conventional OP-AMP circuits which now can be easily implemented in single power supply systems.



Internal Block Diagram



©2010 Fairchild Semiconductor Corporation

Schematic Diagram

(One section only)



Absolute Maximum Ratings

Parameter	Symbol	LM258/LM258A	LM358/LM358A	LM2904	Unit
Supply Voltage	V_{CC}	±16 or 32	±16 or 32	±13 or 26	V
Differential Input Voltage	$V_{I(DIFF)}$	32	32	26	V
Input Voltage	V_I	-0.3 to +32	-0.3 to +32	-0.3 to +26	V
Output Short Circuit to GND $V_{CC} \leq 15V$, $T_A = 25°C$(One Amp)	-	Continuous	Continuous	Continuous	-
Operating Temperature Range	T_{OPR}	-25 ~ +85	0 ~ +70	-40 ~ +85	°C
Maximun Junction Temperature	$T_{J(MAX)}$	+150	+150	+150	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	-65 ~ +150	-65 ~ +150	°C

Electrical Characteristics

(V_{CC} = 5.0V, V_{EE} = GND, T_A = 25°C, unless otherwise specified)

Parameter	Symbol	Conditions	LM258			LM358			LM2904			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω	-	2.9	5.0	-	2.9	7.0	-	2.9	7.0	mV
Input Offset Current	I_{IO}	-	-	3	30	-	5	50	-	5	50	nA
Input Bias Current	I_{BIAS}	-	-	45	150	-	45	250	-	45	250	nA
Input Voltage Range	$V_{I(R)}$	V_{CC} = 30V (LM2904, V_{CC}=26V)	0	-	V_{CC} -1.5	0	-	V_{CC} -1.5	0	-	V_{CC} -1.5	V
Supply Current	I_{CC}	R_L = ∞, V_{CC} = 30V (LM2904, V_{CC}=26V)	-	0.8	2.0	-	0.8	2.0	-	0.8	2.0	mA
		R_L = ∞, V_{CC} = 5V	-	0.5	1.2	-	0.5	1.2	-	0.5	1.2	mA
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L= 2kΩ $V_{O(P)}$ = 1V to 11V	50	100	-	25	100	-	25	100	-	V/mV
Output Voltage Swing	$V_{O(H)}$	V_{CC}=30V (V_{CC} =26V for LM2904) R_L = 2kΩ	26	-	-	26	-	-	22	-	-	V
		R_L= 10kΩ	27	28	-	27	28	-	23	24	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L= 10kΩ	-	5	20	-	5	20		5	20	mV
Common-Mode Rejection Ratio	CMRR	-	70	85	-	65	80	-	50	80	-	dB
Power Supply Rejection Ratio	PSRR	-	65	100	-	65	100	-	50	100	-	dB
Channel Separation	CS	f = 1kHz to 20kHz (Note1)	-	120	-	-	120	-	-	120	-	dB
Short Circuit to GND	I_{SC}	-	-	40	60	-	40	60	-	40	60	mA
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V, V_{CC} = 15V, $V_{O(P)}$ = 2V	20	30	-	20	30	-	20	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 0V, $V_{I(-)}$ = 1V, V_{CC} = 15V, $V_{O(P)}$ = 2V	10	15	-	10	15	-	10	15	-	mA
		$V_{I(+)}$ = 0V,$V_{I(-)}$ =1V , V_{CC} = 15V, $V_{O(P)}$ = 200mV	12	100	-	12	100	-	-	-	-	μA
Differential Input Voltage	$V_{I(DIFF)}$	-	-	-	V_{CC}	-	-	V_{CC}	-	-	V_{CC}	V

Note:

1. This parameter, although guaranteed, is not 100% tested in production.

Electrical Characteristics (Continued)

(V_{CC}= 5.0V, V_{EE} = GND, unless otherwise specified)
The following specification apply over the range of -25°C ≤ T_A ≤ +85°C for the LM258; and the 0°C ≤ T_A ≤ +70°C for the LM358; and the -40°C ≤ T_A ≤ +85°C for the LM2904

Parameter	Symbol	Conditions	LM258			LM358			LM2904			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω	-	-	7.0	-	-	9.0	-	-	10.0	mV
Input Offset Voltage Drift	$\Delta V_{IO}/\Delta T$	R_S = 0Ω	-	7.0	-	-	7.0	-	-	7.0	-	μV/°C
Input Offset Current	I_{IO}	-	-	-	100	-	-	150	-	45	200	nA
Input Offset Current Drift	$\Delta I_{IO}/\Delta T$	-	-	10	-	-	10	-	-	10	-	pA/°C
Input Bias Current	I_{BIAS}	-	-	40	300	-	40	500	-	40	500	nA
Input Voltage Range	$V_{I(R)}$	V_{CC} = 30V (LM2904 , V_{CC} = 26V)	0	-	V_{CC} -2.0	0	-	V_{CC} -2.0	0	-	V_{CC} -2.0	V
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L =2.0kΩ $V_{O(P)}$ = 1V to 11V	25	-	-	15	-	-	15	-	-	V/mV
Output Voltage Swing	$V_{O(H)}$	V_{CC}=30V (V_{CC} = 26V for LM2904) R_L = 2kΩ	26	-	-	26	-	-	22	-	-	V
		R_L=10kΩ	27	28	-	27	28	-	23	24	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L=10kΩ	-	5	20	-	5	20	-	5	20	mV
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V, V_{CC} = 15V, $V_{O(P)}$ = 2V	10	30	-	10	30	-	10	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 0V, $V_{I(-)}$ = 1V, V_{CC} = 15V, $V_{O(P)}$ = 2V	5	8	-	5	9	-	5	9	-	mA
Differential Input Voltage	$V_{I(DIFF)}$	-	-	-	V_{CC}	-	-	V_{CC}	-	-	V_{CC}	V

Electrical Characteristics (Continued)

(V_{CC} = 5.0V, V_{EE} = GND, T_A = 25°C, unless otherwise specified)

Parameter	Symbol	Conditions		LM258A			LM358A			Unit
				Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω		-	1.0	3.0	-	2.0	3.0	mV
Input Offset Current	I_{IO}	-		-	2	15	-	5	30	nA
Input Bias Current	I_{BIAS}	-		-	40	80	-	45	100	nA
Input Voltage Range	$V_{I(R)}$	V_{CC} = 30V		0	-	V_{CC} -1.5	0	-	V_{CC} -1.5	V
Supply Current	I_{CC}	R_L = ∞,V_{CC} = 30V		-	0.8	2.0	-	0.8	2.0	mA
		RL = ∞, V_{CC} = 5V		-	0.5	1.2	-	0.5	1.2	mA
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L= 2kΩ V_O = 1V to 11V		50	100	-	25	100	-	V/mV
Output Voltage Swing	V_{OH}	V_{CC} = 30V	R_L = 2kΩ	26	-	-	26		-	V
			R_L =10kΩ	27	28	-	27	28	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L=10kΩ		-	5	20	-	5	20	mV
Common-Mode Rejection Ratio	CMRR	-		70	85	-	65	85	-	dB
Power Supply Rejection Ratio	PSRR	-		65	100	-	65	100	-	dB
Channel Separation	CS	f = 1kHz to 20kHz (Note1)		-	120	-	-	120	-	dB
Short Circuit to GND	I_{SC}	-		-	40	60	-	40	60	mA
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		20	30	-	20	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		10	15	-	10	15	-	mA
		V_{in+} = 0V, $V_{in(-)}$ = 1V $V_{O(P)}$ = 200mV		12	100	-	12	100	-	μA
Differential Input Voltage	$V_{I(DIFF)}$	-		-	-	V_{CC}	-	-	V_{CC}	V

Note:

1. This parameter, although guaranteed, is not 100% tested in production.

Electrical Characteristics (Continued)

(V_{CC} = 5.0V, V_{EE} = GND, unless otherwise specified)
The following specification apply over the range of -25°C ≤ T_A ≤ +85°C for the LM258A; and the 0°C ≤ T_A ≤ +70°C for the LM358A

Parameter	Symbol	Conditions		LM258A			LM358A			Unit
				Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω		-	-	4.0	-	-	5.0	mV
Input Offset Voltage Drift	$\Delta V_{IO}/\Delta T$	-		-	7.0	15	-	7.0	20	µV/°C
Input Offset Current	I_{IO}	-		-	-	30	-	-	75	nA
Input Offset Current Drift	$\Delta I_{IO}/\Delta T$	-		-	10	200	-	10	300	pA/°C
Input Bias Current	I_{BIAS}	-		-	40	100	-	40	200	nA
Input Common-Mode Voltage Range	$V_{I(R)}$	V_{CC} = 30V		0	-	Vcc -2.0	0	-	Vcc -2.0	V
Output Voltage Swing	$V_{O(H)}$	V_{CC} = 30V	R_L = 2kΩ	26	-	-	26	-	-	V
			R_L = 10kΩ	27	28	-	27	28	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L=10kΩ		-	5	20	-	5	20	mV
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L=2.0kΩ $V_{O(P)}$ = 1V to 11V		25	-	-	15	-	-	V/mV
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		10	30	-	10	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		5	9	-	5	9	-	mA
Differential Input Voltage	$V_{I(DIFF)}$	-		-	-	V_{CC}	-	-	V_{CC}	V

Typical Performance Characteristics



Figure 1. Supply Current vs Supply Voltage



Figure 2. Voltage Gain vs Supply Voltage



Figure 3. Open Loop Frequency Response



Figure 4. Large Signal Output Swing vs Frequency



Figure 5. Output Characteristics vs Current Sourcing



Figure 6. Output Characteristics vs Current Sinking

Typical Performance Characteristics (Continued)



Figure 7. Input Voltage Range vs Supply Voltage



Figure 8. Common-Mode Rejection Ratio



Figure 9. Output Current vs Temperature (Current Limiting)



Figure 10. Input Current vs Temperature



Figure 11. Voltage Follower Pulse Response



Figure 12. Voltage Follower Pulse Response (Small Signal)

Mechanical Dimensions

Package

Dimensions in millimeters

8-DIP



Mechanical Dimensions (Continued)

Package

Dimensions in millimeters

8-SOP



Ordering Information

Product Number	Package	Operating Temperature
LM358N	8-DIP	0 ~ +70°C
LM358AN		
LM358M	8-SOP	
LM358AM		
LM2904N	8-DIP	-40 ~ +85°C
LM2904M	8-SOP	
LM258N	8-DIP	-25 ~ +85°C
LM258AN		
LM258M	8-SOP	
LM258AM		

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2010 Fairchild Semiconductor Corporation

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative