MicroSmart FC6A PLC

Bluetooth Communication



KEY FEATURES

- Supports maintenance and user protocols
- Communicates with FC6A mobile app
- Communicates with barcode reader

Classl Div2
Hazardous
Location


FC6A BLUETOOTH COMMUNICATION CARTRIDGE

Part No.	FC6A-PC4
Bluetooth Standard	Bluetooth ver 2.1 + EDR
Profile	SPP (Serial Port Profile) iAP (iPod Accessory Protocol)
Frequency Range	2,402MHz to 2,480MHz
Wireless Transmission Distance (*1)	10m (Class 2)
Multi-point Function	8 units
Communication Protocol	Maintenance communication protocol User communication protocol
Bluetooth Wireless Approved Regions (*1)	Japan, People's Republic of China, Taiwan, USA, Canada, Australia, New Zealand, Europe

*1: Depending on countries or regions, evaluation on the device equipped with FC6A may be necessary.

DIMENSIONS (mm)

FC6A-PC4



IDEC Corporation • 1175 Elko Drive • Sunnyvale, CA 94089 • 800-262-IDEC (4332) • Fax: 408-745-5258 • www.IDEC.com/usa

©2017 IDEC Corporation. All Rights Reserved. FC9Y-DS300-0c 10/17 PDF Only