FDMS1D2N03DSD

POWERTRENCH® Power Clip 30 V Asymmetric Dual N-Channel MOSFETs

ON Semiconductor®

www.onsemi.com

General Description

This device includes two specialized N-Channel MOSFETs in a dual package. The switch node has been internally connected to enable easy placement and routing of synchronous buck converters. The control MOSFET (Q1) and synchronous SyncFET™ (Q2) have been designed to provide optimal power efficiency.

Features

Q1: N-Channel

- Max $R_{DS(on)}$ = 3.25 mΩ at V_{GS} = 10 V, I_D = 19 A
- Max $R_{DS(on)}$ = 4 mΩ at V_{GS} = 4.5 V, I_D = 17 A

Q2: N-Channel

- Max $R_{DS(on)}$ = 0.97 mΩ at V_{GS} = 10 V, I_D = 37 A
- Max $R_{DS(on)}$ = 1.25 mΩ at V_{GS} = 4.5 V, I_D = 34 A
- Low Inductance Packaging Shortens Rise/Fall Times, Resulting in Lower Switching Losses.
- MOSFET Integration Enables Optimum Layout for Lower Circuit Inductance and Reduced Switch Node Ringing.
- RoHS Compliant

Applications

- Computing
- Communications
- General Purpose Point of Load

ELECTRICAL CONNECTION



N-Channel MOSFET



Top View Bottom View

Power Clip 56
(PQFN8 5x6)
CASE 483AR

PIN ASSIGNMENT



*PAD9 V+(HSD)

MARKING DIAGRAM

$Y	= ON Semiconductor Logo
&Z	= Assembly Plant Code
&3	= Numeric Date Code
&K	= Lot Code
FDMS1D2N03DSD	= Specific Device Code

ORDERING INFORMATION

See detailed ordering and shipping information on page 2 of this data sheet.

© Semiconductor Components Industries, LLC, 2016

MOSFET MAXIMUM RATINGS (T_A = 25°C, Unless otherwise specified)

Symbol	Parameter	Q1	Q2	Unit
V_{DS}	Drain to Source Voltage	30	30	V
V_{GS}	Gate to Source Voltage	+16/−12	+16/−12	V
I_D	Drain Current − Continuous (T_C = 25°C) (Note 5)	70	164	A
	− Continuous (T_C = 85°C) (Note 5)	54	126	
	− Continuous (T_A = 25°C)	19 (Note 1a)	37 (Note 1b)	
	− Continuous (T_A = 85°C)	15 (Note 1a)	29 (Note 1b)	
	− Pulsed (T_A = 25°C) (Note 4)	362	1199	
E_{AS}	Single Pulsed Avalanche Energy (Note 3)	121	337	mJ
P_D	Power Dissipation for Single Operation (T_C = 25°C) (T_A = 25°C)	26 2.1 (Note 1a)	42 2.3 (Note 1b)	W
T_J, T_{STG}	Operating and Storage Junction Temperature Range	−55 to +150		°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Symbol	Parameter	Q1	Q2	Unit
$R_{\theta JC}$	Thermal Resistance, Junction to Case	4.8	3.0	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	60 (Note 1a)	55 (Note 1b)	°C/W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient	130 (Note 1c)	120 (Note 1d)	°C/W

PACKAGE MARKING AND ORDERING INFORMATION

Device	Top Marking	Package	Reel Size	Tape Width	Quantity
FDMS1D2N03DSD	FDMS1D2N03DSD	Power Clip 56 (PGFN8) (Pb-Free / Halogen Free)	13″	12 mm	3,000 Units

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Unit
OFF CHARACTERISTICS							
BV_{DSS}	Drain to Source Breakdown Voltage	I_D = 1 mA, V_{GS} = 0 V	Q1 Q2	30 30	− −	− −	V
$\Delta BV_{DSS}/\Delta T_J$	Breakdown Voltage Temperature Coefficient	I_D = 10 mA, referenced to 25°C	Q1 Q2	− −	15 21	− −	mV/°C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS} = 24 V, V_{GS} = 0 V	Q1 Q2	− −	− −	1 500	μA
I_{GSS}	Gate to Source Leakage Current, Forward	V_{GS} = +16 V/−12 V, V_{DS}= 0 V	Q1 Q2	− −	− −	±100 ±100	nA nA
ON CHARACTERISTICS							
$V_{GS(th)}$	Gate to Source Threshold Voltage	V_{GS} = V_{DS}, I_D = 320 μA V_{GS} = V_{DS}, I_D = 1 mA	Q1 Q2	0.8 1.0	1.3 1.5	2.5 3.0	V
$\Delta V_{GS(th)}/\Delta T_J$	Gate to Source Threshold Voltage Temperature Coefficient	I_D = 1 mA, referenced to 25°C I_D = 10 mA, referenced to 25°C	Q1 Q2	− −	−3 −3	− −	mV/°C

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Symbol	Parameter	Test Conditions	Type	Min	Typ	Max	Unit
ON CHARACTERISTICS							
$R_{DS(on)}$	Drain to Source On Resistance	V_{GS} = 10 V, I_D = 19 A V_{GS} = 4.5 V, I_D = 17 A V_{GS} = 10 V, I_D = 19 A, T_J =125°C	Q1	– – –	2.5 3.0 3.6	3.25 4.0 4.9	mΩ
		V_{GS} = 10 V, I_D = 37 A V_{GS} = 4.5 V, I_D = 34 A V_{GS} = 10 V, I_D = 37 A, T_J =125°C	Q2	– – –	0.73 0.93 1.1	0.97 1.25 1.6	
g_{FS}	Forward Transconductance	V_{DS} = 5 V, I_D = 19 A V_{DS} = 5 V, I_D = 37 A	Q1 Q2	– –	95 247	– –	S
DYNAMIC CHARACTERISTICS							
C_{iss}	Input Capacitance	Q1: V_{DS} = 15 V, V_{GS} = 0 V, f = 1 MHZ Q2: V_{DS} = 15 V, V_{GS} = 0 V, f = 1 MHZ	Q1 Q2	– –	1410 4860	– –	pF
C_{oss}	Output Capacitance		Q1 Q2	– –	564 1845	– –	pF
C_{rss}	Reverse Transfer Capacitance		Q1 Q2	– –	40 123	– –	pF
R_g	Gate Resistance		Q1 Q2	– –	0.3 0.3	– –	Ω
SWITCHING CHARACTERISTICS							
$t_{d(on)}$	Turn-On Delay Time	Q1: V_{DD} = 15 V, I_D = 19 A, R_{GEN} = 6 Ω Q2: V_{DD} = 15 V, I_D = 37 A, R_{GEN} = 6 Ω	Q1 Q2	– –	8 13	– –	ns
t_r	Rise Time		Q1 Q2	– –	2 5	– –	ns
$t_{d(off)}$	Turn-Off Delay Time		Q1 Q2	– –	22 37	– –	ns
t_f	Fall Time		Q1 Q2	– –	2 4	– –	ns
Q_g	Total Gate Charge	V_{GS} = 0 V to 10 V Q1: V_{DD} = 15 V, I_D = 19 A Q2: V_{DD} = 15 V, I_D = 37 A	Q1 Q2	– –	23 84	33 117	nC
Q_g	Total Gate Charge	V_{GS} = 0 V to 4.5 V Q1: V_{DD} = 15 V, I_D = 19 A Q2: V_{DD} = 15 V, I_D = 37 A	Q1 Q2	– –	11 39	15 54	nC
Q_{gs}	Gate to Source Gate Charge	Q1: V_{DD} = 15 V, I_D = 19 A Q2: V_{DD} = 15 V, I_D = 37 A	Q1 Q2	– –	3.1 13	– –	nC
Q_{gd}	Gate to Drain “Miller” Charge	Q1: V_{DD} = 15 V, I_D = 19 A Q2: V_{DD} = 15 V, I_D = 37 A	Q1 Q2	– –	2.5 9	– –	nC
SOURCE-DRAIN DIODE CHARACTERISTICS							
V_{SD}	Source to Drain Diode Forward Voltage	V_{GS} = 0 V, I_S = 19 A (Note 2) V_{GS} = 0 V, I_S = 37 A (Note 2)	Q1 Q2	– –	0.8 0.8	1.2 1.2	V
t_{rr}	Reverse Recovery Time	Q1: I_F = 19 A, di/dt = 100 A/μs Q2: I_F = 37 A, di/dt = 300 A/μs	Q1 Q2	– –	28 43	– –	ns
Q_{rr}	Reverse Recovery Charge		Q1 Q2	– –	12 63	– –	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

NOTES:

1. $R_{\theta JA}$ is determined with the device mounted on a 1 in^2 pad 2 oz copper pad on a 1.5 × 1.5 in. board of FR−4 material. $R_{\theta CA}$ is determined by the user's board design.



a) 60°C/W when mounted on a 1 in^2 pad of 2 oz copper.



b) 55°C/W when mounted on a 1 in^2 pad of 2 oz copper.



c) 130°C/W when mounted on a minimum pad of 2 oz copper.



d) 120°C/W when mounted on a minimum pad of 2 oz copper.

2. Pulse Test: Pulse Width < 300 μs, Duty cycle < 2.0%.
3. Q1: E_{AS} of 121 mJ is based on starting T_J = 25°C; N-ch: L = 3 mH, I_{AS} = 9 A, V_{DD} = 30 V. 100% tested at L = 0.1 mH, I_{AS} = 29 A.
   Q2: E_{AS} of 337 mJ is based on starting T_J = 25°C; N-ch: L = 3 mH, I_{AS} = 15 A, V_{DD} = 30 V. 100% tested at L = 0.1 mH, I_{AS} = 47 A.
4. Pulsed Id please refer to Figure 11 and Figure 24 SOA graphs for more details.
5. Computed continuous current limited to Max Junction Temperature only, actual continuous current will be limited by thermal & electro-mechanical application board design.

TYPICAL CHARACTERISTICS (Q1 N-Channel)

(T_J = 25°C unless otherwise noted)



Figure 1. On-Region Characteristics



Figure 2. Normalized On-Resistance vs. Drain Current and Gate Voltage



Figure 3. Normalized On-Resistance vs. Junction Temperature



Figure 4. On-Resistance vs. Gate to Source Voltage



Figure 5. Transfer Characteristics



Figure 6. Source to Drain Diode Forward Voltage vs. Source Current

TYPICAL CHARACTERISTICS (Q1 N-Channel)

(T_J = 25°C unless otherwise noted)



Figure 7. Gate Charge Characteristics



Figure 8. Capacitance vs. Drain to Source Voltage



Figure 9. Unclamped Inductive Switching Capability



Figure 10. Maximum Continuous Drain Current vs. Case Temperature



Figure 11. Forward Bias Safe Operating Area



Figure 12. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (Q1 N-Channel)

(T_J = 25°C unless otherwise noted)



Figure 13. Junction-to-Case Transient Thermal Response Curve

TYPICAL CHARACTERISTICS (Q2 N-Channel)

(T_J = 25°C unless otherwise noted)



Figure 14. On-Region Characteristics



Figure 15. Normalized On-Resistance vs. Drain Current and Gate Voltage



Figure 16. Normalized On-Resistance vs. Junction Temperature



Figure 17. On-Resistance vs. Gate to Source Voltage



Figure 18. Transfer Characteristics



Figure 19. Source to Drain Diode Forward Voltage vs. Source Current

TYPICAL CHARACTERISTICS (Q2 N-Channel)

(T_J = 25°C unless otherwise noted)



Figure 20. Gate Charge Characteristics



Figure 21. Capacitance vs. Drain to Source Voltage



Figure 22. Unclamped Inductive Switching Capability



Figure 23. Maximum Continuous Drain Current vs. Case Temperature



Figure 24. Forward Bias Safe Operating Area



Figure 25. Single Pulse Maximum Power Dissipation

TYPICAL CHARACTERISTICS (Q2 N-Channel)

(T_J = 25°C unless otherwise noted)



Figure 26. Junction-to-Case Transient Thermal Response Curve

TYPICAL CHARACTERISTICS (continued)

SyncFET Schottky Body Diode Characteristics

ON's SyncFET process embeds a Schottky diode in parallel with PowerTrench MOSFET. This diode exhibits similar characteristics to a discrete external Schottky diode in parallel with a MOSFET. Figure 27 shows the reverse recovery characteristic of the FDMS1D2N03DSD.

Schottky barrier diodes exhibit significant leakage at high temperature and high reverse voltage. This will increase the power in the device.



Figure 27. FDMS1D2N03DSD SyncFET Body Diode Reverse Recovery Characteristic



Figure 28. SyncFET Body Diode Reverse Leakage vs. Drain-Source Voltage

POWERTRENCH is a registered trademark and SyncFET is a trademark of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries.



PQFN−8 5.00x6.00x0.75, 1.27P
CASE 483AR
ISSUE E

DATE 29 JUN 2026











RECOMMENDED LAND PATTERN

*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ONSEMI SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

NOTES: UNLESS OTHERWISE SPECIFIED

A) DOES NOT FULLY CONFORM TO JEDEC REGISTRATION, MO-229, DATED 11/2001.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.70	0.75	0.80
A1	0.00	-	0.05
A3	0.20 REF		
b	0.51 BSC		
D	4.90	5.00	5.10
D2	3.05	3.15	3.25
D3	4.12	4.22	4.32
D4	3.80	3.90	4.00
E	5.90	6.00	6.10
E2	2.36	2.46	2.56
E3	0.81	0.91	1.01
E4	1.27	1.37	1.47
E5	0.59 REF		
e	1.27 BSC		
e/2	0.635 BSC		
e1	3.81 BSC		
k	0.52 REF		
L	0.38	0.48	0.58
L4	1.47	1.57	1.67
z	0.55 REF		
z1	0.39 REF		

DOCUMENT NUMBER:	**98AON13666G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**PQFN−8 5.00x6.00x0.75, 1.27P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales