Data Sheet | January 16, 2006 | FN2793.7

16 x 8 x 1 BiMOS-E Crosspoint Switch

The Intersil CD22M3494 is an array of 128 analog switches capable of handling signals from DC to video. Because of the switch structure, input signals may swing through the total supply voltage range, V_{DD} to V_{EE}. Each of the 128 switches may be addressed via the ADDRESS input to the 7 to 128 line decoder. The state of the addressed switch is established by the signal to the DATA input. A low or zero input will open the switch, while a high logic level or a one will result in closure of the addressed switch when the STROBE input goes high from its normally low state. Any number or combination of connections may be active at one time. Each connection, however, must be made or broken individually in the manner previously described. All switches may be reset by taking the RESET input from a zero state to a one state and then returning it to its normal low state.

CS allows crosspoint array to be cascaded for matrix expansion.


Features

- 128 Analog Switches
- Low r_{ON}
- Guaranteed r_{ON} Matching
- Analog Signal Input Voltage Equal to the Supply Voltage
- Wide Operating Voltage . . . . . 4V to 15V
- Parallel Input Addressing
- High Latch Up Current . . . . . 50mA (Min)
- Very Low Crosstalk
- Pin and Functionally Compatible with the Following Types: SGS M3494 and Mitel MT8816
- Pb-Free Plus Anneal Available (RoHS Compliant)

Applications

- PBX Systems
- Instrumentation
- Analog and Digital Multiplexers
- Video Switching Networks

Block Diagram



CAUTION: These devices are sensitive to electrostatic discharge; follow proper IC Handling Procedures.
1-888-INTERSIL or 1-888-468-3774 | Intersil (and design) is a registered trademark of Intersil Americas Inc.
Copyright Intersil Americas Inc. 2000, 2005, 2006. All Rights Reserved
All other trademarks mentioned are the property of their respective owners.

Ordering Information

PART NUMBER	PART MARKING	TEMP. RANGE (°C)	PACKAGE	PKG. DWG. #
CD22M3494E	CD22M3494E	-40 to 85	40 Ld PDIP	E40.6
CD22M3494EZ (See Note)	CD22M3494EZ	-40 to 85	40 Ld PDIP** (Pb-free)	E40.6
CD22M3494MQ*	CD22M3494MQ	-40 to 85	44 Ld PLCC (Mitel Ld Compatible)	N44.65
CD22M3494MQZ* (See Note)	CD22M3494MQZ	-40 to 85	44 Ld PLCC (Mitel Ld Compatible) (Pb-free)	N44.65
CD22M3494MQA*	CD22M3494MQA	-40 to 85	44 Ld PLCC (Mitel Ld Compatible)	N44.65
CD22M3494MQAZ* (See Note)	CD22M3494MQAZ	-40 to 85	44 Ld PLCC (Mitel Ld Compatible) (Pb-free)	N44.65
CD22M3494SQ	CD22M3494SQ	-40 to 85	44 Ld PLCC (SGS Ld Compatible)	N44.65
CD22M3494SQZ (See Note)	CD22M3494SQZ	-40 to 85	44 Ld PLCC (SGS Ld Compatible) (Pb-free)	N44.65


*Add “96” suffix for tape and reel.

**Pb-free PDIPs can be used for through hole wave solder processing only. They are not intended for use in Reflow solder processing. applications.


NOTE: Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

Pinouts


CD22M3494E
(PDIP)
TOP VIEW



CD22M3494MQ
(PLCC) (MITEL LEAD COMPATIBLE)
TOP VIEW



CD22M3494SQ
(PLCC) (SGS LEAD COMPATIBLE)
TOP VIEW



Absolute Maximum Ratings

DC Supply Voltage (V_{DD})
Voltages Referenced to V_{EE} . . . . . -0.5 to 16V
DC Supply Voltage (V_{DD})
Voltages Referenced to V_{SS} . . . . . -0.5, 16V
DC Input Diode Current, I_{IN}
For V_I, Digital < V_{SS} -0.5V or V_I,
Analog < V_{EE} -0.5V or V_I > V_{DD} 0.5V . . . . . ±20mA
DC Output Diode Current, I_{OK}
For V_O, Digital < V_{SS} -0.5V or V_O,
Analog < V_{EE} -0.5V or V_O > V_{DD} 0.5V . . . . . ±20mA
DC Transmission Gate Current . . . . . ±25mA
Power Dissipation Per Package (Po)
For T_A = -40°C to 85°C (PDIP). 500mW
For T_A = 60°C to 85°C Derate Linearly . . . . . 12mW/°C to 200mW
For T_A = -40°C to 85°C (PLCC) 600mW

Thermal Information

Thermal Resistance (Typical, Note 1) θ_{JA} (°C/W)
PDIP Package* 55
PLCC Package. 43
Maximum Junction Temperature Plastic Package . . . . . 150°C
Maximum Storage Temperature Range (T_{STG}). . . . . -65°C to 150°C
Maximum Lead Temperature (Soldering 10s) . . . . . 300°C
(PLCC - Lead Tips Only)
*Pb-free PDIPs can be used for through hole wave solder processing only. They are not intended for use in Reflow solder processing. applications.

Operating Conditions

Operating Temperature Range (T_A)
Package Type E and Q . . . . . -40°C to 85°C
Supply Voltage Range
For T_A = Full Package Temperature Range
V_{SS} = 0V, V_{EE} = 0V, V_{DD} . . . . . 4V to 15V
DC Input or Output Voltage V_I or V_O . . . . . V_{EE} to V_{DD}
Digital Input Voltage. . . . . V_{SS} to V_{DD}

CAUTION: Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

NOTE:

1. θ_{JA} is measured with the component mounted on an evaluation PC board in free air.

Electrical Specifications

T_A = -40°C to 85°C, V_{DD} = 5V, V_{SS} = 0V, V_{EE} = 0V, Unless Otherwise Specified

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
STATIC CONTROLS						
Supply Current	I_{DD}	V_{DD} = 5V, Logic Inputs = V_{DD}	-	-	2	mA
		V_{DD} = 15V, Logic Inputs = V_{DD}	-	-	5	mA
High-Level Input Voltage	V_{IH}	V_{DD} = 5V	2.4 (Note 2)	-	-	V
Low-Level Input Voltage	V_{IL}		-	-	0.8 (Note 2)	V
Input Leakage Current, Digital	I_{IN}	Reset = Low (Note 3)	-	-	±10 (Note 4)	µA

Electrical Specifications

T_A = -40°C to 85°C, V_{DD} = 12V, V_{SS} = 0V, V_{EE} = 0V, Unless Otherwise Specified.

PARAMETER	SYMBOL	TEST CONDITIONS		MIN	TYP	MAX	UNITS
STATIC CROSSPOINTS							
ON Resistance	r_{ON}	V_{SS} = V_{EE} = 0V, T_A = 25°C, V_{IN} = V_{DD}/2, VX - VY = 0.2V	V_{DD} = 10V	-	40	75	Ω
			V_{DD} = 12V	-	36	65	Ω
ON Resistance	r_{ON}	T_A = -40°C to 85°C, V_{IN} = V_{DD}/2, VX -VY = 0.2V, V_{SS} = V_{EE} = 0V	V_{DD} = 10V	-	50	75	Ω
			V_{DD} = 12V	-	45	65	Ω
Difference in ON Resistance Between Any Two Switches	Δr_{ON}	T_A = 25°C, V_{IN} = V_{DD}/2, VX - VY = 0.2V, V_{SS} = V_{EE} = 0V, V_{DD} = 12V		-	6	10	Ω

Electrical Specifications T_A = -40°C to 85°C, V_{DD} = 12V, V_{SS} = 0V, V_{EE} = 0V, Unless Otherwise Specified. **(Continued)**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Difference in ON Resistance Between Any Two Switches	Δr_{ON}	T_A = -40°C to 85°C, V_{IN} = V_{DD}/2, VX - VY = 0.2V, V_{DD} = 12V V_{SS} = V_{EE} = 0V, VDD = 12V	-	-	10	Ω
OFF-State Leakage Current	I_L	|VX - VY| = 12V	-	-	±10 (Note 4)	µA

Electrical Specifications T_A = 25°C, V_{SS} = 0V, V_{EE} = 0V, V_{DD} = 14V, C_L = 50pF, Unless Otherwise Specified.

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNITS
DYNAMIC CROSSPOINTS						
Switch I/O Capacitance		V_{IN} = V_{DD}/2, f = 1MHz	-	-	20	pF
Switch Feedthrough Capacitance		V_{IN} = V_{DD}/2, f = 1MHz	-	0.3	-	pF
Propagation Delay Time (Switch ON) Signal Input to Output, t_{PHL} or t_{PLH}			-	5	30	ns
Frequency Response Channel ON f = 20log (VX/VY) = -3dB		C_L = 3pF, R_L = 75Ω, V_{IN} = $2V_{P-P}$	-	50	-	MHz
Total Harmonic, THD		V_{IN} = $2V_{P-P}$, f = 1kHz	-	0.01	-	%
Feedthrough Channel OFF Feedthrough = 20log (VX/VY) = F_{DT}		V_{IN} = $2V_{P-P}$, f = 1kHz	-	-95	-	dB
Frequency for Signal Crosstalk, f_{CT} Attenuation of:	40dB	V_{IN} = $2V_{P-P}$, R_L = 75Ω	-	10	-	MHz
	110dB	V_{IN} = $2V_{P-P}$, R_L = 1kΩ || 10pF	-	5	-	kHz
Control Crosstalk DATA-Input, ADDRESS, or STROBE to Output		Control Input = $3V_{P-P}$ Square Wave, t_R = t_F = 10ns R_{IN} = 1K, R_{OUT} = 10kΩ || 10pF	-	75	-	mV_{PEAK}

Electrical Specifications T_A = 25°C, V_{SS} = 0V, V_{EE} = 0V, V_{DD} = 14V, R_L = 1kΩ \|\| 50pF, Unless Otherwise Specified.

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
DYNAMIC CONTROLS						
Digital Input Capacitance	C_{IN}	V_{IN} = 5V, f = 1MHz	-	5	-	pF
Propagation Delay Time STROBE to Output						
Switch Turn-ON	t_{PSN}		-	50	100	ns
Switch Turn-OFF	t_{PSF}		-	50	100	ns
DATA-IN to Output						
Turn-ON to High Level	t_{PZH}		-	60	100	ns
Turn-ON to Low Level	t_{PZL}		-	70	100	ns
ADDRESS to Output						
Turn-ON to High Level	t_{PAN}		-	70	-	ns
Turn-OFF to Low Level	t_{PAF}		-	70	-	ns


Electrical Specifications $T_A = 25°C$, $V_{SS} = 0V$, $V_{EE} = 0V$, $V_{DD} = 14V$, $R_L = 1k\Omega \parallel 50pF$, Unless Otherwise Specified. **(Continued)**

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
Setup Time						
CS to STROBE	t_{CS}		10	-	-	ns
DATA-IN to STROBE	t_{DS}		10	-	-	ns
ADDRESS to STROBE	t_{AS}		10	-	-	ns
Hold Time						
STROBE to CS	t_{CH}		10	-	-	ns
ADDRESS to CS			10	-	-	ns
STROBE to DATA-IN	t_{DH}		20	-	-	ns
STROBE to ADDRESS	t_{AH}		10	-	-	ns
DATA-IN to CS			20	-	-	ns
Pulse Width						
STROBE	t_{SPW}		20	-	-	ns
RESET	t_{RPW}		20	-	-	ns
RESET Turn-OFF to Output Delay	t_{PHZ}		-	70	100	ns

NOTES:

2. Operation of V_{IH} at 2.4V or V_{IL} at 0.8V will result in much higher supply current (I_{DD}) than for logic inputs equal to V_{DD} or V_{SS} respectively.
3. Reset $I_{IH} < 20\mu A$, Reset = V_{IH}.
4. At 25°C Limit is $\pm 100nA$.

Timing Diagram



TRUTH TABLE X AXIS

X ADDRESS				
AX3	**AX2**	**AX1**	**AX0**	**X SWITCH**
0	0	0	0	X0
0	0	0	1	X1
0	0	1	0	X2
0	0	1	1	X3
0	1	0	0	X4
0	1	0	1	X5
0	1	1	0	X12
0	1	1	1	X13
1	0	0	0	X6
1	0	0	1	X7
1	0	1	0	X8
1	0	1	1	X9
1	1	0	0	X10
1	1	0	1	X11
1	1	1	0	X14
1	1	1	1	X15

TRUTH TABLE Y AXIS


Y ADDRESS			
AY2	**AY1**	**AY0**	**Y SWITCH**
0	0	0	Y0
0	0	1	Y1
0	1	0	Y2
0	1	1	Y3
1	0	0	Y4
1	0	1	Y5
1	1	0	Y6
1	1	1	Y7

To make a connection (close switch) between any two points, specify an “X” address, a “Y” address, set “DATA” high, and switch “STROBE” from low to high. To break a connection, follow this same procedure with “DATA” low.

Example:

	DATA	X ADDRESS				Y ADDRESS		
		AX3	AX2	AX1	AX0	AY2	AY1	AY0
To connect switch X3 to switch Y4:	1	0	0	1	1	1	0	0
To connect switch X6 to switch Y7:	1	1	0	0	0	1	1	1
To break connection from X3 to Y4:	0	0	0	1	1	1	0	0

Typical Performance Curve



Pin Descriptions


SYMBOL	40 LD PDIP PIN NO.	44 LD PLCC PIN NO.		DESCRIPTION
		MQ	SQ	
POWER SUPPLIES				
V_{DD}	40	44	44	Positive Supply.
V_{SS}	16	18	17	Negative Supply (Digital).
V_{EE}	20	22	22	Negative Supply (Analog).
ADDRESS				
AX0 - AX3	5, 22, 23 and 4	5, 24, 25 and 4		X Address Lines. These pins select one of the 16 rows of switches. See the Truth Table for the valid addresses.
AY0 - AY2	24, 25 and 2	26, 27 and 2		Y Address Lines. These pins select one of the 8 columns of switches. See the Truth Table for the valid addresses.
CONTROL				
DATA	38	42		DATA Input determines the state of the addressed switch. A high or one will close the switch. A low or zero will open the switch.
STROBE	18	20		STROBE Input enables the action defined by the DATA and ADDRESS Inputs. A low or zero results in no action. The ADDRESS Input must be stable before the STROBE Input goes to the active high level. The DATA Input must be stable on the failing edge of the STROBE.
RESET	3	3		MASTER RESET. A high or one on this line opens all switches.
CS	36	40	39	CHIP SELECT. Device is selected when CS is at a high level, allows the crosspoint array to be cascaded for matrix expansion.

Pin Descriptions (Continued)


SYMBOL	40 LD PDIP PIN NO.	44 LD PLCC PIN NO.		DESCRIPTION
		MQ	SQ	
INPUTS/OUTPUTS				
X0 - X5 X6 - X11 X12 - X15	33-28, 8-13, 27, 26, 6, 7	37-32, 9-14, 31, 30, 7, 8		Analog or Digital Inputs/Outputs. These pins are the rows X0 - X15.
Y0 - Y7 I/O	35, 37, 39, 1, 21, 19, 17, 15	39, 41, 43, 1, 23, 21, 19, 17	40, 41, 43, 1, 23, 21, 19, 18	Analog or Digital Inputs/Outputs. These pins are the columns Y0 - Y7.

Pinouts


CD22M3494E
(PDIP)
TOP VIEW



CD22M3494MQ
(PLCC) (MITEL LEAD COMPATIBLE)
TOP VIEW



CD22M3494SQ
(PLCC) (SGS LEAD COMPATIBLE)
TOP VIEW



All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.
Intersil Corporation's quality certifications can be viewed at www.intersil.com/design/quality

Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.

For information regarding Intersil Corporation and its products, see www.intersil.com