


$$V_{CES} = 600V$$

$$I_C = 100A \text{ at } T_C = 80^\circ C$$

$$t_{SC} \geq 10\mu sec$$

$$V_{CE(ON)} = 1.80V \text{ at } I_C = 100A$$

**IGBT Half-Bridge
POWIR 34™ Package**



Applications:

- Industrial Motor Drive
- Uninterruptible Power Supply
- Welding and Cutting Machine
- Switched Mode Power Supply
- Induction Heating
- AC Inverter Drive

Features	Benefits
Low $V_{CE(ON)}$ and Switching Losses	High Efficiency in a Wide Range of Applications
100% RBSOA Tested	Rugged Transient Performance
10μsec Short Circuit Safe Operating Area	
POWIR 34™ Package	Industry Standard
Lead Free	RoHS Compliant, Environmental Friendly

Base Part Number	Package Type	Standard Pack	Quantity	Orderable Part Number
IRG5K100HF06A	POWIR 34™	Box	80	IRG5K100HF06A

Absolute Maximum Ratings of IGBT

V_{CES}	Collector to Emitter Voltage		600	V
V_{GES}	Continuous Gate to Emitter Voltage		±20	V
I_C	Continuous Collector Current	$T_C = 80^\circ C$	100	A
		$T_C = 25^\circ C$	170	A
I_{CM}	Pulse Collector Current	$T_J = 150^\circ C$	200	A
P_D	Maximum Power Dissipation (IGBT)	$T_C = 25^\circ C, T_J = 150^\circ C$	405	W
T_J	Maximum IGBT Junction Temperature		150	°C
T_{JOP}	Maximum Operating Junction Temperature Range		-40 to +150	°C
T_{stg}	Storage Temperature		-40 to +125	°C

Electrical Characteristics of IGBT at $T_J = 25^\circ\text{C}$ (Unless Otherwise Specified)

Parameter		Min.	Typ.	Max.	Unit	Test Conditions	
V _{(BR)CES}	Collector to Emitter Breakdown Voltage	600			V	V _{GE} = 0V, I _C = 1mA	
V _{GE(th)}	Gate Threshold Voltage	3.5	4.5	5.5	V	I _C = 0.25mA, V _{CE} = V _{GE}	
V _{CE(ON)}	Collector to Emitter Saturation Voltage		1.80	2.10	V	T _J = 25°C	I _C = 100A, V _{GE} = 15V
			2.00		V	T _J = 125°C	
I _{CES}	Collector to Emitter Leakage Current			1	mA	V _{GE} = 0V, V _{CE} = V _{CES}	
I _{GES}	Gate to Emitter Leakage Current			400	nA	V _{GE} = ±20V, V _{CE} = 0	

Switching Characteristics of IGBT

Parameter		Min.	Typ.	Max.	Unit	Test Conditions	
t _{d(on)}	Turn-on Delay Time		175		ns	T _J = 25°C	V _{CC} =300V, I _C = 100A, R _G = 20Ω, V _{GE} =±15V, Inductive Load
			175			T _J = 125°C	
t _r	Rise Time		130		ns	T _J = 25°C	
			125			T _J = 125°C	
t _{d(off)}	Turn-off Delay Time		435		ns	T _J = 25°C	
			445			T _J = 125°C	
t _f	Fall Time		125		ns	T _J = 25°C	
			130			T _J = 125°C	
E _{on}	Turn-on Switching Loss		1.3		mJ	T _J = 25°C	
			1.7			T _J = 125°C	
E _{off}	Turn-off Switching Loss		2.4		mJ	T _J = 25°C	
			2.9			T _J = 125°C	
Q _g	Total Gate Charge		530		nC	T _J = 25°C	
C _{ies}	Input Capacitance		6.2		nF	V _{CE} = 25V, V _{GE} = 0V, f = 1MHz, T _J = 25°C	
C _{oes}	Output Capacitance		0.56				
C _{res}	Reverse Transfer Capacitance		0.22				
RBSOA	Reverse Bias Safe Operating Area	Trapezoid				I _C = 200A,V _{CC} = 480V, V _P = 600V, R _G = 15Ω, V _{GE} = +15V to 0V, T _J = 150°C	
SCSOA	Short Circuit Safe Operating Area	10			μs	V _{CC} = 300V, V _{GE} = 15V, T _J = 150°C	

Absolute Maximum Ratings of Freewheeling Diode







V_{RRM}	Repetitive Peak Reverse Voltage	600	V
I_F	Diode Continuous Forward Current, $T_C = 25^\circ\text{C}$	200	A
	Diode Continuous Forward Current, $T_C = 80^\circ\text{C}$	100	
I_{FM}	Pulse Diode Current	200	A





Electrical and Switching Characteristics of Freewheeling Diode

Parameter		Typ.	Max.	Unit	Test Conditions	
V_F	Forward Voltage	1.50	1.80	V	$T_J = 25^\circ\text{C}$	$I_F = 100\text{A}$, $V_{GE} = 0\text{V}$
		1.50			$T_J = 125^\circ\text{C}$	
I_{rr}	Peak Reverse Recovery Current	30		A	$T_J = 25^\circ\text{C}$	$I_F = 100\text{A}$, $di/dt = 820\text{A}/\mu\text{s}$, $V_{rr} = 300\text{V}$, $V_{GE} = -15\text{V}$
		45			$T_J = 125^\circ\text{C}$	
Q_{rr}	Reverse Recovery Charge	1.4		μC	$T_J = 25^\circ\text{C}$	
		3.5			$T_J = 125^\circ\text{C}$	
E_{rec}	Reverse Recovery Energy	0.14		mJ	$T_J = 25^\circ\text{C}$	
		0.69			$T_J = 125^\circ\text{C}$	


Module Characteristics

Parameter		Min.	Typ.	Max.	Unit
V_{iso}	Isolation Voltage (All Terminals Shorted), $f = 50\text{Hz}$, 1minute			2500	V
$R_{\theta JC}$	Junction-to-Case (IGBT)		0.31		$^\circ\text{C}/\text{W}$
$R_{\theta JC}$	Junction-to-Case (Diode)		1.05		$^\circ\text{C}/\text{W}$
$R_{\theta CS}$	Case-To-Sink (Conductive Grease Applied)		0.1		$^\circ\text{C}/\text{W}$
M	Power Terminals Screw: M5	3.0		5.0	N·m
M	Mounting Screw: M6	4.0		6.0	N·m
G	Weight		180		g



Fig.1 Typical IGBT Saturation Characteristics

Fig.2 Typical IGBT Output Characteristics

Fig.3 Typical Diode Forward Characteristics

Fig. 4 Typical Capacitance Characteristics

Fig.5 Typical Switching Loss vs. Collector Current

Fig.6 Typical Switching Loss vs. Gate Resistance


Fig.7 Typical Load Current vs. Frequency

Fig.8 Reverse Bias Safe Operation Area (RBSOA)

Fig.9 Typical Transient Thermal Impedance (IGBT)

Fig.10 Typical Transient Thermal Impedance (Diode)

Internal Circuit:



Package Outline (Unit: mm):



Qualification Information[†]

Qualification Level	Industrial
Moisture Sensitivity Level	Not Applicable
RoHS Compliant	Yes

[†] Qualification standards can be found at International Rectifier's web site: <http://www.irf.com/product-info/reliability/>

International
IR Rectifier

IR WORLD HEADQUARTERS: 101 North Sepulveda Blvd, El Segundo, California, 90245, USA
To contact International Rectifier, please visit: <http://www.irf.com/whoto-call/>