μIPM™-DIP

1.0Ω, 250V

Integrated Power Module for Small Appliance Motor Drive Applications

Description

IRSM505-044 and IRSM515-044 are 3-phase Integrated Power Modules (IPM) designed for advanced appliance motor drive applications such as energy efficient fans and pumps. These advanced IPMs offers a combination of low $R_{DS(on)}$ Trench FREDFET technology and the industry benchmark half-bridge high voltage, rugged driver in a familiar package. The modules are optimized for low EMI characteristics.
IRSM505-044 includes temperature feedback while IRSM515-044 does not.

Features

- 250V 3-phase inverter including high voltage gate drivers
- Integrated bootstrap functionality
- Low 1.0Ω (max, 25°C) $R_{DS(on)}$ Trench FREDFET
- Under-voltage lockout for all channels
- Matched propagation delay for all channels
- Temperature feedback via NTC (IRSM505-044 only)
- Optimized dV/dt for loss and EMI trade offs
- Open-source for single and leg-shunt current sensing
- 3.3V logic compatible
- Driver tolerant to negative transient voltage (-Vs)
- Advanced input filter
- Rugged design for PM fan and pump motors
- Isolation 1900V_{RMS}, 1min







Base Part Number	NTC	Package Type	Standard Pack		Orderable Part Number
			Form	Quantity	
IRSM505-044	Yes	SOP23	Tube	240	IRSM505-044PA
		DIP23	Tube	240	IRSM505-044DA
		DIP23A	Tube	240	IRSM505-044DA2
IRSM515-044	No	SOP23	Tube	240	IRSM515-044PA
		DIP23	Tube	240	IRSM515-044DA
		DIP23A	Tube	240	IRSM515-044DA2

© 2014 International Rectifier

Internal Electrical Schematic



IRSM505-044



IRSM515-044

Absolute Maximum Ratings

Absolute maximum ratings indicate sustained limits beyond which damage to the module may occur. These are not tested at manufacturing. All voltage parameters are absolute voltages referenced to COM unless otherwise stated in the table.

Symbol	Description	Min	Max	Unit
BV_{DSS}	MOSFET Blocking Voltage	---	250	V
I_O @ T_C=25°C	DC Output Current per MOSFET	---	3.0	A
I_{OP} @ T_C =25°C	Pulsed Output Current per MOSFET (Note 1)	---	15	
P_d @ T_C=25°C	Maximum Power Dissipation per MOSFET	---	16	W
V_{ISO}	Isolation Voltage (1min)	---	1900	V_{RMS}
T_J	Operating Junction Temperature	-40	150	°C
T_C	Operating Case Temperature	-40	150	°C
T_S	Storage Temperature	-40	150	°C
$V_{S1,2,3}$	High Side Floating Supply Offset Voltage	$V_{B1,2,3}$ - 20	$V_{B1,2,3}$ +0.3	V
$V_{B1,2,3}$	High Side Floating Supply Voltage	-0.3	275	V
V_{CC}	Low Side and Logic Supply voltage	-0.3	25	V
V_{IN}	Input Voltage of LIN, HIN	COM -0.3	V_{CC}+0.3	V

Note 1: Pulse Width = 100µs, Single Pulse

 © 2014 International Rectifier Submit Datasheet Feedback

Recommended Operating Conditions

Symbol	Description	Min	Max	Unit
V+	Positive DC Bus Input Voltage	---	200	V
$V_{S1,2,3}$	High Side Floating Supply Offset Voltage	(Note 2)	200	V
$V_{B1,2,3}$	High Side Floating Supply Voltage	V_S+12	V_S+20	V
V_{CC}	Low Side and Logic Supply Voltage	13.5	16.5	V
V_{IN}	Input Voltage of LIN, HIN, I_{TRIP}, EN, FLT	0	5	V
F_p	PWM Carrier Frequency	---	20	kHz

Note 2: Logic operational for Vs from COM-8V to COM+250V. Logic state held for Vs from COM-8V to COM-V_{BS}.

Static Electrical Characteristics

(V_{CC}-COM) = (V_B-V_S) = 15 V. T_C = 25°C unless otherwise specified. The V_{IN} and I_{IN} parameters are referenced to COM and are applicable to all six channels. The $V_{CC_{UV}}$ parameters are referenced to COM. The $V_{BS_{UV}}$ parameters are referenced to V_S.

Symbol	Description	Min	Typ	Max	Units	Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	250	---	---	V	T_J=25°C, I_{LK}=250µA
I_{LKH}	Leakage Current of High Side FET		0.5		µA	T_J=25°C, V_{DS}=250V
I_{LKL}	Leakage Current of Low Side FET Plus Gate Drive IC		1		µA	T_J=25°C, V_{DS}=250V
$R_{DS(on)}$	Drain to Source ON Resistance	---	0.8	1.0	Ω	T_J=25°C, V_{CC}=15V, Id=1.0A
		---	1.8	---	Ω	T_J=150°C, V_{CC}=15V, Id=1.0A (Note 3)
V_{SD}	Mosfet Body Diode Forward Voltage	---	0.8	---	V	T_J=25°C, V_{CC}=15V, I_D=1.0A
$V_{IN,th+}$	Positive Going Input Threshold	2.2	---	---	V	
$V_{IN,th-}$	Negative Going Input Threshold	---	---	0.8	V	
V_{CCUV+}, V_{BSUV+}	V_{CC} and V_{BS} Supply Under-Voltage, Positive Going Threshold	8	8.9	9.8	V	
V_{CCUV-}, V_{BSUV-}	V_{CC} and V_{BS} supply Under-Voltage, Negative Going Threshold	6.9	7.7	8.5	V	
V_{CCUVH}, V_{BSUVH}	V_{CC} and V_{BS} Supply Under-Voltage Lock-Out Hysteresis	---	1.2	---	V	
I_{QBS}	Quiescent V_{BS} Supply Current V_{IN}=0V	---	42	60	µA	
$I_{QBS, ON}$	Quiescent V_{BS} Supply Current V_{IN}=4V	---	42	60	µA	
I_{QCC}	Quiescent V_{CC} Supply Current V_{IN}=0V	---	1.7	4	mA	
$I_{QCC, ON}$	Quiescent V_{CC} Supply Current V_{IN}=4V	---	1.8	4	mA	
I_{IN+}	Input Bias Current V_{IN}=4V	---	5.9	18	µA	V_{IN}=3.3V
I_{IN-}	Input Bias Current V_{IN}=0V	---	---	2	µA	V_{IN}=0V
R_{BR}	Internal Bootstrap Equivalent Resistor Value	---	250	---	Ω	T_J=25°C

Note 3: Characterized, not tested at manufacturing

 © 2014 International Rectifier

Dynamic Electrical Characteristics

(V_{CC}-COM) = (V_B-V_S) = 15 V. T_C = 25°C unless otherwise specified.

Symbol	Description	Min	Typ	Max	Units	Conditions
T_{ON}	Input to Output Propagation Turn-On Delay Time	---	0.7	1.5	µs	I_D=120mA, V+=30V See Fig.1
T_{OFF}	Input to Output Propagation Turn-Off Delay Time	---	0.8	1.5	µs	
$T_{FIL,IN}$	Input Filter Time (HIN, LIN)	200	300	---	ns	V_{IN}=0 & V_{IN}=3.3V
DT	Deadtime Inserted	---	400	---	ns	V_{IN}=0 & V_{IN}=3.3V without external deadtime
E_{ON}	Turn-on switching energy loss	---	11	---	µJ	V_+=150V, I_D=0.5A, L=40mH, T_C=25°C (Note 4)
E_{OFF}	Turn-off switching energy loss	---	3	---	µJ	
E_{REC}	Recovery energy loss	---	3	---	µJ	
$E_{ON,150}$	Turn-on switching energy loss	---	15	---	µJ	V_+=150V, I_D=0.5A, L=40mH, T_C=150°C (Note 4)
$E_{OFF,150}$	Turn-off switching energy loss	---	4	---	µJ	
$E_{REC,150}$	Recovery energy loss	---	5	---	µJ	

Note 4: Characterized, not tested at manufacturing

Thermal and Mechanical Characteristics

Symbol	Description	Min	Typ	Max	Units	Conditions
$R_{th(J-C)}$	Junction to Case Thermal Resistance	---	7.9	---	°C/W	High Side V-Phase Mosfet (Note 5)

Note 5: Characterized, not tested at manufacturing. Case temperature (T_C) point shown in Figure 2.

Internal NTC – Thermistor Characteristics (IRSM505-044 Only)

Symbol	Description	Min	Typ	Max	Units	Conditions
R_{25}	Resistance	---	47	---	kΩ	T_C=25°C, ±5% tolerance
R_{125}	Resistance	---	1.41	---	kΩ	T_C=125°C
B	B-constant (25-50°C)	---	4050	---	K	±2% tolerance (Note 6)
Temperature Range		-40	---	125	°C	

Note 6: See application notes for usage

© 2014 International Rectifier Submit Datasheet Feedback

Qualification Information†

Qualification Level		Industrial††
Moisture Sensitivity Level		MSL3†††
RoHS Compliant		Yes
ESD	**Machine Model**	Class B
	Human Body Model	Class 2

† Qualification standards can be found at International Rectifier's web site http://www.irf.com/


†† Higher qualification ratings may be available should the user have such requirements. Please contact your International Rectifier sales representative for further information.

††† SOP23 package only. Higher MSL ratings may be available for the specific package types listed here. Please contact your International Rectifier sales representative for further information.

 © 2014 International Rectifier

Module Pin-Out Description

Pin	Name	Description
1	COM	Logic Ground
2	V_{B1}	High Side Floating Supply Voltage 1
3	V_{CC1}	15V Supply 1
4	HIN1	Logic Input for High Side Gate Driver - Phase 1
5	LIN1	Logic Input for Low Side Gate Driver - Phase 1
6	NC	Not Connected
7	V_{B2}	High Side Floating Supply Voltage 2
8	V_{CC2}	15V Supply 2
9	HIN2	Logic Input for High Side Gate Driver - Phase 2
10	LIN2	Logic Input for Low Side Gate Driver - Phase 2
11	V_{TH}	Thermistor Output (IRSM505-044DA)
	NC	Not Connected (IRSM515-044DA)
12	V_{B3}	High Side Floating Supply Voltage 3
13	V_{CC3}	15V Supply 3
14	HIN3	Logic Input for High Side Gate Driver - Phase 3
15	LIN3	Logic Input for Low Side Gate Driver - Phase 3
16	NC	Not Connected
17	V+	DC Bus Voltage Positive
18	U/V_{S1}	Output - Phase 1, High Side Floating Supply Offset 1
19	V_{R1}	Phase 1 Low Side Source
20	V_{R2}	Phase 2 Low Side Source
21	V/V_{S2}	Output - Phase 2, High Side Floating Supply Offset 2
22	V_{R3}	Phase 3 Low Side Source
23	W/V_{S3}	Output - Phase 3, High Side Floating Supply Offset 2



 © 2014 International Rectifier

Referenced Figures




Figure 1a: Input to Output propagation turn-on delay time.




Figure 1b: Input to Output propagation turn-off delay time.




Figure 1c: Diode Reverse Recovery.

Figure 1: Switching Parameter Definitions




Figure 2: T_C measurement point for $R_{th(j-C)}$

 © 2014 International Rectifier

Application Notes

A basic application schematic is shown below.




Figure 3: Basic sensor-less motor drive circuit connection. Motor is connected to U, V, W

A complete reference design board for running any permanent magnet motor via sensorless sinusoidal control is available. The board – photo below – features the µIPM™-DIP module and the iMotion™ digital control IC. Reference design kits are available on the International Rectifier website (irf.com > Design Resources > Reference Designs > Intelligent Power Modules)



Figure 4: Reference design board featuring the µIPM™-DIP module and the iMotion™ IRMCF171 digital control IC

 © 2014 International Rectifier

Figures 5-6 show the typical current capability for this module at specified conditions. In all tests, the application board – the IRMCS1071-1-D reference board – was placed in a box to prevent cooling from ambient airflow. The figures represent current capability for the module as used without any heat sink. ΔT_{JA} represents the difference in temperature between the junction of the high-side V-phase Mosfet and the ambient, measured 10cm above and 6cm away from the board. Ambient temperature kept within 28-29°C.




Figure 5: Maximum sinusoidal phase current vs PWM switching frequency, no heat sink. Space Vector Modulation, V+=150V, T_A=28°C, T_J=128°C




Figure 6: Maximum sinusoidal phase current vs PWM switching frequency, no heat sink. Space Vector Modulation, V+=150V, T_A=28°C, T_J=98°C

 © 2014 International Rectifier

The module contains an NTC – connected between COM and the V_{TH} pin – which can be used to monitor the temperature of the module. The NTC is effectively a resistor whose value decreases as the temperature rises. The NTC resistance can be calculated at any temperature as follows:

$R_{TH} = R_{25}e^{\left[B\left(\frac{1}{T_{TH}}-\frac{1}{T_{25}}\right)\right]}$, where $R_{25}$is 47kΩ and B is 4050K

An external resistor network is connected to the NTC, the simplest of which is one resistor pulled up to V_{CC} as shown in Figure 3. The V_{TH} vs NTC temperature, T_{TH} curve for this configuration is shown in Figure 7 below. The min, typical and max curves result from the NTC having a ±5% tolerance on its resistance and ±2% tolerance on the B-parameter.

Figure 8 shows the thermistor temperature, T_{TH} plotted against the high-side V-phase junction temperature, T_J for a module without a heat sink. It is thus advisable to shut down the module when T_{TH} reaches 125°C.




Figure 7: V_{TH} vs T_{TH} with V_{TH} pin pulled up to V_{CC} with a 7.50kΩ (1%, 100ppm) resistor. A 15V, 1% variation in V_{CC} is assumed.

 © 2014 International Rectifier





Figure 8: T_{TH} vs T_J for a module without a heat sink. V_{CC}=15.3V, R=7.50kΩ

 © 2014 International Rectifier


SOP23 Package Outline



Dimensions in mm

 © 2014 International Rectifier


DIP23A Package Outline



Dimensions in mm

 © 2014 International Rectifier


DIP23 Package Outline



Dimensions in mm

 © 2014 International Rectifier

Top Marking



Marking Code P = Pb Free; Y = Engineering Samples

Date Code YWW format, where Y = least significant digit of the production year , WW = two digits representing the week of the production year

Revision History

 © 2014 International Rectifier