KA258/KA258A, KA358/KA358A, KA2904


Dual Operational Amplifier

Features


- Internally Frequency Compensated for Unity Gain
- Large DC Voltage Gain: 100dB
- Wide Power Supply Range:
  KA258/KA258A, KA358/KA358A: 3V ~ 32V (or ±1.5V~ 16V)
  KA2904 : 3V~26V (or ±1.5V ~ 13V)
- Input Common Mode Voltage Range Includes Ground
- Large Output Voltage Swing: 0V DC to Vcc - 1.5V DC
- Power Drain Suitable for Battery Operation.


Description

The KA258 series consist of two independent, high gain, internally frequency compensated operational amplifiers which were designed specifically to operate from a single power supply over a wide range of voltage. Operation from split power supplies is also possible and the low power supply current drain is independent of the magnitude of the power supply voltage. Application areas include transducer amplifier, DC gain blocks and all the conventional OP-AMP circuits which now can be easily implemented in single power supply systems.



Internal Block Diagram






Rev. 1.0.2

©2002 Fairchild Semiconductor Corporation

Schematic Diagram

(One section only)



Absolute Maximum Ratings

Parameter	Symbol	KA258/KA258A	KA358/KA358A	KA2904	Unit
Supply Voltage	V_{CC}	±16 or 32	±16 or 32	±13 or 26	V
Differential Input Voltage	$V_{I(DIFF)}$	32	32	26	V
Input Voltage	V_I	-0.3 to +32	-0.3 to +32	-0.3 to +26	V
Output Short Circuit to GND V_{CC}≤15V, T_A = 25°C(One Amp)	-	Continuous	Continuous	Continuous	-
Operating Temperature Range	T_{OPR}	-25 ~ +85	0 ~ +70	-40 ~ +85	°C
Storage Temperature Range	T_{STG}	-65 ~ +150	-65 ~ +150	-65 ~ +150	°C

Electrical Characteristics

(Vcc = 5.0V, V_{EE} = GND, T_A = 25°C, unless otherwise specified)

Parameter	Symbol	Conditions	KA258			KA358			KA2904			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω	-	2.9	5.0	-	2.9	7.0	-	2.9	7.0	mV
Input Offset Current	I_{IO}	-	-	3	30	-	5	50	-	5	50	nA
Input Bias Current	I_{BIAS}	-	-	45	150	-	45	250	-	45	250	nA
Input Voltage Range	$V_{I(R)}$	V_{CC} = 30V (KA2904, V_{CC} = 26V)	0	-	Vcc -1.5	0	-	Vcc -1.5	0	-	Vcc -1.5	V
Supply Current	I_{CC}	R_L = ∞, V_{CC} = 30V (KA2904, V_{CC} = 26V)	-	0.8	2.0	-	0.8	2.0	-	0.8	2.0	mA
		R_L = ∞, V_{CC} = 5V	-	0.5	1.2	-	0.5	1.2	-	0.5	1.2	mA
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L = 2kΩ $V_{O(P)}$ = 1V to 11V	50	100	-	25	100	-	25	100	-	V/mV
Output Voltage Swing	$V_{O(H)}$	V_{CC} = 30V (V_{CC} = 26V for KA2904), R_L = 2kΩ	26	-	-	26	-	-	22	-	-	V
		V_{CC} = 30V (V_{CC} = 26V for KA2904), R_L = 10kΩ	27	28	-	27	28	-	23	24	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L = 10kΩ	-	5	20	-	5	20	-	5	20	mV
Common-Mode Rejection Ratio	CMRR	-	70	85	-	65	80	-	50	80	-	dB
Power Supply Rejection Ratio	PSRR	-	65	100	-	65	100	-	50	100	-	dB
Channel Separation	CS	f = 1kHz to 20kHz (Note1)	-	120	-	-	120	-	-	120	-	dB
Short Circuit to GND	I_{SC}	-	-	40	60	-	40	60	-	40	60	mA
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V	20	30	-	20	30	-	20	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 0V, $V_{I(-)}$ = 1V V_{CC} = 15V, $V_{O(P)}$ = 2V	10	15	-	10	15	-	10	15	-	mA
		$V_{I(+)}$ = 0V, $V_{I(-)}$ = 1V V_{CC} = 15V, $V_{O(P)}$ = 200mV	12	100	-	12	100	-	-	-	-	µA
Differential Input Voltage	$V_{I(DIFF)}$	-	-	-	V_{CC}	-	-	V_{CC}	-	-	V_{CC}	V

Note:

1. This parameter, although guaranteed, is not 100% tested in production.

Electrical Characteristics (Continued)

(V_{CC} = 5.0V, V_{EE} = GND, unless otherwise specified)
The following specification apply over the range of -25°C ≤ T_A ≤ +85°C for the KA258; and the 0 °C ≤ T_A ≤ +70°C for the KA358; and the -40°C ≤ T_A ≤ +85°C for the KA2904

Parameter	Symbol	Conditions	KA258			KA358			KA2904			Unit
			Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω	-	-	7.0	-	-	9.0	-	-	10.0	mV
Input Offset Voltage Drift	$\Delta V_{IO}/\Delta T$	R_S = 0Ω	-	7.0	-	-	7.0	-	-	7.0	-	μV/°C
Input Offset Current	I_{IO}	-	-	-	100	-	-	150	-	45	200	nA
Input Offset Current Drift	$\Delta I_{IO}/\Delta T$	-	-	10	-	-	10	-	-	10	-	pA/°C
Input Bias Current	I_{BIAS}	-	-	40	300	-	40	500	-	40	500	nA
Input Voltage Range	$V_{I(R)}$	V_{CC} = 30V (KA2904,V_{CC} = 26V)	0	-	Vcc -2.0	0	-	Vcc -2.0	0	-	Vcc -2.0	V
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L=2.0kΩ $V_{O(P)}$ = 1V to 11V	25	-	-	15	-	-	15	-	-	V/mV
Output Voltage Swing	$V_{O(H)}$	V_{CC} = 30V (V_{CC} = 26V for KA2904), R_L = 2kΩ	26	-	-	26	-	-	22	-	-	V
		V_{CC} = 30V (V_{CC} = 26V for KA2904), R_L = 10kΩ	27	28	-	27	28	-	23	24	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L=10kΩ	-	5	20	-	5	20	-	5	20	mV
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V	10	30	-	10	30	-	10	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 0V, $V_{I(-)}$ = 1V V_{CC} = 15V, $V_{O(P)}$ = 2V	5	8	-	5	9	-	5	9	-	mA
Differential Input Voltage	$V_{I(DIFF)}$	-	-	-	V_{CC}	-	-	V_{CC}	-	-	V_{CC}	V

Electrical Characteristics (Continued)

(V_{CC} = 5.0V, V_{EE} = GND, T_A = 25°C, unless otherwise specified)

Parameter	Symbol	Conditions		KA258A			KA358A			Unit
				Min.	Typ.	Max.	Mln.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω		-	1.0	3.0	-	2.0	3.0	mV
Input Offset Current	I_{IO}	-		-	2	15	-	5	30	nA
Input Bias Current	I_{BIAS}	-		-	40	80	-	45	100	nA
Input Voltage Range	$V_{I(R)}$	V_{CC} = 30V		0	-	V_{CC} -1.5	0	-	V_{CC} -1.5	V
Supply Current	I_{CC}	R_L = ∞,V_{CC} = 30V		-	0.8	2.0	-	0.8	2.0	mA
		RL = ∞, V_{CC} = 5V		-	0.5	1.2	-	0.5	1.2	mA
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L=2kΩ V_O = 1V to 11V		50	100	-	25	100	-	V/mV
Output Voltage Swing	V_{OH}	V_{CC} = 30V	R_L = 2kΩ	26	-	-	26	-	-	V
			R_L = 10kΩ	27	28	-	27	28	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L=10kΩ		-	5	20	-	5	20	mV
Common-Mode Rejection Ratio	CMRR	-		70	85	-	65	85	-	dB
Power Supply Rejection Ratio	PSRR	-		65	100	-	65	100	-	dB
Channel Separation	CS	f = 1kHz to 20kHz (Note1)		-	120	-	-	120	-	dB
Short Circuit to GND	I_{SC}	-		-	40	60	-	40	60	mA
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		20	30	-	20	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		10	15	-	10	15	-	mA
		$V_{in(+)}$ = 0V, $V_{in\ (-)}$ = 1V $V_{O(P)}$ = 200mV		12	100	-	12	100	-	µA
Differential Input Voltage	$V_{I(DIFF)}$	-		-	-	V_{CC}	-	-	V_{CC}	V

Note:

1. This parameter, although guaranteed, is not 100% tested in production.

Electrical Characteristics (Continued)

(V_{CC} = 5.0V, V_{EE} = GND, unless otherwise specified)
The following specification apply over the range of -25°C ≤ T_A ≤ +85°C for the KA258A; and the 0°C ≤ T_A ≤ +70°C for the KA358A

Parameter	Symbol	Conditions		KA258A			KA358A			Unit
				Min.	Typ.	Max.	Min.	Typ.	Max.	
Input Offset Voltage	V_{IO}	V_{CM} = 0V to V_{CC} -1.5V $V_{O(P)}$ = 1.4V, R_S = 0Ω		-	-	4.0	-	-	5.0	mV
Input Offset Voltage Drift	$\Delta V_{IO}/\Delta T$	-		-	7.0	15	-	7.0	20	µV/°C
Input Offset Current	I_{IO}	-		-	-	30	-	-	75	nA
Input Offset Current Drift	$\Delta I_{IO}/\Delta T$	-		-	10	200	-	10	300	pA/°C
Input Bias Current	I_{BIAS}	-		-	40	100	-	40	200	nA
Input Common-Mode Voltage Range	$V_{I(R)}$	V_{CC} = 30V		0	-	Vcc -2.0	0	-	Vcc -2.0	V
Output Voltage Swing	$V_{O(H)}$	V_{CC} = 30V	R_L = 2kΩ	26	-	-	26	-	-	V
			R_L = 10kΩ	27	28	-	27	28	-	V
	$V_{O(L)}$	V_{CC} = 5V, R_L=10kΩ		-	5	20	-	5	20	mV
Large Signal Voltage Gain	G_V	V_{CC} = 15V, R_L=2.0kΩ $V_{O(P)}$ = 1V to 11V		25	-	-	15	-	-	V/mV
Output Current	I_{SOURCE}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		10	30	-	10	30	-	mA
	I_{SINK}	$V_{I(+)}$ = 1V, $V_{I(-)}$ = 0V V_{CC} = 15V, $V_{O(P)}$ = 2V		5	9	-	5	9	-	mA
Differential Input Voltage	$V_{I(DIFF)}$	-		-	-	V_{CC}	-	-	V_{CC}	V

Typical Performance Characteristics




Figure 1. Supply Current vs Supply Voltage




Figure 2. Voltage Gain vs Supply Voltage




Figure 3. Open Loop Frequency Response




Figure 4. Large Signal Output Swing vs Frequency




Figure 5. Output Characteristics vs Current Sourcing




Figure 6. Output Characteristics vs Current Sinking

Typical Performance Characteristics (Continued)




Figure 7. Input Voltage Range vs Supply Voltage




Figure 8. Common-Mode Rejection Ratio




Figure 9. Output Current vs Temperature (Current Limiting)




Figure 10. Input Current vs Temperature




Figure 11. Voltage Follower Pulse Response





Figure 12. Voltage Follower Pulse Response (Small Signal)

Mechanical Dimensions

Package

Dimensions in millimeters

8-DIP




Mechanical Dimensions (Continued)

Package

Dimensions in millimeters

8-SOP




Mechanical Dimensions (Continued)

Package

Dimensions in millimeters

9-SIP



Ordering Information

Product Number	Package	Operating Temperature
KA358	8-DIP	0 ~ +70°C
KA358A		
KA358D	8-SOP	
KA358AD		
KA358S	9-SIP	
KA358AS		
KA258	8-DIP	-25 ~ +85°C
KA258A		
KA258D	8-SOP	
KA258AD		
KA2904	8-DIP	-40 ~ +85°C
KA2904D	8-SOP	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2002 Fairchild Semiconductor Corporation