

CONFIDENTIAL. THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF COOPER INDUSTRIES, INC. IT IS NOT FOR PUBLIC DISCLOSURE. POSSESSION OF THE INFORMATION DOES NOT CONVEY ANY RIGHT TO LOAN, SELL OR DISCLOSE THE INFORMATION. UNAUTHORIZED REPRODUCTION OR USE OF THE INFORMATION IS PROHIBITED. THIS DOCUMENT IS TO BE RETURNED TO COOPER INDUSTRIES, INC. UPON COMPLETION OF THE PURPOSE FOR WHICH IT IS LOANED OR UPON REQUEST

COPYRIGHT Cooper Industries, Inc.
This is an unpublished work. The disclosure of this work is limited to select personnel. Further dissemination or disclosure to the public is PROHIBITED. This unpublished work is protected by Federal Copyright law and all rights thereunder are reserved by Cooper Industries, Inc.

SCALE

2X

UNLESS OTHERWISE SPECIFIED
TOLERANCES TO BE:

METRIC $\pm .13\text{mm}$

INCHES $\pm .005"$

ANGULAR $\pm 2'$

▲ (O) INDICATES CRITICAL DIMENSION
OR FEATURE

PAGE 1

DATE

3-8-02

NO.

KTK 35-50

TITLE

LIMITER

SUP. NO.

KTK 35-50 C

DATED

10-23-00

DWG

BAM

CK

CHANGE

E

ENG

SB02087

COOPER Bussmann

St. Louis, MO 63178

DISTRIBUTION


46636

56


J

① METRIC (mm)
INCHES

① REVISED &
REDRAWN



CUSTOMER PRINT



AMP RATING	PART NO.
35	KTK-35
40	KTK-40
45	KTK-45
50	KTK-50

DESIGNED TO:

OPEN IN 2-4 SECONDS AT 500% RATING WHEN
TESTED IN A STANDARD 30 AMPERE CIRCUIT