

KZE Series

- Newly innovative electrolyte is employed to minimize impedance
- Endurance with ripple current: 4,000/5,000 hours at 105°C
- Non solvent resistant type
- RoHS2 Compliant

KZH
Lower Z
KZE
Lower Z
KY





SPECIFICATIONS

Items	Characteristics									
Category	Temperature Range									
Rated Voltage Range	-40 to +105℃									
Capacitance Tolerance	6.3 to 100V _{dc}									
Leakage Current	± 20% (M) (at 20℃, 120Hz)									
Dissipation Factor (tan δ)	I=0.01CV or 3μA, whichever is greater. Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20℃ after 2 minutes)									
Low Temperature Characteristics (Max. Impedance Ratio)	Rated voltage (V _{dc})	6.3V	10V	16V	25V	35V	50V	63V	80V	100V
	tan δ (Max.)	0.22	0.19	0.16	0.14	0.12	0.10	0.09	0.09	0.08
	When nominal capacitance exceeds 1,000μF, add 0.02 to the value above for each 1,000μF increase. (at 20℃, 120Hz)									
Endurance	Z (-25℃) / Z (+20℃)	2max.								
	Z (-40℃) / Z (+20℃)	3max.								
	(at 120Hz)									
	The following specifications shall be satisfied when the capacitors are restored to 20℃ after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage) for the specified period of time at 105℃.									
	Time	φ 10 : 4,000hours φ 12.5 to φ 18 : 5,000hours								
Shelf Life	Capacitance change	≤ ± 25% of the initial value								
	D.F. (tan δ)	≤ 200% of the initial specified value								
	Leakage current	≤ The initial specified value								
	The following specifications shall be satisfied when the capacitors are restored to 20℃ after exposing them for 500 hours at 105℃ without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4.									

DIMENSIONS [mm]


- Terminal Code : E



Gas escape end seal

φD	10, 12.5	16, 18
φd	0.6	0.8
F	5.0	7.5
φD'	φ D+0.5max.	
L'	L+1.5max.	

PART NUMBERING SYSTEM



Please refer to "Product code guide (radial lead type)"

RATED RIPPLE CURRENT MULTIPLIERS

- Frequency Multipliers

Capacitance(μF)	Frequency(Hz)	120	1k	10k	100k
47 to 180		0.40	0.75	0.90	1.00
220 to 560		0.50	0.85	0.94	1.00
680 to 1,800		0.60	0.87	0.95	1.00
2,200 to 3,900		0.75	0.90	0.95	1.00
4,700 to		0.85	0.95	0.98	1.00

The deterioration of aluminum electrolytic capacitors accelerates their life due to the internal heating produced by ripple current. For details, refer to Section "5-3 Ripple Current Effect on Lifetime" in the catalog, Technical Note.



KZE Series

◆ STANDARD RATINGS

WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	Impedance (Ω max./100kHz)		Rated ripple current (mA rms/ 105°C, 100kHz)	Part No.
			20°C	-10°C		
6.3	1,000	10×12.5	0.053	0.16	1,030	EKZE6R3E□□102MJC5S
	1,200	10×16	0.038	0.12	1,430	EKZE6R3E□□122MJ16S
	1,500	10×20	0.023	0.069	1,820	EKZE6R3E□□152MJ20S
	2,200	10×25	0.022	0.066	2,150	EKZE6R3E□□222MJ25S
	3,300	12.5×20	0.021	0.053	2,360	EKZE6R3E□□332MK20S
	3,900	12.5×25	0.018	0.045	2,770	EKZE6R3E□□392MK25S
	4,700	12.5×30	0.016	0.041	3,290	EKZE6R3E□□472MK30S
	5,600	12.5×35	0.015	0.039	3,400	EKZE6R3E□□562MK35S
	5,600	16×20	0.018	0.045	3,140	EKZE6R3E□□562ML20S
	6,800	16×25	0.016	0.043	3,460	EKZE6R3E□□682ML25S
10	680	10×12.5	0.053	0.16	1,030	EKZE100E□□681MJC5S
	1,000	10×16	0.038	0.12	1,430	EKZE100E□□102MJ16S
	1,200	10×20	0.023	0.069	1,820	EKZE100E□□122MJ20S
	1,500	10×25	0.022	0.066	2,150	EKZE100E□□152MJ25S
	2,200	12.5×20	0.021	0.053	2,360	EKZE100E□□222MK20S
	3,300	12.5×25	0.018	0.045	2,770	EKZE100E□□332MK25S
	3,900	12.5×30	0.016	0.041	3,290	EKZE100E□□392MK30S
	3,900	16×20	0.018	0.045	3,140	EKZE100E□□392ML20S
	4,700	12.5×35	0.015	0.039	3,400	EKZE100E□□472MK35S
	5,600	16×25	0.016	0.043	3,460	EKZE100E□□562ML25S
16	470	10×12.5	0.053	0.16	1,030	EKZE160E□□471MJC5S
	680	10×16	0.038	0.12	1,430	EKZE160E□□681MJ16S
	1,000	10×20	0.023	0.069	1,820	EKZE160E□□102MJ20S
	1,200	10×25	0.022	0.066	2,150	EKZE160E□□122MJ25S
	1,500	12.5×20	0.021	0.053	2,360	EKZE160E□□152MK20S
	2,200	12.5×25	0.018	0.045	2,770	EKZE160E□□222MK25S
	2,700	12.5×30	0.016	0.041	3,290	EKZE160E□□272MK30S
	2,700	16×20	0.018	0.045	3,140	EKZE160E□□272ML20S
	3,300	12.5×35	0.015	0.039	3,400	EKZE160E□□332MK35S
	3,900	16×25	0.016	0.043	3,460	EKZE160E□□392ML25S
25	330	10×12.5	0.053	0.16	1,030	EKZE250E□□331MJC5S
	470	10×16	0.038	0.12	1,430	EKZE250E□□471MJ16S
	680	10×20	0.023	0.069	1,820	EKZE250E□□681MJ20S
	820	10×25	0.022	0.066	2,150	EKZE250E□□821MJ25S
	1,000	12.5×20	0.021	0.053	2,360	EKZE250E□□102MK20S
	1,500	12.5×25	0.018	0.045	2,770	EKZE250E□□152MK25S
	1,800	12.5×30	0.016	0.041	3,290	EKZE250E□□182MK30S
	1,800	16×20	0.018	0.045	3,140	EKZE250E□□182ML20S
	2,200	12.5×35	0.015	0.039	3,400	EKZE250E□□222MK35S
	2,700	16×25	0.016	0.043	3,460	EKZE250E□□272ML25S
35	220	10×12.5	0.053	0.16	1,030	EKZE350E□□221MJC5S
	330	10×16	0.038	0.12	1,430	EKZE350E□□331MJ16S
	470	10×20	0.023	0.069	1,820	EKZE350E□□471MJ20S
	560	10×25	0.022	0.066	2,150	EKZE350E□□561MJ25S
	680	12.5×20	0.021	0.053	2,360	EKZE350E□□681MK20S
	1,000	12.5×25	0.018	0.045	2,770	EKZE350E□□102MK25S
	1,200	12.5×30	0.016	0.041	3,290	EKZE350E□□122MK30S
	1,200	16×20	0.018	0.045	3,140	EKZE350E□□122ML20S
	1,500	12.5×35	0.015	0.039	3,400	EKZE350E□□152MK35S
	1,800	16×25	0.016	0.043	3,460	EKZE350E□□182ML25S
50	150	10×12.5	0.061	0.18	979	EKZE500E□□151MJC5S
	220	10×16	0.042	0.12	1,370	EKZE500E□□221MJ16S
	270	10×20	0.030	0.090	1,580	EKZE500E□□271MJ20S
	330	10×25	0.028	0.085	1,870	EKZE500E□□331MJ25S
	470	12.5×20	0.027	0.068	2,050	EKZE500E□□471MK20S
	560	12.5×25	0.023	0.059	2,410	EKZE500E□□561MK25S
	680	12.5×30	0.021	0.052	2,860	EKZE500E□□681MK30S
	820	12.5×35	0.019	0.051	2,960	EKZE500E□□821MK35S
	820	16×20	0.023	0.059	2,730	EKZE500E□□821ML20S
	1,000	16×25	0.021	0.056	3,010	EKZE500E□□102ML25S
63	82	10×12.5	0.11	0.44	690	EKZE630E□□820MJC5S
	120	10×16	0.076	0.31	950	EKZE630E□□121MJ16S
	180	10×20	0.056	0.23	1,150	EKZE630E□□181MJ20S
	180	12.5×16	0.072	0.29	1,150	EKZE630E□□181MK16S
	220	10×25	0.046	0.19	1,350	EKZE630E□□221MJ25S
	270	12.5×20	0.041	0.13	1,500	EKZE630E□□271MK20S
	390	12.5×25	0.031	0.093	1,900	EKZE630E□□391MK25S
	470	12.5×30	0.028	0.084	2,300	EKZE630E□□471MK30S
	470	16×20	0.032	0.096	2,000	EKZE630E□□471ML20S
	560	12.5×35	0.024	0.072	2,500	EKZE630E□□561MK35S
80	680	12.5×40	0.021	0.063	2,800	EKZE630E□□681MK40S
	680	16×25	0.025	0.075	2,600	EKZE630E□□681ML25S
	680	18×20	0.030	0.090	2,500	EKZE630E□□681MM20S
	820	16×31.5	0.021	0.063	2,850	EKZE630E□□821MLN3S
	820	18×25	0.024	0.072	2,800	EKZE630E□□821MM25S
	1,000	16×35.5	0.019	0.057	2,900	EKZE630E□□102MLP1S
	1,200	16×40	0.018	0.054	3,400	EKZE630E□□122ML40S
	1,200	18×31.5	0.020	0.060	3,300	EKZE630E□□122MMN3S
	1,500	18×35.5	0.018	0.054	3,400	EKZE630E□□152MMP1S
	1,800	18×40	0.017	0.051	3,500	EKZE630E□□182MM40S
100	68	10×12.5	0.17	0.66	480	EKZE800E□□680MJC5S
	100	10×16	0.11	0.47	600	EKZE800E□□101MJ16S
	120	10×20	0.084	0.34	800	EKZE800E□□121MJ20S
	150	10×25	0.069	0.28	900	EKZE800E□□151MJ25S
	150	12.5×16	0.11	0.34	750	EKZE800E□□151MK16S
	220	12.5×20	0.062	0.18	1,100	EKZE800E□□221MK20S
	330	12.5×25	0.047	0.14	1,250	EKZE800E□□331MK25S
	330	16×20	0.048	0.15	1,350	EKZE800E□□331ML20S
	390	12.5×30	0.042	0.13	1,500	EKZE800E□□391MK30S
	470	12.5×35	0.036	0.11	1,650	EKZE800E□□471MK35S
100	470	16×25	0.038	0.12	1,700	EKZE800E□□471ML25S
	470	18×20	0.045	0.14	1,500	EKZE800E□□471MM20S
	560	12.5×40	0.032	0.095	1,800	EKZE800E□□561MK40S
	680	16×31.5	0.032	0.095	1,850	EKZE800E□□681MLN3S
	680	18×25	0.036	0.11	1,750	EKZE800E□□681MM25S
	820	16×35.5	0.029	0.086	2,000	EKZE800E□□821MLP1S
	820	18×31.5	0.030	0.090	1,900	EKZE800E□□821MMN3S
	1,000	16×40	0.027	0.081	2,200	EKZE800E□□102ML40S
	1,000	18×35.5	0.027	0.081	2,200	EKZE800E□□102MMP1S
	1,200	18×40	0.026	0.077	2,700	EKZE800E□□122MM40S
100	47	10×12.5	0.17	0.66	480	EKZE101E□□470MJC5S
	68	10×16	0.11	0.47	600	EKZE101E□□680MJ16S
	82	10×20	0.084	0.34	800	EKZE101E□□820MJ20S
	100	12.5×16	0.11	0.34	750	EKZE101E□□101MK16S
	120	10×25	0.069	0.28	900	EKZE101E□□121MJ25S
	150	12.5×20	0.062	0.18	1,100	EKZE101E□□151MK20S
	220	12.5×25	0.047	0.14	1,250	EKZE101E□□221MK25S
	220	16×20	0.048	0.15	1,350	EKZE101E□□221ML20S
	270	12.5×30	0.042	0.13	1,500	EKZE101E□□271MK30S
	330	12.5×35	0.036	0.11	1,650	EKZE101E□□331MK35S
100	330	16×25	0.038	0.12	1,700	EKZE101E□□331ML25S
	330	18×20	0.045	0.14	1,500	EKZE101E□□331MM20S
	390	12.5×40	0.032	0.095	1,800	EKZE101E□□391MK40S
	470	16×31.5	0.032	0.095	1,850	EKZE101E□□471MLN3S
	470	18×25	0.036	0.11	1,750	EKZE101E□□471MM25S
	560	16×35.5	0.029	0.086	2,000	EKZE101E□□561MLP1S
	560	18×31.5	0.030	0.090	1,900	EKZE101E□□561MMN3S
	680	16×40	0.027	0.081	2,200	EKZE101E□□681ML40S
	680	18×35.5	0.027	0.081	2,200	EKZE101E□□681MMP1S
	820	18×40	0.026	0.077	2,700	EKZE101E□□821MM40S

□ □ : Enter the appropriate lead forming or taping code.



- Always read "Notes on Use" before using the product in order to enable you to use the product correctly and prevent any faults and accidents from occurring.
- Request the Product Specification on the product of NIPPON CHEMI-CON CORPORATION to refer to it as well as this brochure prior to the order of the products. Some specific notes on use of the ordered product may be described in the specifications.
- The products listed in this catalog are designed and manufactured for general electronics equipment use and are not intended for use in applications that can adversely affect human life; where the malfunction of equipment may cause damage to life or property. In addition, our products are not intended to be used in specific applications that may cause a major social impact. Please consult with us in advance of usage of our products in the following listed applications. ① Aerospace equipment ② Power generation equipment such as thermal power, nuclear power etc. ③ Medical equipment ④ Transport equipment (automobiles, trains, ships, etc.) ⑤ Transportation control equipment ⑥ Disaster prevention / crime prevention equipment ⑦ Highly publicized information processing equipment ⑧ Submarine equipment ⑨ Other applications that are not considered general-purpose applications.
- The circuits described as examples in this catalog and the "delivery specifications" are featured in order to show the operations and usage of our products, however, this fact does not guarantee that the circuits are available to function in your equipment systems. We are not in any case responsible for any failures or damage caused by the use of information contained herein. You should examine our products, of which the characteristics are described in the "delivery specifications" and other documents, and determine whether or not our products suit your requirements according to the specifications of your equipment systems. Therefore, you bear final responsibility regarding the use of our products.
Please make sure that you take appropriate safety measures such as use of redundant design and malfunction prevention measures in order to prevent fatal accidents and/or fires in the event any of our products malfunction.
- We strongly recommend our customers to purchase Nippon Chemi-Con products only through our official sales channels. We assume no responsibility for any defects or damages caused by using products purchased from outside our official sales channel or of counterfeit goods. In addition, we will ask the customer to pay the investigation cost for products purchased outside our official sales channel.
- We reserve the right to discontinue production and delivery of products. We do not guarantee that all the products included in this catalog will be available in the future.
The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products
- We continually strive to improve the quality and reliability of our products, but in any case that our product does not meet our published specifications, please stop using it promptly and contact us immediately. As for compensation for non-conforming goods delivered by Chemi-Con, we will limit it only to goods found in non-compliance of our published specifications. This may be accomplished by a no cost replacement of non-conforming individual products, a credit of the piece price paid per each individual non-conforming product, or in other ways deemed necessary.
In addition, we have an established system with enhanced traceability, therefore we will limit the applicable lot items for any potential compensation.

[Part Numbering System](#)

[Part Numbering System \(Appendix\)](#)

[Standardization](#)

[Available Items by Manufacturing Locations](#)

[Environmental Measures](#)

[Technical Note](#)

[Precautions and Guidelines](#)

[Recommended Soldering Conditions](#)

[Taping, Lead-preforming and Packaging](#)

[Available Terminals for Snap-in and Screw Mount Type](#)