


LP11 SERIES PUSHBUTTON SWITCH


ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS




APPLICATIONS / MARKETS




Audio / Visual




Consumer Electronics




Vending Machines



Kiosks



Instrumentation



Medical Equipment

RoHS

SPECIFICATIONS

Electrical Rating: 100mA @ 12VDC
Contact Arrangement: SPST
Electrical Life: 1,000,000 Cycles
Contact Resistance: 200mΩ Max. initial
Insulation Resistance: 100 MΩ Min. @ 500VDC
Dielectric Strength: 500VAC for 1 Minute
Travel: 4.50mm (Momentary)
 3.50mm (Latching)
Actuation Force: 160 gf (Momentary)
 200 gf (Latching)
Operating Temperature: -40°C to 85°C

FEATURES & BENEFITS

- RGB or multiple bi-color illumination options
- Tactile or non tactile feel
- Multiple cap sizes
- Long electrical life
- Latching and momentary functions

PART NUMBER CONFIGURATOR

Series	Function	Circuit	Actuators	Cap	Cap Configuration	LED Color Options*
LP11	OA OA - Momentary EE EE - Latching (Only using N Actuator Type)	1 1 - SPST	N N - Non Tactile T T - Tactile	A A - 12mm square B B - 15mm square C C - 17.4mm square	S S - Sculptured	RR RR - Red-Red RG RG - Red-Green RB RB - Red-Blue RY RY - Red-Yellow RW RW - Red-White BB BB - Blue-Blue BW BW - Blue-White GG GG - Green-Green GB GB - Green-Blue GW GW - Green-White YY YY - Yellow-Yellow YG YG - Yellow-Green YB YB - Yellow-Blue YW YW - Yellow-White WW WW - White-White RGB RGB - Red-Green-Blue

* Please refer to individual part number drawings for LED specifications.

Specifications subject to change without notice 9.13.2018



E-SWITCH®


www.e-switch.com

800.867.2717


1

LP11 SERIES PUSHBUTTON SWITCH




BODY DIMENSIONS MOMENTARY LED



PCB LAYOUT



SCHEMATIC



OA - MOMENTARY WITH A - 12MM CAP
LED ILLUMINATION



E-SWITCH®

www.e-switch.com






800.867.2717

2

ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS

LP11 SERIES PUSHBUTTON SWITCH

BODY DIMENSIONS MOMENTARY RGB



OA - MOMENTARY WITH A - 12MM CAP
RGB ILLUMINATION



E-SWITCH®


www.e-switch.com

800.867.2717


3

LP11 SERIES PUSHBUTTON SWITCH




BODY DIMENSIONS LATCHING LED



PCB LAYOUT



SCHEMATIC



EE - LATCHING WITH A - 12MM CAP
LED ILLUMINATION



E-SWITCH®



www.e-switch.com

800.867.2717

4

ANTI-VANDAL SWITCHES
DETECTOR SWITCHES
DIP SWITCHES
KEYLOCK SWITCHES
NAVIGATION SWITCHES
PUSHBUTTON SWITCHES
ROCKER SWITCHES
ROTARY SWITCHES
SLIDE SWITCHES
SNAP ACTION SWITCHES
TACTILE SWITCHES
TOGGLE SWITCHES
CAP OPTIONS

TOGGLE CAP
TOGGLE CAP
TACTILE SWITCHES
SNAP ACTION SWITCHES
SLIDE SWITCHES
ROTARY SWITCHES
ROCKER SWITCHES
PUSHBUTTON SWITCHES
NAVIGATION SWITCHES
KEYLOCK SWITCHES
DIP SWITCHES
DETECTOR SWITCHES
DETECTOR SWITCHES
ANTI-VANDAL SWITCHES

[illegible]

5

CAP OPTIONS

