General Specifications

Electrical Capacity (Resistive Load)

Power Level (silver): 6A @ 125V AC or 3A @ 250V AC or 3A @ 30V DC
Logic Level (gold): 0.4VA maximum @ 28V AC/DC maximum
(Applicable Range 0.1mA ~ 0.1A @ 20mV ~ 28V)
Note: Find additional explanation of operating range in Supplement section.

Other Ratings

Contact Resistance: 10 milliohms maximum for silver; 20 milliohms maximum for gold
Insulation Resistance: 1,000 megohms minimum @ 500V DC
Dielectric Strength: 1,000V AC minimum between contacts for 1 minute minimum;
1,500V AC minimum between contacts & case for 1 minute minimum
Mechanical Life: 50,000 operations minimum
Electrical Life: 25,000 operations minimum
Nominal Operating Force:

	On-to-On Position	Off-to-On Position
Single Pole	3.19N	3.92N
Double Pole	4.41N	7.06N

Angle of Throw: 20°

Materials & Finishes

Bushing: Brass with nickel plating
Housing: Stainless steel
Mounting Bracket: Steel with tin plating
Movable Contacts: Silver alloy or silver alloy with gold plating
Stationary Contacts: Silver with silver plating or copper or brass with gold plating
Lamp Contacts: Phosphor bronze
Base: Diallyl phthalate (UL94V-0)
Switch Terminals: Copper with silver or gold plating
Lamp Terminals: Brass with silver or gold plating

Environmental Data

Operating Temp Range: –10°C through +55°C (+14°F through +131°F)
Humidity: 90 ~ 95% humidity for 96 hours @ 40°C (104°F)
Vibration: 10 ~ 55Hz with peak-to-peak amplitude of 1.5mm traversing the frequency range & returning in 1 minute; 3 right angled directions for 2 hours
Shock: 50G (490m/s^2) acceleration (tested in 6 right angled directions, with 5 shocks in each direction)

Installation

Mounting Torque: 1.47Nm (13 lb•in) for double nut; .67Nm (6 lb•in) for single nut
Soldering Time & Temp: Wave Soldering (PC version): See Profile B in Supplement section.
Manual Soldering: See Profile B in Supplement section.
Note: Lever must be in center position while soldering.
Cleaning: PC mountable device is not process sealed. Hand clean locally using alcohol based solution.

Standards & Certifications

Flammability Standards: UL94V-0 base
UL: **File No. E44145 - Recognized only when ordered with marking on switch.**
Add "/U" to end of part number to order UL recognized switch.
Single pole with synchronous circuits & single color LEDs & solder lug or PC recognized at 6A @ 125V AC.
CSA: **File No. 023535_0_000 - Certified only when ordered with marking on switch.**
Add "/C" to end of part number to order CSA certified switch.
All single pole with synchronous circuits & single color LEDs certified at 6A @ 125V AC.

Distinctive Characteristics

Industry's first LED illumination at tip of toggle switches.

Single color LEDs of red, yellow, and green, plus bicolor red/green, to meet varied design requirements.

LEDs can operate independently from or synchronously with switching operation.

Antijamming feature to protect contacts from damage due to excessive downward force on the toggle.

High torque bushing prevents the bushing from rotating or separating from the metal frame during installation.


Stainless steel frame resists corrosion.

Silver contacts are of specially composed alloy for hardness.


High insulating barriers protect against crossover in double pole devices.

Terminals are molded in and epoxy sealed to lock out flux, dust, and other contaminants.

1,500V dielectric strength between switch contacts and case is accomplished by clinching the frame away from the terminals.



Actual Size



TYPICAL SWITCH ORDERING EXAMPLE

M21 [1] [2] [T] [C] [W] [01] [ ]

Poles

1	SPDT
*** 2**	DPDT

* Available only with Terminals 01, 02, 03

LED Circuits & Actuator Types

L	Isolated
T	Synchronous

Contact Materials & Ratings

W	Silver; Rated 6A @ 125V AC
G	Gold; Rated 0.4VA max @ 28V AC/DC max

Threaded Bushings

No Code	1/4–40 Thread (Inch)
/M	6mm Thread (Metric)

Circuits

2	ON	NONE	ON
3	ON	OFF	ON

NONE = No Position

LED Colors

Single Color	
C	Red
E	Yellow
F	Green
Bicolor	
CF	Red/Green

Terminals & Mounting Types


01	Solder Lug with Threaded Bushing
02	Quick Connect with Threaded Bushing
03	Straight PC with Threaded Bushing
30	Right Angle PC with Smooth Bushing (available with gold contacts only)

IMPORTANT:

Switches are supplied without UL & CSA marking unless specified.
UL & CSA recognized only when ordered with marking on the switch.
Specific models, ratings, & ordering instructions are noted on the General Specifications page.

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

M2112TCW01



POLES & CIRCUITS & LED ILLUMINATION

Model	Pole & Throw	Toggle Position & Terminal Numbers (NONE = No Position) Down	Center	Up	Schematics
		Keyway			Notes: Terminal numbers are not actually on the switch. LEDs require an external power source.
M2112	**SPDT**	ON	NONE	ON	Isolated Single Color LED
Connected Power Terminals		2-3	NONE	2-1	
LED Circuit	**Isolated LEDs** (see schematics)	ON	NONE	ON	
	Connected LED Terminals	4-6	NONE	4-6	
	Synchronous Single Color LED	ON	NONE	OFF	Isolated Bicolor LED
	Connected LED Terminals	4-6	NONE	OPEN	
	Synchronous Bicolor LED	Red	NONE	Green	
	Connected LED Terminals	5-6	NONE	5-4	
M2113	**SPDT**	ON	OFF	ON	Synchronous Single Color LED
Connected Power Terminals		2-3	OPEN	2-1	
LED Circuit	**Isolated LEDs** (see schematics)	ON	ON	ON	
	Connected LED Terminals	4-6	4-6	4-6	
	Synchronous Single Color LED	ON	OFF	ON	Synchronous Bicolor LED
	Connected LED Terminals	4-6	OPEN	4-6	
	Synchronous Bicolor LED	Red	OFF	Green	
	Connected LED Terminals	5-6	OPEN	5-4	
M2122	**DPDT**	ON	NONE	ON	Isolated Single Color LED
Connected Power Terminals		2-3 5-6	NONE	2-1 5-4	
LED Circuit	**Isolated LEDs** (see schematics)	ON	NONE	ON	
	Connected LED Terminals	7-9	NONE	7-9	
	Synchronous Single Color LED	ON	NONE	OFF	Isolated Bicolor LED
	Connected LED Terminals	7-9	NONE	OPEN	
	Synchronous Bicolor LED	Red	NONE	Green	
	Connected LED Terminals	8-9	NONE	8-7	
M2123	**DPDT**	ON	OFF	ON	Synchronous Single Color LED
Connected Power Terminals		2-3 5-6	OPEN	2-1 5-4	
LED Circuit	**Isolated LEDs** (see schematics)	ON	ON	ON	
	Connected LED Terminals	7-9	7-9	7-9	
	Synchronous Single Color LED	ON	OFF	ON	Synchronous Bicolor LED
	Connected LED Terminals	7-9	OPEN	7-9	
	Synchronous Bicolor LED	Red	OFF	Green	
	Connected LED Terminals	8-9	OPEN	8-7	

Series M2100

LED Tipped Toggles

LED COLORS & SPECIFICATIONS

The electrical specifications shown are determined at a basic temperature of 25°C. LED circuit is isolated and requires an external power source. If the source voltage exceeds the rated voltage, a ballast resistor is required. The resistor value can be calculated by using the formula in Supplement Section.

The LED is an integral part of the switch and not available separately. Bicolor LED is translucent white when unlit.		Single Color			Bicolor	
		C	E	F	CF	
	Color	Red	Yellow	Green	Red/Green	Units
Maximum Forward Current	I_{FM}	30	30	30	25	mA
Typical Forward Current	I_F	20	20	20	10	mA
Forward Voltage	V_F	2.2	2.1	2.2	1.7/2.0	V
Maximum Reverse Voltage	V_{RM}	4	4	4	—	V
Current Reduction Rate Above 25°C	ΔI_F	0.38	0.38	0.38	0.33/0.33	mA/°C
Ambient Temperature Range		−10° ~ +55°C				


LED CIRCUIT, TOGGLE, & MOUNTING TYPE COMBINATIONS

L **Toggle with Isolated LED Circuit**


T **Toggle with Synchronous LED Circuit**

Finish: Brushed aluminum

Standard Hardware: 2 AT513H Hex Nuts, 1 AT507H Locking Ring, 1 AT509 Lockwasher Standard & optional hardware details in Accessories & Hardware section.




Threaded Bushing combines with Terminal codes 01, 02, & 03.




Smooth Bushing combines with Terminal code 30.

Max. Panel Thickness with Standard Hardware .102" (2.6mm)



Max. Panel Thickness without Locking Ring .134" (3.4mm)




TYPICAL SWITCH DIMENSIONS


Solder Lug




M2112TCFW01



Single Pole






Single color LED switch does not have terminal 5.

TYPICAL SWITCH DIMENSIONS

Double Pole




Single color LED switch does not have terminal 8.

Solder Lug



M2122TCFW01

Single Pole Only



Single color LED switch does not have terminal 5.

Right Angle PC



Gold contact material only

M2112TCFG30


CONTACT MATERIALS & RATINGS

W	Silver over Silver	Power Level	6A @ 125V AC & 3A @ 250V AC
G	Gold over Brass or Copper	Logic Level	0.4VA maximum @ 28V AC/DC maximum


Complete explanation of operating range in Supplement section.

TERMINALS


01 Solder Lug with Turret LED Terminal




02 Quick Connect



03 Straight PC with Turret LED Terminal




Single Pole



Single color LED & isolated bicolor LED switches do not have terminal 5.


Double Pole




Single color LED & isolated bicolor LED switches do not have terminal 8.

30 Right Angle PC

LED terminals only available in brass with silver plating



Single Pole




Single color LED & isolated bicolor LED switches do not have terminal 5.

STANDARD MOUNTING HARDWARE


AT513H Hexagon Nut
(2 per switch)

Material:
Brass with nickel plating




AT507H Locking Ring
(1 per switch)

Material:
Steel with chromate over zinc



AT509 Lockwasher
(1 per switch)

Material:
Steel with chromate over zinc



Optional Hardware: Knurled nuts, dress nuts, and ON-OFF plates are available; see details in Accessories & Hardware section.