

"MINI" AUTOMOTIVE FUSE CLIPS & HOLDERS



For .110 (2.8) × .032 (.80) MINI BLADE FUSES


For Littelfuse Mini 297 or 997 series/Bussmann ATM series or equivalent

VERTICAL FUSE ENTRY


Thru Hole Mount




- Low Profile



Mounting Detail For Two Clips



Pad Layout For Two Clips



CAT. NO. 3564

MATERIAL:


.016 (.41) Brass, Matte Tin Plate
UL Current Rating: 15 Amps @ 500V AC

AVAILABLE ON TAPE AND REEL

Surface Mount



- Low Profile




CAT. NO. 3563 (Bulk)

CAT. NO. 3563TR (Tape & Reel)


Tape & Reel Spec's: 24mm wide; 12mm pitch; 13 inch reel (1500 pieces per reel)

SPECIFICATIONS

Material: .012 (.30) Brass
Insulator: Nylon, UL Rated 94V-0
UL Temperature Rating: -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips



CAT. NO. 3544 Tin-Nickel Plate

UL Current Rating: 30 Amps @ 500V AC


UL Current Rating: 20 Amps @ 500V AC

CAT. NO. 3544-2 Tin Plate




LOW PROFILE MINI FUSE HOLDER

For Littelfuse Low Profile Mini 897 series or equivalent



Mounting Detail



CAT. NO. 3557-2

- Low insertion force
- Thru hole PC mountable, maintains position during wave soldering
- Fuse holder fully insulates clips to protect fuse from shorting
- Holder assures proper spacing and reduces assembly time


SPECIFICATIONS

Contacts: .016 (.41) Brass, Tin-Nickel Plate
Insulator: Nylon 4/6, UL Rated 94V-0
UL Current Rating: 30 Amps @ 500V AC
UL Temperature Rating: -58°F to +292°F (-50°C to +145°C)




Refer to page 41 for Cat. No. 3557 Clip details

Mounting Detail



MINI FUSE HOLDER

For Littelfuse Mini 297 or 997 series/Bussmann ATM or equivalents




CAT. NO. 3568

HORIZONTAL FUSE ENTRY


For Littelfuse Mini 297 or 997 series/Bussmann ATM series or equivalent

SPECIFICATIONS

Contacts: .012 (.30) Brass
Insulator: Nylon 6/6, UL Rated 94V-0
UL Temperature Rating: -58°F to +292°F (-50°C to +145°C)



Mounting Detail For Two Clips



CAT. NO. 3549 Nickel Plate

UL Current Rating: 30 Amps @ 500V AC

UL Current Rating: 20 Amps @ 500V AC

CAT. NO. 3549-2 Tin Plate

