19-2942; Rev 1; 11/06

EVALUATION KIT AVAILABLE

0.5Ω, Quad SPDT Switches in UCSP/QFN

General Description

The MAX4754/MAX4754A/MAX4755/MAX4756/MAX4756A low on-resistance, analog switches operate from a single +1.8V to +5.5V supply. The MAX4754/MAX4754A and MAX4755 are dual, double-pole, double-throw (DPDT) switches. The MAX4756/MAX4756A are quad, single-pole double-throw (SPDT) switches. They are configured to route either audio or data signals.

The MAX4754/MAX4754A have four 0.5Ω SPDT switches for audio-signal routing and two logic control inputs. The MAX4755 has four 0.5Ω SPDT switches (with two switches that have an additional 11Ω series resistor at the NC terminals). This allows users to drive an 8Ω speaker as a 32Ω load (ear speaker). The MAX4756/MAX4756A have four 0.5Ω SPDT switches controlled by one logic control input and an enable input ($\overline{EN}$) to disable the switches.

The MAX4754/MAX4754A/MAX4755/MAX4756/MAX4756A are available in a space-saving 16-pin TQFN and a tiny 16-bump, 2mm x 2mm chip-scale package (UCSP™).

Applications

Speaker-Headset Switching
Audio-Signal Routing
Cellular Phones
PDAs/Handheld Devices
Notebook Computers

UCSP is a trademark of Maxim Integrated Products, Inc.

Pin Configurations appear at end of data sheet.

Features

- **Data and Audio-Signal Routing**
- **Low R_{ON} (0.5Ω typ) Audio Switches**
- **0.1Ω (typ) Channel-to-Channel Matching**
- **0.2Ω (typ) On-Resistance Flatness**
- **0.035% (typ) THD**
- **Improved Power-Supply Current for Non-Rail-to-Rail Control Logic Inputs (MAX4754A/MAX4756A)**
- **+1.8V to +5.5V Supply Range**
- **Rail-to-Rail Signal Handling**
- **16-Bump UCSP (2mm x 2mm)**

Ordering Information

PART	PIN-PACKAGE	PKG CODE
MAX4754EBE+T	16 UCSP-16	B16-1
MAX4754ETE+T	16 TQFN-EP**	T1644-4
MAX4754AEBE+T	16 UCSP-16	B16-1
MAX4754AETE+T	16 TQFN-EP**	T1644-4
MAX4755EBE+T*	16 UCSP-16	B16-1
MAX4755ETE+T*	16 TQFN-EP**	T1644-4
MAX4756EBE+T*	16 UCSP-16	B16-1
MAX4756ETE+T*	16 TQFN-EP**	T1644-4
MAX4756AEBE+T*	16 UCSP-16	B16-1
MAX4756AETE+T*	16 TQFN-EP**	T1644-4

Note: *These devices operate over the -40°C to +85°C operating temperature range.*

**Future product—contact factory for availability.*

***EP = Exposed paddle.*

+Denotes lead-free package.

Functional Diagrams



For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.

0.5Ω, Quad SPDT Switches in UCSP/QFN

ABSOLUTE MAXIMUM RATINGS

(All voltages referenced to GND.)
V+, IN_, EN .....-0.3V to +6V
COM_, NO_, NC_ (Note 1) .....-0.3V to (V+ + 0.3V)
Continuous Current
NC1, NC2, COM1, COM2 (MAX4755).....±100mA
NO_, NC_, COM_ (remaining terminal connections) ....±300mA
Peak Current NC1, NC2, COM1, COM2 (MAX4755)
(Pulsed at 1ms, 10% duty cycle).....±200mA
(Pulsed at 1ms, 50% duty cycle).....±150mA
Peak Current NO_, NC_,
COM__ (remaining terminal connections)
(Pulsed at 1ms, 10% duty cycle).....±500mA
(Pulsed at 1ms, 50% duty cycle).....±400mA

Continuous Power Dissipation (T_A = +70°C)
16-Bump UCSP (derate 8.2mW/°C above +70°C) 660mW
16-Pin TQFN (derate 16.9mW/°C above +70°C).....1349mW
ESD per Method 3015.7.....±2kV
Operating Temperature Range .....-40°C to +85°C
Junction Temperature.....+150°C
Storage Temperature Range .....-65°C to +150°C
Bump Temperature (soldering)
Infrared (15s) .....+220°C
Vapor Phase (60s) .....+215°C
Lead Temperature (soldering, 10s) .....+300°C

Note 1: Signals on NO_, NC_, COM_ exceeding V+ or GND are clamped by internal diodes. Limit forward-diode current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

(V+ = +2.7V to +5.25V, T_A = -40°C to +85°C, unless otherwise noted. Typical values are at +3V and T_A = +25°C.) (Notes 2, 3)

PARAMETER	SYMBOL	CONDITIONS		T_A	MIN	TYP	MAX	UNITS
ANALOG SWITCH								
Analog Signal Range	$V_{COM_}$, $V_{NO_}$, $V_{NC_}$			T_{MIN} to T_{MAX}	0		V+	V
On-Resistance	R_{ON}	V+ = 2.7V, $I_{COM_}$ = 10mA, $V_{NC_}$ or $V_{NO_}$ = 0V or V+ (Note 4)	MAX4755 (NO1, NO2, N_3, N_4), MAX4754/ MAX4754A/MAX4756/ MAX4756A	+25°C		0.5	0.85	Ω
				T_{MIN} to T_{MAX}			1.0	
			MAX4755 (NC1, NC2)	+25°C		11.5		
				T_{MIN} to T_{MAX}	8.0		12.5	
On-Resistance Match Between Channels	ΔR_{ON}	V+ = 2.7V, $I_{COM_}$ = 10mA, $V_{NC_}$ or $V_{NO_}$ = +1.5V (Notes 4, 5)	MAX4755 (NO1, NO2, N_3, N_4) MAX4754/ MAX4756	+25°C		0.1	0.35	Ω
				T_{MIN} to T_{MAX}			0.55	
			MAX4755 (NC1, NC2)	+25°C		0.2	0.4	
				T_{MIN} to T_{MAX}			0.55	
		V+ = +2.7V $I_{COM_}$ = 10mA, $V_{NC_}$ or $V_{NO_}$ = 0 or V+ (Notes 4, 5)	MAX4754A/MAX4756A	+25°C		0.1	0.35	Ω
				T_{MIN} to T_{MAX}			0.55	
On-Resistance Flatness	$R_{FLAT(ON)}$	V+ = 3V, $I_{COM_}$ = 10mA, $V_{NO_}$ or $V_{NC_}$ = 0V, 0.6V, or V+ (Note 6)	MAX4755 (NO1, NO2, N_3, N_4, NO1, NO2), MAX4754/ MAX4754A/MAX4756/ MAX4756A	+25°C		0.2	0.4	Ω
				T_{MIN} to T_{MAX}			0.55	

ELECTRICAL CHARACTERISTICS (continued)

(V+ = +2.7V to +5.25V, T_A = -40°C to +85°C, unless otherwise noted. Typical values are at +3V and T_A = +25°C.) (Notes 2, 3)

PARAMETER	SYMBOL	CONDITIONS	T_A	MIN	TYP	MAX	UNITS
NO_, NC_ Off-Leakage Current	$I_{NO_(OFF)}$, $I_{NC_(OFF)}$	V+ = 3.6V; $V_{COM_}$ = 3.3V, 0.3V; $V_{NO_}$ or $V_{NC_}$ = 0.3V, 3.3V MAX4754/MAX4754A/MAX4755/MAX4756/ MAX4756A	+25°C	-4		+4	nA
			T_{MIN} to T_{MAX}	-10		+10	
COM_ Off-Leakage Current	$I_{COM_(OFF)}$	V+ = 3.6V (MAX4756/MAX4756A); $V_{COM_}$ = 3.3V, 0.3V; $V_{NO_}$ or $V_{NC_}$ = 0.3V, 3.3V	+25°C	-6	0.01	+6	Ω
			T_{MIN} to T_{MAX}	-15		+15	
COM_ On-Leakage Current	$I_{COM_(ON)}$	V+ = 3.6V; $V_{COM_}$ = 3.3V, 0.3V; $V_{NO_}$ or $V_{NC_}$ = 3.3V, 0.3V or unconnected	+25°C	-3		+3	nA
			T_{MIN} to T_{MAX}	-15		+15	
DYNAMIC							
Turn-On Time NC_	$t_{ON, NC}$	V+ = 2.7V, $V_{NC_}$ = 1.5V, R_L = 50Ω, C_L = 35pF (Figure 1) MAX4754A/MAX4756A	+25°C		320	650	ns
			T_{MIN} to T_{MAX}			900	
Turn-Off Time NC_	$t_{OFF, NC}$	V+ = 2.7V, $V_{NC_}$ = 1.5V, R_L = 50Ω, C_L = 35pF (Figure 1) MAX4754A/MAX4756A	+25°C		27	60	ns
			T_{MIN} to T_{MAX}			70	
Turn-On Time NO_	$t_{ON, NO}$	V+ = 2.7V, $V_{NC_}$ = 1.5V, R_L = 50Ω, C_L = 35pF (Figure 1) MAX4754A/MAX4756A	+25°C		70	150	ns
			T_{MIN} to T_{MAX}			200	
Turn-Off Time NO_	$t_{OFF, NO}$	V+ = 2.7V, $V_{NC_}$ = 1.5V, R_L = 50Ω, C_L = 35pF (Figure 1) MAX4754A/MAX4756A	+25°C		300	650	ns
			T_{MIN} to T_{MAX}			900	
Turn-On Time	t_{ON}	V+ = 2.7V, $V_{NO_}$, or $V_{NC_}$ = 1.5V; R_L = 50Ω; C_L = 35pF, (Figure 1) MAX4754/MAX4755/MAX4756	+25°C		45	140	ns
			T_{MIN} to T_{MAX}			150	
Turn-Off Time	t_{OFF}	V+ = 2.7V, $V_{NO_}$, or $V_{NC_}$ = 1.5V; R_L = 50Ω; C_L = 35pF (Figure 1) MAX4754/MAX4755/MAX4756	+25°C		25	50	ns
			T_{MIN} to T_{MAX}			60	
Break-Before-Make	t_{BBM}	V+ = 2.7V, $V_{NO_}$, or $V_{NC_}$ = 1.5V; R_L = 50Ω, C_L = 35pF (Figure 2) (Note 7)	+25°C		15		ns
			T_{MIN} to T_{MAX}	2			
Charge Injection	Q	V_{GEN} = 0V, R_{GEN} = 0, C_L = 1.0nF (Figure 3)	+25°C		300		pC
On-Channel -3dB Bandwidth	BW	Signal = 0dBm, C_L = 50pF, R_S = 50Ω, R_L = 50Ω	+25°C		10		MHz
Off-Isolation	V_{ISO}	C_L = 5pF, R_L = 50Ω, $V_{COM_}$ = $1V_{P-P}$ f = 100kHz (Figure 4) (Note 8)	+25°C		-65		dB
Crosstalk	V_{CT}	C_L = 5pF, R_L = 50Ω, $V_{COM_}$ = $1V_{P-P}$ f = 100kHz (Figure 4) (Note 9)	+25°C		-90		dB

ELECTRICAL CHARACTERISTICS (continued)

(V+ = +2.7V to +5.25V, T_A = -40°C to +85°C, unless otherwise noted. Typical values are at +3V and T_A = +25°C.) (Notes 2, 3)

PARAMETER	SYMBOL	CONDITIONS	T_A	MIN	TYP	MAX	UNITS
Total Harmonic Distortion	THD	f = 20Hz to 20kHz, $1V_{P-P}$, R_L = 32Ω, V_{DC} = V+/2	+25°C		0.035		%
NO_, NC_ Off-Capacitance	$C_{NO_(OFF)}$, $C_{NC_(OFF)}$	V_{NO}, $V_{NC_}$ = GND, f = 1MHz (Figure 5)	+25°C		180		pF
COM_ Off-Capacitance	$C_{COM_(OFF)}$	$V_{COM_}$ = GND, f = 1MHz (Figure 5)	+25°C		300		pF
COM_ On-Capacitance	$C_{(ON)}$	$V_{COM_}$ = GND, f = 1MHz (Figure 5)	+25°C		400		pF
DIGITAL I/O (IN_, $\overline{EN}$)							
Input Logic-High	V_{IH}	V+ = 2.7V to 3.6V, MAX4754/MAX4755/MAX4756	T_{MIN} to T_{MAX}	1.4			V
		V+ = 2.7V to 5.25V, MAX4754A/MAX4756A	T_{MIN} to T_{MAX}	1.4			
		V+ = 3.6V to 5.25V, MAX4754/MAX4755/MAX4756	T_{MIN} to T_{MAX}	2.0			
Input Logic-Low	V_{IL}	V+ = 2.7V to 3.6V, MAX4754/MAX4755/MAX4756	T_{MIN} to T_{MAX}			0.5	V
		V+ = 2.7V to 5.25V, MAX4754A/MAX4756A	T_{MIN} to T_{MAX}			0.5	
		V+ = 3.6V to 5.25V, MAX4754/MAX4755/MAX4756	T_{MIN} to T_{MAX}			0.6	
Input Leakage Current	I_{IN}	V_{IN} = 0V or V+	T_{MIN} to T_{MAX}			1	µA
POWER SUPPLY							
Power-Supply Range	V+		T_{MIN} to T_{MAX}	1.8		5.5	V
Power-Supply Current	I+	V+ = 5.5V, $V_{IN_}$ = 0V or V+, MAX4754/MAX4754A/MAX4755/MAX4756/MAX4756A	+25°C		0.2		µA
			T_{MIN} to T_{MAX}			2	
		V+ = 5.5V, $V_{IN_}$ = 0.5V or 1.4V, MAX4754A/MAX4756A	+25°C		6.5		µA
			T_{MIN} to T_{MAX}			12	

Note 2: The algebraic convention is used in this data sheet; the most negative value is shown in the minimum column.

Note 3: UCSP parts are 100% tested at +25°C and limits across the full temperature range are guaranteed by correlation and design. TQFN parts are 100% tested at +85°C and limits across the full temperature range are guaranteed by correlation and design.

Note 4: R_{ON} and ΔR_{ON} matching specifications are guaranteed by design and correlation.

Note 5: $\Delta R_{ON} = R_{ON(MAX)} - R_{ON(MIN)}$.

Note 6: Flatness is defined as the difference between the maximum and minimum value of on-resistance as measured over the specified analog signal ranges.

Note 7: Guaranteed by design, not production tested.

Note 8: Off-Isolation = $20\log_{10}$ [V_{COM} / (V_{NO} or V_{NC})], V_{COM} = output, V_{NO} or V_{NC} = input to off switch.

Note 9: Between any two switches.

Typical Operating Characteristics

(V+ = 3V, T_A = +25°C, unless otherwise noted.)

ON-RESISTANCE vs. V_{COM} (MAX4754A/MAX4756A)



ON-RESISTANCE vs. V_{COM} AND TEMPERATURE



ON-RESISTANCE vs. V_{COM} AND TEMPERATURE



ON-RESISTANCE vs. V_{COM}



ON-RESISTANCE vs. V_{COM} AND TEMPERATURE



ON-RESISTANCE vs. V_{COM} AND TEMPERATURE



NO/NC OFF-LEAKAGE CURRENT vs. TEMPERATURE (MAX4754/MAX4755/MAX4756)



COM ON-LEAKAGE CURRENT vs. TEMPERATURE



CHARGE INJECTION vs. V_{COM} (MAX4754/MAX4755/MAX4756)



0.5Ω, Quad SPDT Switches in UCSP/QFN

Typical Operating Characteristics (continued)

(V+ = 3V, T_A = +25°C, unless otherwise noted.)

CHARGE INJECTION vs. V_{COM}



SUPPLY CURRENT vs. SUPPLY VOLTAGE



SUPPLY CURRENT vs. TEMPERATURE (MAX4754/MAX4755/MAX4756)



SUPPLY CURRENT vs. TEMPERATURE (MAX4754A/MAX4756A)



LOGIC THRESHOLD vs. SUPPLY VOLTAGE (MAX4754/MAX4755/MAX4756)



LOGIC THRESHOLD vs. SUPPLY VOLTAGE (MAX4754A/MAX4756A)



TURN-ON/OFF TIMES vs. SUPPLY VOLTAGE (MAX4754/MAX4755/MAX4756)



TURN-ON/OFF TIMES vs. SUPPLY VOLTAGE (MAX4754A)



TURN-ON/OFF TIMES vs. TEMPERATURE (MAX4754/MAX4755/MAX4756)



Typical Operating Characteristics (continued)

(V+ = 3V, T_A = +25°C, unless otherwise noted.)

TURN-ON/OFF TIMES vs. TEMPERATURE (MAX4754A)



SUPPLY CURRENT vs. LOGIC CONTROL INPUT



FREQUENCY REPSONSE



TOTAL HARMONIC DISTORTION PLUS NOISE vs. FREQUENCY



Pin Description

PIN						NAME	FUNCTION
MAX4754/MAX4754A		MAX4755		MAX4756/MAX4756A			
UCSP	QFN	UCSP	QFN	UCSP	QFN		
C1	1	C1	1	C1	1	NO1	Analog Switch 1. Normally open terminal 1.
C2	2	C2	2	C2	2	INA	Logic Control Digital Input for Switches 1 and 2. Digital control input for switches 1–4 for MAX4756.
B1	3	B1	3	B1	3	COM1	Analog Switch 1. Common terminal.
A1	4	A1	4	A1	4	NC1	Analog Switch 1. Normally closed terminal 1.
A2	5	A2	5	A2	5	NO4	Analog Switch 4. Normally open terminal 4.
B2	6	B2	6	B2	6	V+	Positive Supply Voltage
A3	7	A3	7	A3	7	COM4	Analog Switch 4. Common terminal.
A4	8	A4	8	A4	8	NC4	Analog Switch 4. Normally closed terminal 4.
B4	9	B4	9	B4	9	NO2	Analog Switch 2. Normally open terminal 2.
B3	10	B3	10	—	—	INB	Logic Control Digital Input for Switches 3 and 4
—	—	—	—	B3	10	$\overline{EN}$	Output Enable. Active low.
C4	11	C4	11	C4	11	COM2	Analog Switch 2. Common terminal 2.
D4	12	D4	12	D4	12	NC2	Analog Switch 2. Normally closed terminal 2.
D3	13	D3	13	D3	13	NO3	Analog Switch 3. Normally open terminal 3.
C3	14	C3	14	C3	14	GND	Ground
D2	15	D2	15	D2	15	COM3	Analog Switch 3. Common terminal 3.
D1	16	D1	16	D1	16	NC3	Analog Switch 4. Normally closed terminal 3.
—	EP	—	EP	—	EP	EP	Exposed Paddle. Connect EP to GND.

Typical Operating Circuit



Detailed Description

The MAX4754/MAX4754A/MAX4755/MAX4756/MAX4756A low on-resistance analog switches operate from a single +1.8V to +5.5V supply. The devices are fully specified for nominal 3V applications.

The MAX4754/MAX4754A DPDT switch have two logic control inputs with each input controlling two SPDT switches. Each switch has a 0.5Ω on-resistance in the NO and NC terminals making it ideal for switching audio signals.

The MAX4755 DPDT switch also has four 0.5Ω SPDT switches with the switch pairs 1 and 2 adding an 11.5Ω series resistor to the NC terminal. This feature allows the user to drive an 8Ω speaker as a 32Ω load, allowing it to be used as an ear speaker. Two logic control inputs are used to control the four switches.

The MAX4756/MAX4756A has four 0.5Ω SPDT switches controlled by one logic control input (INA) and $\overline{EN}$ input to disable the switches.

Applications Information

Digital Control Inputs

The MAX4754/MAX4754A/MAX4755/MAX4756/MAX4756A logic inputs accept up to +5.5V regardless of the supply voltage. For example, with a +3.3V supply IN_ can be driven low to GND and high to +5.5V, which allows mixed logic levels in a system. Driving the control logic inputs rail-to-rail also minimizes power consumption. For a +3V supply voltage, the logic thresholds are 0.5V (low) and 1.4V (high).

For the MAX4756/MAX4756A, drive $\overline{EN}$ low to enable the COM_. When $\overline{EN}$ is high, COM _ is high impedance.

Analog Signal Levels

Analog signal inputs over the full voltage range (0V to V+) are passed through the switch with minimal change in on-resistance (see the *Typical Operating Characteristics*). The switches are bidirectional so NO_, NC_, and COM_ can be either inputs or outputs.

Power-Supply Bypassing

Power-supply bypassing improves noise margin and prevents switching noise from propagating from the V+ supply to other components. A 0.1µF capacitor connected from V+ to GND is adequate for most applications.

UCSP Applications Information

For the latest application details on UCSP construction, dimensions, tape carrier information, printed circuit board techniques, bump-pad layout, and recommended reflow temperature profile, as well as the latest information on reliability testing results, go to the Maxim website at www.maxim-ic.com/ucsp for the Application Note: *UCSP—A Wafer-Level Chip-Scale Package*.

0.5Ω, Quad SPDT Switches in UCSP/QFN

Timing Circuits/Timing Diagrams



Figure 1. Switching Time



Figure 2. Break-Before-Make Interval



Figure 3. Charge Injection

Timing Circuits/Timing Diagrams (continued)



Figure 4. On-Loss, Off-Isolation, and Crosstalk



Figure 5. Channel On-/Off-Capacitance

0.5Ω, Quad SPDT Switches in UCSP/QFN

Pin Configurations/Truth Tables

TOP VIEW

(BUMP SIDE DOWN)

MAXIM

MAX4754/MAX4754A/MAX4755/
MAX4756/MAX4756A



( ) FOR MAX4756/MAX4756A.

UCSP

MAXIM

MAX4754
MAX4754A
MAX4755
MAX4756
MAX4756A



TQFN

***EP:** EXPOSED PADDLE CONNECTED TO GND.

MAX4754/MAX4754A/MAX4755

INA	NO1/NO2	NC1/NC2	NO3/NO4	NC3/NC4
LOW	OFF	ON	—	—
HIGH	ON	OFF	—	—
INB				
LOW	—	—	OFF	ON
HIGH	—	—	ON	OFF

MAX4756/MAX4756A

$\overline{EN}$	INA	NO_	NC_
LOW	LOW	OFF	ON
LOW	HIGH	ON	OFF
HIGH	X	OFF	OFF
HIGH	X	OFF	OFF

Chip Information

PROCESS: CMOS

Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to **www.maxim-ic.com/packages**.)

24L QFN THIN.EPS



0.5Ω, Quad SPDT Switches in UCSP/QFN

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to **www.maxim-ic.com/packages**.)

COMMON DIMENSIONS															
PKG	12L 4x4			16L 4x4			20L 4x4			24L 4x4			28L 4x4		
REF.	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	0.70	0.75	0.80	0.70	0.75	0.80	0.70	0.75	0.80	0.70	0.75	0.80	0.70	0.75	0.80
A1	0.0	0.02	0.05	0.0	0.02	0.05	0.0	0.02	0.05	0.0	0.02	0.05	0.0	0.02	0.05
A2	0.20 REF			0.20 REF			0.20 REF			0.20 REF			0.20 REF		
b	0.25	0.30	0.35	0.25	0.30	0.35	0.20	0.25	0.30	0.18	0.23	0.30	0.15	0.20	0.25
D	3.90	4.00	4.10	3.90	4.00	4.10	3.90	4.00	4.10	3.90	4.00	4.10	3.90	4.00	4.10
E	3.90	4.00	4.10	3.90	4.00	4.10	3.90	4.00	4.10	3.90	4.00	4.10	3.90	4.00	4.10
e	0.80 BSC.			0.65 BSC.			0.50 BSC.			0.50 BSC.			0.40 BSC.		
k	0.25	-	-	0.25	-	-	0.25	-	-	0.25	-	-	0.25	-	-
L	0.45	0.55	0.65	0.45	0.55	0.65	0.45	0.55	0.65	0.30	0.40	0.50	0.30	0.40	0.50
N	12			16			20			24			28		
ND	3			4			5			6			7		
NE	3			4			5			6			7		
Jedec Var.	WGGB			WGGC			WGGD-1			WGGD-2			WGGE		

EXPOSED PAD VARIATIONS							
PKG. CODES	D2			E2			DOWN BONDS ALLOWED
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.	
T1244-3	1.95	2.10	2.25	1.95	2.10	2.25	YES
T1244-4	1.95	2.10	2.25	1.95	2.10	2.25	NO
T1644-3	1.95	2.10	2.25	1.95	2.10	2.25	YES
T1644-4	1.95	2.10	2.25	1.95	2.10	2.25	NO
T2044-2	1.95	2.10	2.25	1.95	2.10	2.25	YES
T2044-3	1.95	2.10	2.25	1.95	2.10	2.25	NO
T2444-2	1.95	2.10	2.25	1.95	2.10	2.25	YES
T2444-3	2.45	2.60	2.63	2.45	2.60	2.63	YES
T2444-4	2.45	2.60	2.63	2.45	2.60	2.63	NO
T2844-1	2.50	2.60	2.70	2.50	2.60	2.70	NO

NOTES:

1. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
2. ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
3. N IS THE TOTAL NUMBER OF TERMINALS.
4. THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JESD 95-1 SPP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
5. DIMENSION b APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25 mm AND 0.30 mm FROM TERMINAL TIP.
6. ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE RESPECTIVELY.
7. DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
8. COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
9. DRAWING CONFORMS TO JEDEC MO220, EXCEPT FOR T2444-3, T2444-4 AND T2844-1.
10. MARKING IS FOR PACKAGE ORIENTATION REFERENCE ONLY.
11. COPLANARITY SHALL NOT EXCEED 0.08mm
12. WARPAGE SHALL NOT EXCEEND 0.10mm
13. LEAD CENTERLINES TO BE AT TRUE POSITION AS DEFINED BY BASIC DIMENSION "e", ±0.05.
14. NUMBER OF LEADS SHOWN ARE FOR REFERENCE ONLY

-DRAWING NOT TO SCALE-

DALLAS SEMICONDUCTOR MAXIM

TITLE: PACKAGE OUTLINE, 12, 16, 20, 24, 28L THIN QFN, 4x4x0.8mm			
APPROVAL	DOCUMENT CONTROL NO. 21-0139	REV. E	2/2

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to **www.maxim-ic.com/packages**.)

16L,UCSP.EPS



TOP VIEW

COMMON DIMENSIONS	
A	0.62+0.05-0.08
A1	0.29±0.02
A2	0.33 REF.
b	ø0.35±0.03
D1	1.50 BASIC
E1	1.50 BASIC
e	0.50 BASIC
SD	0.25 BASIC
SE	0.25 BASIC

PKG. CODE	VARIABLE DIMENSIONS		DEPOPULATED SOLDER BALLS
	D	E	
B16-1	2.02±0.05	2.02±0.05	NONE
B16-2	2.02±0.05	2.02±0.05	B3, C3
B16-3	2.02±0.05	2.02±0.05	B3, C2
B16-4	2.02±0.05	2.02±0.05	B2, C3
B16-5	2.02±0.05	2.02±0.05	B2, B3, C2, C3
B16-6	2.02±0.05	2.02±0.05	C3

NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. PRODUCT MARKING: NUMBER OF CHARACTERS AND LINES VARY PER PRODUCT.



BOTTOM VIEW



SIDE VIEW

DALLAS SEMICONDUCTOR MAXIM
PROPRIETARY INFORMATION

TITLE: PACKAGE OUTLINE, 4x4 UCSP

APPROVAL	DOCUMENT CONTROL NO.	REV.	
	21-0101	H	1/1

Revision History

Pages changed at Rev 1: 1–5, 7, 8, 13, 14, 15

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

© 2006 Maxim Integrated Products MAXIM is a registered trademark of Maxim Integrated Products, Inc.