


DWG. NO. 10-5263-1

PART MDSR-4

**ELECTRICAL RATINGS**

|                    |                  |                 |       |
|--------------------|------------------|-----------------|-------|
| CONTACT FORM       |                  |                 | A     |
| CONTACT RATING     |                  | WATTS           | 10    |
| RATING SENSITIVITY |                  | AMPERE TURNS    | 20    |
| VOLTAGE            | SWITCHING        | VDC-MAX.        | 200   |
|                    | BREAKDOWN        | VDC-MIN         | 250   |
|                    | ARC-QUENCH       | VDC-MIN         | 200   |
| CURRENT            | SWITCHING        | AMPERES-MAX.    | 0.5   |
|                    | CARRY            | AMPERES-MAX.    | 1.2   |
| RESISTANCE         | CONTACT, INITIAL | OHMS-MAX.       | 0.10  |
|                    | INSULATION       | OHMS-MIN.       | 10 10 |
| CAPACITANCE        |                  | PICOFARADS-TYP. | 0.2   |

**MAGNETIC CHARACTERISTICS**

|                     |              |       |
|---------------------|--------------|-------|
| TEST COIL           |              | L4989 |
| STANDARD TOLERANCE  | AMPERE TURNS | 12-23 |
| PULL-IN RANGES      |              | 17-28 |
|                     |              | 22-33 |
|                     |              | 27-38 |
| TIGHTENED TOLERANCE | AMPERE TURNS | 12-18 |
| PULL-IN RANGES      |              | 17-23 |
|                     |              | 22-28 |
|                     |              | 27-33 |
|                     |              | 32-38 |


**OPERATING CHARACTERISTICS**

|                       |                              |             |                              |
|-----------------------|------------------------------|-------------|------------------------------|
| OPERATE TIME          |                              | ms-MAX.     | 0.6                          |
| RELEASE TIME          |                              | ms-MAX.     | 0.2                          |
| SHOCK                 | G's MAX., 11ms 1/2 SINE WAVE |             | 100                          |
| VIBRATION             | G's MAX., 50-2000 HERTZ      |             | 30                           |
| RESONANT FREQUENCY    |                              | HERTZ, TYP. | 3900                         |
| TEMPERATURE OPERATING | DEGREES, CELSIUS             |             | -40 TO +125                  |
|                       | STORAGE                      |             | DEGREES, CELSIUS -65 TO +125 |

SEE REED SWITCH CATALOG FOR DEFINITION OF TERMS

**DRAWING REVISIONS**

| REV. NO. | DATE | DCR NO. |
|----------|------|---------|
|          |      |         |
|          |      |         |
|          |      |         |
|          |      |         |
|          |      |         |

**DROP-OUT (DESIGN PARAMETER)**

EXAMPLE:  
17-33 AT PULL-IN  
8-21 AT DROP-OUT

**HAMLIN**

1993

THIS DESIGN AND PRINT IS COPYRIGHT AND IS THE PROPERTY OF HAMLIN INC. IT MUST NOT BE COPIED OR PERMITTED TO BE COPIED. NOR MUST ITS CONTENTS BE DIVULGED TO ANY THIRD PARTY WITHOUT PRIOR WRITTEN PERMISSION FROM THE COMPANY.

SHEET 1 OF 1 SHEET(S)

DIM.: INCHES (mm)

DWG. NO. 10-5263-1