FAIRCHILD
SEMICONDUCTOR™

GlobalOptoisolator™

VDE | UL | CSA | SETI | SEMKO | DEMKO | NEMKO | BABT

6-Pin DIP Optoisolators Logic Output

MOC5007
MOC5008
MOC5009

The MOC5007, MOC5008 and MOC5009 have a gallium arsenide IRED optically coupled to a high–speed integrated detector with Schmitt trigger output. Ideal for applications requiring electrical isolation, fast response time, noise immunity and digital logic compatibility.

- Guaranteed Switching Times — t_{on}, t_{off} 4 < µs
- Built–In ON/OFF Threshold Hysteresis
- High Data Rate, 1 MHz Typical (NRZ)
- Wide Supply Voltage Capability
- Microprocessor Compatible Drive
- ***To order devices that are tested and marked per VDE 0884 requirements, the suffix "V" must be included at end of part number. VDE 0884 is a test option.***



STANDARD THRU HOLE

SCHEMATIC



PIN 1. ANODE
2. CATHODE
3. NC
4. OPEN COLLECTOR OUTPUT
5. GROUND
6. V_{CC}

Applications

- Interfacing Computer Terminals to Peripheral Equipment
- Digital Control of Power Supplies
- Line Receiver — Eliminates Noise
- Digital Control of Motors and Other Servo Machine Applications
- Logic to Logic Isolator
- Logic Level Shifter — Couples TTL to CMOS

MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Rating	Symbol	Value	Unit
INPUT LED			
Reverse Voltage	V_R	6	Volts
Forward Current — Continuous Peak Pulse Width = 300 µs, 2% Duty Cycle	I_F	60 1.2	mA Amp
LED Power Dissipation @ T_A = 25°C Derate above 25°C	P_D	120 1.41	mW mW/°C
OUTPUT DETECTOR			
Output Voltage Range	V_o	0–16	Volts
Supply Voltage Range	V_{CC}	3–16	Volts
Output Current	I_O	50	mA
Detector Power Dissipation @ T_A = 25°C Derate above 25°C	P_D	150 1.76	mW mW/°C
TOTAL DEVICE			
Total Device Power Dissipation @ T_A = 25°C Derate above 25°C	P_D	250 2.94	mW mW/°C
Maximum Operating Temperature	T_A	–40 to +85	°C
Storage Temperature Rang	T_{stg}	–55 to +150	°C
Soldering Temperature (10 s)	T_L	260	°C
Isolation Surge Voltage(1) (Peak ac Voltage, 60 Hz, 1 Second Duration)	V_{ISO}	7500	Vac(pk)

1. Isolation surge voltage is an internal device dielectric breakdown rating. For this test, Pins 1 and 2 are common, and Pins 4, 5 and 6 are common.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)(1)

Characteristic		Symbol	Min	Typ1)	Max	Unit
INPUT LED						
Reverse Leakage Current (V_R = 3 V, RL = 1 MΩ)		I_R	—	0.05	10	µA
Forward Voltage (I_F = 10 mA) (I_F = 0.3 mA)		V_F	— 0.75	1.2 0.95	1.5 —	Volts
Capacitance (V_R = 0 V, f = 1 MHz)		C	—	18	—	pF
OUTPUT DETECTOR						
Operating Voltage		V_{CC}	3	—	15	Volts
Supply Current (I_F = 0, V_{CC} = 5 V)		$I_{CC(off)}$	—	1	5	mA
Output Current, High (I_F = 0, V_{CC} = V_o = 15 V)		I_{OH}	—	—	100	µA
COUPLED						
Supply Current (I_F = $I_{F(on)}$, V_{CC} = 5 V)		$I_{CC(on)}$	—	1.6	5	mA
Output Voltage, Low (R_L = 270 Ω, V_{CC} = 5 V, I_F = $I_{F(on)}$)		V_{OL}	—	0.2	0.4	Volts
Threshold Current, ON (R_L = 270 Ω, V_{CC} = 5 V)	MOC5007 MOC5008 MOC5009	$I_{F(on)}$	— — —	1.2 — —	1.6 4 10	mA
Threshold Current, OFF (R_L = 270 Ω, V_{CC} = 5 V)	MOC5007 MOC5008, 5009	$I_{F(off)}$	0.3 0.3	0.75 —	— —	mA
Hysteresis Ratio (R_L = 270 Ω, V_{CC} = 5 V)		$\frac{I_{F(off)}}{I_{F(on)}}$	0.5	0.75	0.9	
Isolation Voltage(2) 60 Hz, AC Peak, 1 second, T_A = 25°C		V_{ISO}	7500	—	—	Vac(pk)
Turn–On Time	R_L = 270 Ω(3) V_{CC} = 5 V, I_F = $I_{F(on)}$ T_A = 25°C	t_{on}	—	1.2	4	µs
Fall Time		t_f	—	0.1	—	
Turn–Off Time		t_{off}	—	1.2	4	
Rise Time		t_r	—	0.1	—	

1. Always design to the specified minimum/maximum electrical limits (where applicable).
2. For this test, IRED Pins 1 and 2 are common and Output Gate Pins 4, 5, 6 are common.
3. R_L value effect on switching time is negligible.



Figure 1. Switching Test Circuit

TYPICAL CHARACTERISTICS



Figure 2. Transfer Characteristics for MOC5007



Figure 3. Threshold Current versus Supply Voltage



Figure 4. Threshold Current versus Temperature



Figure 5. Output Voltage, Low versus Load Current



Figure 6. Supply Current versus Supply Voltage

PACKAGE DIMENSIONS



STYLE 5:
PIN 1. ANODE
2. CATHODE
3. NC
4. OUTPUT
5. GROUND
6. V_{CC}

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.320	0.350	8.13	8.89
B	0.240	0.260	6.10	6.60
C	0.115	0.200	2.93	5.08
D	0.016	0.020	0.41	0.50
E	0.040	0.070	1.02	1.77
F	0.010	0.014	0.25	0.36
G	0.100 BSC		2.54 BSC	
J	0.008	0.012	0.21	0.30
K	0.100	0.150	2.54	3.81
L	0.300 BSC		7.62 BSC	
M	0°	15°	0°	15°
N	0.015	0.100	0.38	2.54

THRU HOLE



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.320	0.350	8.13	8.89
B	0.240	0.260	6.10	6.60
C	0.115	0.200	2.93	5.08
D	0.016	0.020	0.41	0.50
E	0.040	0.070	1.02	1.77
F	0.010	0.014	0.25	0.36
G	0.100 BSC		2.54 BSC	
H	0.020	0.025	0.51	0.63
J	0.008	0.012	0.20	0.30
K	0.006	0.035	0.16	0.88
L	0.320 BSC		8.13 BSC	
S	0.332	0.390	8.43	9.90

SURFACE MOUNT



NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.320	0.350	8.13	8.89
B	0.240	0.260	6.10	6.60
C	0.115	0.200	2.93	5.08
D	0.016	0.020	0.41	0.50
E	0.040	0.070	1.02	1.77
F	0.010	0.014	0.25	0.36
G	0.100 BSC		2.54 BSC	
J	0.008	0.012	0.21	0.30
K	0.100	0.150	2.54	3.81
L	0.400	0.425	10.16	10.80
N	0.015	0.040	0.38	1.02

0.4" LEAD SPACING

FAIRCHILD
SEMICONDUCTOR™

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.

2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2000 Fairchild Semiconductor Corporation