



Best Value in the Industry

3-5/6 True-RMS Compact Digital Multimeter

Item: **MT-1236**

Full assortment of test functions

Precise ACV ACA True RMS Measurements

Overload Protection

Non-contact voltage detection

Includes test leads

Large backlit screen



LCD Display	3-5/6 5999 Counts
DCV	600mV/6V/60V/600V $\pm$ (0.5% +5d)
ACV	600mV/6V/60V/600V $\pm$ (1% +4d) TRUE-RMS
DCA	60mA/600mA $\pm$ (1.2% +5 d) , 10A $\pm$ (3.0% +5d)
ACA	60mA/600mA $\pm$ (1.5% +5 d) , 10A $\pm$ (3.0% +5d) TRUE-RMS
Frequency	9.999Hz/99.99Hz/999.9Hz/9.999KHz/99.99KHz/999.9KHz/9.999MHz $\pm$ (1.5% +5d)
Duty Cycle	1%~99% $\pm$ (2.5% +5 d)
Resistance Ω	600 Ω /6k/60k/600k/6M/60M Ω $\pm$ (0.8% +5d)
Capacitance	60nF/600nF/6uF/60uF/600uF/6mF $\pm$ (4% +5d) ,100mF $\pm$ (4% +10d)
Temperature(C/F)	-20°C~1000°C $\pm$ (1% +3d) -4°F~2372°F $\pm$ (1% +3d)
Continuity Buzzer	$\leq$ 30 Ω , buzzer beeps
Diode Test	Y
NCV Detection	Y
Data Hold	Y
LED Light	Y
LCD Backlight	Y
Analog Bar	Y
Low Battery Indication	Y
Accessories	Test Lead, K-type thermocouple, Manual
Power	1.5V AAA x 3pcs (Not Included)
Dimensions	5.8 x 3.1 x 1.9 in.
Weight	0.46 lbs (without battery)

Order Today! SalesSupport@EclipseTools.com

Eclipse Enterprises, Inc. • Tel: 804.561.2610 • Fax: 804.561.2642

13302 Chula Road, Amelia Court House, VA 23002 • EclipseTools.com

