NLAS4053

Analog Multiplexer/ Demultiplexer

Triple 2:1 Analog Switch–Multiplexer Improved Process, Sub–Micron Silicon Gate CMOS

The NLAS4053 is an improved version of the MC14053 and MC74HC4053 fabricated in sub–micron Silicon Gate CMOS technology for lower $R_{DS(on)}$ resistance and improved linearity with low current. This device may be operated either with a single supply or dual supply up to ±3 V to pass a 6 V_{PP} signal without coupling capacitors.


When operating in single supply mode, it is only necessary to tie V_{EE}, pin 7 to ground. For dual supply operation, V_{EE} is tied to a negative voltage, not to exceed maximum ratings. Pin for pin compatible with all industry standard versions of '4053.'

- Improved $R_{DS(on)}$ Specifications
- Pin for Pin Replacement for MAX4053 and MAX4053A
  – One Half the Resistance Operating at 5.0 Volts
- Single or Dual Supply Operation
  – Single 3–5 Volt Operation, or Dual ±3 Volt Operation
  – With V_{CC} of 3.0 to 3.3 V, Device Can Interface with 1.8 V Logic, No Translators Needed
  – Address and Inhibit Pins are Over–Voltage Tolerant and May Be Driven Up +6 V Regardless of V_{CC}
- Address and Control Pins are Standard TTL Compatible
  – Greatly Improved Noise Margin Over MAX4053 and MAX4053A
- Improved Linearity Over Standard HC4053 Devices
- Popular SOIC, and Space Saving TSSOP, and QSOP 16 Pin Packages

ON Semiconductor®


http://onsemi.com

MARKING DIAGRAMS





SO–16
D SUFFIX
CASE 751B






TSSOP–16
DT SUFFIX
CASE 948F





QSOP–16
QS SUFFIX
CASE 492



A = Assembly Location
L, WL = Wafer Lot
Y, YY = Year
W, WW = Work Week

ORDERING INFORMATION

Device	Package	Shipping
NLAS4053D	SO–16	48 Units/Rail
NLAS4053DR2	SO–16	2500 Units/Reel
NLAS4053DT	TSSOP–16	96 Units/Rail
NLAS4053DTR2	TSSOP–16	2500 Units/Reel
NLAS4053QS	QSOP–16	48 Units/Rail
NLAS4053QSR	QSOP–16	2000 Units/Reel

© Semiconductor Components Industries, LLC, 2002




Figure 1. Pin Connection
(Top View)




Figure 2. Logic Diagram

TRUTH TABLE

Inhibit	Address			ON SWITCHES*
	C	B	A	
1	X don't care	X don't care	X don't care	All switches open
0	0	0	0	COM_A–NC_A, COM_B–NC_B, COM_C–NC_C
0	0	0	1	COM_A–NO_A, COM_B–NC_B, COM_C–NC_C
0	0	1	0	COM_A–NC_A, COM_B–NO_B, COM_C–NC_C
0	0	1	1	COM_A–NO_A, COM_B–NO_B, COM_C–NC_C
0	1	0	0	COM_A–NC_A, COM_B–NC_B, COM_C–NO_C
0	1	0	1	COM_A–NO_A, COM_B–NC_B, COM_C–NO_C
0	1	1	0	COM_A–NC_A, COM_B–NO_B, COM_C–NO_C
0	1	1	1	COM_A–NO_A, COM_B–NO_B, COM_C–NO_C

*NO, NC, and COM pins are identical and interchangeable. Either may be considered an input or output; signals pass equally well in either direction.

MAXIMUM RATINGS (Note 1)

Symbol	Parameter		Value	Unit
V_{EE}	Negative DC Supply Voltage	(Referenced to GND)	–7.0 to +0.5	V
V_{CC}	Positive DC Supply Voltage (Note 2)	(Referenced to GND) (Referenced to V_{EE})	–0.5 to +7.0 –0.5 to +7.0	V
V_{IS}	Analog Input Voltage		V_{EE} –0.5 to V_{CC} +0.5	V
V_{IN}	Digital Input Voltage	(Referenced to GND)	–0.5 to 7.0	V
I	DC Current, Into or Out of Any Pin		±50	mA
T_{STG}	Storage Temperature Range		–65 to +150	°C
T_L	Lead Temperature, 1 mm from Case for 10 Seconds		260	°C
T_J	Junction Temperature under Bias		+150	°C
θ_{JA}	Thermal Resistance	SOIC TSSOP QSOP	143 164 164	°C/W
P_D	Power Dissipation in Still Air,	SOIC TSSOP QSOP	500 450 450	mW
MSL	Moisture Sensitivity		Level 1	
F_R	Flammability Rating	Oxygen Index: 30% – 35%	UL 94 V–0 @ 0.125 in	
V_{ESD}	ESD Withstand Voltage	Human Body Model (Note 3) Machine Model (Note 4) Charged Device Model (Note 5)	>2000 >200 >1000	V
$I_{LATCH–UP}$	Latch–Up Performance	Above V_{CC} and Below GND at 125°C (Note 6)	±300	mA

1. Absolute maximum continuous ratings are those values beyond which damage to the device may occur. Extended exposure to these conditions or conditions beyond those indicated may adversely affect device reliability. Functional operation under absolute maximum–rated conditions is not implied.
2. The absolute value of $V_{CC} \pm |V_{EE}| \le 7.0$.
3. Tested to EIA/JESD22–A114–A.
4. Tested to EIA/JESD22–A115–A.
5. Tested to JESD22–C101–A.
6. Tested to EIA/JESD78.

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter		Min	Max	Unit
V_{EE}	Negative DC Supply Voltage	(Referenced to GND)	–5.5	GND	V
V_{CC}	Positive DC Supply Voltage	(Referenced to GND) (Referenced to V_{EE})	2.5 2.5	5.5 6.6	V
V_{IS}	Analog Input Voltage		V_{EE}	V_{CC}	V
V_{IN}	Digital Input Voltage	(Note 7) (Referenced to GND)	0	5.5	V
T_A	Operating Temperature Range, All Package Types		–55	125	°C
t_r, t_f	Input Rise/Fall Time (Channel Select or Enable Inputs)	V_{CC} = 3.0 V ± 0.3 V V_{CC} = 5.0 V ± 0.5 V	0 0	100 20	ns/V

7. Unused digital inputs may not be left open. All digital inputs must be tied to a high–logic voltage level or a low–logic input voltage level.

DC CHARACTERISTICS – Digital Section (Voltages Referenced to GND)

Symbol	Parameter	Condition	V_{CC} V	Guaranteed Limit			Unit
				–55 to 25°C	≤ 85°C	≤ 125°C	
V_{IH}	Minimum High–Level Input Voltage, Address and Inhibit Inputs		2.0 3.0 4.5 5.5	1.5 2.1 3.15 3.85	1.5 2.1 3.15 3.85	1.5 2.1 3.15 3.85	V
V_{IL}	Maximum Low–Level Input Voltage, Address and Inhibit Inputs		2.0 3.0 4.5 5.5	0.5 0.9 1.35 1.65	0.5 0.9 1.35 1.65	0.5 0.9 1.35 1.65	V
I_{IN}	Maximum Input Leakage Current, Address or Inhibit Inputs	V_{IN} = 6.0 or GND	0 V to 6.0 V	±0.1	±1.0	±1.0	μA
I_{CC}	Maximum Quiescent Supply Current (per Package)	Channel Select, Enable and V_{IS} = V_{CC} or GND	6.0	4.0	40	80	μA

DC ELECTRICAL CHARACTERISTICS – Analog Section

Symbol	Parameter	Test Conditions	V_{CC} V	V_{EE} V	Guaranteed Limit			Unit
					–55 to 25°C	≤ 85°C	≤ 125°C	
R_{ON}	Maximum “ON” Resistance	V_{IN} = V_{IL} or V_{IH} V_{IS} = V_{EE} to V_{CC} $\|I_S\|$ = 10 mA (Figures 4 thru 9)	3.0 4.5 3.0	0 0 –3.0	86 37 26	108 46 33	120 55 37	Ω
ΔR_{ON}	Maximum Difference in “ON” Resistance Between Any Two Channels in the Same Package	V_{IN} = V_{IL} or V_{IH}, V_{IS} = 2.0 V V_{IS} = 3.5 V $\|I_S\|$ = 10 mA, V_{IS} = 2.0 V	3.0 4.5 3.0	0 0 –3.0	15 13 10	20 18 15	20 18 15	Ω
$R_{flat(ON)}$	COM–NO On–Resistance Flatness	V_{com} 1, 2, 3.5 V V_{com} –2, 0, 2 V $\|I_S\|$ = 10 mA	4.5 3.0	0 –3.0	4 2	4 2	5 3	Ω
$I_{NC(OFF)}$ $I_{NO(OFF)}$	Maximum Off–Channel Leakage Current	Switch Off V_{IN} = V_{IL} or V_{IH} V_{IO} = V_{CC} –1.0 V or V_{EE} +1.0 V (Figure 17)	6.0 3.0	0 –3.0	0.1 0.1	5.0 5.0	100 100	nA
$I_{COM(ON)}$	Maximum On–Channel Leakage Current, Channel– to–Channel	Switch On V_{IO} = V_{CC} –1.0 V or V_{EE} +1.0 V (Figure 17)	6.0 3.0	0 –3.0	0.1 0.1	5.0 5.0	100 100	nA

AC CHARACTERISTICS (Input $t_r = t_f = 3$ ns)

Symbol	Parameter	Test Conditions	V_{CC} V	V_{EE} V	Guaranteed Limit				Unit
					–55 to 25°C		≤ 85°C	≤ 125°C	
					Min	Typ*			
t_{BBM}	Minimum Break–Before–Make Time	$V_{IN} = V_{IL}$ or V_{IH} $V_{IS} = V_{CC}$ R_L = 300 Ω, C_L = 35 pF (Figure 19)	3.0 4.5 3.0	0.0 0.0 –3.0	1.0 1.0 1.0	6.5 5.0 3.5	– – –	– – –	ns

*Typical Characteristics are at 25°C.

AC CHARACTERISTICS (C_L = 50 pF, Input $t_r = t_f = 3$ ns)

Symbol	Parameter	V_{CC} V	V_{EE} V	Guaranteed Limit							Unit
				–55 to 25°C			≤ 85°C		≤ 125°C		
				Min	Typ	Max	Min	Max	Min	Max	
t_{TRANS}	Transition Time (Address Selection Time) (Figure 18)	2.5 3.0 4.5 3.0	0 0 0 –3.0			40 28 23 23		45 30 25 25		50 35 30 28	ns
t_{ON}	Turn–on Time (Figures 14, 15, 20, and 21) Enable to N_O or N_C	2.5 3.0 4.5 3.0	0 0 0 –3.0			40 28 23 23		45 30 25 25		50 35 30 28	ns
t_{OFF}	Turn–off Time (Figures 14, 15, 20, and 21) Enable to N_O or N_C	2.5 3.0 4.5 3.0	0 0 0 –3.0			40 28 23 23		45 30 25 25		50 35 30 28	ns

		Typical @ 25°C, V_{CC} = 5.0 V	
C_{IN}	Maximum Input Capacitance,Select Inputs	8	pF
C_{NO} or C_{NC}	Analog I/O	10	
C_{COM}	Common I/O	10	
$C_{(ON)}$	Feedthrough	1.0	

ADDITIONAL APPLICATION CHARACTERISTICS (GND = 0 V)

Symbol	Parameter	Condition	V_{CC} V	V_{EE} V	Typ 25°C	Unit
BW	Maximum On–Channel Bandwidth or Minimum Frequency Response	V_{IS} = ½ (V_{CC} – V_{EE}) Source Amplitude = 0 dBm (Figures 10 and 22)	3.0 4.5 6.0 3.0	0.0 0.0 0.0 –3.0	145 165 180 180	MHz
V_{ISO}	Off–Channel Feedthrough Isolation	f = 100 kHz; V_{IS} = ½ (V_{CC} – V_{EE}) Source = 0 dBm (Figures 12 and 22)	3.0 4.5 6.0 3.0	0.0 0.0 0.0 –3.0	–93 –93 –93 –93	dB
V_{ONL}	Maximum Feedthrough On Loss	V_{IS} = ½ (V_{CC} – V_{EE}) Source = 0 dBm (Figures 10 and 22)	3.0 4.5 6.0 3.0	0.0 0.0 0.0 –3.0	–2 –2 –2 –2	dB
Q	Charge Injection	V_{IN} = V_{CC} to V_{EE}, f_{IS} = 1 kHz, t_r = t_f = 3 ns R_{IS} = 0 Ω, C_L= 1000 pF, Q = C_L * ΔV_{OUT} (Figures 16 and 23)	5.0 3.0	0.0 –3.0	9.0 12	pC
THD	Total Harmonic Distortion THD + Noise	f_{IS} = 1 MHz, R_L = 10 KΩ, C_L = 50 pF, V_{IS} = 5.0 V_{PP} sine wave V_{IS} = 6.0 V_{PP} sine wave (Figure 13)	 6.0 3.0	 0.0 –3.0	 0.10 0.05	%




Figure 3. I_{CC} versus Temp, V_{CC} = 3 V and 5 V




Figure 4. R_{ON} versus V_{CC}, Temp = 25°C




Figure 5. Typical On Resistance
V_{CC} = 2.0 V, V_{EE} = 0 V




Figure 6. Typical On Resistance
V_{CC} = 3.0 V, V_{EE} = 0 V




Figure 7. Typical On Resistance
V_{CC} = 4.5 V, V_{EE} = 0 V




Figure 8. Typical On Resistance
V_{CC} = 5.5 V, V_{EE} = 0 V




Figure 9. Typical On Resistance
V_{CC} = 3.3 V, V_{EE} = –3.3 V




Figure 10. Bandwidth




Figure 11. Phase Shift




Figure 12. Off Isolation




Figure 13. Total Harmonic Distortion




Figure 14. t_{ON} and t_{OFF} versus V_{CC}




Figure 15. t_{ON} and t_{OFF} versus Temp




Figure 16. Charge Injection versus COM Voltage




Figure 17. Switch Leakage versus Temperature




Figure 18. Channel Selection Propagation Delay




Figure 19. t_{BBM} (Time Break–Before–Make)




Figure 20. t_{ON}/t_{OFF}





Figure 21. t_{ON}/t_{OFF}



Channel switch control/s test socket is normalized. Off isolation is measured across an off channel. On loss is the bandwidth of an On switch. V_{ISO}, Bandwidth and V_{ONL} are independent of the input signal direction.

V_{ISO} = Off Channel Isolation = 20 Log $\left(\frac{V_{OUT}}{V_{IN}}\right)$ for V_{IN} at 100 kHz

V_{ONL} = On Channel Loss = 20 Log $\left(\frac{V_{OUT}}{V_{IN}}\right)$ for V_{IN} at 100 kHz to 50 MHz

Bandwidth (BW) = the frequency 3 dB below V_{ONL}

Figure 22. Off Channel Isolation/On Channel Loss (BW)/Crosstalk (On Channel to Off Channel)/V_{ONL}




Figure 23. Charge Injection: (Q)

TYPICAL OPERATION




Figure 24. 5.0 Volts Single Supply
V_{CC} = 5.0 V, V_{EE} = 0





Figure 25. Dual Supply
V_{CC} = 3.0 V, V_{EE} = –3.0 V

PACKAGE DIMENSIONS

SOIC–16
D SUFFIX
CASE 751B–05
ISSUE J




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSIONS A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	9.80	10.00	0.386	0.393
B	3.80	4.00	0.150	0.157
C	1.35	1.75	0.054	0.068
D	0.35	0.49	0.014	0.019
F	0.40	1.25	0.016	0.049
G	1.27 BSC		0.050 BSC	
J	0.19	0.25	0.008	0.009
K	0.10	0.25	0.004	0.009
M	0°	7°	0°	7°
P	5.80	6.20	0.229	0.244
R	0.25	0.50	0.010	0.019

PACKAGE DIMENSIONS

TSSOP–16
DT SUFFIX
CASE 948F–01
ISSUE O




NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A DOES NOT INCLUDE MOLD FLASH. PROTRUSIONS OR GATE BURRS. MOLD FLASH OR GATE BURRS SHALL NOT EXCEED 0.15 (0.006) PER SIDE.
4. DIMENSION B DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.25 (0.010) PER SIDE.
5. DIMENSION K DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 (0.003) TOTAL IN EXCESS OF THE K DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.
7. DIMENSION A AND B ARE TO BE DETERMINED AT DATUM PLANE –W–.

	MILLIMETERS		INCHES	
DIM	MIN	MAX	MIN	MAX
A	4.90	5.10	0.193	0.200
B	4.30	4.50	0.169	0.177
C	---	1.20	---	0.047
D	0.05	0.15	0.002	0.006
F	0.50	0.75	0.020	0.030
G	0.65 BSC		0.026 BSC	
H	0.18	0.28	0.007	0.011
J	0.09	0.20	0.004	0.008
J1	0.09	0.16	0.004	0.006
K	0.19	0.30	0.007	0.012
K1	0.19	0.25	0.007	0.010
L	6.40 BSC		0.252 BSC	
M	0°	8°	0°	8°

PACKAGE DIMENSIONS

QSOP–16
M SUFFIX
CASE 492–01
ISSUE O



DETAIL E

NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. THE BOTTOM PACKAGE SHALL BE BIGGER THAN THE TOP PACKAGE BY 4 MILS (NOTE: LEAD SIDE ONLY). BOTTOM PACKAGE DIMENSION SHALL FOLLOW THE DIMENSION STATED IN THIS DRAWING.
4. PLASTIC DIMENSIONS DOES NOT INCLUDE MOLD FLASH OR PROTRUSIONS. MOLD FLASH OR PROTRUSIONS SHALL NOT EXCEED 6 MILS PER SIDE.
5. BOTTOM EJECTOR PIN WILL INCLUDE THE COUNTRY OF ORIGIN (COO) AND MOLD CAVITY I.D.

	INCHES		MILLIMETERS	
DIM	MIN	MAX	MIN	MAX
A	0.189	0.196	4.80	4.98
B	0.150	0.157	3.81	3.99
C	0.061	0.068	1.55	1.73
D	0.008	0.012	0.20	0.31
F	0.016	0.035	0.41	0.89
G	0.025 BSC		0.64 BSC	
H	0.008	0.018	0.20	0.46
J	0.0098	0.0075	0.249	0.191
K	0.004	0.010	0.10	0.25
L	0.230	0.244	5.84	6.20
M	0°	8°	0°	8°
N	0°	7°	0°	7°
P	0.007	0.011	0.18	0.28
Q	0.020 DIA		0.51 DIA	
R	0.025	0.035	0.64	0.89
U	0.025	0.035	0.64	0.89
V	0°	8°	0°	8°

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

Literature Fulfillment:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303–675–2175 or 800–344–3860 Toll Free USA/Canada
Fax: 303–675–2176 or 800–344–3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com

N. American Technical Support: 800–282–9855 Toll Free USA/Canada

JAPAN: ON Semiconductor, Japan Customer Focus Center
4–32–1 Nishi–Gotanda, Shinagawa–ku, Tokyo, Japan 141–0031
Phone: 81–3–5740–2700
Email: r14525@onsemi.com

ON Semiconductor Website: http://onsemi.com

For additional information, please contact your local Sales Representative.