


OD6025 5 Volt Series



DC Fans - 5V
60mm x 25mm (2.4" x 1.0")




Frame	PBT, UL94 V-0 Plastic	<u>Operating Temperature</u> -20°C ~ +65°C	
Impeller	PBT, UL94 V-0 Plastic	<u>Storage Temperature</u> -20°C ~ +70°C	
Connection	2x Lead Wires, 24 AWG	<u>Life Expectancy</u> 70,000 Hours (L10 at 40°C)	
Motor	Brushless DC, Auto Cutoff, Auto Restart, Polarity Protected, Electronically Protected	<u>Available Options</u> PWM Speed Control Input Tachometer Output Alarm Output	
Bearing System	Dual Ball Bearings	Weight: 0.14 lbs.	
Dielectric Strength	500VDC/min, <1mA		
Insulation Resistance	≥10MΩ @ 500 VDC		

Part Number	Rated Voltage (Volts DC)	Voltage Range (Volts DC)	Input Power (Watts)	Rated Current (Amps)	Rated Speed (RPM)	Max Airflow (CFM)	Noise Level (dBA)	Max Static Pressure ("H ₂ O)
OD6025-05HB	5	4.5 ~ 5.5	1.6	0.32	3575	25	30.2	0.22
OD6025-05MB	5	4.5 ~ 5.5	1.2	0.24	3180	20	26.4	0.17
OD6025-05LB	5	4.5 ~ 5.5	0.9	0.17	2795	15	21.1	0.14

OD6025 5 Volt Series with Tachometer




DC Fans - 5V
60mm x 25mm (2.4" x 1.0")



Frame	PBT, UL94 V-0 Plastic	<u>Operating Temperature</u> -20°C ~ +65°C	
Impeller	PBT, UL94 V-0 Plastic	<u>Storage Temperature</u> -20°C ~ +70°C	
Connection	3x Lead Wires, 26 AWG	<u>Life Expectancy</u> 70,000 Hours (L10 at 40°C)	
Motor	Brushless DC, Auto Cutoff, Auto Restart, Polarity Protected, Electronically Protected	<u>Installed Options</u> Open Collector Tach Output	
Bearing System	Dual Ball Bearings	<u>Available Options</u> 5V TTL Tachometer Type	
Dielectric Strength	500VDC/min, <1mA	Weight: 0.14 lbs.	
Insulation Resistance	≥10MΩ @ 500 VDC		

Part Number	Rated Voltage (Volts DC)	Voltage Range (Volts DC)	Input Power (Watts)	Rated Current (Amps)	Rated Speed (RPM)	Max Airflow (CFM)	Noise Level (dBA)	Max Static Pressure ("H ₂ O)
OD6025-05HB01A	5	4.5 ~ 5.5	1.6	0.32	3575	25	30.2	0.22
OD6025-05MB01A	5	4.5 ~ 5.5	1.2	0.24	3180	20	26.4	0.17
OD6025-05LB01A	5	4.5 ~ 5.5	0.9	0.17	2795	15	21.1	0.14



Tach Max Pullup Voltage: 5V DC
Tach Max Sink Current: 5mA
Tach Cycles per Rotation: 2