Ordering number : ENN7010

ON Semiconductor®

ON Semiconductor

DATA SHEET

MCH3406 — N-Channel Silicon MOSFET

Ultrahigh-Speed Switching Applications

Features

- Low ON-state resistance.
- Ultrahigh-speed switching.
- 1.8V drive.

Package Dimensions

unit : mm

2167A



Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DSS}		20	V
Gate-to-Source Voltage	V_{GSS}		±10	V
Drain Current (DC)	I_D		3	A
Drain Current (Pulse)	I_{DP}	PW≤10μs, duty cycle≤1%	12	A
Allowable Power Dissipation	P_D	Mounted on a ceramic board (900mm²×0.8mm)	1	W
Channel Temperature	Tch		150	°C
Storage Temperature	Tstg		-55 to +150	°C

Electrical Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=1mA, V_{GS}=0	20			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=20V, V_{GS}=0			1	μA
Gate-to-Source Leakage Current	I_{GSS}	V_{GS}=±8V, V_{DS}=0			±10	μA
Cutoff Voltage	V_{GS}(off)	V_{DS}=10V, I_D=1mA	0.4		1.3	V
Forward Transfer Admittance	|yfs|	V_{DS}=10V, I_D=1.5A	3.9	5.6		S
Static Drain-to-Source On-State Resistance	R_{DS}(on)1	I_D=1.5A, V_{GS}=4V		48	63	mΩ
	R_{DS}(on)2	I_D=1A, V_{GS}=2.5V		58	82	mΩ
	R_{DS}(on)3	I_D=0.5A, V_{GS}=1.8V		72	110	mΩ

Marking : KF

Continued on next page.

© 2011, SCILLC. All rights reserved.

Continued from preceding page.

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Input Capacitance	Ciss	V_{DS}=10V, f=1MHz		280		pF
Output Capacitance	Coss	V_{DS}=10V, f=1MHz		60		pF
Reverse Transfer Capacitance	Crss	V_{DS}=10V, f=1MHz		38		pF
Turn-ON Delay Time	t_d(on)	See specified Test Circuit		13		ns
Rise Time	t_r	See specified Test Circuit		35		ns
Turn-OFF Delay Time	t_d(off)	See specified Test Circuit		35		ns
Fall Time	t_f	See specified Test Circuit		25		ns
Total Gate Charge	Qg	V_{DS}=10V, V_{GS}=4V, I_D=3A		8.8		nC
Gate-to-Source Charge	Qgs	V_{DS}=10V, V_{GS}=4V, I_D=3A		0.85		nC
Gate-to-Drain “Miller” Charge	Qgd	V_{DS}=10V, V_{GS}=4V, I_D=3A		0.85		nC
Diode Forward Voltage	V_{SD}	I_S=3A, V_{GS}=0		0.82	1.2	V

Switching Time Test Circuit












|yfs| – ID
VDS=10V
Ta= –25°C
25°C
75°C
Forward Transfer Admittance, |yfs| – S
Drain Current, ID – A
IT03494


IF – VSD
VGS=0
Ta=75°C
25°C
–25°C
Forward Current, IF – A
Diode Forward Voltage, VSD – V
IT03495


SW Time – ID
VDD=10V
VGS=4V
td(off)
tr
tf
td(on)
Switching Time, SW Time – ns
Drain Current, ID – A
IT03496


Ciss, Coss, Crss – VDS
f=1MHz
Ciss
Coss
Crss
Ciss, Coss, Crss – pF
Drain-to-Source Voltage, VDS – V
IT03497


VGS – Qg
VDS=10V
ID=3A
Gate-to-Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT03498


A S O
IDP=12A
<10μs
100μs
1ms
10ms
100ms
DC operation
ID=3A
Operation in this
area is limited by RDS(on).
Ta=25°C
Single pulse
Mounted on a ceramic board(900mm²×0.8mm)
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT03499


PD – Ta
Mounted on a ceramic board(900mm²×0.8mm)
Allowable Power Dissipation, PD – W
Ambient Temperature, Ta – °C
IT03500

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. SCILLC strives to supply high-quality high-reliability products and recommends adopting safety measures when designing equipment to avoid accidents or malfunctions. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals," must be validated for each customer application by customer's technical experts. SCILLC shall not be held liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affi liates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affi rmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada.
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website:www.onsemi.com

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative