
FAIRCHILD
SEMICONDUCTOR™

SLOTTED OPTICAL SWITCH

OPB866T51/OPB866T55

PACKAGE DIMENSIONS



ST2166

NOTES:
1. DIMENSIONS ARE IN INCHES (mm).
2. TOLERANCE IS ±.010 (.25) UNLESS OTHERWISE SPECIFIED.
3. NUMBER INDICATES APERTURE SIZE. (5=.050", 1=.010")

APERTURE OPTIONS:

	LED	PHOTOTRANSISTOR
OPB866T51	.050	.010
OPB866T55	.050	.050

DESCRIPTION

The OPB866T series of switches is designed to allow the user maximum flexibility in applications. Each switch consists of an infrared emitting diode facing an NPN phototransistor across a .125" (3.18 mm) gap. A unique housing design provides a smooth external surface to prevent dust build-up while molded internal apertures give precise positioning and also provide protection from ambient light interference.

FEATURES

- Fully enclosed design allows dust and ambient light protection.
- Lead spacing at .220".
- .050" and .010" aperture options.
- PCB mountable.

FAIRCHILD
SEMICONDUCTOR™

SLOTTED OPTICAL SWITCH

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C Unless Otherwise Specified)

Storage Temperature ..... −40°C to + 85°C
Operating Temperature ..... −40°C to + 85°C
Soldering:
Lead Temperature (Iron) ..... 240°C for 5 sec. [2,3,4]
Lead Temperature (Flow) ..... 260°C for 10 sec. [2,3]

INPUT DIODE
Continuous Forward Current ..... 50 mA
Reverse Voltage ..... 5.0 Volts
Power Dissipation ..... 100 mW[1]

OUTPUT TRANSISTOR
Collector-Emitter Voltage ..... 30.0 Volts
Emitter-Collector Voltage ..... 5.0 Volts
Power Dissipation ..... 100 mW[1]

ELECTRICAL CHARACTERISTICS (T_A = 25°C Unless Otherwise Specified)

PARAMETER	SYMBOL	MIN.	MAX.	UNITS	TEST CONDITIONS
INPUT DIODE					
Forward Voltage	V_F	—	1.70	V	I_F = 20 mA
Reverse Leakage Current	I_R	—	100	μA	V_R = 2.0 V
OUTPUT TRANSISTOR					
Emitter-Collector Breakdown	BV_{ECO}	5	—	V	I_E = 100 μA, Ee = 0
Collector-Emitter Breakdown	BV_{CEO}	30	—	V	I_C = 1.0 mA, Ee = 0
Collector-Emitter Leakage	I_{CEO}	—	100	nA	V_{CE} = 10.0 V, Ee = 0
COUPLED					
On-State Collector Current					
OPB866T51	$I_{C(ON)}$	1.0	—	mA	I_F = 10 mA, V_{CE} = 5 V
OPB866T55	$I_{C(ON)}$	1.0	—	mA	I_F = 10 mA, V_{CE} = 5 V
Saturation Voltage	$V_{CE(SAT)}$	—	0.40	V	I_F = 10 mA, I_C = 800 μA

NOTES

1. *Derate power dissipation linearly 1.67 mW/°C above 25°C.*
2. *RMA flux is recommended.*
3. *Methanol or Isopropyl alcohols are recommended as cleaning agents.*
4. *Soldering iron tip 1/16" (1.6 mm) from housing.*

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

© 2000 Fairchild Semiconductor Corporation