High Voltage Isolator

OPI1268



Features:

- TTL compatible output
- 16 kV dc isolation
- 2 Mbit/s
- t_{PHL}-t_{PLH} ≤ 500 ns
- Creepage path: 0.970" (24.64 mm)
- Air path: 0.970" (24.64 mm)
- UL recognized file No. E58730

Description:


The **OPI1268** is a high voltage isolator with a digital output that is capable of high speed data transmission. The input of the OPI1268 consists of a high-efficiency GaAlAs LED with a peak wavelength of 850 nm, which is optically coupled to the output optical IC. A photodiode in the output IC detects the incoming modulated light and converts it to a proportionate current. This current is fed into a high-gain linear amplifier which is temperature, current and voltage compensated. The result is a highly stable digital output with an open collector inverter configuration. This device produces DC and AC voltage isolation between the input and output circuitry while providing TTL signal integrity.


Applications:

- Data transmission for High voltage isolation
- PCBoard power system isolation
- Industrial equipment power isolation
- Medical equipment power isolation
- Office equipment

Ordering Information							
Part Number	**LED Peak Wavelength**	**Sensor Photologic®**	**Isolation Voltage kVDC**	**t_{PLH} / t_{PHL}** Max (ns)	**I_F (mA)** Typ / Max	**V_{CE} (V)** Max	**Lead Length**
OPI1268	**850 nm**	**Open Collector**	**16**	**100 / 200**	**10 / 50**	**18**	**0.14"**

Pin	Function
1	Cathode
2	Anode
3	V_{CC}
4	Output
5	Ground





Pb-Free
(RoHS)

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com

Electrical Specifications

Absolute Maximum Ratings (T_A = 25° C unless otherwise noted)

Storage Temperature	-40° C to +100° C
Operating Temperature	-40° C to +100° C
Input-to-Output Isolation Voltage[2]	16 kVDC
Lead Soldering Temperature (1/16" (1.6 mm) from case for 5 seconds with soldering iron)[3]	260° C
Input Diode	
Continuous Forward Current	30 mA
Peak Forward current (1 µs pulse width, 300 pps)	3.0 A
Reverse Voltage	3.0 V
Power Dissipation[1]	100 mW
Output IC	
Maximum Supply Voltage	7 V
Power Dissipation[4]	100 mW
Maximum Output Voltage	18 V
Maximum Output Current	25 mA

Electrical Characteristics (T_A = 0° C to 70° C unless otherwise noted)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Input Diode						
V_F	Forward Voltage	-	1.3	1.6	V	I_F = 20 mA
I_R	Reverse Current	-	0.1	100	µA	V_R = 2.0 V
Output IC (V_{CC} = 4.5 V to 5.25 V) (See OPL550 for additional information—for reference only.)						
I_{OH}	High Level Output Current	-	0.20	10	µA	I_F = 0.0 mA, V_{OH} = 18.0 V, V_{CC} = 5.25 V
V_{OL}	Low Level Output Voltage	-	0.44	0.55	V	I_F = 10.0 mA, I_{OL} = 8.0 mA, V_{CC} = 4.5 V
I_{CCH}	High Level Supply Current	-	4.2	7	mA	I_F = 0, V_{CC} = 5.25 V
I_{CCL}	Low Level Supply Current	-	6.7	10		I_F = 10.0 mA, V_{CC} = 5.25 V
Coupled Characteristics (V_{CC} = 5 V)						
C_{IO}	Coupling Capacitance	-	-	2	pF	Input and output leads shorted.
t_{PLH}	Propagation Delay to Low Output Level	-	-	200	ns	V_{CC} = 5 V, I_F = 30 mA, R_L = 560 Ω
t_{PHL}	Propagation Delay to High Output Level	-	-	100		
I_{ISO}	Isolation Leakage Current[5]	-	-	20	µA	VISO = 19.2 kV dc
I_F+	LED Positive Going Threshold Current	0.8	1.7	5.0	mA	V_{CC} = 5 V, I_{OL} = 8.0 mA


Notes:
(1) Derate LED linearly 1.33 mW/°C above 25° C.
(2) UL recognition is for 16 kV dc for one minute.
(3) RMA flux is recommended.
(4) Derate linearly 1.33 mW/°C above 25° C.
(5) Measured with input leads shorted together and output leads shorted together in air with a maximum relative humidity of 50 %.

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.


© TT electronics plc

TT Electronics | OPTEK Technology
2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200
www.ttelectronics.com | sensors@ttelectronics.com


IF(+) vs Ta




$V_{(out)}$ vs I_F




Vol vs Ambient Temperature




I_{OH} vs. Ambient Temperature



Supply Current vs I_{CCH} and I_{CCL} vs Ambient temperature



Variable Diode Forward Current (I_F) vs Propagation Delay Time - (t_{PLH}, t_{PHL})



General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc


TT Electronics | OPTEK Technology

2900 E. Plano Pkwy, Plano, TX 75074 | Ph: +1 972 323 2200


www.ttelectronics.com | sensors@ttelectronics.com

dV/dT

OPI1268 dV/dT Emitter



OPI1268 dV/dT Sensor



General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc