



Transfer or duplication of this doucument as well as the utilisation or communication of its content are not permitted unless express consen is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.









RECOMMENDED PCB LAYOUT

Technical data

1.Nominal voltage: 300V/15A
PITCH:5.0mm

2.Insulation Withstanding Voltage:
AC 1600V/MIN

3.Insulation Resistance:
1000MΩ or more at DC500V

4.Operating temperature range:-40°C~115°C

5.Soldering temperature range:250°C±10°C/5sec

6.Safety approval:

7.RoHS Compliance

8.Undimensioned Tolerances:

Dim.L=Px5.0
Dim.B=(P-1)x5.0
P= number of poles 2-24P

	Dim B	Dim L
0~30mm	±0.15	±0.20
over 30mm~60mm	±0.20	±0.25
over 60mm~90mm	±0.25	±0.30
over 90mm	±0.30	±0.40

Part No.:

OSTOQXX7051

No. of Poles
02 2 Poles
03 3 Poles
... ...
24 24 Poles

COLOR
0: Black
2: Red
3: Orange
4: Yellow
5: Green (Standard)
6: Blue
8: Grey

Nonstandard colors
Mins could apply

ITEM	NAME OF PART	MATERIAL	NOTES	Q"TY
2	PIN	BRASS	TIN PLATED	P
1	BODY	PA66 UL94V-0		1

DWG.	Marvin Zhang	DATE	2016.05.21	UNITS:	MM	SHEET: 1 OF 1	Tolerance
CHK.	Marvin Zhang	DATE	2016.05.21	SCALE:	NONE 4:1 (:)	REV.: A	X. ±0.50
APP.		DATE		TITLE:	OSTOQ 5.0 Series Open type Right-angle (90D)		X.X ±0.30
							X.XX ±0.10
							X° ±1°
				PART NO.	OSTOQXX7051		
				DWG NO.	OSTOQXX7051.dwg		

ON-SHORE TECHNOLOGY, INC.

SIGN	DESCRIPTION	CHK.	DATE
⚠			