


Transfer or duplication of this doucument as well as the utilisation or communication of its content are not permitted unless express consen is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.





N=Number of contacts



Technical Data:

Electrical

- Pitch: 7.62mm
- Voltage rating: 300V
- Current rating: 16 Amps
- Contact resistance: 20mΩ(max)
- Withstanding Voltage: 2500VAC(1min) Test time=60sec/1pcs
- Wire range: 12-26AWG
- Wire strip length: 7-8mm

Mechanical:

- Torque: 5.0kgf.cm/M3
- Operating temperature: -40°C to +105°C
- Safety approval:
- RoHS Compliance

Part No.:

OSTTJXX0150

No. of Poles		COLOR
02	2 Poles	0: Black
03	3 Poles	2: Red
...	...	3: Orange
24	24 Poles	4: Yellow
		5: Green (Standard)
		6: Blue
		8: Grey

Nonstandard colors
Mins could apply

ITEM	NAME OF PART	MATERIAL	NOTES	Q"TY
5	Screw	Steel / M3.0	Cr3+ plated	1×N
4	Contact	Copper Alloy	Ni plated	1×N
3	Wire guard	Copper Alloy	Tin plated	1×N
2	Cover	PA66 UL94V-0		1
1	Body	PA66 UL94V-0		1

DWG.		DATE		UNITS:	MM	SHEET: 1 OF 1	Tolerance
CHK.		DATE		SCALE:	NONE 3:1 (:)	REV.: A	X. ±0.50
APP.		DATE		TITLE:	OSTTJ SERIES 7.62MM		X.X ±0.30
							X.XX ±0.10
				PART NO.	OSTTJXX0150		X° ±1°
				DWG NO.	OSTTJXX0150.DWG		

REV	SIGN	DESCRIPTION	CHK.	DATE
	⚠			

ON-SHORE TECHNOLOGY, INC.