Heyco® Open/Closed Bushings

Mounting Hole Diameter Range: .375″ (9,5 mm) to 2.500″ (63,5 mm)

Small Packs Available





MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PACKAGING		PART DIMENSIONS					
				BULK (Std)	SMALL PACK*	A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	Black				in.	mm.	in.	mm.	in.	mm.
Multiple Locking Steps for Panel Thickness up to .125″ (3,2 mm)											
.375	9,5	**2865**	OCB 375	20000	100	.27	6,7	.42	10,7	.39	9,9
.437	11,1	**2867**	OCB 437	15000	100	.33	8,4	.50	12,7	.41	10,3
.500	12,7	**2871**	OCB 500	20000	100	.31	7,9	.56	14,3		
.512	13,0	**2875**	OCB 512	20000	100	.35	9,0	.59	14,9		
.562	14,3	**2869**	OCB 562	15000	100	.39	9,9	.64	16,3		
.625	15,9	**2872**	OCB 625	8500	100	.45	11,1	.69	17,5		
.650	16,5	**2914**	OCB 650	8500	100	.48	12,3	.73	18,6		
.750	19,1	**2873**	OCB 750	10000	100	.55	14,0	.78	19,8		
.866	22,0	**2917**	OCB 866	7500	100	.68	17,3	.98	24,8		
.875	22,2	**2874**	OCB 875	7500	100	.67	17,0	.92	23,4		
.984	25,0	**2920**	OCB 984	4000	100	.79	20,1	1.04	26,4		
1.000	25,4	**2878**	OCB 1000	4000	50	.80	20,3	1.05	26,6		
1.093	27,8	**2879**	OCB 1093	4000	50	.88	20,6	1.16	29,4		
1.250	31,8	**2881**	OCB 1250	5000	50	1.05	25,8	1.34	34,1		
1.375	34,9	**2882**	OCB 1375	2500	50	1.17	29,8	1.47	37,3		
1.500	38,1	**2883**	OCB 1500	2500	25	1.25	31,8	1.58	40,1	.42	10,7
2.000	50,8	**2900**	OCB 2000	2000	25	1.73	43,9	2.12	53,9		
Multiple Locking Steps for Panel Thickness up to .250″ (6,4 mm)											
2.500	63,5	**2909**	OCB 2.5	500	10	2.00	50,8	2.60	66,0	.72	18,3

Standard color black. Consult Heyco for white and other colors.

*To order Small Packs, please add the suffix -P to Part No., e.g., 2865-P

- **Split design allows side entry** and encirclement of preassembled harnesses, capillary tubes, computer cables, power cords, or other assemblies that have segments larger than the bushing's I.D.
- May also be assembled into holes that already contain cable, wire or other filaments.
- Fingertip pressure snap-locks the bushing into its mounting hole.
- Locking fingers in fractional increments up to the maximum panel thickness.
- Multiple sizes for use in mounting holes from .375″ (9,5 mm) to 2.500″ (63,5 mm).





Heyco® Open/Closed Shorty Bushings

Single Locking Step for Panel Thickness up to .062″ (1,6 mm)

Mounting Hole Diameter Range: 7,0 mm (.276″) 27,0 mm (1.063″)

MOUNTING HOLE DIAMETER		PART NO.	DESCRIPTION	PART DIMENSIONS					
				A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	Black		in.	mm.	in.	mm.	in.	mm.
.276	7,0	**2934**	SOCB 07M	.22	5,6	.35	8,9	.24	6,0
.512	13,0	**2938**	SOCB 13M	.38	9,7	.56	14,2	.25	6,4
.630	16,0	**2941**	SOCB 16M	.52	13,2	.71	18,0		
.748	19,0	**2943**	SOCB 19M	.63	16,0	.83	21,1		
.866	22,0	**2945**	SOCB 22M	.70	17,8	.91	23,1		
.945	24,0	**2947**	SOCB 24M	.82	20,8	1.06	26,9		
1.063	27,0	**2950**	SOCB 27M	.86	21,8	1.11	28,2	.26	6,5

Standard color black. Consult Heyco for white and other colors.

Material	Nylon 6/6
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E15331
	Certified by the Canadian Standards Association File 8919
Flammability Rating	94V-2
Temperature Range	-.4°F (-18°C) to 221°F (105°C)

- **For use in panels .062″ (1,6 mm) and thinner.**
- Lower overall height protrudes less through thin mounting panels; thus Shorty Open/Closed Bushings occupy less "real estate" inside your application.
- **Split design allows side entry** and encirclement of preassembled harnesses, power cords, capillary tubes or other assemblies that have segments larger than the bushing's ID.
- May also be assembled into holes that already contain cable, wire or other filaments.
- Fingertip pressure snap-locks the bushing into its mounting hole.