Important notice

Dear Customer,

On 7 February 2017 the former NXP Standard Product business became a new company with the tradename **Nexperia**. Nexperia is an industry leading supplier of Discrete, Logic and PowerMOS semiconductors with its focus on the automotive, industrial, computing, consumer and wearable application markets

In data sheets and application notes which still contain NXP or Philips Semiconductors references, use the references to Nexperia, as shown below.

Instead of http://www.nxp.com, http://www.philips.com/ or http://www.semiconductors.philips.com/, use **http://www.nexperia.com**

Instead of sales.addresses@www.nxp.com or sales.addresses@www.semiconductors.philips.com, use **salesaddresses@nexperia.com** (email)

Replace the copyright notice at the bottom of each page or elsewhere in the document, depending on the version, as shown below:
- © NXP N.V. (year). All rights reserved or © Koninklijke Philips Electronics N.V. (year). All rights reserved
Should be replaced with:
- **© Nexperia B.V. (year). All rights reserved**.

If you have any questions related to the data sheet, please contact our nearest sales office via e-mail or telephone (details via **salesaddresses@nexperia.com**). Thank you for your cooperation and understanding,

Kind regards,

Team Nexperia

PBLS1503Y; PBLS1503V

15 V PNP BISS loadswitch

Rev. 03 — 24 August 2009 Product data sheet

1. Product profile

1.1 General description

Low V_{CEsat} PNP transistor and NPN resistor-equipped transistor in one package.

Table 1. Product overview

Type number	Package	
	NXP	JEITA
PBLS1503Y	SOT363	SC-88
PBLS1503V	SOT666	-

1.2 Features

- Low V_{CEsat} (BISS) and resistor-equipped transistor in one package
- Low 'threshold' voltage (< 1 V) compared to MOSFET
- Low drive power required
- Space-saving solution
- Reduction of component count

1.3 Applications

- Supply line switches
- Battery charger switches
- High-side switches for LEDs, drivers and backlights
- Portable equipment

1.4 Quick reference data

Table 2. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
TR1; PNP; low V_{CEsat} transistor						
V_{CEO}	collector-emitter voltage	open base	-	-	–15	V
I_C	collector current (DC)		-	-	–500	mA
R_{CEsat}	equivalent on-resistance	I_C = –500 mA; I_B = –50 mA	-	300	500	mΩ
TR2; NPN; resistor-equipped transistor						
V_{CEO}	collector-emitter voltage	open base	-	-	50	V

NXP founded by Philips


Table 2. Quick reference data *…continued*

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_O	output current (DC)		-	-	100	mA
R1	bias resistor 1 (input)		7	10	13	kΩ
R2/R1	bias resistor ratio		0.8	1	1.2	


2. Pinning information

Table 3. Discrete pinning

Pin	Description	Simplified outline	Symbol
1	emitter TR1		
2	base TR1		
3	output (collector) TR2		
4	GND (emitter) TR2		
5	input (base) TR2		
6	collector TR1		



001aab555



sym036

3. Ordering information

Table 4. Ordering information

Type number	Package		
	Name	Description	Version
PBLS1503Y	SC-88	plastic surface mounted package; 6 leads	SOT363
PBLS1503V	-	plastic surface mounted package; 6 leads	SOT666

4. Marking

Table 5. Marking codes

Type number	Marking code[1]
PBLS1503Y	*C3
PBLS1503V	C3

[1] * = -: made in Hong Kong
* = p: made in Hong Kong
* = t: made in Malaysia
* = W: made in China

© NXP B.V. 2009. All rights reserved.

5. Limiting values

Table 6. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
Transistor TR1: PNP						
V_{CBO}	collector-base voltage	open emitter		-	–15	V
V_{CEO}	collector-emitter voltage	open base		-	–15	V
V_{EBO}	emitter-base voltage	open collector		-	–6	V
I_C	collector current (DC)			-	–500	mA
I_{CM}	peak collector current	$t_p \leq 1$ ms; $\delta \leq 0.02$		-	–1	A
I_B	base current (DC)			-	–50	mA
I_{BM}	peak base current	$t_p \leq 1$ ms; $\delta \leq 0.02$		-	–100	mA
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C	[1]	-	200	mW
Transistor TR2: NPN						
V_{CBO}	collector-base voltage	open emitter		-	50	V
V_{CEO}	collector-emitter voltage	open base		-	50	V
V_{EBO}	emitter-base voltage	open collector		-	10	V
V_I	input voltage			-		
	positive			-	+40	V
	negative			-	–10	V
I_O	output current (DC)			-	100	mA
I_{CM}	peak collector current			-	100	mA
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C	[1]	-	200	mW
Per device						
P_{tot}	total power dissipation	$T_{amb} \leq 25$ °C		-	300	mW
T_{stg}	storage temperature			–65	+150	°C
T_j	junction temperature			-	150	°C
T_{amb}	ambient temperature			–65	+150	°C

[1] Device mounted on a FR4 printed-circuit board, single-sided copper, tin-plated and standard footprint.

6. Thermal characteristics

Table 7. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
Per device							
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air					
	SOT363		[1]	-	-	416	K/W
	SOT666		[1][2]	-	-	416	K/W

[1] Device mounted on a FR4 printed-circuit board, single-sided copper, tin-plated and standard footprint.

[2] Reflow soldering is the only recommended soldering method.

© NXP B.V. 2009. All rights reserved.

7. Characteristics


Table 8. Characteristics

T_{amb} = 25 °C unless otherwise specified

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
Transistor TR1: PNP							
I_{CBO}	collector-base cut-off current	V_{CB} = –15 V; I_E = 0 A		-	-	–100	nA
		V_{CB} = –15 V; I_E = 0 A; T_j = 150 °C		-	-	–50	µA
I_{CES}	collector-emitter cut-off current	V_{CE} = –15 V; V_{BE} = 0 V		-	-	–100	nA
I_{EBO}	emitter-base cut-off current	V_{EB} = –5 V; I_C = 0 A		-	-	–100	nA
h_{FE}	DC current gain	V_{CE} = –2 V; I_C = –10 mA		200	-	-	
		V_{CE} = –2 V; I_C = –100 mA	[1]	150	-	-	
		V_{CE} = –2 V; I_C = –500 mA	[1]	90	-	-	
V_{CEsat}	collector-emitter saturation voltage	I_C = –10 mA; I_B = –0.5 mA		-	-	–25	mV
		I_C = –200 mA; I_B = –10 mA		-	-	–150	mV
		I_C = –500 mA; I_B = –50 mA	[1]	-	-	–250	mV
R_{CEsat}	equivalent on-resistance	I_C = –500 mA; I_B = –50 mA	[1]	-	300	500	mΩ
V_{BEsat}	base-emitter saturation voltage	I_C = –500 mA; I_B = –50 mA	[1]	-	-	–1.1	V
V_{BEon}	base-emitter turn-on voltage	V_{CE} = –2 V; I_C = –100 mA	[1]	-	-	–0.9	V
f_T	transition frequency	V_{CE} = –5 V; I_C = –100 mA; f = 100 MHz		100	280	-	MHz
C_c	collector capacitance	V_{CB} = –10 V; I_E = i_e = 0 A; f = 1 MHz		-	-	10	pF
Transistor TR2: NPN							
I_{CBO}	collector-base cut-off current	V_{CB} = 50 V; I_E = 0 A		-	-	100	nA
I_{CEO}	collector-emitter cut-off current	V_{CE} = 30 V; I_B = 0 A		-	-	1	µA
		V_{CE} = 30 V; I_B = 0 A; T_j = 150 °C		-	-	50	µA
I_{EBO}	emitter-base cut-off current	V_{EB} = 5 V; I_C = 0 A		-	-	400	µA
h_{FE}	DC current gain	V_{CE} = 5 V; I_C = 5 mA		30	-	-	
V_{CEsat}	collector-emitter saturation voltage	I_C = 10 mA; I_B = 0.5 mA		-	-	150	mV
$V_{I(off)}$	off-state input voltage	V_{CE} = 5 V; I_C = 100 µA		-	1.1	0.8	V
$V_{I(on)}$	on-state input voltage	V_{CE} = 0.3 V; I_C = 10 mA		2.5	1.8	-	V
R1	bias resistor 1 (input)			7	10	13	kΩ
R2/R1	bias resistor ratio			0.8	1	1.2	
C_c	collector capacitance	V_{CB} = 10 V; I_E = i_e = 0 A; f = 1 MHz		-	-	2.5	pF

[1] Pulse test: $t_p \leq 300$ µs; $\delta \leq 0.02$

© NXP B.V. 2009. All rights reserved.




V_{CE} = −2 V

(1) T_{amb} = 150 °C

(2) T_{amb} = 25 °C

(3) T_{amb} = −55 °C

Fig 1. TR1(PNP): DC current gain as a function of collector current; typical values




I_C/I_B = 20

(1) T_{amb} = 150 °C

(2) T_{amb} = 25 °C

(3) T_{amb} = −55 °C

Fig 2. TR1(PNP): Collector-emitter saturation voltage as a function of collector current; typical values




V_{CE} = −2 V

(1) T_{amb} = −55 °C

(2) T_{amb} = 25 °C

(3) T_{amb} = 150 °C

Fig 3. TR1(PNP): Base-emitter voltage as a function of collector current; typical values



I_C/I_B = 20


(1) T_{amb} = 150 °C

(2) T_{amb} = 25 °C

(3) T_{amb} = −55 °C

Fig 4. TR1(PNP): Base-emitter saturation voltage as a function of collector current; typical values


© NXP B.V. 2009. All rights reserved.



T_{amb} = 25 °C

(1) I_B = – 7.0 mA
(2) I_B = – 6.3 mA
(3) I_B = – 5.6 mA
(4) I_B = – 4.9 mA
(5) I_B = – 4.2 mA
(6) I_B = – 3.5 mA
(7) I_B = – 2.8 mA
(8) I_B = – 2.1 mA
(9) I_B = – 1.4 mA
(10) I_B = – 0.7 mA

Fig 5. TR1(PNP): Collector current as a function of collector-emitter voltage; typical values




I_C/I_B = 20

(1) T_{amb} = –55 °C
(2) T_{amb} = 25 °C
(3) T_{amb} = 150 °C

Fig 6. TR1(PNP): Equivalent on-resistance as a function of collector current; typical values

© NXP B.V. 2009. All rights reserved.




T_{amb} = 25 °C

(1) I_C/I_B = 100

(2) I_C/I_B = 50

(3) I_C/I_B = 10

Fig 7. TR1(PNP): Collector-emitter saturation voltage as a function of collector current; typical values



T_{amb} = 25 °C


(1) I_C/I_B = 100

(2) I_C/I_B = 50

(3) I_C/I_B = 10

Fig 8. TR1(PNP): Equivalent-on resistance as a function of collector current; typical values

© NXP B.V. 2009. All rights reserved.




V_{CE} = 5 V

(1) T_{amb} = 150 °C

(2) T_{amb} = 25 °C

(3) T_{amb} = –40 °C

Fig 9. TR2(NPN): DC current gain as a function of collector current; typical values




I_C/I_B = 20

(1) T_{amb} = 100 °C

(2) T_{amb} = 25 °C

(3) T_{amb} = –40 °C

Fig 10. TR2(NPN): Collector-emitter saturation voltage as a function of collector current; typical values




V_{CE} = 0.3 V

(1) T_{amb} = –40 °C

(2) T_{amb} = 25 °C

(3) T_{amb} = 100 °C

Fig 11. TR2(NPN): On-state input voltage as a function of collector current; typical values



V_{CE} = 5 V

(1) T_{amb} = –40 °C

(2) T_{amb} = 25 °C


(3) T_{amb} = 100 °C

Fig 12. TR2(NPN): Off-state input voltage as a function of collector current; typical values

© NXP B.V. 2009. All rights reserved.

8. Package outline

Plastic surface-mounted package; 6 leads **SOT363**



DIMENSIONS (mm are the original dimensions)


UNIT	A	A_1 max	b_p	c	D	E	e	e_1	H_E	L_p	Q	v	w	y
mm	1.1 0.8	0.1	0.30 0.20	0.25 0.10	2.2 1.8	1.35 1.15	1.3	0.65	2.2 2.0	0.45 0.15	0.25 0.15	0.2	0.2	0.1

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT363			SC-88			~~04-11-08~~ 06-03-16

Fig 13. Package outline SOT363 (SC-88)

© NXP B.V. 2009. All rights reserved.

Plastic surface-mounted package; 6 leads **SOT666**



DIMENSIONS (mm are the original dimensions)

UNIT	A	b_p	c	D	E	e	e_1	H_E	L_p	w	y
mm	0.6 0.5	0.27 0.17	0.18 0.08	1.7 1.5	1.3 1.1	1.0	0.5	1.7 1.5	0.3 0.1	0.1	0.1

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	JEITA			
SOT666						~~04-11-08~~ 06-03-16

Fig 14. Package outline SOT666

© NXP B.V. 2009. All rights reserved.

9. Packing information

Table 9. Packing methods

The indicated -xxx are the last three digits of the 12NC ordering code.[1]

Type number	Package	Description		Packing quantity		
				3000	4000	10000
PBLS1503Y	SOT363	4 mm pitch, 8 mm tape and reel; T1	[2]	-115	-	–135
		4 mm pitch, 8 mm tape and reel; T2	[3]	-125	-	-165
PBLS1503V	SOT666	4 mm pitch, 8 mm tape and reel		-	-115	-

[1] For further information and the availability of packing methods, see Section 12.

[2] T1: normal taping

[3] T2: reverse taping

© NXP B.V. 2009. All rights reserved.

10. Revision history

Table 10. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
PBLS1503Y_PBLS1503V_3	20090824	Product data sheet	-	PBLS1503Y_PBLS1503V_2
Modifications:	• This data sheet was changed to reflect the new company name NXP Semiconductors, including new legal definitions and disclaimers. No changes were made to the technical content. • Table 3 “Discrete pinning”: amended • Figure 13 “Package outline SOT363 (SC-88)”: updated • Figure 14 “Package outline SOT666”: updated			
PBLS1503Y_PBLS1503V_2	20041125	Product data sheet	-	PBLS1503V_1
PBLS1503V_1	20031107	Product specification	-	-

© NXP B.V. 2009. All rights reserved.

11. Legal information

11.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.nxp.com.

11.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local NXP Semiconductors sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

11.3 Disclaimers

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at http://www.nxp.com/profile/terms, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

11.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

12. Contact information

For more information, please visit: **http://www.nxp.com**

For sales office addresses, please send an email to: **salesaddresses@nxp.com**

© NXP B.V. 2009. All rights reserved.

13. Contents

1	**Product profile**	**1**
1.1	General description	1
1.2	Features	1
1.3	Applications	1
1.4	Quick reference data	1
2	**Pinning information**	**2**
3	**Ordering information**	**2**
4	**Marking**	**2**
5	**Limiting values**	**3**
6	**Thermal characteristics**	**3**
7	**Characteristics**	**4**
8	**Package outline**	**9**
9	**Packing information**	**11**
10	**Revision history**	**12**
11	**Legal information**	**13**
11.1	Data sheet status	13
11.2	Definitions	13
11.3	Disclaimers	13
11.4	Trademarks	13
12	**Contact information**	**13**
13	**Contents**	**14**

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2009. All rights reserved.

For more information, please visit: http://www.nxp.com
For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 24 August 2009

Document identifier: PBLS1503Y_PBLS1503V_3

founded by

PHILIPS