PASTERNACK
an INFINITE brand

2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector



Antennas Technical Data Sheet PE51RD1032

Features

- 0 to 4 dBi Gain
- Tilt and Swivel Design
- SMA Male Connector
- Blade Design

Applications

- Infotainment Systems, Routers, WiFi Hotspots, HD Video Transmission, Gateways, Dash Cameras, Public Transportation
- Connected Cars or Self-Driving Cars, Fleet Management, Logistics
- 4G & 5G Networks
- 600, 700, 800, 850, 900, 1800, 1900, 2100, 2600, 3500, 5800 MHz Bands
- IoT, Cellular, Zigbee, Z-Wave, Bluetooth, CBRS, WiFi, C-Band, UNII

Description

The 5G Pasternack PE51RD1032 Rubber Duck Antenna is a high performance omnidirectional “rubber-duck” antenna. Designed for 617 MHz to 5800 MHz bands, it is in stock and can ship same day. It features a tilt-and-swivel SMA-Plug (male) connector, allowing them to be used at a right angle, vertically or any angle in-between. It is a coaxial sleeve design with an omni-directional pattern. The PE51RD1032 is ideally suited 4G, 5G, LTE, CBRS, UNII bands.

The Pasternack high performance rubber-duck PE51RD1032 is a flexible antenna providing broad coverage and 1-4 dBi gain. This SMA male rubber duck is suitable for commercial radios in public and private 5G and Cellular networks that are equipped with SMA female connectors. Pasternack’s PE51RD1032 from Pasternack supports 600, 700, 800, 850, 900, 1800, 2100, 2400, 2600, 3500, 5800 MHz bands.

This 5G 617 MHz to 5850 MHz rubber duck antenna with a SMA male connector just like the other RF components from Pasternack is in stock and ships the same day. Contact our knowledgeable and friendly technical support and sales staff for your answers on any Pasternack products.

Configuration

Design	Portable
Band Type	Multi
Radiation Pattern	Omni Directional
Wavelength	1/2
Polarization	Vertical
Connector Type	SMA Male

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	617		5.85	MHz
Input VSWR			3.5:1	
Impedance		50		Ohms
Gain	1	2		dBi

Specifications by Band

Description	Band 1	Band 2	Band 3	Band 4	Band 5	Units
Range	617-960	1,427-2,700	3,300-5,850			MHz

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector PE51RD1032

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved

PASTERNACK
an INFINITE brand

2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector



Antennas Technical Data Sheet PE51RD1032

Gain	1	2	4	dBi
VSWR Max	3:1	3.5:1	3.5:1	

Mechanical Specifications

Radome Material	ABS
Width	0.79 in [20.07 mm]
Height	5.33 in [135.38 mm]

Environmental Specifications

Temperature

Operating Range	-20 to +65 deg C
Storage Range	-20 to +65 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector PE51RD1032

URL: https://www.pasternack.com/multi-antenna-617-mhz-5.85-ghz-2-dbi-gain-sma-pe51rd1032-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

© 2020 Pasternack Enterprises All Rights Reserved

PE51RD1032 CAD Drawing

2 dBi MultiBand Rubber Duck Portable Antenna 617-5850 MHz SMA Connector

REVISIONS

REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	10/08/2020	KHIETPAS



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [ ] ARE MILLIMETERS

TOLERANCES:

.X = ± .2 [5.08] | FRACTIONS ± 1/32
.XX = ± .02 [.51] | ANGLES ± 1°
.XXX = ± .005 [.13]

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305] = +1 [25] / -0
12 [305] < L ≤ 60 [1524] = +2 [51] / -0
60 [1524] < L ≤ 120 [3048] = +4 [102] / -0
120 [3048] < L ≤ 300 [7620] = +6 [152] / -0
300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

PASTERNACK an INFINITE brand

Pasternack Enterprises, Inc.
P.O.Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNACK CORPORATION ALL RIGHTS RESERVED.

SIZE	CAGE CODE	DRAWN BY	ITEM NO.	REV
A	53919	BPUCHASKI	PE51RD1032	A

SHEET 1 OF 1

SCALE N/A

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

T-Rev.D

© 2020 Pasternack Enterprises All Rights Reserved