DATA SHEET

74F125, 74F126
Quad buffers (3-State)

Product specification
IC15 Data Handbook

1989 March 28

Philips
Semiconductors



PHILIPS

Quad buffers (3-State) 74F125, 74F126

FEATURE

- High impedance NPN base inputs for reduced loading (20μA in High and Low states)

TYPE	TYPICAL PROPAGATION DELAY	TYPICAL SUPPLY CURRENT (TOTAL)
74F125	5.0ns	23mA
74F126	5.0ns	26mA

ORDERING INFORMATION


DESCRIPTION	COMMERCIAL RANGE V_{CC} = 5V ±10%, T_{amb} = 0°C to +70°C	PKG DWG #
14-pin plastic DIP	N74F125N, N74F126N	SOT27-1
14-pin plastic SO	N74F125D, N74F126D	SOT108-1


INPUT AND OUTPUT LOADING AND FAN OUT TABLE

PINS	DESCRIPTION	74F (U.L.) HIGH/LOW	LOAD VALUE HIGH/LOW
D0–D3	Data inputs	1.0/0.033	20μA/20μA
$\overline{OE}0$–$\overline{OE}3$	Output Enable inputs (active Low), 74F125	1.0/0.033	20μA/20μA
OE0–OE3	Output Enable inputs (active High), 74F126	1.0/0.033	20μA/20μA
Q0–Q3	Data outputs	750/106.7	15mA/64mA


NOTE: One (1.0) FAST unit load is defined as: 20μA in the High state and 0.6mA in the Low state.


PIN CONFIGURATIONS







LOGIC SYMBOLS







IEC/IEEE SYMBOLS





LOGIC DIAGRAMS





FUNCTION TABLE, 74F125

I NPUTS		OUTPUT
$\overline{OE}n$	Dn	Qn
L	L	L
L	H	H
H	X	Z

FUNCTION TABLE, 74F126

I NPUTS		OUTPUT
OEn	Dn	Qn
H	L	L
H	H	H
L	X	Z

NOTES TO THE FUNCTION TABLES:
H = High voltage level
L = Low voltage level
X = Don't care
Z = High impedance "off" state

ABSOLUTE MAXIMUM RATINGS

(Operation beyond the limit set forth in this table may impair the useful life of the device.
Unless otherwise noted these limits are over the operating free-air temperature range.)

SYMBOL	PARAMETER	RATING	UNIT
V_{CC}	Supply voltage	–0.5 to +7.0	V
V_{IN}	Input voltage	–0.5 to +7.0	V
I_{IN}	Input current	–30 to +5	mA
V_{OUT}	Voltage applied to output in High output state	–0.5 to V_{CC}	V
I_{OUT}	Current applied to output in Low output state	128	mA
T_{amb}	Operating free-air temperature range	0 to +70	°C
T_{stg}	Storage temperature range	–65 to +150	°C

RECOMMENDED OPERATING CONDITIONS

SYMBOL	PARAMETER	LIMITS			UNIT
		MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5.0	5.5	V
V_{IH}	High-level input voltage	2.0			V
V_{IL}	Low-level input voltage			0.8	V
I_{IK}	Input clamp current			–18	mA
I_{OH}	High-level output current			–15	mA
I_{OL}	Low-level output current			64	mA
T_{amb}	Operating free air temperature range	0		+70	°C

DC ELECTRICAL CHARACTERISTICS

(Over recommended operating free-air temperature range unless otherwise noted.)

SYMBOL	PARAMETER			TEST CONDITIONS[1]			LIMITS			UNIT
							MIN	TYP[2]	MAX	
V_{OH}	High-level output voltage			V_{CC} = MIN, V_{IL} = MAX, V_{IH} = MIN	I_{OH}=–3mA	±10%V_{CC}	2.4			V
						±5%V_{CC}	2.7	3.3		V
					I_{OH}=–15mA	±10%V_{CC}	2.0			V
						±5%V_{CC}	2.0			V
V_{OL}	Low-level output voltage			V_{CC} = MIN, V_{IL} = MAX, V_{IH} = MIN	I_{OH}= MAX	±10%V_{CC}			0.55	V
						±5%V_{CC}		0.42	0.55	V
V_{IK}	Input clamp voltage			V_{CC} = MIN, I_I = I_{IK}				–0.73	–1.2	V
I_I	Input current at maximum input voltage			V_{CC} = 0.0V, V_I = 7.0V					100	µA
I_{IH}	High-level input current			V_{CC} = MAX, V_I = 2.7V					20	µA
I_{IL}	Low-level input current			V_{CC} = MAX, V_I = 0.5V					–20	µA
I_{OZH}	Off-state output current, High-level voltage applied			V_{CC} = MAX, V_O = 2.7V					50	µA
I_{OZL}	Off-state output current, Low-level voltage applied			V_{CC} = MAX, V_O = 0.5V					–50	µA
I_{OS}	Short circuit output current[3]			V_{CC} = MAX			–100		–225	mA
I_{CC}	Supply current (total)	74F125	I_{CCH}	V_{CC} = MAX	$\overline{OE}$n = GND, Dn = 4.5V			17	24	mA
			I_{CCL}		$\overline{OE}$n = Dn = GND			28	40	mA
			I_{CCZ}		$\overline{OE}$n = Dn = 4.5V			25	35	mA
		74F126	I_{CCH}	V_{CC} = MAX	OEn = Dn = 4.5V			20	30	mA
			I_{CCL}		OEn = 4.5V, Dn = GND			32	48	mA
			I_{CCZ}		OEn = GND, Dn = 4.5V			26	39	mA

NOTES:


1. For conditions shown as MIN or MAX, use the appropriate value specified under recommended operating conditions for the applicable type.
2. All typical values are at V_{CC} = 5V, T_{amb} = 25°C.
3. Not more than one output should be shorted at a time. For testing I_{OS}, the use of high-speed test apparatus and/or sample-and-hold techniques are preferable in order to minimize internal heating and more accurately reflect operational values. Otherwise, prolonged shorting of a High output may raise the chip temperature well above normal and thereby cause invalid readings in other parameter tests. In any sequence of parameter tests, I_{OS} tests should be performed last.

AC ELECTRICAL CHARACTERISTICS


SYMBOL	PARAMETER		TEST CONDITION	LIMITS					UNIT
				V_{CC} = +5.0V T_{amb} = +25°C C_L = 50pF, R_L = 500Ω			V_{CC} = +5.0V ± 10% T_{amb} = 0°C to +70°C C_L = 50pF, R_L = 500Ω		
				MIN	TYP	MAX	MIN	MAX	
t_{PLH} t_{PHL}	Propagation delay Dn to Qn	74F125	Waveform 1	2.0 3.0	4.0 5.5	6.0 7.5	2.0 3.0	6.5 8.0	ns
t_{PZH} t_{PZL}	Output Enable time to High or Low level		Waveform 2 Waveform 3	3.5 4.0	5.5 6.0	7.5 8.0	3.5 4.0	8.5 9.0	ns
t_{PHZ} t_{PLZ}	Output Disable time from High or Low level		Waveform 2 Waveform 3	1.5 1.5	3.5 3.5	5.0 5.5	1.5 1.5	6.0 6.0	ns
t_{PLH} t_{PHL}	Propagation delay Dn to Qn	74F126	Waveform 1	2.0 3.0	4.0 5.5	6.5 8.0	2.0 3.0	7.0 8.5	ns
t_{PZH} t_{PZL}	Output Enable time to High or Low level		Waveform 2 Waveform 3	4.0 4.0	6.0 6.0	7.5 8.0	3.5 3.5	8.5 8.5	ns
t_{PHZ} t_{PLZ}	Output Disable time from High or Low level		Waveform 2 Waveform 3	2.0 3.0	4.5 5.5	6.5 7.5	2.0 3.0	7.5 8.0	ns

AC WAVEFORMS


For all waveforms, V_M = 1.5V.



Waveform 1. Propagation Delay for Input to Output




Waveform 3. 3-State Output Enable Time to Low Level and Output Disable Time from Low Level




Waveform 2. 3-State Output Enable Time to High Level and Output Disable Time from High Level

TEST CIRCUIT AND WAVEFORM



Test Circuit for Open Collector Outputs



Input Pulse Definition

SWITCH POSITION

TEST	SWITCH
t_{PLZ}	closed
t_{PZL}	closed
All other	open

DEFINITIONS:

R_L = Load resistor; see AC electrical characteristics for value.


C_L = Load capacitance includes jig and probe capacitance; see AC electrical characteristics for value.

R_T = Termination resistance should be equal to Z_{OUT} of pulse generators.

family	INPUT PULSE REQUIREMENTS					
	amplitude	V_M	rep. rate	t_w	t_{TLH}	t_{THL}
74F	3.0V	1.5V	1MHz	500ns	2.5ns	2.5ns

SF00128

DIP14: plastic dual in-line package; 14 leads (300 mil) **SOT27-1**



DIMENSIONS (inch dimensions are derived from the original mm dimensions)


UNIT	A max.	A_1 min.	A_2 max.	b	b_1	c	D (1)	E (1)	e	e_1	L	M_E	M_H	w	Z (1) max.
mm	4.2	0.51	3.2	1.73 1.13	0.53 0.38	0.36 0.23	19.50 18.55	6.48 6.20	2.54	7.62	3.60 3.05	8.25 7.80	10.0 8.3	0.254	2.2
inches	0.17	0.020	0.13	0.068 0.044	0.021 0.015	0.014 0.009	0.77 0.73	0.26 0.24	0.10	0.30	0.14 0.12	0.32 0.31	0.39 0.33	0.01	0.087


Note

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT27-1	050G04	MO-001AA				~~92-11-17~~ 95-03-11

SO14: plastic small outline package; 14 leads; body width 3.9 mm **SOT108-1**





DIMENSIONS (inch dimensions are derived from the original mm dimensions)

UNIT	A max.	A_1	A_2	A_3	b_p	c	$D^{(1)}$	$E^{(1)}$	e	H_E	L	L_p	Q	v	w	y	$Z^{(1)}$	θ
mm	1.75	0.25 0.10	1.45 1.25	0.25	0.49 0.36	0.25 0.19	8.75 8.55	4.0 3.8	1.27	6.2 5.8	1.05	1.0 0.4	0.7 0.6	0.25	0.25	0.1	0.7 0.3	8^o 0^o
inches	0.069	0.010 0.004	0.057 0.049	0.01	0.019 0.014	0.0100 0.0075	0.35 0.34	0.16 0.15	0.050	0.244 0.228	0.041	0.039 0.016	0.028 0.024	0.01	0.01	0.004	0.028 0.012	

Note

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.

OUTLINE VERSION	REFERENCES				EUROPEAN PROJECTION	ISSUE DATE
	IEC	JEDEC	EIAJ			
SOT108-1	076E06S	MS-012AB				~~95-01-23~~ 97-05-22

NOTES

Data sheet status

Data sheet status	Product status	Definition [1]
Objective specification	Development	This data sheet contains the design target or goal specifications for product development. Specification may change in any manner without notice.
Preliminary specification	Qualification	This data sheet contains preliminary data, and supplementary data will be published at a later date. Philips Semiconductors reserves the right to make chages at any time without notice in order to improve design and supply the best possible product.
Product specification	Production	This data sheet contains final specifications. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product.

[1] Please consult the most recently issued datasheet before initiating or completing a design.

Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Disclaimers

Life support — These products are not designed for use in life support appliances, devices or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

Philips Semiconductors
811 East Arques Avenue
P.O. Box 3409
Sunnyvale, California 94088–3409
Telephone 800-234-7381

© Copyright Philips Electronics North America Corporation 1998
All rights reserved. Printed in U.S.A.

print code Date of release: 10-98

Document order number: 9397-750-05073

Let's make things better.

Philips Semiconductors

PHILIPS