PI74FCT374T/534T/574T
(25Ω Series) PI74FCT2374T/2574T

Fast CMOS Octal D Registers (3-State)

Product Features:

- PI74FCT374/534/574/2374/2574T is pin compatible with bipolar FAST™ Series at a higher speed and lower power consumption
- 25Ω series resistor on all outputs (FCT2XXX only)
- TTL input and output levels
- Low ground bounce outputs
- Extremely low static power
- Hysteresis on all inputs
- Industrial operating temperature range: –40°C to +85°C
- Packages available:
  - 20-pin 173 mil wide plastic TSSOP (L)
  - 20-pin 300 mil wide plastic DIP (P)
  - 20-pin 150 mil wide plastic QSOP (Q)
  - 20-pin 150 mil wide plastic TQSOP (R)
  - 20-pin 300 mil wide plastic SOIC (S)


Product Description:

Pericom Semiconductor's PI74FCT series of logic circuits are produced in the Company's advanced 0.6/0.8 micron CMOS technology, achieving industry leading speed grades. All PI74FCT2XXX devices have a built-in 25 ohm series resistor on all outputs to reduce noise resulting from reflections, thus eliminating the need for an external terminating resistor.


The PI74FCT374T/534T/574T and P174FCT2374T/2574T are 8-bit wide octal registers designed with eight D-type flip-flops with a buffered common clock and buffered 3-state outputs. When output enable ($\overline{OE}$) is LOW, the outputs are enabled. When $\overline{OE}$ is HIGH, the outputs are in the high impedance state. Input data meeting the setup and hold time requirements of the D inputs is transferred to the O outputs on the LOW-to-HIGH transition of the clock input.

Device models available upon request.

PI74FCT374/2374T and PI74FCT574/2574T Logic Block Diagram




PI74FCT534T Logic Block Diagram




PS2016A 03/11/96


PI74FCT374/2374T Product Pin Configuration



PI74FCT534T Product Pin Configuration



PI74FCT574/2574T Product Pin Configuration



Product Pin Description

Pin Name	Description
$\overline{OE}$	Output Enable Input (Active LOW)
CP	Clock Pulse for the register. Enters data on LOW-to-HIGH transition
D0-D7	Data Inputs
O0-O7	3-State Outputs (true)
$\overline{O}$0-$\overline{O}$7	3-State Outputs (inverted)
GND	Ground
VCC	Power

PI74FCT534T Truth Table[1]

	Inputs			Outputs	Internal
Function	$\overline{OE}$	CP	D_N	$\overline{O}_N$	Q_N
High-Z	H	L	X	Z	NC
	H	H	X	Z	NC
Load Register	L	↑	L	H	L
	L	↑	H	L	H
	H	↑	L	Z	L
	H	↑	H	Z	H

PI74FCT374/574/2374/2574T Truth Table[1]

	Inputs			Outputs	Internal
Function	$\overline{OE}$	CP	D_N	O_N	$\overline{Q}_N$
High-Z	H	L	X	Z	NC
	H	H	X	Z	NC
Load Register	L	↑	L	L	H
	L	↑	H	H	L
	H	↑	L	Z	H
	H	↑	H	Z	L

1. H = High Voltage Level
   L = Low Voltage Level
   X = Don't Care
   Z = High Impedance
   NC = No Change
   ↑= LOW-to-HIGH transition

Maximum Ratings

(Above which the useful life may be impaired. For user guidelines, not tested.)

Storage Temperature	–65°C to +150°C
Ambient Temperature with Power Applied	-40°C to +85°C
Supply Voltage to Ground Potential (Inputs & Vcc Only)	–0.5V to +7.0V
Supply Voltage to Ground Potential (Outputs & D/O Only)	–0.5V to +7.0V
DC Input Voltage	–0.5V to +7.0V
DC Output Current	120 mA
Power Dissipation	0.5W

Note:
Stresses greater than those listed under MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

DC Electrical Characteristics (Over the Operating Range, T_A = –40°C to +85°C, V_{CC} = 5.0V ± 5%)

Parameters	Description	Test Conditions[1]		Min.	Typ[2]	Max.	Units
V_{OH}	Output HIGH Voltage	V_{CC} = Min., V_{IN} = V_{IH} or V_{IL}	I_{OH} = –15.0 mA	2.4	3.0		V
V_{OL}	Output LOW Current	V_{CC} = Min., V_{IN} = V_{IH} or V_{IL}	I_{OL} = 64 mA		0.3	0.55	V
V_{OL}	Output LOW Current	V_{CC} = Min., V_{IN} = V_{IH} or V_{IL}	I_{OL} = 12 mA (25Ω Series)		0.3	0.50	V
V_{IH}	Input HIGH Voltage	Guaranteed Logic HIGH Level		2.0			V
V_{IL}	Input LOW Voltage	Guaranteed Logic LOW Level				0.8	V
I_{IH}	Input HIGH Current	V_{CC} = Max.	V_{IN} = V_{CC}			1	µA
I_{IL}	Input LOW Current	V_{CC} = Max.	V_{IN} = GND			–1	µA
I_{OZH}	High Impedance	V_{CC} = MAX.	V_{OUT} = 2.7V			1	µA
I_{OZL}	Output Current		V_{OUT} = 0.5V			–1	µA
V_{IK}	Clamp Diode Voltage	V_{CC} = Min., I_{IN} = –18 mA			–0.7	–1.2	V
I_{OFF}	Power Down Disable	V_{CC} = GND, V_{OUT} = 4.5V		—	—	100	µA
I_{OS}	Short Circuit Current	V_{CC} = Max.[3], V_{OUT} = GND		–60	–120		mA
V_H	Input Hysteresis				200		mV

Capacitance (T_A = 25°C, f = 1 MHz)

Parameters[4]	Description	Test Conditions	Typ	Max.	Units
C_{IN}	Input Capacitance	V_{IN} = 0V	6	10	pF
C_{OUT}	Output Capacitance	V_{OUT} = 0V	8	12	pF

Notes:
1. For Max. or Min. conditions, use appropriate value specified under Electrical Characteristics for the applicable device type.
2. Typical values are at Vcc = 5.0V, +25°C ambient and maximum loading.
3. Not more than one output should be shorted at one time. Duration of the test should not exceed one second.
4. This parameter is determined by device characterization but is not production tested.

Power Supply Characteristics

Parameters	Description	Test Conditions[1]		Min.	Typ[2]	Max.	Units
I_{CC}	Quiescent Power Supply Current	V_{CC} = Max.	V_{IN} = GND or V_{CC}		0.1	500	µA
ΔI_{CC}	Supply Current per Input @ TTL HIGH	V_{CC} = Max.	V_{IN} = 3.4V[3]		0.5	2.0	mA
I_{CCD}	Supply Current per Input per MHz[4]	V_{CC} = Max., Outputs Open $\overline{OE}$ = GND One Input Toggling 50% Duty Cycle	V_{IN} = V_{CC} V_{IN} = GND		0.15	0.25	mA/ MHz
I_C	Total Power Supply Current[6]	V_{CC} = Max., Outputs Open f_{CP} = 10 MHz 50% Duty Cycle $\overline{OE}$ = GND f_I = 5 MHz One Bit Toggling	V_{IN} = V_{CC} V_{IN} = GND		1.5	3.5[5]	mA
			V_{IN} = 3.4V V_{IN} = GND		2.0	5.5[5]	
		V_{CC} = Max., Outputs Open f_{CP} = 10 MHz 50% Duty Cycle $\overline{OE}$ = GND Eight Bits Toggling f_I = 2.5 MHz 50% Duty Cycle	V_{IN} = V_{CC} V_{IN} = GND		3.8	7.3[5]	
			V_{IN} = 3.4V V_{IN} = GND		6.0	16.3[5]	

Notes:
1. For conditions shown as Max. or Min., use appropriate value specified under Electrical Characteristics for the applicable device.
2. Typical values are at Vcc = 5.0V, +25°C ambient.
3. Per TTL driven input (V_{IN} = 3.4V); all other inputs at Vcc or GND.
4. This parameter is not directly testable, but is derived for use in Total Power Supply Calculations.
5. Values for these conditions are examples of the Icc formula. These limits are guaranteed but not tested.
6. $I_C = I_{QUIESCENT} + I_{INPUTS} + I_{DYNAMIC}$
   $I_C = I_{CC} + \Delta I_{CC} D_H N_T + I_{CCD} (f_{CP}/2 + f_I N_I)$
   I_{CC} = Quiescent Current
   ΔI_{CC} = Power Supply Current for a TTL High Input (V_{IN} = 3.4 V)
   D_H = Duty Cycle for TTL Inputs High
   N_T = Number of TTL Inputs at D_H
   I_{CCD} = Dynamic Current Caused by an Input Transition Pair (HLH or LHL)
   f_{CP} = Clock Frequency for Register Devices (Zero for Non-Register Devices)
   f_I = Input Frequency
   N_I = Number of Inputs at f_I
   All currents are in milliamps and all frequencies are in megahertz.

PI74FCT374/2374T Switching Characteristics over Operating Range

Parameters	Description	Conditions[1]	374T/2374T Com.		374AT/2374AT Com.		374CT/2374CT Com.		374DT Com.		Unit
			Min	Max	Min	Max	Min	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay CP to O_N	C_L = 50 pF R_L = 500Ω	2.0	10.0	2.0	6.5	2.0	5.2	2.0	4.5	ns
t_{PZH} t_{PZL}	Output Enable Time $\overline{OE}$ to O_N		1.5	12.5	1.5	6.5	1.5	5.5	1.5	5.5	ns
t_{PHZ} t_{PLZ}	Output Disable Time[3] $\overline{OE}$ to O_N		1.5	8.0	1.5	5.5	1.5	5.0	1.5	5.0	ns
t_{SU}	Setup Time HIGH or LOW, D_N to CP		2.0	—	2.0	—	2.0	—	2.0	—	ns
t_H	Hold Time HIGH or LOW, D_N to CP		1.5	—	1.5	—	1.5	—	1.0	—	ns
t_W	CP Pulse Width[3] HIGH or LOW		7.0	—	5.0	—	5.0	—	3.0	—	ns

PI74FCT534T Switching Characteristics over Operating Range

Parameters	Description	Conditions[1]	534T Com.		534AT Com.		534CT Com.		534DT Com.		Unit
			Min	Max	Min	Max	Min	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay CP to O_N	C_L = 50 pF R_L = 500Ω	2.0	10.0	2.0	6.5	2.0	5.2	2.0	4.5	ns
t_{PZH} t_{PZL}	Output Enable Time $\overline{OE}$ to O_N		1.5	12.5	1.5	6.5	1.5	5.5	1.5	5.5	ns
t_{PHZ} t_{PLZ}	Output Disable Time[3] $\overline{OE}$ to O_N		1.5	8.0	1.5	5.5	1.5	5.0	1.5	5.0	ns
t_{SU}	Setup Time HIGH or LOW, D_N to CP		2.0	—	2.0	—	2.0	—	2.0	—	ns
t_H	Hold Time HIGH or LOW, D_N to CP		1.5	—	1.5	—	1.5	—	1.0	—	ns
t_W	CP Pulse Width[3] HIGH or LOW		7.0	—	5.0	—	5.0	—	3.0	—	ns

Notes:
1. See test circuit and wave forms.
2. Minimum limits are guaranteed but not tested on Propagation Delays.
3. This parameter is guaranteed but not production tested.

PI74FCT574/2574T Switching Characteristics over Operating Range

Parameters	Description	Conditions[1]	574T/2574T Com.		574AT/2574AT Com.		574CT/2574CT Com.		574DT Com.		Unit
			Min	Max	Min	Max	Min	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay CP to $\overline{O}_N$	C_L = 50 pF R_L = 500Ω	2.0	8.5	2.0	6.5	2.0	5.2	2.0	4.5	ns
t_{PZH} t_{PZL}	Output Enable Time $\overline{OE}$ to O_N		1.5	10.0	1.5	6.5	1.5	5.5	1.5	5.5	ns
t_{PHZ} t_{PLZ}	Output Disable Time[3] $\overline{OE}$ to O_N		1.5	6.5	1.5	5.5	1.5	5.0	1.5	5.0	ns
t_{SU}	Setup Time HIGH or LOW, D_N to CP		2.0	—	2.0	—	2.0	—	2.0	—	ns
t_H	Hold Time HIGH or LOW, D_N to CP		1.5	—	1.5	—	1.5	—	1.0	—	ns
t_W	CP Pulse Width[3] HIGH or LOW		7.0	—	5.0	—	5.0	—	3.0	—	ns

Notes:
1. See test circuit and wave forms.
2. Minimum limits are guaranteed but not tested on Propagation Delays.
3. This parameter is guaranteed but not production tested.