

DATA SHEET

CURRENT SENSOR - LOW TCR

AUTOMOTIVE GRADE

PE Series - Wide Terminal

5%, 1%, 0.5%

sizes 0508/0612/0815/1225

RoHS compliant & Halogen free



SCOPE

This specification describes PE series wide-terminal current sensor - low TCR chip resistors made by metal alloy process.

APPLICATIONS

- Battery pack
- Inverter/converter (DC-DC/AC-DC/DC-AC)
- Consumer electronics
- Laptops
- Automotive
- Alternative Energy

FEATURES

- AEC-Q200 qualified
- Moisture sensitivity level: MSL 1
- Total lead free without RoHS exemption
- High component and equipment reliability
- Ultra low resistance and narrow tolerance suitable for current detection

ORDERING INFORMATION - GLOBAL PART NUMBER

Global part numbers are identified by the series, size, tolerance, packing type, temperature coefficient, taping reel and resistance value.

GLOBAL PART NUMBER

PE XXXX X X X XX XXXX L
(1) (2) (3) (4) (5) (6) (7)

(1) SIZE

0508/0612/0815/1225

(2) TOLERANCE

D = $\pm 0.5\%$ (by request) F = $\pm 1\%$ J = $\pm 5\%$

(3) PACKAGING TYPE

R = Paper taping reel
K = Embossed taping reel

(4) TEMPERATURE COEFFICIENT OF RESISTANCE

E = ± 50 ppm/ $^{\circ}$ C
M = ± 75 ppm/ $^{\circ}$ C
F = ± 100 ppm/ $^{\circ}$ C
L = ± 150 ppm/ $^{\circ}$ C

(5) TAPING REEL

07/7W = 7 inch dia. Reel and specific rated power. Detailed power ratings are shown in the Table 2

(6) RESISTANCE VALUE

0R001 (1 m Ω) ~ 1R (1 Ω)
There are 3~5 digits indicated the resistance value. Letter R is decimal point.

(7) DEFAULT CODE

L = system default code for ordering only

ORDERING EXAMPLE


The ordering code of a PE0508 1W chip resistor, value 0.01 Ω with $\pm 1\%$ tolerance TCR ± 75 ppm/ $^{\circ}$ C, supplied in 7-inch tape reel with 5Kpcs quantity is: PE0508FRM070R01L.

NOTE

1. All our RSMD products are RoHS compliant. "LFP" of the internal 2D reel label mentions "Lead-Free Process"


MARKING

PE0508



3 digits

PE0612/0815/1225



4 digits


The "R" is used as a decimal point; the other 3 digits are significant.

CONSTRUCTION

The resistors are constructed using outstanding TCR level material, which makes Yageo PE resistors excellent for current sensing application.

The composition of the resistive material is adjusted to give the approximate required resistance and is covered with a protective coating. Marking is printed on the top side of the resistor.

Finally, the three external terminations (Cu / Ni / matte Tin) are added, as shown in Fig. 3.

Outlines

YNSC117

Fig. 3 Chip resistor outlines

DIMENSION

Table 1

TYPE	RESISTANCE RANGE	L (mm)	W (mm)	H (mm)	L ₁ (mm)
PE0508	$5\text{ m}\Omega \leq R \leq 1\Omega$	1.25 ± 0.10	2.00 ± 0.10	0.55 ± 0.15	0.35 ± 0.15
	$1\text{ m}\Omega$	1.60 ± 0.20	3.20 ± 0.20	0.60 ± 0.15	0.55 ± 0.20
PE0612	$2\text{ m}\Omega \leq R \leq 4\text{ m}\Omega$	1.60 ± 0.20	3.20 ± 0.20	0.60 ± 0.15	0.40 ± 0.15
	$5\text{ m}\Omega \leq R \leq 1\Omega$	1.60 ± 0.20	3.20 ± 0.20	0.60 ± 0.15	0.30 ± 0.15
PE0815	$1\text{ m}\Omega \leq R \leq 2\text{ m}\Omega$	2.00 ± 0.20	3.70 ± 0.20	0.60 ± 0.15	0.50 ± 0.20
	$3\text{ m}\Omega \leq R \leq 20\text{ m}\Omega$	2.00 ± 0.20	3.70 ± 0.20	0.60 ± 0.15	0.60 ± 0.20
PE1225	$6\text{ m}\Omega \leq R \leq 150\text{ m}\Omega$	3.20 ± 0.20	6.40 ± 0.20	0.60 ± 0.15	0.50 ± 0.25

Note:

1. For relevant physical dimensions, please refer to construction outlines.
2. Please contact with sales offices, distributors and representatives in your region before ordering.

ELECTRICAL CHARACTERISTICS

Table 2

SIZE	POWER RATING ⁽⁴⁾	RESISTANCE RANGE	TOLERANCE ⁽²⁾	TEMPERATURE COEFFICIENT OF RESISTANCE ⁽³⁾
PE0508	1W	$5\text{ m}\Omega \leq R < 75\text{ m}\Omega$ $10\text{ m}\Omega \leq R \leq 1\Omega$	0.5% (By request) $\pm 1\%$ $\pm 5\%$	$\pm 100\text{ ppm}/^\circ\text{C}$ $\pm 50\text{ ppm}/^\circ\text{C}$
	1W	$1\text{ m}\Omega \leq R \leq 1\Omega$	0.5% (By request) $\pm 1\%$ $\pm 5\%$	$1\text{ m}\Omega : \pm 150\text{ ppm}/^\circ\text{C}$ $2\text{ m}\Omega : \pm 100\text{ ppm}/^\circ\text{C}$ $3\text{ m}\Omega \leq R \leq 1\Omega : \pm 50\text{ ppm}/^\circ\text{C}, \pm 75\text{ ppm}/^\circ\text{C}, \pm 100\text{ ppm}/^\circ\text{C}$
PE0612	2W	$1\text{ m}\Omega \leq R \leq 10\text{ m}\Omega$	0.5% (By request) $\pm 1\%$ $\pm 5\%$	$1\text{ m}\Omega : \pm 150\text{ ppm}/^\circ\text{C}$ $2\text{ m}\Omega : \pm 100\text{ ppm}/^\circ\text{C}$ $3\text{ m}\Omega \leq R \leq 10\text{ m}\Omega : \pm 50\text{ ppm}/^\circ\text{C}, \pm 75\text{ ppm}/^\circ\text{C}, \pm 100\text{ ppm}/^\circ\text{C}$
	1/2W	$1\text{ m}\Omega \leq R \leq 20\text{ m}\Omega$	0.5% (By request) $\pm 1\%$ $\pm 5\%$	$1\text{ m}\Omega \leq R \leq 20\text{ m}\Omega : \pm 75\text{ ppm}/^\circ\text{C}, \pm 100\text{ ppm}/^\circ\text{C}$
PE0815	1W	$1\text{ m}\Omega \leq R \leq 20\text{ m}\Omega$	$\pm 1\%$ $\pm 5\%$	$1\text{ m}\Omega \leq R \leq 20\text{ m}\Omega : \pm 75\text{ ppm}/^\circ\text{C}, \pm 100\text{ ppm}/^\circ\text{C}$
PE1225	3/2W	$6\text{ m}\Omega \leq R \leq 150\text{ m}\Omega$	$\pm 1\%$ $\pm 5\%$	$6\text{ m}\Omega \leq R \leq 150\text{ m}\Omega : \pm 50\text{ ppm}/^\circ\text{C}, \pm 75\text{ ppm}/^\circ\text{C}, \pm 100\text{ ppm}/^\circ\text{C}$
	3W	$6\text{ m}\Omega \leq R \leq 150\text{ m}\Omega$	$\pm 1\%$ $\pm 5\%$	$6\text{ m}\Omega \leq R \leq 150\text{ m}\Omega : \pm 50\text{ ppm}/^\circ\text{C}, \pm 75\text{ ppm}/^\circ\text{C}, \pm 100\text{ ppm}/^\circ\text{C}$

Note:

1. Please contact with sales offices, distributors and representatives in your region before ordering
2. Global part number (code 7)
3. Global part number (code 9)
4. Global part number (code 10-11)

FUNCTIONAL DESCRIPTION

OPERATING TEMPERATURE RANGE

PE0612/PE0815 Range: -55°C to +155°C

PE0508/PE1225 Range: -55°C to +170°C

POWER RATING

Standard rated power at 70°C:

PE0508 = 1W

PE0612 = 1W; 2W

PE0815 = 1/2W; 1W

PE1225 = 3/2W; 3W

RATED VOLTAGE

The DC or AC (rms) continuous working voltage corresponding to the rated power is determined by the following formula:

$$V = \sqrt{(P \cdot R)}$$

Where

V = Continuous rated DC or AC (rms) working voltage (V)

P = Rated power (W)

R = Resistance value (Ω)




Fig. 4 Maximum dissipation (P_{max}) in percentage of rated power as a function of the operating ambient temperature (T_{amb})





Fig. 5 Maximum dissipation (P_{max}) in percentage of rated power as a function of the operating ambient temperature (T_{amb})

PACKING STYLE AND PACKAGING QUANTITY**Table 3** Packing style and packaging quantity

PACKING STYLE	REEL DIMENSION	PE0508	PE0612	PE0815	PE1225
Paper taping reel (R)	7" (178 mm)	5,000	---	---	---
Embossed taping reel (K)	7" (178 mm)	---	5000	4000	4000

PAPER TAPE**Fig. 6** Paper Tape**Table 4** Dimensions of paper tape for relevant chip resistors size

SIZE	SYMBOL										Unit: mm
	A ₀	B ₀	W	E	F	P ₀	P ₁	P ₂	ØD ₀	T	
PE0508	1.50±0.15	2.25±0.15	8.00±0.30	1.75±0.10	3.50±0.10	4.00±0.10	4.00±0.10	2.00±0.10	1.50±0.10	0.75±0.15	

EMBOSSED TAPE




Table 5 Dimensions of embossed tape for relevant chip resistors size

SIZE	SYMBOL										Unit: mm
	A_0	B_0	W	E	F	P_0	P_1	P_2	$\varnothing D_0$	D_1	
PE0612	2.20 ± 0.15	3.80 ± 0.15	8.00 ± 0.30	1.75 ± 0.10	3.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	1.50 ± 0.10	1.00 ± 0.10	1.10 ± 0.15
PE0815	2.75 ± 0.15	4.50 ± 0.15	12.00 ± 0.30	1.75 ± 0.10	5.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	1.50 ± 0.10	1.50 ± 0.15	0.90 ± 0.15
PE1225	3.80 ± 0.15	7.00 ± 0.15	12.00 ± 0.30	1.75 ± 0.10	5.50 ± 0.10	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.10	1.50 ± 0.10	1.60 ± 0.10	1.10 ± 0.15

REEL SPECIFICATION




Table 6 Dimensions of reel specification for relevant chip resistors size

SIZE	SYMBOL	Unit: mm					
	8 mm TAPE WIDE	A	N	C	D	W _I	W ₂ MAX.
PE0508	7" (Ø178 mm)	178.0±5	60.0+1/-0	13.00±0.5	17.70±0.5	8.4 +1/-0	12.4±1
PE0612	7" (Ø178 mm)	178.0±5	60.0+1/-0	13.00±0.5	17.70±0.5	8.4 +1/-0	12.4±1

SIZE	SYMBOL	Unit: mm					
	12 mm TAPE WIDE	A	N	C	D	W _I	W ₂ MAX.
PE0815	7" (Ø178 mm)	178.0 ±5	60.0 +1/-0	13.00±0.5	17.70±0.5	12.3 +1/-0	18.4±1
PE1225	7" (Ø178 mm)	178.0 ±5	60.0 +1/-0	13.00±0.5	17.70±0.5	12.3 +1/-0	18.4±1

SOLDERING PROFILES

For recommended soldering profiles, please refer to data sheet “Chip resistors mounting”.


FOOTPRINT

Table 7 Footprint dimensions

SIZE	RESISTANCE RANGE	Unit: mm			
		A	B	C	D
PE0508	$5\text{ m}\Omega \leq R \leq 1\Omega$	1.80~2.00	0.40~0.60	0.70	2.00
	$1\text{ m}\Omega \leq R \leq 4\text{m}\Omega$	4.60	0.40	2.10	3.68
PE0612	$5\text{ m}\Omega \leq R \leq 1\Omega$	4.60	0.60	2.00	3.68
PE0815	$1\text{ m}\Omega \leq R \leq 20\text{m}\Omega$	3.38	0.58	1.40	4.20
PE1225	$6\text{ m}\Omega \leq R \leq 150\text{m}\Omega$	6.1	1.4	2.35	7.25

TESTS AND REQUIREMENTS

Table 8 Test condition, procedure and requirements

TEST	TEST METHOD	PROCEDURE	REQUIREMENTS
Life/ Endurance	IEC 60115-1 4.25.1	1,000 hours at 70±5 °C applied rated power 1.5 hours on, 0.5 hour off, still air required	±(1%+0.0005 Ω)
High Temperature Exposure/ Endurance at Upper Category Temperature	IEC 60068-2-2	1,000 hours at maximum operating temperature depending on specification, unpowered No direct impingement of forced air to the parts PE0612 / PE0815: 155 °C±5°C PE0508 / PE1225: 170 °C±5 °C	±(1%+0.0005 Ω)
Moisture Resistance	MIL-STD-202 Method 106	Each temperature / humidity cycle is defined at 8 hours (method 106F), 3 cycles / 24 hours for 10d with 25 °C / 65 °C 95% R.H, without steps 7a & 7b, unpowered Parts mounted on test-boards, without condensation on parts Measurement at 24±2 hours after test conclusion	±(0.5%+0.0005 Ω)
Short Time Overload	IEC60115-1 4.13	5 times of rated power for 5 seconds at room temperature	±(0.5%+0.0005 Ω) No visible damage
Board Flex/ Bending	IEC60068-2-21	Device mounted on glass epoxy resin PCB test board (FR4), 2 mm bending Bending time: 60±5 seconds	±(1%+0.0005 Ω) No visible damage

TEST	TEST METHOD	PROCEDURE	REQUIREMENTS
Solderability Wetting	J-STD-002B test B	Electrical Test not required Magnification 50X SMD conditions: 1 st step: method B, aging 4 hours at 155 °C dry heat 2 nd step: leadfree solder bath at 245±3 °C Dipping time: 3±0.5 seconds	Well tinned (≥95% covered) No visible damage
Resistance to Soldering Heat	IEC 60068-2-58	Condition B, no pre-heat of samples Leadfree solder, 260 °C, 10±1 seconds immersion time Procedure 2 for SMD: devices fluxed and cleaned with isopropanol	±(0.5%+0.0005 Ω) No visible damage

REVISION HISTORY

REVISION	DATE	CHANGE NOTIFICATION	DESCRIPTION
Version 5	Feb. 24 2026	-	- Update 1225 TCR range
Version 4	Dec. 22, 2025	-	- Update 0508 operating power
Version 3	Nov. 21, 2025	-	- Update 0508 TCR range.
Version 2	May. 17, 2023	-	- Add PE1225 - Extend PE0612 power rating
Version 1	Apr. 13, 2021	-	- Update the marking of PE0508
Version 0	Dec. 03, 2018	-	- New datasheet for current sensor - low TCR wide terminal PE series with lead-free terminations.

LEGAL DISCLAIMER

YAGEO, its distributors and agents (collectively, “YAGEO”), hereby disclaims any and all liabilities for any errors, inaccuracies or incompleteness contained in any product related information, including but not limited to product specifications, datasheets, pictures and/or graphics. YAGEO may make changes, modifications and/or improvements to product related information at any time and without notice.

YAGEO makes no representation, warranty, and/or guarantee about the fitness of its products for any particular purpose or the continuing production of any of its products. To the maximum extent permitted by law, YAGEO disclaims (i) any and all liability arising out of the application or use of any YAGEO product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability.

YAGEO products are designed for general purpose applications under normal operation and usage conditions. Please contact YAGEO for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life, body or property: Aerospace equipment (artificial satellite, rocket, etc.), Atomic energy-related equipment, Aviation equipment, Disaster prevention equipment, crime prevention equipment, Electric heating apparatus, burning equipment, Highly public information network equipment, data-processing equipment, Medical devices, Military equipment, Power generation control equipment, Safety equipment, Traffic signal equipment, Transportation equipment and Undersea equipment, or for any other application or use in which the failure of YAGEO products could result in personal injury or death, or serious property damage. Particularly **YAGEO Corporation and its affiliates do not recommend the use of commercial, automotive, and/or COTS grade products for high reliability applications or manned space flight.**

Information provided here is intended to indicate product specifications only. YAGEO reserves all the rights for revising this content without further notification, as long as products are unchanged. Any product change will be announced by PCN.