

Technical Data Sheet


SMA ATTENUATOR 6 DB 2 GHZ 80/100W

PAGE **1/2**	ISSUE **17-08-18B**	SERIES **ATTENUATOR**	PART NUMBER **R417806128**





All dimensions are in mm. Tolerances according ISO 2768 m-H



COMPONENTS	MATERIALS	PLATING (µm)
Body	**STAINLESS STEEL**	**PASSIVATED**
Male center contact	**BERYLLIUM COPPER**	**GOLD 0.5 OVER NICKEL PHOSPHORUS 2**
Female center contact	**BERYLLIUM COPPER**	**GOLD 0.5 OVER NICKEL PHOSPHORUS 2**
Outer contact		
Insulator	**PTFE**	
Gasket	**SILICONE RUBBER**	
Substrate	**ALUMINA**	
Resistor	**THICK FILM**	
Others parts	**ALUMINIUM**	**BLACK PAINTING**

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

ELECTRICAL CHARACTERISTICS

Frequency (GHz)	DC - 1	1 - 2
V.S.W.R (≤)	1.10	1.25
Deviation(±dB)	1.0	1.0


Operating Frequency Range	DC - 2	GHz
Impedance	50	Ω
Nominal Attenuation	6	dB
Peak power at 25°C (1µs, 1‰)	5000	W
Average power at 25°C	80	W (Free Air Cooled)
	100	W (Conduction Cooled)
For conduction cooling, a plate 1000 cm2 x 3 mm(156 sq.in*1/8) min. is required		

MECHANICAL CHARACTERISTICS

Connectors	SMA	Male Female	MIL-C 39012
Weight	602,3300 g		

ENVIRONMENTAL CHARACTERISTICS

Operating temperature range	-55 /+125 °C
Storage temperature range	-55 /+125 °C



SPECIFICATION

OTHER CHARACTERISTICS

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.