Technical Data Sheet

SP12T Ramses SMA 18GHz Latching Self-cut-off Auto-reset Indicators
28Vdc TTL Diodes D-sub connector

PAGE **1/2**	ISSUE **06-02-18**	SERIE : **SPnT**	PART NUMBER : **R573F93225**

RF CHARACTERISTICS

Number of ways	: **12**
Frequency range	: **0 - 18 GHz**
Impedance	: **50 Ohms**

Frequency (GHz)	DC - 3	3 - 8	8 - 12.4	12.4 - 15	15 - 18
VSWR max	1.20	1.40	1.60	1.70	1.80
Insertion loss max	0.20 dB	0.40 dB	0.60 dB	0.70 dB	0.80 dB
Isolation min	80 dB	70 dB	60 dB	60 dB	50 dB
Average power (*)	240 W	150 W	120 W	110 W	100 W

ELECTRICAL CHARACTERISTICS

Actuator		: **LATCHING**
Nominal current **		: **500 mA**
Actuator voltage (Vcc)		: **28V (24 to 30V)**
Terminals		: **44 pins D-SUB male connector**
Indicator rating		: **1 W / 30 V / 100 mA**
Self cut-off time		: **40 ms < CT < 120 ms**
TTL inputs (E)	- High level	: **2.2 to 5.5 V / 800µA at 5.5 V**
	- Low level	: **0 to 0.8 V / 20µA at 0.8 V**

MECHANICAL CHARACTERISTICS

Connectors	: **SMA female per MIL-C 39012**
Life	: **2 million cycles per position**
Switching Time***	: **< 50 ms**
Construction	: **Splashproof**
Weight	: **< 400 g**


ENVIRONMENTAL CHARACTERISTICS

Operating temperature range	: **-40°C to +85°C**
Storage temperature range	: **-55°C to +85°C**


(* Average power at 25°C per RF Path)
(** At 25° C ±10%)
(*** Nominal voltage ; 25° C)

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

DRAWING




TTL input	RF Continuity	Ind.
E1 = 1	IN ↔ 1	D.E
E2 = 1	IN ↔ 2	D.F
E3 = 1	IN ↔ 3	D.G
E4 = 1	IN ↔ 4	D.H
E5 = 1	IN ↔ 5	D.I
E6 = 1	IN ↔ 6	D.J
E7 = 1	IN ↔ 7	D.K
E8 = 1	IN ↔ 8	D.L
E9 = 1	IN ↔ 9	D.M
E10 = 1	IN ↔ 10	D.N
E11 = 1	IN ↔ 11	D.O
E12 = 1	IN ↔ 12	D.P




General tolerances : ±0,5 mm [0,02 in]

LABEL





SCHEMATIC DIAGRAM



This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.