Technical Data Sheet

DPDT Ramses SMA 3GHz Latching Indicators 12Vdc Pins Terminals with bracket

PAGE **1/2**	ISSUE **11-04-17**	SERIE : **DPDT**	PART NUMBER : **R577342000**

RF CHARACTERISTICS

Frequency range	: **0 - 3 GHz**
Impedance	: **50 Ohms**

Frequency (GHz)	**DC - 3**
VSWR max	**1.20**
Insertion loss max	**0.20 dB**
Isolation min	**80 dB**
Average power (*)	**240 W**

ELECTRICAL CHARACTERISTICS

Actuator	: **LATCHING**
Nominal current **	: **320 mA**
Actuator voltage (Vcc)	: **12V (10.2 to 13V) / NEGATIVE COMMON**
Terminals	: **solder pins (250°C max. / 30 sec.)**
Indicator rating	: **1 W / 30 V / 100 mA**

MECHANICAL CHARACTERISTICS

Connectors	: **SMA female per MIL-C 39012**
Life	: **2.5 million cycles**
Switching Time***	: **< 15 ms**
Construction	: **Splashproof**
Weight	: **< 100 g**


ENVIRONMENTAL CHARACTERISTICS

Operating temperature range	: **-40°C to +85°C**
Storage temperature range	: **-55°C to +85°C**

(* Average power at 25°C per RF Path)
(** At 25° C ±10%)
(*** Nominal voltage ; 25° C)


This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

DRAWING




General tolerances : ±0,5 mm [0,02 in]

LABEL



SCHEMATIC DIAGRAM



Voltage	RF Continuity	Ind.
-C +1	1 ↔ 3 / 2 ↔ 4	C.1
-C +2	1 ↔ 2 / 3 ↔ 4	C.2

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.