Javascript must be enabled to view full functionality of our site.

S912ZVMBA6F0MLH(Active)

Package LQFP64 LQFP64, plastic, low profile quad flat package; 64 terminals; 0.5 mm pitch; 10 mm x 10 mm x 1.4 mm body



Buy Options | Operating Characteristics | Environmental Information | Quality Information | Shipping Information

Buy Options

S912ZVMBA6F0MLH
935351004557
Active
TRAY-Tray, Bakeable, Multiple in Drypack

Min. Package Quantity: 160

Lead Time: 12 weeks

10K @ US

Available Distributors: S912ZVMBA6F0MLH

Operating Characteristics

No information available

Environmental Information

Material Declaration	PbFree	EU RoHS	Halogen Free	RHF Indicator	2nd Level Interconnect	REACH SVHC	Weight (mg)
S912ZVMBA6F0MLH(935351004557)	Yes	Yes Certificate Of Analysis (CoA)	Yes	D	e3	REACH SVHC	346.5536

Quality Information

Material Declaration	Safe Assure Functional Safety	Moisture Sensitivity Level (MSL)	Peak Package Body Temperature (PPT) (C°)	Maximum Time at Peak Temperatures (s)
		Lead Free Soldering	Lead Free Soldering	Lead Free Soldering
S912ZVMBA6F0MLH (935351004557)	No	3	260	40

Shipping Information

Part Number	Harmonized Tariff (US)	Export Control Classification Number

	Disclaimer	(US)
S912ZVMBA6F0MLH (935351004557)	854231	3A991A2

News 25 Jun 2020 | The Zephyr Project Marks Critical Milestones for Security and Product-Ready Maturity Read More

ABOUT NXP CAREERS INVESTORS MEDIA CONTACT SUBSCRIBE

Privacy | Terms of Use | Terms of Sale | Slavery and Human Trafficking Statement | Accessibility

©2006-2020 NXP Semiconductors. All rights reserved.