




- NOTES:
- 1. TO BE USED WITH PROBE P25-XX26.
 - 2. MINIMUM CENTRES = 2.54mm.
 - 3. MATERIAL = BRASS,
FINISH = GOLD PLATED.
 - 4. RECOMMENDED MOUNTING HOLE = Ø1.70mm.
 - 5. ALL SPECIFICATIONS ARE STATED ON THE PROBE
DRAWING P25-XX26.
 - 6. ALL DIMENSIONS ON S25-526 APPLY TO ALL SLEEVES
UNLESS OTHERWISE STATED.

HEIGHT ABOVE PLATE	CONNECTION TYPE			
	CRIMP	SOLDER	TERMINAL	WIRE-WRAP
0.3mm	S25-566	S25-066	S25-466	S25-366
2.5mm	S25-526	S25-036	S25-406	S25-326
5.0mm	S25-536	S25-046	S25-416	S25-336
7.5mm	S25-546	S25-056	S25-426	S25-346

CUSTOMER
INFORMATION
SHEET

1	14/01/97	----
ISS.	DATE	C/N
APPROVED:		
CHECKED:		
DRAWN: W. BOURNE		
CUSTOMER REF.		
ASSEMBLY DRG:		

OBSOLETE

ORDER CODE:
S25-XX6
SPRING PROBE
SLEEVE (SEE DRAWING)

HARWIN INC
U.S.A.
TEL: (812) 285 0055
FAX: (812) 285 0056

HARWIN PLC
U.K.
TEL: 01705 370451
FAX: 01705 314590

HARWIN PTE
SINGAPORE
TEL: 65 7794909
FAX: 65 7793868

HARWIN CONNECTORS
KOREA
TEL: 822 521 0747
FAX: 822 521 0749

TOLERANCES
X. = ±1mm
XX = ±0.25mm
XXX = ±0.10mm
XXXX = ±0.01mm
ANGLES = ±1°
UNLESS STATED

MATERIAL:
SEE NOTE 3

FINISH: SEE NOTE 3

S/AREA: mm

TITLE:
2.54mm MIN. CENTRE TWO-PIECE
SPRING PROBE SLEEVE

DRAWING NUMBER:
S25-XX6

SHT
2 OF 2