

3 Way-0° Power Splitter/Combiner

SCG-3-392+

Typical Performance Data

FREQ. (MHz)	TOTAL LOSS ¹			AMP. UNBAL. (dB)	ISOLATION			PHASE UNBAL. (deg.)	FREQ. (MHz)	VSWR			
	S-1	S-2	S-3		1-2	1-3	2-3			S	1	2	3
2000	5.86	5.79	5.96	0.17	12.94	12.53	12.22	1.62	2000	2.28	1.12	1.16	1.16
2050	5.83	5.77	5.93	0.17	13.29	12.80	12.54	1.69	2050	2.25	1.11	1.15	1.13
2100	5.80	5.74	5.90	0.16	13.68	13.09	12.88	1.76	2100	2.20	1.09	1.13	1.12
2150	5.77	5.71	5.87	0.16	14.06	13.39	13.24	1.85	2150	2.16	1.08	1.12	1.10
2200	5.74	5.68	5.84	0.15	14.49	13.70	13.61	1.92	2200	2.12	1.07	1.11	1.08
2250	5.72	5.66	5.81	0.15	14.93	14.03	14.01	1.98	2250	2.08	1.07	1.10	1.06
2300	5.69	5.64	5.78	0.14	15.39	14.35	14.43	2.04	2300	2.04	1.06	1.10	1.05
2350	5.67	5.62	5.76	0.14	15.87	14.70	14.85	2.10	2350	2.01	1.06	1.10	1.05
2400	5.65	5.59	5.73	0.14	16.38	15.05	15.29	2.15	2400	1.97	1.07	1.10	1.04
2450	5.63	5.57	5.71	0.14	16.94	15.43	15.80	2.21	2450	1.93	1.07	1.10	1.05
2500	5.60	5.55	5.68	0.14	17.53	15.83	16.29	2.25	2500	1.89	1.08	1.10	1.06
2550	5.58	5.53	5.67	0.13	18.11	16.21	16.80	2.31	2550	1.85	1.09	1.11	1.07
2600	5.56	5.51	5.64	0.14	18.72	16.59	17.33	2.34	2600	1.82	1.09	1.12	1.08
2650	5.54	5.49	5.62	0.13	19.38	16.99	17.89	2.41	2650	1.79	1.10	1.12	1.09
2700	5.51	5.46	5.60	0.13	20.12	17.43	18.52	2.44	2700	1.74	1.11	1.13	1.10
2750	5.49	5.44	5.57	0.14	20.93	17.90	19.17	2.50	2750	1.70	1.12	1.14	1.11
2800	5.47	5.42	5.55	0.13	21.71	18.33	19.82	2.54	2800	1.66	1.13	1.15	1.13
2850	5.45	5.39	5.53	0.14	22.54	18.75	20.48	2.60	2850	1.63	1.15	1.16	1.14
2900	5.42	5.37	5.51	0.14	23.56	19.25	21.26	2.67	2900	1.58	1.16	1.17	1.15
2950	5.40	5.34	5.49	0.14	24.74	19.80	22.14	2.73	2950	1.54	1.17	1.18	1.17
3000	5.38	5.32	5.47	0.15	25.90	20.30	22.99	2.78	3000	1.50	1.18	1.19	1.18
3050	5.36	5.30	5.45	0.15	27.24	20.83	23.92	2.86	3050	1.47	1.19	1.21	1.19
3100	5.34	5.28	5.44	0.16	28.91	21.47	25.03	2.90	3100	1.43	1.20	1.22	1.21
3150	5.32	5.26	5.42	0.16	30.72	22.13	26.24	2.98	3150	1.39	1.21	1.23	1.22
3200	5.31	5.24	5.41	0.17	32.40	22.80	27.43	3.04	3200	1.37	1.23	1.24	1.23
3250	5.31	5.25	5.42	0.17	33.27	23.50	28.70	3.08	3250	1.34	1.24	1.25	1.24
3300	5.30	5.24	5.41	0.17	32.46	24.21	29.47	3.13	3300	1.33	1.25	1.26	1.26
3350	5.32	5.25	5.43	0.18	30.63	24.81	29.54	3.18	3350	1.34	1.26	1.28	1.27
3400	5.32	5.25	5.44	0.18	28.92	25.31	29.13	3.21	3400	1.35	1.28	1.29	1.29
3450	5.35	5.27	5.46	0.19	27.21	25.81	28.24	3.24	3450	1.36	1.29	1.31	1.30
3500	5.37	5.29	5.48	0.19	25.61	26.00	27.03	3.28	3500	1.38	1.30	1.32	1.32
3550	5.40	5.32	5.51	0.19	24.25	25.93	25.71	3.34	3550	1.42	1.31	1.33	1.33
3600	5.44	5.36	5.55	0.19	23.13	25.62	24.62	3.34	3600	1.46	1.33	1.34	1.35
3650	5.48	5.39	5.59	0.20	22.19	25.32	23.62	3.41	3650	1.50	1.34	1.36	1.37
3700	5.53	5.43	5.62	0.19	21.27	24.90	22.68	3.39	3700	1.54	1.35	1.37	1.38
3750	5.59	5.48	5.68	0.20	20.38	24.23	21.69	3.51	3750	1.59	1.37	1.38	1.40
3800	5.65	5.54	5.73	0.19	19.63	23.46	20.86	3.51	3800	1.66	1.39	1.40	1.43
3850	5.72	5.60	5.79	0.20	19.00	22.82	20.18	3.62	3850	1.73	1.41	1.42	1.45
3900	5.79	5.66	5.86	0.20	18.40	22.19	19.54	3.65	3900	1.79	1.43	1.43	1.47
3950	5.87	5.73	5.93	0.19	17.89	21.55	18.93	3.80	3950	1.87	1.45	1.45	1.50
4000	5.95	5.81	6.01	0.20	17.44	20.98	18.45	3.82	4000	1.95	1.47	1.47	1.53

¹Total Loss = Insertion Loss + 4.8dB Splitter Loss



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 • Fax (718) 332-4661 For detailed performance specs & shopping online see Mini-Circuits web site
The Design Engineers Search Engine Provides ACTUAL Data Instantly From MINI-CIRCUITS At: www.minicircuits.com

IF/RF MICROWAVE COMPONENTS

REV. OR
SCG-3-392+
3/23/2021
Page 1 of 1